ETSI TS 123 379 V14.1.0 (2017-05)

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/92eff561-0779-49d4-a144-17f8502a87eb/etsi-ts-123-379-v14.1.0-2017-05

LTE;
Functional architecture and information flows to support Mission Critical Push To Talk (MCPTT);
Stage 2
(3GPP TS 23.379 version 14.1.0 Release 14)

Reference
DTS/TSGS-0623379ve10

Keywords
LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/0d4561-07f9-4f4-144-1485-92a87e/etsi-ts-123-379-v14.1.0-2017-05

Important notice

The present document can be downloaded from:
http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx

If you find errors in the present document, please send your comment to one of the following services:
https://portal.etsi.org/People/CommiteeSupportStaff.aspx

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.
The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.
All rights reserved.

DECT™, **PLUGTESTS**™, **UMTS**™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE**™ are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
oneM2M logo is protected for the benefit of its Members
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under http://webapp.etsi.org/key/queryform.asp.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the ETSI Drafting Rules (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/92eff5c1-0779-49d4-a144-17f8502a87eb/etsi-ts-123-379-v14.1.0-2017-05

Contents

Intellectual Property Rights 2
Foreword 2
Modal verbs terminology 2
Foreword 10
1 Scope 11
2 References 11
3 Definitions, symbols and abbreviations 12
3.1 Definitions 12
3.2 Symbols 13
3.3 Abbreviations 13
4 Introduction 14
5 Architectural requirements 15
5.1 Media routing requirements 15
5.2 Requirements for user identity management 15
5.3 MCPTT group affiliation and MCPTT group de-affiliation 15
5.4 MCPTT call requirements 15
5.4.1 General 15
5.4.2 Group call requirements 15
5.5 GCS AS requirements for the MCPTT service 16
5.6 Group selection 16
5.7 Bearer management 16
5.7.1 General 16
5.7.2 EPS bearer considerations 16
5.7.2.1 Void 16
5.7.2.2 Void 16
5.7.3 EPS unicast bearer considerations for MCPTT 16
5.7.4 MBMS bearer management 17
5.8 MCPTT system interconnect requirements 17
6 Involved business relationships 17
7 Functional model 17
7.1 General 17
7.2 Description of the planes 17
7.3 Functional model description 17
7.3.1 On-network functional model 17
7.3.2 Off-network functional model 19
7.4 Functional entities description 20
7.4.1 General 20
7.4.2 Application plane of MCPTT service 20
7.4.2.1 General 20
7.4.2.2 Common services core 20
7.4.2.3 MCPTT application service 20
7.4.2.3.1 MCPTT client 20
7.4.2.3.2 MCPTT server 20
7.4.2.3.3 Floor participant 22
7.4.2.3.4 Floor control server 22
7.4.2.3.5 Media distribution function 22
7.4.2.3.6 Media mixer 22
7.4.2.3.7 MCPTT user database 22
7.4.3 Signalling control plane 22
7.5 Reference points 23
7.5.1 General reference point principle 23
7.5.2 Application plane of MCPTT service 23

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/92eff561-0779-49d4-a144-97f8502287eb/etsi-ts-123-379-v14.1.0-2017-05

7.5.2.1 General 23
7.5.2.2 Reference point MCPTT-1 (between the MCPTT client and the MCPTT server) 23
7.5.2.3 Reference point MCPTT-2 (between the MCPTT server and the MCPTT user database) 23
7.5.2.4 Reference point MCPTT-3 (between the MCPTT server and the MCPTT server) 23
7.5.2.5 Reference point MCPTT-4 (unicast between the floor control server and the floor participant) 24
7.5.2.6 Reference point MCPTT-5 (between the media distribution function and the EPS) 24
7.5.2.7 Reference point MCPTT-6 (between the MCPTT server and the EPS) 24
7.5.2.8 Reference point MCPTT-7 (unicast between the media distribution function and the media mixer) 24
7.5.2.9 Reference point MCPTT-8 (multicast between the media distribution function and the media mixer) 24
7.5.2.10 Reference point MCPTT-9 (multicast between the floor control server and the floor participant) 24
7.5.2.11 Reference point IWF-1 (between the MCPTT server and the interworking function to legacy systems) 24
7.5.2.12 Reference points of common services core used in the MCPTT service 25

8 Identities 25

9 Application of functional model to deployments 25

10 Procedures and information flows 25
10.1 MCPTT service configuration 25
10.2 User authentication and authorization for MCPTT service 25
10.3 Affiliation and de-affiliation to/from MCPTT group(s) 26
10.4 MCPTT group selection 26
10.4.1 General 26
10.4.2 Information flows for group selection 27
10.4.2.1 Group selection change request 27
10.4.2.2 Group selection change response 27
10.4.2.3 Group selection change notification 27
10.4.3 Authorized user remotely changes another MCPTT user's selected MCPTT group – mandatory mode 27
10.5 Pre-established session (on-network) 28
10.5.1 General 28
10.5.2 Information flows for pre-established session 29
10.5.2.1 Pre-established session establishment 29
10.5.2.2 Pre-established session modification 29
10.5.2.3 Pre-established session release - client initiated 30
10.5.2.4 Pre-established session release - server initiated 30
10.5.2.5 Pre-established session call connect request 31
10.5.2.6 Pre-established session call disconnect request 31
10.5.3 Procedures 31
10.5.3.1 General 31
10.5.3.2 Call connect and disconnect procedures using pre-established session 31
10.5.3.2.1 Call connect over unicast 31
10.5.3.2.2 Call disconnect over unicast 32
10.6 Group call 33
10.6.1 General 33
10.6.2 On-network group call 33
10.6.2.1 General 33
10.6.2.2 Information flows for group call in on-network 33
10.6.2.2.1 MCPTT emergency group call request 33
10.6.2.2.1a MCPTT emergency group call response 33
10.6.2.2.2 MCPTT emergency group call cancel request 33
10.6.2.2.2a MCPTT emergency group call cancel response 34
10.6.2.2.3 MCPTT emergency alert request 34
10.6.2.2.3a MCPTT emergency alert response 35
10.6.2.2.3b MCPTT emergency alert area trigger 35
10.6.2.2.4 MCPTT emergency state cancel request 35
10.6.2.2.4a MCPTT emergency state cancel response 35
10.6.2.2.5 MCPTT imminent peril group call request 35
10.6.2.2.5a MCPTT imminent peril group call response 36
10.6.2.2.6 MCPTT imminent peril group call cancel request 36

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/92eff561-0779-40d4-a144-7f8502a87eb/etsi-ts-123-379-v14.1.0-2017-05

10.6.2.2.6a MCPTT imminent peril group call cancel response 36
10.6.2.2.7 Group call request (MCPTT client – MCPTT server) 36
10.6.2.2.8 Group call request (MCPTT server – MCPTT server) 37
10.6.2.2.9 Group call request (MCPTT server – MCPTT client) 37
10.6.2.2.10 Group call response (MCPTT server – MCPTT client) 38
10.6.2.2.11 Group call response (MCPTT server – MCPTT server) 38
10.6.2.2.12 Group call response (MCPTT client – MCPTT server) 38
10.6.2.2.13 Group call notify (MCPTT server – MCPTT client) 39
10.6.2.2.14 Group call release request (MCPTT server – MCPTT client) 39
10.6.2.2.14a Group call release request (MCPTT client – MCPTT server) 39
10.6.2.2.15 Group call release request (MCPTT server – MCPTT server) 39
10.6.2.2.16 Group call release response (MCPTT client – MCPTT server) 40
10.6.2.2.17 Group call release response (MCPTT server – MCPTT server) 40
10.6.2.2.18 Group call rejoin request (MCPTT client – MCPTT server) 40
10.6.2.2.19 Group call rejoin response (MCPTT server – MCPTT client) 40
10.6.2.2.20 Group join request (MCPTT client – MCPTT server) 41
10.6.2.2.21 Group join response (MCPTT server – MCPTT client) 41
10.6.2.2.22 Group call leave request (MCPTT server – MCPTT client) 41
10.6.2.2.23 Group call leave response (MCPTT client – MCPTT server) 42
10.6.2.2.24 Group interrogate request (MCPTT server – MCPTT server) 42
10.6.2.2.25 Group interrogate response (MCPTT server – MCPTT server) 42
10.6.2.2.26 Group-broadcast group call request (MCPTT client – MCPTT server) 42
10.6.2.2.27 Group-broadcast group call request (MCPTT server – MCPTT client) 43
10.6.2.2.28 Group-broadcast group call response (MCPTT client – MCPTT server) 43
10.6.2.2.29 Group-broadcast group call response (MCPTT server – MCPTT client) 43
10.6.2.2.30 Group-broadcast group call release request (MCPTT client – MCPTT server) 44
10.6.2.2.31 Group-broadcast group call release request (MCPTT server – MCPTT client) 44
10.6.2.2.32 Group-broadcast group call release response (MCPTT server – MCPTT client) 44
10.6.2.2.33 Group-broadcast group call release response (MCPTT client – MCPTT server) 44
10.6.2.3 Group call within one MCPTT system 45
10.6.2.3.1 Group call models 45
10.6.2.3.1.1 Pre-arranged group call 45
10.6.2.3.1.2 Chat group call 50
10.6.2.3.2 Exiting group call due to de-affiliation 54
10.6.2.4 Group call involving groups from multiple MCPTT systems 55
10.6.2.4.1 Group call for temporary groups across multiple MCPTT systems 55
10.6.2.4.1.1 Group call setup 55
10.6.2.4.1.2 Group call release 58
10.6.2.4.2 Group call for temporary group formed by group regroup procedure involving multiple MCPTT systems via trusted mode 59
10.6.2.4.3 Group call for an MCPTT group defined in the partner MCPTT system 61
10.6.2.4.3.1 Group call setup procedure – initiating side 61
10.6.2.4.3.2 Group call setup – terminating side 62
10.6.2.4.4 Merging of groups involving multiple MCPTT systems 62
10.6.2.5 Broadcast group call 64
10.6.2.5.1 General 64
10.6.2.5.2 Common broadcast group call procedure 64
10.6.2.5.2.1 Group-broadcast group call procedure 64
10.6.2.5.2.2 Group-broadcast group call procedure when a subordinate group has an on-going MCPTT emergency group call 66
10.6.2.5.2.3 Group-broadcast group call release procedure 67
10.6.2.5.3 Temporary group – broadcast group call procedure 68
10.6.2.6 Emergency and imminent peril procedures 70
10.6.2.6.1 MCPTT emergency group call 70
10.6.2.6.1.1 MCPTT emergency group call commencement 70
10.6.2.6.1.2 MCPTT group call upgraded to an MCPTT emergency group call 72
10.6.2.6.1.3 MCPTT emergency group call cancel 74
10.6.2.6.2 MCPTT imminent peril group call 76
10.6.2.6.2.1 MCPTT imminent peril group call commencement 76
10.6.2.6.2.2 Imminent peril group call upgrade 78
10.6.2.6.2.3 MCPTT imminent peril group call cancel 80
10.6.2.6.3 MCPTT emergency alert 81

ETSI STANDARD PREVIEW (standards.iteh.ai) Full standard: https://standards.iteh.ai/catalog/standards/sist/2e6e5617-3...-a144-17...-...-...-

10.6.2.6.3.1 MCPTT emergency alert initiation 81
10.6.2.6.3.2 MCPTT emergency state cancel 83
10.6.2.6.3.3 Entering MCPTT emergency alert area 84
10.6.2.7 Location of current talker 85
10.6.2.8 Temporary group call – user regroup 86
10.6.2.8.1 General 86
10.6.2.8.2 Group call setup 86
10.6.2.8.3 Group call end (by authorized user) 87
10.6.3 Off-network group call 89
10.6.3.1 General 89
10.6.3.2 Information flows for group call in off-network 89
10.6.3.2.1 Group call announcement 89
10.6.3.2.2 MCPTT upgrade to emergency call 89
10.6.3.2.3 MCPTT emergency group cancel 90
10.6.3.2.4 Response 90
10.6.3.2.5 MCPTT emergency alert request 90
10.6.3.2.6 MCPTT emergency alert cancel 90
10.6.3.2.7 MCPTT upgrade to imminent peril call 91
10.6.3.2.8 MCPTT imminent peril group call cancel 91
10.6.3.3 Group call setup 91
10.6.3.4 Passive join to group call 92
10.6.3.5 Join to ongoing group call when new entry member initiates the call with on-going group call id 93
10.6.3.6 Immediate group call announcement to join an ongoing group call 94
10.6.3.7 Group call release due to inactivity 95
10.6.3.8 Broadcast group call 96
10.6.3.9 Emergency and imminent peril procedures 96
10.6.3.9.1 Emergency group call 96
10.6.3.9.2 MCPTT imminent peril 97
10.6.3.9.3 MCPTT emergency alert 97
10.6.3.9.3.1 MCPTT emergency alert initiation 97
10.6.3.9.3.2 MCPTT emergency state cancel 99
10.7 Private call 100
10.7.1 General 100
10.7.2 Private call in on-network 100
10.7.2.1 Information flows for private call in on-network 100
10.7.2.1.1 MCPTT private call request (MCPTT client – MCPTT server) 100
10.7.2.1.2 MCPTT private call request (MCPTT server – MCPTT server) 100
10.7.2.1.2a MCPTT private call request (MCPTT server – MCPTT client) 101
10.7.2.1.3 MCPTT private call response (MCPTT client – MCPTT server) 101
10.7.2.1.4 MCPTT private call response 101
10.7.2.1.4a MCPTT call end request 102
10.7.2.1.5 MCPTT emergency private call request (MCPTT client to MCPTT server) 102
10.7.2.1.5a MCPTT emergency private call request (MCPTT server to MCPTT client) 102
10.7.2.1.6 MCPTT progress indication 103
10.7.2.1.7 MCPTT ringing 103
10.7.2.2 Private call within one MCPTT system 103
10.7.2.2.1 Private call setup in automatic commencement mode 103
10.7.2.2.2 Private call setup in manual commencement mode 105
10.7.2.2.2.1 Description 105
10.7.2.2.2.2 Procedure 105
10.7.2.2.3 Private call release 107
10.7.2.2.3.1 Client initiated 107
10.7.2.2.3.2 Server initiated 108
10.7.2.3 Private call within several MCPTT systems 109
10.7.2.3.1 Private call setup in automatic commencement mode – MCPTT users in multiple MCPTT systems 109
10.7.2.3.2 Private call setup in manual commencement mode – MCPTT users in multiple MCPTT systems 111
10.7.2.3.3 Private call release – MCPTT users in multiple MCPTT systems 113
10.7.2.4 MCPTT emergency private call 113
10.7.2.4.1 MCPTT emergency private call commencement 113
10.7.2.4.2 MCPTT private call emergency upgrade 115

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/92ef5561-0779-4d4a-a44f-7858a87eb/etsi-ts-123-379-v14.1.0-2017-05

10.7.3 Private call in off-network 116
10.7.3.1 Information flows for private call in off-network 116
10.7.3.1.1 Call setup request 116
10.7.3.1.2 Call setup response 116
10.7.3.1.3 Call release request 116
10.7.3.1.4 Call release response 116
10.7.3.2 Use of ProSe capability for private call 117
10.7.3.3 Private call setup in automatic commencement mode 117
10.7.3.4 Private call setup in manual commencement mode 118
10.7.3.5 Private call release 119
10.7.3.6 MCPTT emergency private call 120
10.7.4 MCPTT private call call-back request 120
10.7.4.1 Information flows for MCPTT private call call-back request 120
10.7.4.1.1 MCPTT private call call-back request 120
10.7.4.1.2 MCPTT private call call-back response 120
10.7.4.1.3 MCPTT private call call-back cancel request 121
10.7.4.1.4 MCPTT private call call-back cancel response 121
10.7.4.2 MCPTT private call call-back request within one MCPTT system 121
10.7.4.3 MCPTT private call call-back cancel request within one MCPTT system 122
10.7.4.4 MCPTT private call call-back request fulfillment within one MCPTT system 123
10.8 Simultaneous session for MCPTT calls (on-network) 124
10.8.1 General 124
10.9 Floor control 124
10.9.1 Floor control for on-network MCPTT service 124
10.9.1.1 General 124
10.9.1.2 Information flows for floor control for on-network 125
10.9.1.2.1 General 125
10.9.1.2.2 Floor request 125
10.9.1.2.3 Floor granted 125
10.9.1.2.4 Floor rejected 125
10.9.1.2.5 Floor request cancel 126
10.9.1.2.6 Floor request cancel response 126
10.9.1.2.7 Floor request cancel notify 126
10.9.1.2.8 Floor idle 127
10.9.1.2.9 Floor release 127
10.9.1.2.10 Floor taken 127
10.9.1.2.11 Floor revoked 127
10.9.1.2.12 Floor acknowledgement 128
10.9.1.2.13 Queue position request 128
10.9.1.2.14 Queue position info 128
10.9.1.3 Floor control within one MCPTT system 128
10.9.1.3.1 Floor request, floor granted and floor taken during an MCPTT session 128
10.9.1.3.2 Floor override 130
10.9.1.3.2.1 Floor override using floor revoked (also floor rejected) during an MCPTT session 130
10.9.1.3.2.2 Floor override without using floor revoked during an MCPTT session 131
10.9.1.3.3 Queue position during an MCPTT session 132
10.9.1.3.4 Floor request cancellation from the floor request queue 133
10.9.1.3.4.1 Floor request cancellation from the queue – MCPTT user initiated 133
10.9.1.3.4.2 Floor request cancellation from the queue - floor control server initiated 134
10.9.1.4 Floor control involving groups from multiple MCPTT systems 135
10.9.1.4.1 Partner MCPTT system routes all floor control messages to primary MCPTT system's floor control server 135
10.9.1.4.2 Partner MCPTT system performs filtering of floor control messages entering and leaving the partner MCPTT system 137
10.9.1.5 Floor control for audio cut-in enabled group 140
10.9.2 Floor control for off-network MCPTT service 142
10.9.2.1 General 142
10.9.2.2 Information flows for floor control for off-network 143
10.9.2.2.1 General 143
10.9.2.2.2 Floor granted 143
10.9.2.3 Floor control during silence 143
10.9.2.3.1 Successful floor taken (No floor contention) 143

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/92eff561-0779-49d4-a144-17f8502a87eb/etsi-ts-123-379-v14.1.0-2017-05

10.9.2.4 Simultaneous floor requests 144
10.9.2.5 Floor request during speaking with queue 145
10.9.2.6 Floor request during speaking without queue 146
10.9.2.7 Override 147
10.9.2.8 Floor queue status 148
10.10 Use of MBMS transmission (on-network) 149
10.10.1 Information flows for MBMS Transmission 149
10.10.1.1 MapGroupToBearer 149
10.10.1.2 UnmapGroupFromBearer 150
10.10.1.3 Application group paging 150
10.10.2 Use of pre-established MBMS bearers 150
10.10.3 Use of dynamic MBMS bearer establishment 150
10.10.4 Call connect and disconnect over MBMS 151
10.10.4.1 General 151
10.10.4.2 Procedure 151
10.10.4.2.1 Call connect over MBMS 151
10.10.4.2.2 Call disconnect over MBMS 152
10.10.5 Switching from MBMS bearer to unicast bearer 153
10.10.6 Enhanced MCPTT group call setup procedure with MBMS bearer 153
10.10.6.1 Description 153
10.10.6.2 Procedure 154
10.11 MCPTT resource management (on-network) 154
10.11.1 General 154
10.11.2 Request for unicast resources at session establishment 155
10.11.3 Request for modification of unicast resources 156
10.11.4 Management of multicast media bearers 157
10.11.5 Request for resources with shared priority 157
10.11.5.1 General 157
10.11.5.2 Procedure 157
10.12 MCPTT media plane transmissions with partner MCPTT systems (on-network) 158
10.13 Location information (on-network) 160
10.14 Ambient listening call 161
10.14.1 General 161
10.14.2 Information flows for ambient listening call 161
10.14.2.1 Ambient listening call request 161
10.14.2.2 Ambient listening call response 161
10.14.2.3 Ambient listening call release request 162
10.14.2.4 Ambient listening call release response 162
10.14.2.5 Ambient listening call release notification 162
10.14.3 Ambient listening call procedures 163
10.14.3.1 Remotely initiated ambient listening call setup 163
10.14.3.2 Locally initiated ambient listening call setup 164
10.14.3.3 Ambient listening call release – server initiated 165
10.14.3.4 Remotely initiated ambient listening call release – "listening" user initiated 165
10.14.3.5 Ambient listening call release – "listened to" user initiated 166
10.15 First-to-answer call setup 167
10.15.1 Description 167
10.15.2 Information flows for first-to-answer call 167
10.15.3 Procedure 167
10.16 Remotely initiated MCPTT call 169
10.16.1 General 169
10.16.2 Information flows for remotely initiated MCPTT call 170
10.16.2.1 Remotely initiated MCPTT call request 170
10.16.2.2 Remotely initiated MCPTT call response 170
10.16.3 Procedure 170
10.16.3.1 Remotely initiated MCPTT call request 170
10.17 Support for multiple devices 172
10.17.1 General 172

Annex A (normative): MCPTT related configuration data 173

A.1 General 173

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/92ef561-0779-4d1a-a417-8502a87eb/etsi-ts-123379-v14.1.0-2017-05

A.2 MCPTT UE configuration data 174
A.3 MCPTT user profile configuration data 174
A.4 MCPTT related group configuration data 180
A.5 MCPTT service configuration data 183
Annex B (informative): Local UE settings for MCPTT 186
B.1 Local UE settings for MCPTT 186
Annex C (informative): Change history 187
History 190

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/92eff561-0779-49d4-a144-17f8502a87eb/etsi-ts-123-379-v14.1.0-2017-05

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/92eff561-0779-49d4-a144-17f8502a87eb/etsi-ts-123-379-v14.1.0-2017-05

1 Scope

This document specifies the functional architecture, procedures and information flows needed to support the mission critical push to talk (MCPTT) service. The MCPTT service utilizes the common functional architecture to support MC services over LTE including the common services core defined in 3GPP TS 23.280 [16].Support for both MCPTT group calls and MCPTT private calls operating in on-network and off-network modes of operation is specified.

The corresponding service requirements are defined in 3GPP TS 22.179 [2] and 3GPP TS 22.280 [17].

The present document is applicable primarily to MCPTT voice service using E-UTRAN access based on the EPC architecture defined in 3GPP TS 23.401 [8]. Certain application functions of the MCPTT service such as dispatch and administrative functions could also be supported via non-3GPP access networks but no additional functionality is specified to support non-3GPP access.

The MCPTT service requires preferential handling compared to normal telecommunication services e.g. in support of police or fire brigade including the handling of prioritised MCPTT calls for emergency and imminent threats.

The MCPTT service can be used for public safety applications and also for general commercial applications e.g. utility companies and railways.

In the present document, MCPTT calls between MCPTT users on different MCPTT systems are considered.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

[1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".

[2] 3GPP TS 22.179: "Mission Critical Push to Talk (MCPTT) over LTE"; Stage 1.

[3] 3GPP TS 23.002: "Network Architecture".

[4] 3GPP TS 23.203: "Policy and charging control architecture".

[5] 3GPP TS 23.228: "IP Multimedia Subsystem (IMS); Stage 2".

[6] 3GPP TS 23.237: "IP Multimedia Subsystem (IMS) Service Continuity; Stage 2".

[7] 3GPP TS 23.303: "Proximity-based services (ProSe); Stage 2".

[8] 3GPP TS 23.401: "General Packet Radio Service (GPRS) enhancements for Evolved Universal Terrestrial Radio Access Network (E-UTRAN) access".

[9] 3GPP TS 23.468: "Group Communication System Enablers for LTE (GCSE_LTE); Stage 2".

[10] 3GPP TS 29.468: "Group Communication System Enablers for LTE (GCSE_LTE); MB2 Reference Point; Stage 3".

[11] 3GPP TS 33.179: "Security of Mission Critical Push-To-Talk (MCPTT)".

[12] 3GPP TS 36.331: "Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC); Protocol specification".

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/9eff561-0779-49d4-a444-17f8560a8eb/etsi-ts-123-379-v14.1.0-2017-05

[13] IETF RFC 5245 (April 2010): "Interactive Connectivity Establishment (ICE): A Protocol for Network Address Translator (NAT) Traversal for Offer/Answer Protocols".

[14] void

[15] void

[16] 3GPP TS 23.280: "Common functional architecture to support mission critical services".

[17] 3GPP TS 22.280: "Mission Critical Common Requirements (MCCoRe); Stage 1".

[18] 3GPP TS 29.283: "Diameter data management applications".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

Automatic commencement mode: A mode in which the initiation of the private call does not require any action on the part of the receiving MCPTT user.

First-to-answer call: A call that is started when the first MCPTT user among multiple potential target recipients answers. This call requires the answering MCPTT user to answer manually; automatic answer is not allowed

Group call: A mechanism by which an MCPTT user can make a one-to-many MCPTT transmission to other users that are members of MCPTT group(s).

Group home MCPTT system: The MCPTT system where the MCPTT group is defined.

Group host MCPTT server: The MCPTT server within an MCPTT system that provides centralised support for MCPTT services of an MCPTT group defined in a group home MCPTT system.

Manual commencement mode: A mode in which the initiation of the private call requires the receiving MCPTT user to perform some action to accept or reject the call setup.

MCPTT client: An instance of an MC service client that provides the client application function for the MCPTT service.

MCPTT group: An MC service group configured for MCPTT service.

MCPTT group affiliation: An MC service group affiliation for MCPTT.

MCPTT group de-affiliation: An MC service group de-affiliation for MCPTT.

MCPTT ID: An instance of an MC service ID within the MCPTT service.

MCPTT server: An instance of an MC service server that provides the server application function for the MCPTT service.

On-network MCPTT service: The collection of functions and capabilities required to provide MCPTT via EPS bearers using E-UTRAN to provide the last hop radio bearers.

Pre-selected MCPTT user profile: An instance of the pre-selected MC service user profile for MCPTT.

UE-to-network relay MCPTT service: The collection of functions and capabilities required to provide MCPTT via a ProSe UE-to-network relay using ProSe direct communication paths to provide the last hop radio bearer(s).

For the purposes of the present document, the following terms and definitions given in 3GPP TS 22.179 [2] apply:

Dispatcher

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/9...-ff561-077...
4cd4-a1f4-...-f8850...b/etsi-ts-123-37...-v14.1.0-2017-05