
Truck and bus tyres and rims (metric series) —

**Part 2:
Rims**

Pneumatiques et jantes (séries millimétriques) pour camions et autobus —

Partie 2: Jantes

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 4209-2:2012

<https://standards.iteh.ai/catalog/standards/sist/98e2c08d-3f35-4eee-b976-1774b36e7b45/iso-4209-2-2012>



iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 4209-2:2012

<https://standards.iteh.ai/catalog/standards/sist/98e2c08d-3f35-4eee-b976-1774b36e7b45/iso-4209-2-2012>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Designation and marking	1
5 5° tapered (drop-centre) rims	1
5.1 Rim flange	1
5.2 Rim contours	1
5.3 Rim diameter and hump circumference	4
5.4 Valve holes	4
6 15° tapered (drop-centre) rims	6
6.1 Rim contours	6
6.2 Rim diameters	8
6.3 Valve holes	9
Bibliography	11

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 4209-2:2012](https://standards.iteh.ai/catalog/standards/sist/98e2c08d-3b5-4eee-b976-1774b36e7b45/iso-4209-2-2012)

<https://standards.iteh.ai/catalog/standards/sist/98e2c08d-3b5-4eee-b976-1774b36e7b45/iso-4209-2-2012>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 4209-2 was prepared by Technical Committee ISO/TC 31, *Tyres, rims and valves*, Subcommittee SC 4, *Truck and bus tyres and rims*.

This fourth edition cancels and replaces the third edition (ISO 4209-2:2001), which has been technically revised.

ISO 4209 consists of the following parts, under the general title *Truck and bus tyres and rims (metric series)*:

- Part 1: Tyres
- Part 2: Rims

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 4209-2:2012](https://standards.iteh.ai/catalog/standards/sist/98e2c08d-3B5-4eee-b976-1774b36e7b45/iso-4209-2-2012)
<https://standards.iteh.ai/catalog/standards/sist/98e2c08d-3B5-4eee-b976-1774b36e7b45/iso-4209-2-2012>

Truck and bus tyres and rims (metric series) —

Part 2: Rims

1 Scope

This part of ISO 4209 specifies the designations, contours and dimensions of drop-centre (one-piece) rims for use on trucks and buses.

The rim dimensions are those rim contour dimensions necessary for mounting and fitment of the tyre to the rim.

Tyre designations, dimensions and load ratings are given in ISO 4209-1.

2 Normative references

The following referenced documents are indispensable for the application of the document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3911, *Wheels and rims for pneumatic tyres — Vocabulary, designation and marking*

ISO 4000-2, *Passenger car tyres and rims — Part 2: Rims*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 3911 apply.

4 Designation and marking

The rim shall be designated by its nominal rim diameter code and nominal rim width code (e.g. 17.5 × 5.25), and rim flange when specified (for example: 16 × 6 K).

5 5° tapered (drop-centre) rims

5.1 Rim flange

Recommended rim flange contours for K rims are given in Table 1.


Refer to ISO 4000-2 for B and J contour rims.

5.2 Rim contours

The dimensions and tolerances of the rims shall be as given in Figure 1 and Tables 1 and 2.

Optional bead seat contours and their dimensions are given in Figure 2 and Table 3.

Dimensions in millimetres



Key

1 valve hole (see 5.4)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

NOTE For use with tubeless tyres, humps are necessary on the vehicle outboard side and preferred on the vehicle inboard side.

- a Tyre-mounting side.
- b Break corner equivalent to 0,5 minimum R.
- c Flange width includes edge radius. The portion of a flange beyond the minimum width shall not be higher than the highest point of the flange.
- d These dimensions comprise the minimum well envelope for tyre-mounting purposes, except for localized areas at the weld or the valve hole.

Figure 1 — Contour of 5° tapered (drop-centre) rims

Table 1 — Dimensions of 5° (drop-centre) rim contours

Dimensions in millimetres

Nominal rim diameter code	Nominal rim width code and flange type ^b	B min.	G ±1,0	P min.	P ₁ min.	H ^a gauge	L gauge	M max.	R ₂ min.
16	6 K and wider	11,5	20	19,5	19,5	20	22	47	10,5

^a Minimum dimensions for the well depth, H, and the well angle are required for tyre-mounting. Larger values may be required to ensure sufficient space for tubeless tyre valve seating.



^b Dimension A = nominal rim width code × 25,4 (rounded to 0,5 mm) (increments of code = 0,5).

Table 2 — Nominal rim width code

Nominal rim width code		A mm
6.00	6	152,5
6.50	6 1/2	165
7.00	7	178
7.50	7 1/2	190,5
8.00	8	203
8.50	8 1/2	216
9.00	9	228,5
9.50	9 1/2	241,5
10.00	10	254
10.50	10 1/2	266,5
11.00	11	279,5
12.00	12	305
13.00	13	330
14.00	14	355,5
15.00	15	381

Dimensions in millimetres

iTeh STANDARD PREVIEW
(standards.iteh.ai)



- a Non-mounting side.
- b Tyre-mounting side.

Figure 2 — Optional bead seat contours

Table 3 — *E* dimension for round humps

Nominal rim width code and flange type	<i>E</i> mm
6 K and wider	21 ^{+2,0} ₀
For <i>E</i> , 19,5 ^{+2,0} ₀ is also permitted.	

5.3 Rim diameter and hump circumference

The specified rim diameter, *D*, for the appropriate nominal rim diameter code and the hump circumferences are given in Table 4.

Table 4 — Specified rim diameter and hump circumference of 5° tapered (drop-centre) rims

Dimensions in millimetres

Nominal rim diameter code	Specified rim diameter ^a <i>D</i> ± 0,4	Hump circumference	
		Flat hump $\varnothing D_F -3,5^0$	Round hump ^b $\varnothing D_H -3,0^0$
16	405,6	1 274,2	1 276,4

^a The tolerance for the specified rim diameter is for tyre design purposes only. The rim measurement is by a circumference-measuring tape related to a mandrel.

^b For round humps on the vehicle inboard side only, a tolerance of $\pm 0,3$ is also permitted.

ITC STANDARD PREVIEW
(standards.iteh.ai)

[ISO 4209-2:2012](https://standards.iteh.ai/catalog/standards/sist/98e2c08d-3b35-4eee-b976-1774b36e7b45/iso-4209-2-2012)

<https://standards.iteh.ai/catalog/standards/sist/98e2c08d-3b35-4eee-b976-1774b36e7b45/iso-4209-2-2012>

5.4 Valve holes

5.4.1 Valve hole edges on the tyre side of rim shall be rounded or chamfered.


5.4.2 Valve hole edges on the weather (external) side of the rim shall be free from any burrs that could damage the valve.

5.4.3 To provide for adequate sealing, an unbroken, smooth inside surface having at least 0,75 mm or 25 % of rim thickness, whichever is greater, shall be maintained.

5.4.4 Suitable valves shall be used. Valve hole details for snap-in valves shall be as shown in Figures 3 and 4.

NOTE Holes for other valves are under consideration for a future revision of this part of ISO 4209.

Dimensions in millimetres



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 4209-2:2012
<https://standards.iteh.ai/catalog/standards/sist/6c2200d-929-429-9ee-b976-1774b36e7b45/iso-4209-2-2012>
Figure 3 — Valve hole dimensions