



SLOVENSKI STANDARD SIST EN 300 476-3 V1.2.1:2003

01-december-2003

8 [[]HJbY]nVc`ýUbYvfYnj fj] bYHfY_ca i b]_UWfYfB97HLÈG_i db]j a Ygb]_`f7 ÷È
DfcZcfa U]nUj Yc`g`UXbcgh`]nj YXVYdfcfc_c`UfD=7 GLÈ' "XY.D`Ugh_fa]`YbU
XcghcdUXc`dfYbcgbY[Ua YX]UfA57LÈDfYbcgbUfUX]g_UnU`f]Hj`fDHL

Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI);
Protocol Implementation Conformance Statement (PICS) proforma; Part 3: Medium
Access Control (MAC) layer - Portable radio Termination (PT)

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 476-3 V1.2.1:2003](https://standards.iteh.ai/catalog/standards/sist/431c7ca6-c149-499e-919a-284b5d24a26a/sist-en-300-476-3-v1-2-1-2003)

[https://standards.iteh.ai/catalog/standards/sist/431c7ca6-c149-499e-919a-](https://standards.iteh.ai/catalog/standards/sist/431c7ca6-c149-499e-919a-284b5d24a26a/sist-en-300-476-3-v1-2-1-2003)

[284b5d24a26a/sist-en-300-476-3-v1-2-1-2003](https://standards.iteh.ai/catalog/standards/sist/431c7ca6-c149-499e-919a-284b5d24a26a/sist-en-300-476-3-v1-2-1-2003)

Ta slovenski standard je istoveten z: **EN 300 476-3 Version 1.2.1**

ICS:

33.070.30 Öä äæ) ^/á à| lzæ) ^ Digital Enhanced Cordless
à: ^: ç: çã } ^/æ | ^ \ [{ ~ } ä æä Telecommunications (DECT)
ÖÖÖVD

SIST EN 300 476-3 V1.2.1:2003 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 476-3 V1.2.1:2003

<https://standards.iteh.ai/catalog/standards/sist/431c7ca6-c149-499e-919a-284b5d24a26a/sist-en-300-476-3-v1-2-1-2003>

ETSI EN 300 476-3 V1.2.1 (2000-11)

European Standard (Telecommunications series)

**Digital Enhanced Cordless Telecommunications (DECT);
Common Interface (CI);
Protocol Implementation Conformance
Statement (PICS) proforma;
Part 3: Medium Access Control (MAC)
layer - Portable radio Termination (PT)**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 476-3 V1.2.1:2003](https://standards.iteh.ai/catalog/standards/sist/431c7ca6-c149-499e-919a-284b5d24a26a/sist-en-300-476-3-v1-2-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/431c7ca6-c149-499e-919a-284b5d24a26a/sist-en-300-476-3-v1-2-1-2003>



Reference

REN/DECT-040106-3

Keywords

access, DECT, PICS, radio, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 476-3 V1.2.1:2003

<https://standards.iteh.ai/catalog/standards/sist/431c7ca6-c149-499e-919a-284b5d24a26a/sist-en-300-476-3-v1-2-1-2003>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights	8
Foreword	8
1 Scope	9
2 References	9
3 Definitions and abbreviations	9
3.1 Definitions	9
3.2 Abbreviations	10
4 Conformance requirement to this PICS proforma specification	10
Annex A (normative): PICS proforma for DECT MAC PT	11
A.1 Introduction for completing the PICS proforma	11
A.1.1 Purposes and structure	11
A.1.2 Symbols, abbreviations and conventions	11
A.1.3 Guidances for completing the PICS	12
A.2 Identification of the implementation	13
A.2.1 Date of statement	13
A.2.2 Implementation Under Test (IUT) identification	13
A.2.3 System Under Test (SUT) identification	13
A.2.4 Product supplier	13
A.2.5 Client identification	14
A.2.6 Contact person	14
A.3 Identification of the protocol	14
A.4 Global statement of conformance	14
A.5 Capabilities	15
A.5.1 Services	15
A.5.1.1 Connection oriented control services	15
A.5.1.2 Broadcast control services	16
A.5.1.3 Connectionless control services	16
A.5.1.3.1 Downlink connectionless services	16
A.5.1.3.2 Uplink connectionless services	17
A.5.1.4 Multiplexing services	17
A.5.1.5 Management services	18
A.5.2 Procedures	18
A.5.2.1 Connection procedures	19
A.5.2.1.1 Connection setup procedures	19
A.5.2.1.2 Connection modification procedures	20
A.5.2.1.3 Connection data transfer procedures	20
A.5.2.1.4 Handover procedures	21
A.5.2.1.5 Connection release procedures	21
A.5.2.1.6 Procedures for FT connections with CRFP	21
A.5.2.2 Broadcast procedures	21
A.5.2.3 Connectionless procedures	22
A.5.2.3.1 Downlink connectionless procedures	22
A.5.2.3.2 Uplink connectionless procedures	22
A.5.2.4 CSF multiplexing procedures	22
A.5.2.5 Layer management procedures	22
A.5.3 Other capabilities	23
A.6 Protocol parameters	23
A.6.1 Timer support	23
A.6.2 Protocol constants	24

A.6.3	Channel selection parameters.....	24
A.6.4	Channels supported	24
A.6.5	Bearer types supported	25
A.6.6	Slot types supported	25
A.7	Messages	25
A.7.1	A - field header	25
A.7.1.1	A - field header - Tail Identification	25
A.7.1.2	A - field header - "Q1/BCK" bit	26
A.7.1.3	A - field header - B-field identification	26
A.7.1.4	A - field header - "Q2" bit	27
A.7.2	A - field identities information (N_T) message	27
A.7.3	A - field system information (Q_T) messages	28
A.7.4	A - field paging tail (P_T) messages	28
A.7.4.1	Paging tail messages supported	28
A.7.4.2	P_T messages information type.....	28
A.7.5	A - field MAC control (M_T) messages.....	29
A.7.5.1	Mac control messages supported	29
A.7.5.2	Basic connection control messages	30
A.7.5.3	MAC layer test messages	30
A.7.5.4	Advanced connection control messages	31
A.7.5.5	Quality control (QC) messages.....	32
A.7.5.6	Broadcast and connectionless (BCL) messages.....	33
A.7.5.7	Encryption control (EC) messages.....	33
A.7.5.8	REP connection control (RCC) messages	34
A.7.6	B - Field Messages	34
A.7.6.1	B - Field Messages supported	34
A.7.6.2	B - Field Advanced connection control messages.....	35
A.7.6.3	B - Field - Null messages	36
A.7.6.4	B - Field - Quality control messages.....	37
A.7.6.5	B - Field - G_T -channel data packet messages.....	38
A.8	MAC messages format and field value.....	39
A.8.1	A - field identities information (N_T) message	39
A.8.2	A - field system information (Q_T) messages	40
A.8.2.1	Q_T - Static system information.....	40
A.8.2.2	Q_T - Extended RF carrier information	40
A.8.2.3	Q_T - Fixed part capability	41
A.8.2.4	Q_T - Extended fixed part capabilities	41
A.8.2.5	Q_T - Secondary access rights identities	42
A.8.2.6	Q_T - Multi-frame number	42
A.8.2.7	Q_T - escape	42
A.8.3	A - field paging tail (P_T) messages	42
A.8.3.1	P_T message - Full page	42
A.8.3.2	P_T message - Long page	43
A.8.3.3	P_T message - Short page	43
A.8.3.4	P_T message - Zero length page.....	43
A.8.3.5	P_T messages - MAC info. element	43
A.8.3.5.1	MAC info. element - Fill bits	43
A.8.3.5.2	MAC info. element - Blind full slot.....	44
A.8.3.5.3	MAC info. element - Other bearer.....	44
A.8.3.5.4	MAC info. element - Recommended other bearer.....	44
A.8.3.5.5	MAC info. element - Good RFP bearer	44
A.8.3.5.6	MAC info. element - Dummy or C/L bearer position.....	45
A.8.3.5.7	MAC info. element - RFP identity.....	45
A.8.3.5.8	MAC info. element - Escape	45
A.8.3.5.9	MAC info. element - Dummy or C/L bearer marker	45
A.8.3.5.10	MAC info. element - Bearer handover information.....	45

A.8.3.5.11	MAC info. element - RFP status.....	46
A.8.3.5.12	MAC info. element - Active carriers	46
A.8.3.5.13	MAC info. element - C/L bearer position	46
A.8.3.5.14	MAC info. element - Recommended PP power level	46
A.8.3.5.15	MAC info. element - Blind double slot / RFP-FP interface resource information.....	47
A.8.3.5.16	MAC info. element - Modulation types information	47
A.8.4	A - field MAC control (M _T) messages.....	47
A.8.4.1	Basic connection control messages	47
A.8.4.1.1	Basic CC - access request	47
A.8.4.1.2	Basic CC - bearer handover request.....	48
A.8.4.1.3	Basic CC - connection handover request	48
A.8.4.1.4	Basic CC - unconfirmed access request	49
A.8.4.1.5	Basic CC - bearer confirm.....	49
A.8.4.1.6	Basic CC - wait	49
A.8.4.1.7	Basic CC - release	50
A.8.4.1.8	Basic CC - attributes_T request.....	50
A.8.4.1.9	Basic CC - attributes_T confirm.....	51
A.8.4.2	MAC layer test messages	52
A.8.4.2.1	MAC test - force transmit	52
A.8.4.2.2	MAC test - loopback data	52
A.8.4.2.3	MAC test - defeat antenna diversity	53
A.8.4.2.4	MAC test - escape	53
A.8.4.2.5	MAC test - network test.....	53
A.8.4.2.6	MAC test - clear test modes	53
A.8.4.2.7	MAC test - change modulation scheme.....	54
A.8.4.3	Advanced connection control messages	54
A.8.4.3.1	Advanced CC - access request	54
A.8.4.3.2	Advanced CC - bearer handover request.....	54
A.8.4.3.3	Advanced CC - connection handover request.....	55
A.8.4.3.4	Advanced CC - unconfirmed access request	55
A.8.4.3.5	Advanced CC - bearer confirm.....	56
A.8.4.3.6	Advanced CC - wait.....	56
A.8.4.3.7	Advanced CC - Attributes_T request.....	57
A.8.4.3.8	Advanced CC - Attributes_T confirm.....	58
A.8.4.3.9	Advanced CC - Bandwidth_T request	59
A.8.4.3.10	Advanced CC - Bandwidth_T confirm	59
A.8.4.3.11	Advanced CC - Channel List.....	60
A.8.4.3.12	Advanced CC - Unconfirmed_dummy	61
A.8.4.3.13	Advanced CC - Unconfirmed_handover.....	61
A.8.4.3.14	Advanced CC - release.....	62
A.8.4.4	Quality control messages.....	62
A.8.4.4.1	QC - antenna switch single bearer request / reject.....	62
A.8.4.4.2	QC - antenna switch all bearers request / reject.....	63
A.8.4.4.3	QC - bearer handover reject / request	63
A.8.4.4.4	QC - connection handover reject / request	64
A.8.4.4.5	QC - frequency control single bearer reject / request.....	64
A.8.4.4.6	QC - frequency control all bearers reject / request	65
A.8.4.4.7	QC - advance timing all bearers reject / request	65
A.8.4.4.8	QC - send prolonged preamble request.....	66
A.8.4.4.9	QC - transmit prolonged preamble confirm	66
A.8.4.4.10	QC - frequency replacement request / confirm.....	67
A.8.4.4.11	QC - frequency replacement grant.....	67
A.8.4.5	Broadcast and connectionless (BCL) messages	68
A.8.4.5.1	BCL - CLF, first of 2 transmissions, half slot	68
A.8.4.5.2	BCL - CLF, first of 2 transmissions, full slot.....	68
A.8.4.5.3	BCL - CLF, first of 2 transmissions, double slot	68
A.8.4.5.4	BCL - CLF, last transmission, half slot.....	68
A.8.4.5.5	BCL - CLF, last transmission, full slot	69
A.8.4.5.6	BCL - CLF, last transmission, double slot	69
A.8.4.5.7	BCL - C/L single transmission, no CLF or CLS	69
A.8.4.5.8	BCL - CLS service, first transmission	69

A.8.4.5.9	BCL - change dummy bearer position	70
A.8.4.5.10	BCL - extended system info., A-field procedure	70
A.8.4.5.11	BCL - extended system info., B-field procedure	70
A.8.4.6	Encryption control messages	71
A.8.4.6.1	EC - Encryption start	71
A.8.4.6.2	EC - Encryption stop	72
A.8.4.7	M _T message - B - field setup.....	73
A.8.4.8	M _T message - Escape.....	73
A.8.4.9	M _T message - TARI	74
A.8.4.10	REP connection control messages	74
A.8.4.10.1	RCC - REP access request	74
A.8.4.10.2	RCC - REP bearer handover request.....	74
A.8.4.10.3	RCC - REP bearer confirm.....	75
A.8.4.10.4	RCC - REP wait	75
A.8.4.10.5	RCC - REP release	75
A.8.4.10.6	RCC - REP channel map request.....	76
A.8.4.10.7	RCC - REP channel map confirm.....	77
A.8.5	B - Field Messages	77
A.8.5.1	B - Field - Advanced CC messages.....	77
A.8.5.1.1	B-field Advanced CC - Access request.....	77
A.8.5.1.2	B-field Advanced CC - Bearer handover request	78
A.8.5.1.3	B-field Advanced CC - Connection handover request	79
A.8.5.1.4	B-field Advanced CC - Unconfirmed access request.....	80
A.8.5.1.5	B-field Advanced CC - Bearer confirm	80
A.8.5.1.6	B-field Advanced CC - Wait	81
A.8.5.1.7	B-field Advanced CC - Attributes_B request	82
A.8.5.1.8	B-field Advanced CC - Attributes_B confirm	83
A.8.5.1.9	B-field Advanced CC - Bandwidth_B request	84
A.8.5.1.10	B-field Advanced CC - Bandwidth_B confirm	85
A.8.5.1.11	B-field Advanced CC - Channel List.....	86
A.8.5.1.12	B-field Advanced CC - Unconfirmed Dummy.....	87
A.8.5.1.13	B-field Advanced CC - Unconfirmed Handover.....	87
A.8.5.1.14	B-field Advanced CC - Release.....	88
A.8.5.2	B-field - Null Messages (NM)	89
A.8.5.2.1	B-field - NM No C _F or CL _F data in the B-field	89
A.8.5.2.2	B-field - NM One B-subfield contains C _F or CL _F data	89
A.8.5.2.3	B-field - NM Two B-subfields contain C _F or CL _F data	90
A.8.5.2.4	B-field - NM Three B-subfields contain C _F or CL _F data	91
A.8.5.2.5	B-field - NM Four B-subfields contain C _F or CL _F data	91
A.8.5.2.6	B-field - NM Five B-subfields contain C _F or CL _F data.....	92
A.8.5.2.7	B-field - NM Six B-subfields contain C _F or CL _F data	93
A.8.5.2.8	B-field - NM Seven B-subfields contain C _F or CL _F data.....	93
A.8.5.2.9	B-field - NM Eight B-subfields contain C _F or CL _F data	94
A.8.5.2.10	B-field - NM Nine B-subfields contain C _F or CL _F data.....	95
A.8.5.3	B - Field - Quality control (QC) messages	95
A.8.5.3.1	B - Field QC - Antenna switch single bearer request / reject	95
A.8.5.3.2	B - Field QC - Antenna switch all bearers request / reject	96
A.8.5.3.3	B - Field QC - Bearer handover reject / request	97
A.8.5.3.4	B - Field QC - Connection handover reject / request	97
A.8.5.3.5	B - Field QC - Frequency control single bearer reject / request	98
A.8.5.3.6	B - Field QC - Frequency control all bearers reject / request	99
A.8.5.3.7	B - Field QC - Advance timing all bearers reject / request.....	99
A.8.5.3.8	B-field QC - Send prolonged preamble request.....	100
A.8.5.3.9	B-field QC - Transmit prolonged preamble confirm.....	101
A.8.5.3.10	B-field QC - Frequency replacement request / confirm	101
A.8.5.3.11	B-field QC - Frequency replacement grant	102
A.8.5.3.12	B - Field QC - Reset request first TDMA half frame.....	102
A.8.5.3.13	B - Field QC - Reset request second TDMA half frame	103

A.8.5.3.14	B - Field QC - Reset request both TDMA half frames.....	104
A.8.5.3.15	B - Field QC - Reset confirm first TDMA half frame.....	104
A.8.5.3.16	B - Field QC - Reset confirm second TDMA half frame	105
A.8.5.3.17	B - Field QC - Reset confirm both TDMA half frames.....	106
A.8.5.3.18	B - Field QC - MOD2 ACK	106
A.8.5.4	B - Field - Extended system information (ES) messages.....	107
A.8.5.4.1	B - Field - ES TARI message.....	107
A.8.5.5	B - Field - G _F -channel data packet messages.....	107
A.8.5.5.1	B - Field - G _F -No C _F data in the B-field	107
A.8.5.5.2	B - Field - G _F -One B-subfield contains C _F data	108
A.8.5.5.3	B - Field - G _F -Two B-subfields contain C _F data.....	108
A.8.5.5.4	B - Field - G _F -Three B-subfields contain C _F data.....	109
A.8.5.5.5	B - Field - G _F -Four B-subfields contain C _F data	109
A.8.5.5.6	B - Field - G _F -Five B-subfields contain C _F data.....	110
A.8.5.5.7	B - Field - G _F -Six B-subfields contain C _F data	110
A.8.5.5.8	B - Field - G _F -Seven B-subfields contain C _F data	111
A.8.5.5.9	B - Field - G _F -Eight B-subfields contain C _F data	111
A.8.5.5.10	B - Field - G _F -Nine B-subfields contain C _F data	112
A.8.5.6	B - Field - Escape message.....	112
Bibliography.....		113
History		114

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 300 476-3 V1.2.1:2003

<https://standards.iteh.ai/catalog/standards/sist/431c7ca6-c149-499e-919a-284b5d24a26a/sist-en-300-476-3-v1-2-1-2003>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Project Digital Enhanced Cordless Telecommunications (DECT).

The present document is part 3 of a multi-part deliverable covering the Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Protocol Implementation Conformance Statement (PICS) proforma, as identified below:

- Part 1: "Network (NWK) layer - Portable radio Termination (PT)";
- Part 2: "Data Link Control (DLC) layer - Portable radio Termination (PT)";
- Part 3: "Medium Access Control (MAC) layer - Portable radio Termination (PT)";**
- Part 4: "Network (NWK) layer - Fixed radio Termination (FT)";
- Part 5: "Data Link Control (DLC) layer - Fixed radio Termination (FT)";
- Part 6: "Medium Access Control (MAC) layer - Fixed radio Termination (FT)";
- Part 7: "Physical layer".

Annex A of this specification contains the PICS proforma for the PT medium access control layer.

National transposition dates	
Date of adoption of this EN:	24 November 2000
Date of latest announcement of this EN (doa):	28 February 2001
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 August 2001
Date of withdrawal of any conflicting National Standard (dow):	31 August 2001

1 Scope

The present document provides the Protocol Implementation Conformance Statement (PICS) proforma for the Digital Enhanced Cordless Telecommunications Medium Access Control layer at the Portable Termination as defined in EN 300 175-3 [2] in compliance with the relevant requirements and in accordance with the relevant guidance given in ISO/IEC 9646-7 [4].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] ETSI EN 300 175-1: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview".
- [2] ETSI EN 300 175-3: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer".
- [3] ISO/IEC 9646-1: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts".
<https://standards.ietf.org/catalog/standards/sist/451e7cab-c149-499e-919a-284b5d24a36a/sist-en-300-476-3-v1.2.1-2003>
- [4] ISO/IEC 9646-7: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

- terms given in EN 300 175-1 [1];
- terms given in ISO/IEC 9646-1 [3] and in ISO/IEC 9646-7 [4].

In particular, the following terms given in ISO/IEC 9646-1 [3] apply:

Implementation Conformance Statement (ICS): statement made by the supplier of an implementation or system claimed to conform to a given specification, stating which capabilities have been implemented. The ICS can take several forms: protocol ICS, profile ICS, profile specific ICS, information object ICS, etc.

ICS proforma: document, in the form of a questionnaire, which when completed for an implementation or system becomes an ICS.

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in ISO/IEC 9646-1 [3], the medium access control layer abbreviations given in EN 300 175-3 [2], and the following apply:

ICS	Implementation Conformance Statement
IUT	Implementation Under Test
PICS	Protocol Implementation Conformance Statement
SUT	System Under Test

4 Conformance requirement to this PICS proforma specification

The supplier of a protocol implementation which is claimed to conform to the portable termination specific requirements of EN 300 175-3 [2] shall complete a copy of the PICS proforma provided in annex A and shall provide the information necessary to identify both the supplier and the implementation.

An ICS which conforms to the present document shall be a conforming PICS proforma completed in accordance with the guidances for completion given in clause A.1.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 476-3 V1.2.1:2003](https://standards.iteh.ai/catalog/standards/sist/431c7ca6-c149-499e-919a-284b5d24a26a/sist-en-300-476-3-v1-2-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/431c7ca6-c149-499e-919a-284b5d24a26a/sist-en-300-476-3-v1-2-1-2003>

Annex A (normative): PICS proforma for DECT MAC PT

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the PICS proforma in this annex so that it can be used for its intended purposes and may further publish the completed PICS.

A.1 Introduction for completing the PICS proforma

A.1.1 Purposes and structure

The purpose of this PICS is to provide a mechanism whereby a supplier of an implementation of the portable termination specific medium access control layer requirements of EN 300 175-3: DECT Medium Access Control Layer may provide information in a standard form.

The PICS proforma is subdivided into subclauses for the following categories of information:

- guidances for completing the PICS proforma;
- identification of the implementation;
- identification of the protocol;
- services, procedures and functions;
- timers and protocol parameters;
- messages.


 (standards.iteh.ai)
<https://standards.iteh.ai/catalog/standards/sist/431c7ca6-c149-499e-919a-284b5d24a26a/sist-en-300-476-3-v1-2-1-2003>
 SIST EN 300 476-3 V1.2.1:2003

A.1.2 Symbols, abbreviations and conventions

The PICS proforma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7.

Item column

The item column contains a number which identifies the item in the table.

Item description column

The item description column describes in free text each respective item (e.g. parameters, timers, etc.). It implicitly means "is <item description> supported by the implementation?".

Status column

The following notations, defined in ISO/IEC 9646-7, are used for the status column:

- | | |
|-----|---|
| m | mandatory - the capability is required to be supported; |
| o | optional - the capability may be supported or not (e.g. the capability is not allowed because the underlying DECT layers (service provider) cannot handle it or the requirement belongs to an application i.e. does not belong to the data link control layer); |
| n/a | not applicable - in the given context, it is impossible to use the capability; |
| x | prohibited (excluded) - there is a requirement not to use this capability in the given context; |

- o.i qualified optional - for mutually exclusive or selectable options from a set. "i" is an integer which identifies an unique group of related optional items and the logic of their selection which is defined immediately following the table;
- ci conditional - the requirement on the capability ("m", "o", "x" or "n/a") depends on the support of other optional or conditional items. "i" is an integer identifying an unique conditional status expression which is defined immediately following the table.

Reference column

The reference column gives reference to EN 300 175-3, except where explicitly stated otherwise.

Support column

The support column shall be filled in by the supplier of the implementation. The following common notations, defined in ISO/IEC 9646-7, are used for the support column:

- Y or y supported by the implementation;
- N or n not supported by the implementation;
- N/A, n/a or - no answer required (allowed only if the status is n/a, directly or after evaluation of a conditional status).

In each context, the kind of "non-support" which is implemented at the receipt may be additionally indicated such as:

- Err the item is treated as a protocol error;
- Ig the item is received and ignored (i.e. processed syntactically, but not semantically);
- rj the item is received and rejected.

NOTE: As stated in ISO/IEC 9646-7, support for a received PDU requires the ability to parse all valid parameters of that PDU. Supporting a PDU while having no ability to parse a valid parameter is non-conformant. Support for a parameter on a PDU means that the semantics of that parameter are supported.

Values allowed column

The values allowed column contains the values or the ranges of values allowed. The range of value is defined as follows: [min value] to [max value]. Alternative values are defined as follows:

[value1], [value 2], to., [value n].

EXAMPLE: '00110000'B to '01001011'B is the value range
from '00110000'B to '01001011'B
'00110000'B, '01001011'B the value can be '00110000'B or '01001011'B.

Values supported column

The values supported column shall be filled in by the supplier of the implementation. In this column, the values or the ranges of values supported by the implementation shall be indicated.

Prerequisite line

A prerequisite line takes the form: Prerequisite: <predicate>.

A prerequisite line before a table title indicates that the whole table is not required to be completed if the predicate is FALSE.

A.1.3 Guidances for completing the PICS

The supplier of the implementation shall enter an explicit statement in each of the tables provided using the notation described in subclause A.1.2. If necessary, specific instruction is provided in the text which precedes each table.

A.2 Identification of the implementation

A.2.1 Date of statement

Identification of the Implementation Under Test (IUT) and the system in which it resides (the System Under Test (SUT)) should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

Table A.1: Date of statement

Date of statement		
Day	Month	Year

A.2.2 Implementation Under Test (IUT) identification

The supplier of the implementation shall enter information necessary to uniquely identify the IUT in table A.2.

Table A.2: IUT identification

IUT identification	
IUT name	
IUT version	

iTech STANDARD PREVIEW
(standards.iteh.ai)

A.2.3 System Under Test (SUT) identification

The supplier of the implementation shall enter information necessary to uniquely identify the SUT in table A.3.

Table A.3: SUT identification

IUT identification	
SUT name	International Portable Equipment Identity (IPEI):
Hardware configuration	

A.2.4 Product supplier

Table A.4 : Product supplier

Product supplier	
Name	
Address	
Phone No.	
Fax No.	
E-mail address	
Additional information	