

SLOVENSKI STANDARD SIST ISO 12643-1:2010

01-maj-2010

Nadomešča:

SIST ISO 12643-1:2008

Grafična tehnologija – Varnostne zahteve za grafično tehnološko opremo in sisteme – 1. del: Splošne zahteve

Graphic technology - Safety requirements for graphic technology equipment and systems - Part 1: General requirements

iTeh STANDARD PREVIEW

(standards.iteh.ai)

Technologie graphique - Exigences de sécurité pour les systèmes et l'équipement de technologie graphique - Partie 1: Exigences générales

https://standards.iteh.ai/catalog/standards/sist/38093ed4-2745-44c7-b461-3054068231bc/sist-iso-12643-1-2010

Ta slovenski standard je istoveten z: ISO 12643-1:2009

ICS:

37.100.10 Reprodukcijska oprema Reproduction equipment

SIST ISO 12643-1:2010 en

SIST ISO 12643-1:2010

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 12643-1:2010</u> https://standards.iteh.ai/catalog/standards/sist/38093ed4-2745-44c7-b461-3054068231bc/sist-iso-12643-1-2010 SIST ISO 12643-1:2010

INTERNATIONAL STANDARD

ISO 12643-1

Second edition 2009-12-15

Graphic technology — Safety requirements for graphic technology equipment and systems —

Part 1: General requirements

Technologie graphique Exigences de sécurité pour les systèmes et l'équipement de technologie graphique —

Partie 1: Exigences générales

<u>SIST ISO 12643-1:2010</u> https://standards.iteh.ai/catalog/standards/sist/38093ed4-2745-44c7-b461-3054068231bc/sist-iso-12643-1-2010



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 12643-1:2010</u> https://standards.iteh.ai/catalog/standards/sist/38093ed4-2745-44c7-b461-3054068231bc/sist-iso-12643-1-2010



COPYRIGHT PROTECTED DOCUMENT

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Forewordv				
Introductionvi				
1	Scope	1		
2	Normative references	2		
3	Terms and definitions	4		
4	Conformity with this part of ISO 12643	11		
5	Risk assessment			
6	Guarding of significant hazards			
6.1	General	12		
6.2	Guards			
6.3	In-running (in-going) nips			
6.4	Guarding in-running nips			
6.5	Interlocks			
6.6	Hold-to-run controls			
6.7	Other safeguarding measures	24		
6.8	Guarding reel unwinding, rewinding and transport devices	25		
6.9 6.10	Threading of web material transplants (pile lifting and lowering devices)			
6.10				
7	Requirements for protection against other hazards	33		
7.1	Generalhttps://standarde.itehai/catalog/standarde/sist/38003cd4-2745-44c7-h464	33		
7.2	Fire and explosion3054068231bc/sist-iso-12643-1-2010	33		
7.3	Electrical equipment	34		
7.4	Working platforms, access stairs, passageways and raised workplaces			
7.5	Stability			
7.6	High contact temperatures			
7.7	Noise			
7.8	Radiation hazards			
7.9	Stationary knives			
7.10	Rotary tools			
7.11	Transport and storage of hazardous tools			
7.12	Protruding machine parts Handwheels and cranks			
7.13 7.14	Routine handling of heavy machine parts			
7.14 7.15	Oxidizers, incinerators or thermal cleaning plants			
7.15 7.16	Protection against crushing and shearing hazards			
7.17	Contact with hazardous substances			
7.17				
8	Release from hazardous situation	45		
9	Control zones	45		
9.1	General			
9.2	Purpose of zone configuration	45		
9.3	Motion-control stations in control zones	45		
10	Controls	46		
10.1	General			
10.2	Manual control devices	_		
10.3	Initiating machine motion	54		
10.4	Hold-to-run controls	54		
10.5	Two-hand controls	55		

SIST ISO 12643-1:2010

ISO 12643-1:2009(E)

10.6	Electro-sensitive protective devices	55
10.7 10.8	Pressure-sensitive mats, pressure-sensitive bumpers, trip devices Braking devices and clutches	
11	Control stations	_
11.1	Motion-control stations	
11.2	Remote access	58
12	Control systems	
12.1	Hydraulic, pneumatic, electric and electronic control systems	
12.2 12.3	Electronic adjustable speed drives Cut-off of main energy source	
12.3 12.4	Residual-pile monitoring systems	
12.5	Unobserved unguarded hazard zones	
12.6	Cableless controls	63
12.7	Additional requirements for hand-fed machines	63
13	Ergonomics and labelling of indicators and actuators	64
14	Signals and warning devices	64
14.1	General	
14.2	Audible warning system	
14.3	Area-light warning system	
15	Safety signs and labels	
15.1	General	
15.2	Specific requirements for machine markings	
16	Contents of instruction handbook A. N.D. A. R.D P.R.E. V. I.E. V	68
16.1 16.2	General	68
16.2 16.3	Machines using flammable liquids tandards.itch.ai) Machines with cutting knives	وه وم
16.4	Handling heavy machine parts	69
16.5	Machines with automatic paper loading ST ISO 12643-1:2010	70
16.6	Handling heavy machine parts Machines with automatic paper loading STISO 12643-1:2010 Residual risks using ESPD ards.itch.ai/caialog/standards/sist/38093cd4-2745-44c7-b461- Pile turners and reel turners	70
16.7	Pile turners and reel turners 3054068231bc/sist-iso-12643-1-2010	70
16.8 16.9	Pile carriers Residual risk for hold-to-run speeds of above 10 m/min under two-hand control	
16.10	Use of stroboscopes	
	A (informative) Risk analysis relating to the pitch angle of access stairs	
	B (informative) Noise	
	C (normative) Area-light warning system	
	D (informative) Example layout of instruction handbooks	
Bibliod	ıraphy	79

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12643-1 was prepared by Technical Committee ISO/TC 130, Graphic technology.

This second edition of ISO 12643-1 constitutes a technical revision of the first edition (ISO 12643-1:2007). Significant changes incorporated into this second edition include, but are not limited to, the following:

- addition of prepress systems, converting equipment and systems, and stand-alone platen presses to the Scope;
- requirements for performance levels (PL) or safety integrity levels (SIL) as defined in the current version of ISO 13849-1 and IEC 62061 respectively dards/sist/38093ed4-2745-44c7-b461-
- additional requirements for fixed guards;
- additional requirements for interlocking with guard locking;
- additional requirements for hydraulic, pneumatic, electric and electronic control systems.

It is the intent of ISO/TC 130 that both the first and second editions of ISO 12643-1 be applicable until 2010-12-31. ISO 12643-1:2007 is thus provisionally retained until this date.

As from 2011-01-01, ISO 12643-1:2009 will cancel and replace ISO 12643-1:2007. Accordingly, as from 2011-01-01, only ISO 12643-1:2009 will be applicable to new equipment manufactured.

ISO 12643 consists of the following parts, under the general title *Graphic technology* — *Safety requirements* for graphic technology equipment and systems:

- Part 1: General requirements
- Part 2: Prepress and press equipment and systems
- Part 3: Binding and finishing equipment and systems
- Part 4: Converting equipment and systems
- Part 5: Stand-alone platen presses

Requirements specific to printing prepress and press equipment and systems, binding and finishing equipment and systems, converting equipment and systems and stand-alone platen presses that are not included in this part of ISO 12643, are given in subsequent parts of ISO 12643 that contain additional requirements specific to that type of equipment.

Introduction

During the development of this part of ISO 12643, existing relevant standards of other countries were taken into consideration. An effort has been made to take into consideration the requirements of many countries, recognizing that national standards or laws may dictate national requirements. In cases where it was known that there is a national requirement that differs from this part of ISO 12643, that has been noted.

This part of ISO 12643 was developed to harmonize the requirements of the following U.S. and European safety standards:

- ANSI B65.1, Graphic technology Safety standard Printing press systems;
- ANSI B65.2, Graphic technology Safety requirements for binding and finishing systems and equipment;
- ANSI B65.3, Safety standard Guillotine paper cutters, mill trimmers, and integral handling equipment,
- ANSI B65.4, Safety standard Three-knife trimmers, including rotary, and single- and multiple-knife trimmers:
- ANSI B65.5, Safety standard Stand-alone platen presses
- EN 1010-1, Safety of machinery Safety requirements for the design and construction of printing and paper converting machines — Part 1: Common requirements;
- SIST ISO 12643-1:2010

 EN 1010-2, Safety of machinery and Safety requirements for the design and construction of printing and paper converting machines Part 2: Printing and varnishing machines including pre-press machinery;
- EN 1010-3, Safety of machinery Safety requirements for the design and construction of printing and paper converting machines Part 3: Cutting machines;
- EN 1010-4, Safety of machinery Safety requirements for the design and construction of printing and paper converting machines Part 4: Bookbinding, paper converting and finishing machines.

Graphic technology — Safety requirements for graphic technology equipment and systems —

Part 1:

General requirements

1 Scope

This part of ISO 12643 provides safety specifications for the design and construction of new equipment used in prepress systems, printing press systems, binding and finishing systems, converting systems and stand-alone platen presses. It is applicable to equipment used in stand-alone mode, or in combination with other machines, including ancillary equipment, in which all the machine actuators (e.g. drives) of the equipment are controlled by the same control system.

The requirements given in this part of ISO 12643 are applicable to the equipment covered by all parts of ISO 12643, unless otherwise noted. This part of ISO 12643 is intended to be used in conjunction with the applicable part of ISO 12643 that contains additional requirements specific to a particular type of equipment.

(standards.iteh.ai)
This part of ISO 12643 addresses recognized significant hazards specific to equipment and systems in the following areas:

SIST ISO 12643-1:2010
https://standards.iteh.ai/catalog/standards/sist/38093ed4-2745-44c7-b461-

—	mechanical;	3054068231bc/sist-iso-12643-1-2010
	electrical;	
_	slipping, trippir	ng, falling;
_	ergonomics;	
_	noise;	
_	UV and laser r	adiation;
_	fire and explos	ion;
_	thermal;	
	other types of	emissions [e.g. ozone, ink mist, volatile organic compounds (VOCs), etc.].

The safety principles established in this part of ISO 12643 can also be applicable to the design of equipment within areas of technology that are not specified in ISO 12643.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

- ISO 3864-1, Graphical symbols Safety colours and safety signs Part 1: Design principles for safety signs in workplaces and public areas
- ISO 3864-2, Graphical symbols Safety colours and safety signs Part 2: Design principles for product safety labels
- ISO 3864-3, Graphical symbols Safety colours and safety signs Part 3: Design principles for graphical symbols for use in safety signs
- ISO 7010, Graphical symbols Safety colours and safety signs Safety signs used in workplaces and public areas
- ISO 8031, Rubber and plastics hoses and hose assemblies Determination of electrical resistance and conductivity
- ISO 11553-1, Safety of machinery Laser processing machines Part 1: General safety requirements
- ISO/TR 11688-1, Acoustics Recommended practice for the design of low-noise machinery and equipment Part 1: Planning

 iTeh STANDARD PREVIEW
- ISO 11689, Acoustics Procedure for the comparison of noise-emission data for machinery and equipment (Standards.iten.al)
- ISO 12100-1, Safety of machinery Basic concepts, general principles for design Part 1: Basic terminology, methodology SIST ISO 12643-1:2010

https://standards.iteh.ai/catalog/standards/sist/38093ed4-2745-44c7-b461-

- ISO 12100-2, Safety of machinery Basic4concepts; general4principles for design Part 2: Technical principles
- ISO 12643-2, Graphic technology Safety requirements for graphic technology equipment and systems Part 2: Prepress and press equipment and systems
- ISO 12643-3, Graphic technology Safety requirements for graphic technology equipment and systems Part 3: Binding and finishing equipment and systems
- ISO 12643-4, Graphic technology Safety requirements for graphic technology equipment and systems Part 4: Converting equipment and systems
- ISO 12643-5, Graphic technology Safety requirements for graphic technology equipment and systems Part 5: Stand-alone platen presses
- ISO 13732-1, Ergonomics of the thermal environment Methods for the assessment of human responses to contact with surfaces Part 1: Hot surfaces
- ISO 13849-1, Safety of machinery Safety-related parts of control systems Part 1: General principles for design
- ISO 13850, Safety of machinery Emergency stop Principles for design
- ISO 13851, Safety of machinery Two-hand control devices Functional aspects and design principles
- ISO 13854, Safety of machinery Minimum gaps to avoid crushing of parts of the human body

- ISO 13855, Safety of machinery Positioning of protective equipment with respect to the approach speeds of parts of the human body
- ISO 13856-1, Safety of machinery Pressure-sensitive protective devices Part 1: General principles for design and testing of pressure-sensitive mats and pressure-sensitive floors
- ISO 13857, Safety of machinery Safety distances to prevent hazard zones being reached by upper and lower limbs
- ISO 14119:1998, Safety of machinery Interlocking devices associated with guards Principles for design and selection
- ISO 14120, Safety of machinery Guards General requirements for the design and construction of fixed and movable guards
- ISO 14121-1, Safety of machinery Risk assessment Part 1: Principles
- ISO 14122-1, Safety of machinery Permanent means of access to machinery Part 1: Choice of fixed means of access between two levels
- ISO 14122-2, Safety of machinery Permanent means of access to machinery Part 2: Working platforms and walkways
- ISO 14122-3, Safety of machinery Permanent means of access to machinery Part 3: Stairs, stepladders and guard-rails

 iTeh STANDARD PREVIEW
- ISO/TR 15847, Graphic technology Graphical symbols for printing press systems and finishing systems, including related auxiliary equipment tandards.iteh.al)
- IEC 60079-1, Explosive atmospheres <u>Plart 1s(Equipment) pr</u>otection by flameproof enclosures "d" https://standards.iteh.ai/catalog/standards/sist/38093ed4-2745-44c7-b461-
- IEC 60079-2, Explosive atmospheres and Rant 2: Equipment protection by pressurized enclosures "p"
- IEC 60079-5, Explosive atmospheres Part 5: Equipment protection by powder filling "q"
- IEC 60079-6, Explosive atmospheres Part 6: Equipment protection by oil immersion "o"
- IEC 60079-7, Explosive atmospheres Part 7: Equipment protection by increased safety "e"
- IEC 60079-11, Explosive atmospheres Part 11: Equipment protection by intrinsic safety "i"
- IEC 60079-14, Explosive atmospheres Part 14: Electrical installations design, selection and erection
- IEC 60079-18, Explosive atmospheres Part 18: Equipment protection by encapsulation "m"
- IEC 60204-1, Safety of machinery Electrical equipment of machines Part 1: General requirements
- IEC 60825-1, Safety of laser products Part 1: Equipment classification and requirements
- IEC 60947-2, Low-voltage switchgear and controlgear Part 2: Circuit-breakers
- IEC 60947-3, Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
- IEC 60947-5-1, Low-voltage switchgear and controlgear Part 5-1: Control circuit devices and switching elements Electromechanical control circuit devices

IEC 61010-1, Safety requirements for electrical equipment for measurement, control, and laboratory use — Part 1: General requirements

IEC 61310-1, Safety of machinery — Indication, marking and actuation — Part 1: Requirements for visual, acoustic and tactile signals

IEC 61310-2, Safety of machinery — Indication, marking and actuation — Part 2: Requirements for marking

IEC 61310-3, Safety of machinery — Indication, marking and actuation — Part 3: Requirements for the location and operation of actuators

IEC 61496-1, Safety of machinery — Electro-sensitive protective equipment — Part 1: General requirements and tests

IEC 61496-2, Safety of machinery — Electro-sensitive protective equipment — Part 2: Particular requirements for equipment using active opto-electronic protective devices (AOPDs)

IEC 62061, Safety of machinery — Functional safety of safety-related electrical, electronic and programmable electronic control systems

EN 1127-1, Explosive atmosphere — Explosion prevention and protection — Part 1: Basic concepts and methodology

EN 1760-2, Safety of machinery — Pressure sensitive protective devices — Part 2: General principles for the design and testing of pressure sensitive edges and pressure sensitive bars

EN 12198-1:2000, Safety of machinery — Assessment and reduction of risks arising from radiation emitted by machinery — Part 1: General principles (Standards.iten.al)

EN 13023, Noise measurement methods for printing, paper converting, paper making machines and auxiliary equipment — Accuracy grades 2 and 3 standards.iteh.ai/catalog/standards/sist/38093ed4-2745-44c7-b461-3054068231bc/sist-iso-12643-1-2010

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 13849-1 and the following apply.

3.1

actuator

part of the actuating system to which an external actuating force is applied

[IEV 441-15-22]^[22]

NOTE 1 The actuator can take the form of a handle, knob, pushbutton, roller, plunger, trip wire, pressure-sensitive mat, etc.

NOTE 2 There are some actuating means that do not require an external actuating force, but only an action; e.g. light beams. Such actuating means are not considered to be actuators.

3.2

armed condition

machine status in which machine motion can be automatically initiated

NOTE **Zero speed** (3.68) is considered to be an armed condition.

3.3

audible alarm

horn, bell or other distinctive audible warning device that sounds to indicate impending machine motion

3.4

authorized person

person identified by management as having special training or designated to act in specified situations

NOTE Examples of "specified situations" include:

- special tasks to be performed;
- the function of the adjustments in the work zone;
- proper operation of adjustments and controls;
- all types of hazards in the area where the task is to be performed;
- the application of equivalent, alternative protection to perform the task;
- improper actions that can cause injury and the consequences of those improper actions.

3.5

auxiliary device

mechanism or machine, either built-in or attached, used for the production process

3.6

barrier guard

 ${f guard}$ (3.21) that reduces or prevents physical access to a hazard zone by closing off access to an area containing one or more hazards ${f STANDARD}$ ${f PREVIEW}$

EXAMPLE A perimeter fence or tunnel guard and site hail

3.7

binding and finishing system

SIST ISO 12643-1:2010

combination of machines functioning in an integrated configuration to turn an incomplete printed product into a finished product by means of one of more processes, such as cutting, folding, binding, stitching, gluing, wrapping, etc.

3.8

Category 0 stop

uncontrolled stop

stopping by immediate removal of power to the **machine actuators** (3.29)

[IEC 60204-1:2009, 9.2.2]

3.9

Category 1 stop

controlled stop with power available to the **machine actuators** (3.29) to achieve the stop and then removal of power when the stop is achieved

[IEC 60204-1:2009, 9.2.2]

3.10

Category 2 stop

controlled stop with power left available to the machine actuators (3.29)

[IEC 60204-1:2009, 9.2.2]

3.11

continuous run

machine motion at a steady speed initiated by a momentary-contact control

3.12

control station

defined location containing one or more controls

3.13

control zone

control configuration of single or multiple machine motions using the same control devices

NOTE See Clause 9.

3.14

drive

mechanism, divided into the following two general categories, which causes a machine or any of its elements to move:

- drives with no stored energy, which include, but are not limited to, direct-motor drives;
- drives having stored energy, which include, but are not limited to, motor-flywheel-clutch drives and hydraulic-pneumatic drives

3.15

electrical hazard

source of potential injury or death from electric shock or burn

NOTE Adapted from ISO 12100-1:2003.

3.16

iTeh STANDARD PREVIEW

electro-sensitive protective device ESPD

(standards.iteh.ai)

apparatus that detects the presence of a person or part of a person or object in a defined area, using any detection means, including, but not limited to, photoelectric dight screen, ultrasonic, etc.

https://standards.iteh.ai/catalog/standards/sist/38093ed4-2745-44c7-b461-

3.17

3054068231bc/sist-iso-12643-1-2010

emergency stop device

manually actuated control used to initiate an emergency stop function (3.18)

NOTE Adapted from ISO 13850:1996.

3.18

emergency stop function

mechanism activated by a single human motion and intended to halt machine activity in order to avoid injury to persons, damage to machinery or damage to work in progress

3.19

exposing device

machinery used for creating images by exposing photo-sensitive material such as printing plates or printing formes

3.20

fixed guard

guard (3.21) that is securely affixed by fasteners that require a tool(s) to remove in order to gain access to an area with a significant hazard

3.21

guard

physical barrier that restricts access to a significant hazard

3.22

hazard point

location of a hazard on a machine where a person can be injured

3.23

hazard zone

any area within and/or around machinery in which a person is exposed to risk of injury or damage to health

Adapted from ISO 12100-1:2003. NOTE

3.24

hold-to-run control

control that starts and maintains machine motion only as long as the control is activated

3.25

inch

jog

(operation of machinery) machine motion requiring maintained activation engagement of a hold-to-run control and which will continue until the control is released or until a pre-determined displacement (limited inch) has been reached

3.26

infrequently used workplace

area in which an activity is carried out, such as observation, make-ready, jam clearing, minor servicing, crossing inserting hoppers or conveyer belts, etc., that is routine, repetitive, integral to (but not necessarily during) production, and is done only on an occasional basis

3.27

in-running nip

in-going nip area created either by two rotating components that are rotating inward, or by one component rotating toward an adjacent surface (standards.iteh.ai)

NOTE See Figure 3 for examples of in-running nips.

https://standards.iteh.ai/catalog/standards/sist/38093ed4-2745-44c7-b461-3.28

3054068231bc/sist-iso-12643-1-2010 interlock

(for safeguarding) arrangement that interconnects guard(s) or device(s) with the control system and/or all or part of the electrical energy distributed to the machine

[IEC 60204-1:2009, definition 3.32]

3.29

machine actuator

power mechanism used to affect motion of the machine

[IEC 60204-1:2009, definition 3.34]

3.30

maintained-contact control

control that remains in an open or closed state after its activation

3.31

maintenance

operation(s) required to ensure that the machine remains in acceptable operating condition and that is/are usually performed when the machine is not available for production

NOTE Maintenance (for example, repairing or replacing broken, worn or damaged parts; performing lubrication; preventive servicing) is normally performed by qualified maintenance personnel, or operators, who have been trained about the types of hazards in the area in which their tasks are to be performed and about how these hazards can be avoided. Such maintenance is generally performed with energy isolated, when possible.

7 © ISO 2009 - All rights reserved