



**SLOVENSKI STANDARD**  
**SIST EN 300 356-8 V3.1.3:2003**  
**01-december-2003**

8 [[ ]HJbc`ca fYy^Y'n]bhY[ f]fUb]a ]gfcf]hj Ua ]fG8 BŁĚ'G]ghYa `g][ bU]nUW^Y'ýH'+ Ě  
HfYhUfUn` ]WU=G8 B!i dcfUVb]ý\_Y[ UXYUfIGI DŁnUa YXbUfcXb]j a Ygb]\_Ě, "XY.  
8 cdc`b]bUgfcf]hYj. `a YXi dcfUVb]ý\_Ug][ bU]nUW^Ufl I GŁQlf]dcfc ]c`#H !H'E"+ +ž  
%`lc \_Uf% - +ŁžgdfYa Yb^YbcQ

Integrated Services Digital Network (ISDN); Signalling System No.7; ISDN User Part (ISUP) version 3 for the international interface; Part 8: User-to-User Signalling (UUS) supplementary service [ITU-T Recommendation Q.737, clause 1 (1997), modified]

**iteh STANDARD PREVIEW**  
**(standards.iteh.ai)**

<https://standards.iteh.ai/catalog/standards/sist/b90e9753-6d1b-4f35-b2d6-3307acd47364/sist-en-300-356-8-v3-1-3-2003>

**Ta slovenski standard je istoveten z: EN 300 356-8 Version 3.1.3**

**ICS:**

33.080	Digitalno omrežje z integriranimi storitvami (ISDN)	Integrated Services Digital Network (ISDN)
--------	---	--

**SIST EN 300 356-8 V3.1.3:2003**                      **en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 300 356-8 V3.1.3:2003

<https://standards.iteh.ai/catalog/standards/sist/b90e9753-6d1b-4f35-b2d6-3307acd47364/sist-en-300-356-8-v3-1-3-2003>

# EN 300 356-8 V3.1.3 (1998-08)

*European Standard (Telecommunications series)*

**Integrated Services Digital Network (ISDN);  
Signalling System No.7;  
ISDN User Part (ISUP) version 3 for the international interface;  
Part 8: User-to-User Signalling (UUS)  
supplementary service**

[ITU-T Recommendation Q.737, clause 1 (1997), modified]

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 300 356-8 V3.1.3:2003](https://standards.iteh.ai/catalog/standards/sist/b90e9753-6d1b-4f35-b2d6-3307acd47364/sist-en-300-356-8-v3-1-3-2003)

<https://standards.iteh.ai/catalog/standards/sist/b90e9753-6d1b-4f35-b2d6-3307acd47364/sist-en-300-356-8-v3-1-3-2003>



---

**Reference**

REN/SPS-01039-8 (3aq01ie0.PDF)

---

**Keywords**

ISDN, ISUP, SS7, supplementary service, UUS

**ETSI**

---

**Postal address**

F-06921, Sophia Antipolis Cedex - FRANCE

---

**Office address**

650 Route des Lucioles - Sophia Antipolis  
Valbonne - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 / NAF 742 C

Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Internet**

secretariat@etsi.fr

<http://www.etsi.fr>

<http://www.etsi.org>

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1998.  
All rights reserved.

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.fr/ipr> or <http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Signalling Protocols and Switching (SPS).

The present document is part 8 of a multi-part EN covering the ISDN User Part (ISUP) version 3 for the international interface, as identified below:

- Part 1: "Basic services";
- Part 2: "ISDN supplementary services";
- Part 3: "Calling Line Identification Presentation (CLIP) supplementary service";
- Part 4: "Calling Line Identification Restriction (CLIR) supplementary service";
- Part 5: "Connected Line Identification Presentation (COLP) supplementary service";
- Part 6: "Connected Line Identification Restriction (COLR) supplementary service";
- Part 7: "Terminal Portability (TP) supplementary service";
- Part 8: "User-to-User Signalling (UUS) supplementary service";**
- Part 9: "Closed User Group (CUG) supplementary service";
- Part 10: "Subaddressing (SUB) supplementary service";
- Part 11: "Malicious Call Identification (MCID) supplementary service";
- Part 12: "Conference Call, add-on (CONF) supplementary service";
- Part 14: "Explicit Call Transfer (ECT) supplementary service";
- Part 15: "Diversion supplementary services";
- Part 16: "Call Hold (HOLD) supplementary service";
- Part 17: "Call Waiting (CW) supplementary service";
- Part 18: "Completion of Calls to Busy Subscriber (CCBS) supplementary service";
- Part 19: "Three party (3PTY) supplementary service".
- Part 20: "Completion of Calls on No Reply (CCNR) supplementary service";
- Part 31: "Protocol Implementation Conformance Statement (PICS) proforma specification for basic services"
- Part 32: "Test Suite Structure and Test Purposes (TSS&TP) specification for basic services"
- Part 33: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for basic services"
- Part 34: "Protocol Implementation Conformance Statement (PICS) proforma specification for supplementary services"
- Part 35: "Test Suite Structure and Test Purposes (TSS&TP) specification for supplementary services"
- Part 36: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for supplementary services"

NOTE: Part 13 has not been issued.

In accordance with CCITT Recommendation I.130, the following three level structure is used to describe the supplementary telecommunication services as provided by European public telecommunications operators under the pan-European Integrated Services Digital Network (ISDN):

- Stage 1: is an overall service description, from the user's stand-point;
- Stage 2: identifies the functional capabilities and information flows needed to support the service described in stage 1; and
- Stage 3: defines the signalling system protocols and switching functions needed to implement the service described in stage 1.

The present document details the stage three aspects (signalling system protocols and switching functions) needed to support the User-to-User Signalling (UUS) supplementary service. The stage 1 and stage 2 aspects are detailed in ETS 300 284 and ETS 300 285, respectively.

<b>National transposition dates</b>	
Date of adoption of this EN:	7 August 1998
Date of latest announcement of this EN (doa):	30 November 1998
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 May 1999
Date of withdrawal of any conflicting National Standard (dow):	31 May 1999

**iTeh STANDARD PREVIEW**  
(standards.itech.ai)

## Endorsement notice

The text of ITU-T Recommendation Q.737, clause 1 (1997), was approved by ETSI as an EN with agreed modifications as given below.

- NOTE: New or modified text is indicated using sidebars. In addition, underlining and/or strike-out are used to highlight detailed modifications where necessary.

---

# Global modifications to ITU-T Recommendation Q.737, clause 1

Insert the following two clauses (Scope and Normative references) at the start of clause 1:

---

## Scope

This eighth part of EN 300 356 specifies the stage three of the User-to-User Signalling (UUS) supplementary service for the pan-European Integrated Services Digital Network (ISDN) as provided by the European public telecommunications operators by means of the Signalling System No.7 protocol for the ISDN User Part (ISUP). Stage three identifies the protocol procedures and switching functions needed to support a telecommunication service (see CCITT Recommendation I.130 [1]).

The present document does not specify the additional protocol requirements where the service is provided to the user via a telecommunications network that is not an ISDN.

The present document does not specify the additional protocol requirements for the national signalling interface.

Although the present document applies only to the international interconnection, the specification of functions, formats and codes of messages and signals, and actions performed at originating and destination local exchanges are retained.

Formats, codes and procedures marked for national use are included for informative purposes for the international interface specification. If these items so marked are supported within a national network and operator's network, then it is proposed that they shall be supported in this manner.

**NOTE:** In the case where a national signalling system behaves differently, the international gateway exchange is to support both the concerned national and international network.

The UUS supplementary service allows an ISDN user to send/receive a limited amount of information to/from another ISDN user over the signalling channel in association with a call to the other ISDN user.

The UUS supplementary service is applicable to all telecommunication services.

---

## Normative references

References may be made to:

- a) specific versions of publications (identified by date of publication, edition number, version number, etc.), in which case, subsequent revisions to the referenced document do not apply; or
- b) all versions up to and including the identified version (identified by "up to and including" before the version identity); or
- c) all versions subsequent to and including the identified version (identified by "onwards" following the version identity); or
- d) publications without mention of a specific version, in which case the latest version applies.

A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] CCITT Recommendation I.130 (1988): "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [2] ETS 300 121 (1992): "Integrated Services Digital Network (ISDN); Application of the ISDN User Part (ISUP) of CCITT Signalling System No.7 for international ISDN interconnections (ISUP version 1)".

- [3] ETS 300 284: "Integrated Services Digital Network (ISDN); User-to-User Signalling (UUS) supplementary service; Service description".
- [4] ETS 300 285: "Integrated Services Digital Network (ISDN); User-to-User Signalling (UUS) supplementary service; Functional capabilities and information flows".
- [5] ETS 300 286-1: "Integrated Services Digital Network (ISDN); User-to-User Signalling (UUS) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [6] EN 300 356-1: "Integrated Services Digital Network (ISDN); Signalling System No.7; ISDN User Part (ISUP) version 3 for the international interface; Part 1: Basic services [ITU-T Recommendations Q.761 to Q.764 (1997), modified]".
- [7] EN 300 356-2: "Integrated Services Digital Network (ISDN); Signalling System No.7; ISDN User Part (ISUP) version 3 for the international interface; Part 2: ISDN supplementary services [ITU-T Recommendation Q.730 (1997), modified]".
- [8] EN 300 356-18: "Integrated Services Digital Network (ISDN); Signalling System No.7; ISDN User Part (ISUP) version 3 for the international interface; Part 18: Completion of Calls to Busy Subscriber (CCBS) supplementary service [ITU-T Recommendation Q.733, clause 3 (1997), modified]".
- [9] EN 300 403-1: "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 1: Protocol specification [ITU-T Recommendation Q.931 (1993), modified]".

Throughout the text of ITU-T Recommendation Q.737, clause 1

Replace references as shown in table 1.

(standards.iteh.ai)

Table 1

SIST EN 300 356-8 V3.1.3:2003

<https://standards.iteh.ai/catalog/standards/sist/b90e9753-6d11-4056-b016-3307acd47364/sist-en-300-356-8-v3-1-3-2003>

Reference in ITU-T Recommendation Q.737, clause 1	Modified reference
CCITT Recommendation I.257.1	ETS 300 284 [3]
ITU-T Recommendation Q.87, clause 1	ETS 300 285 [4]
ITU-T Recommendation Q.730	ITU-T Recommendation Q.730 as modified by EN 300 356-2 [7]
ITU-T Recommendation Q.761	ITU-T Recommendation Q.761 as modified by EN 300 356-1 [6]
ITU-T Recommendation Q.762	ITU-T Recommendation Q.762 as modified by EN 300 356-1 [6]
ITU-T Recommendation Q.763	ITU-T Recommendation Q.763 as modified by EN 300 356-1 [6]
ITU-T Recommendation Q.764	ITU-T Recommendation Q.764 as modified by EN 300 356-1 [6]
ITU-T Recommendation Q.767	ETS 300 121 [2]
ITU-T Recommendation Q.931	ITU-T Recommendation Q.931 as modified by EN 300 403-1 [9]
ITU-T Recommendation Q.957, clause 1	ETS 300 286-1 [5]

#### Subclause 1.1.6.10

Replace the complete text of subclause 1.1.6.10 and all of its subclauses by:

No impact on ISUP.

#### Subclause 1.1.6.19

Replace the text by:

Interactions are described in EN 300 356-18 [8].



## Subclause 1.1.7, table 1-1/Q.737

Modify table 1-1/Q.737 as shown in table 2.

Table 2

Interworking network	Implicit request	Non-essential request	Essential request
Non-SS No.7 network	ACM; interworking ind.: "interw. encountered"	ACM; UUI ind.: "service 1 not provided"	REL #29 + diagnostics (note 1)
SS No.7 network, not ISUP or TUP+	ACM; ISUP ind.: "ISUP not all the way"	ACM; UUI ind.: "service 1 not provided"	REL #29 + diagnostics (note 1)
SS No.7 network not supporting the service	ACM or CON; UUI ind.: "UUI discarded" (note 2)	ACM or CON; UUI ind.: "service 1 not provided" (note 3)	REL #29 + diagnostics (notes 1 and 3)
SS No.7 TUP+ network not supporting the service	ACM or CON; UUI ind.: "UUI discarded" (note 2)	ACM or CON; UUI ind.: "service 1 not provided"	REL #29 + diagnostics (note 1)

NOTE 1: The diagnostics field contains the user-to-user indicators parameter name.  
 NOTE 2: If the UUI in the IAM has been discarded, the user-to-user indicators parameter contains "UUI discarded by the network".  
 If it is detected that the originating exchange has performed segmentation by sending UUI in the additional segment, and a subsequent exchange knows that the segmentation procedure is not supported by the succeeding network, the latter exchange will code the user-to-user indicators parameter "UUI discarded by the network". This knowledge may be obtained by reception of a confusion message indicating that the segmentation message has been discarded.  
 NOTE 3: A transit or international gateway exchange may have to generate service rejection in case a confusion message is received indicating that the user-to-user indicators requesting the service are not supported by the succeeding network.  
 Two ISDN networks that interwork may have to retain knowledge of the service request until it is clear whether both can support the service.

(standards.iteh.ai)

## Subclause 1.2.6.10

Replace the complete text of subclause 1.2.6.10 and all of its subclauses by:

No impact on ISUP.

## Subclause 1.2.6.19

Replace the text by:

Interactions are described in EN 300 356-18 [8].

## Subclause 1.3.2.1

Delete the text:

Use is also made of SCCP class 2 protocols defined in Recommendations Q.711 to 714 and Recommendations Q.730. However, the procedures for the application of SCCP class 2 protocols for User-to-User Signalling service 3 are for further study.

## Subclause 1.3.5.2.5.2.2

Add the following at the end of the subclause:

The cause indicators parameter in the facility reject message is supplied as follows:

- a) if the called user does not respond to the service request, then cause value #69 "requested facility not implemented" without diagnostics is used;
- b) in other situations, e.g. called user rejects the service, network or called user cannot support the service, then cause value #29 "facility rejected" without diagnostics is used.