

SLOVENSKI STANDARD SIST EN 300 356-14 V3.1.3:2003

01-december-2003

8][]HUbcʻcafYÿʻYʻn`]bHY[f]fUb]a]`ghcf]hjUa]`fHG8B4'E`G][bU`]nUVVYUýH'+`E`HfYh1U fUn`]]WUf=G8B!idcfUVb]ý_Y[UXY`UfHGIDE'nUaYXbUfcXb]`jaYgb]_`E`%("XY`. 8cdc`b]`bU`ghcf]HYj.`bYXjciabU`dfYXU'U_`]WUf197HE'Qdf]dcfc]`c`=HI!H`E"+'&zhc_U +`ff%-*EzgdfYaYb^Q

Integrated Services Digital Network (ISDN); Signalling System No.7; ISDN User Part (ISUP) version 3 for the international interface; Part 14: Explicit Call Transfer (ECT) supplementary service [ITU-T Recommendation Q.732, clause 7 (1996), modified]

(standards.iteh.ai)

<u>SIST EN 300 356-14 V3.1.3:2003</u> https://standards.iteh.ai/catalog/standards/sist/a2a2f6b4-e199-4628-b385-71311cdb38b6/sist-en-300-356-14-v3-1-3-2003

en

Ta slovenski standard je istoveten z: EN 300 356-14 Version 3.1.3

ICS:

33.080 Digitalno omrežje z integriranimi storitvami (ISDN) Integrated Services Digital Network (ISDN)

SIST EN 300 356-14 V3.1.3:2003

iTeh STANDARD PREVIEW (standards.iteh.ai)


<u>SIST EN 300 356-14 V3.1.3:2003</u> https://standards.iteh.ai/catalog/standards/sist/a2a2f6b4-e199-4628-b385-71311cdb38b6/sist-en-300-356-14-v3-1-3-2003

EN 300 356-14 V3.1.3 (1998-08)

European Standard (Telecommunications series)

Integrated Services Digital Network (ISDN); Signalling System No.7; ISDN User Part (ISUP) version 3 for the international interface; Part 14: Explicit Call Transfer (ECT) supplementary service

[ITU-T Recommendation Q.732, clause 7 (1996), modified]



Reference REN/SPS-01039-14 (3ari1ie0.PDF)

Keywords

ISDN, ISUP, SS7, supplementary service, ECT

ETSI

Postal address

TehF-06921 Sophia Antipolis Cedex - FRANCE

(stan Office address eh ai) 650 Route des Lucioles - Sophia Antipolis Valbonne - FRANCE Tel.: +33 4 92 94 42 006 Fax +33 4 93 65 47 16 https://standards.it.Siret/Ni1348_623.562 00017/2NAE1742 C 199-4628-b385-713 Association à but non lucratif enregistrée à la 003 Sous-Préfecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr http://www.etsi.fr http://www.etsi.org

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

> © European Telecommunications Standards Institute 1998. All rights reserved.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://www.etsi.fr/ipr or http://www.etsi.org/ipr).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Signalling Protocols and Switching (SPS).

The present document is part 14 of a multi-part EN covering the ISDN User Part (ISUP) version 3 for the international interface, as identified below:

- Part 1: "Basic services";
- Part 2: "ISDN supplementary services";
- Part 3: "Calling Line Identification Presentation (CLIP) supplementary service";
- Part 4: "Calling Line Identification Restriction (CLIR) supplementary service";
- Part 5: "Connected Line Identification Presentation (COLP) supplementary service";
- Part 6: "Connected Line Identification Restriction (COLR) supplementary service";
- Part 7: "Terminal Portability (TP) supplementary service" (ten.al)
- Part 8: "User-to-User Signalling (UUS) supplementary service";
- Part 9: "Closed User Group (CUG) supplementary service", 1,3:2003
- Part 10: "Subaddressing (SUB) supplementary service" is/sist/a2a2f6b4-e199-4628-b385-
- Part 11: "Malicious Call Identification (MCID) supplementary service"3-2003
- Part 12: "Conference Call, add-on (CONF) supplementary service";
- Part 14: "Explicit Call Transfer (ECT) supplementary service";
- Part 15: "Diversion supplementary services";
- Part 16: "Call Hold (HOLD) supplementary service";
- Part 17: "Call Waiting (CW) supplementary service";
- Part 18: "Completion of Calls to Busy Subscriber (CCBS) supplementary service";
- Part 19: "Three party (3PTY) supplementary service".
- Part 20: "Completion of Calls on No Reply (CCNR) supplementary service";
- Part 31: "Protocol Implementation Conformance Statement (PICS) proforma specification for basic services"
- Part 32: "Test Suite Structure and Test Purposes (TSS&TP) specification for basic services"
- Part 33: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for basic services"
- Part 34: "Protocol Implementation Conformance Statement (PICS) proforma specification for supplementary services"
- Part 35: "Test Suite Structure and Test Purposes (TSS&TP) specification for supplementary services"
- Part 36: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for supplementary services"
 - NOTE: Part 13 has not been issued.

In accordance with CCITT Recommendation I.130, the following three level structure is used to describe the supplementary telecommunication services as provided by European public telecommunications operators under the pan-European Integrated Services Digital Network (ISDN):

- Stage 1: is an overall service description, from the user's stand-point;
- Stage 2: identifies the functional capabilities and information flows needed to support the service described in stage 1; and
- Stage 3: defines the signalling system protocols and switching functions needed to implement the service described in stage 1.

The present document details the stage three aspects (signalling system protocols and switching functions) needed to support the Explicit Call Transfer (ECT) supplementary service. The stage 1 and stage 2 aspects are detailed in ETS 300 367 and ETS 300 368, respectively.

| National transposition dates | | |
|--|------------------|--|
| Date of adoption of this EN: | 7 August 1998 | |
| Date of latest announcement of this EN (doa): | 30 November 1998 | |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 31 May 1999 | |
| Date of withdrawal of any conflicting National Standard (dow): | 31 May 1999 | |
| iTeh STANDARD PRE | CVIEW | |

Endorsement notice

SIST EN 300 356-14 V3.1.3:2003

The text of ITU-T Recommendation Q 732 clause 7 (1996), was approved by ETSI as an EN with agreed modifications as given below. 71311cdb38b6/sist-en-300-356-14-v3-1-3-2003

NOTE: New or modified text is indicated using sidebars. In addition, underlining and/or strike-out are used to highlight detailed modifications where necessary.

Global modifications to ITU-T Recommendation Q.732, clause 7

Insert the following two clauses (Scope and Normative references) at the start of clause 7:

1 Scope

This fourteenth part of EN 300 356 specifies the stage three of the Explicit Call Transfer (ECT) supplementary service for the pan-European Integrated Services Digital Network (ISDN) as provided by the European public telecommunications operators by means of the Signalling System No.7 protocol for the ISDN User Part (ISUP). Stage three identifies the protocol procedures and switching functions needed to support a telecommunication service (see CCITT Recommendation I.130 [1]).

The present document does not specify the additional protocol requirements where the service is provided to the user via a telecommunications network that is not an ISDN.

Although the present document applies only to the international interconnection, the specification of functions, formats and codes of messages and signals, and actions performed at originating and destination local exchanges are retained.

Formats, codes and procedures marked for national use are included for informative purposes for the international interface specification. If these items so marked are supported within a national network and operator's network, then it is proposed that they shall be supported in this manner.

NOTE: In the case where a national signalling system behaves differently, the international gateway exchange is to support both the concerned national and international network."

Charging aspects are outside the scope of the present document.

The ECT supplementary service enables a user who has two calls each of which can be an incoming call or an outgoing call, to connect together the other users in the two calls into one call 2a2f6b4-e199-4628-b385-

The ECT supplementary service is applicable to all circuit-switched telecommunication services.

2 Normative references

References may be made to:

- a) specific versions of publications (identified by date of publication, edition number, version number, etc.), in which case, subsequent revisions to the referenced document do not apply; or
- b) all versions up to and including the identified version (identified by "up to and including" before the version identity); or
- c) all versions subsequent to and including the identified version (identified by "onwards" following the version identity); or
- d) publications without mention of a specific version, in which case the latest version applies.

A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] CCITT Recommendation I.130 (1988): "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [2] ETS 300 121 (1992): "Integrated Services Digital Network (ISDN); Application of the ISDN User Part (ISUP) of CCITT Signalling System No.7 for international ISDN interconnections (ISUP version 1)".

| [3] | EN 300 356-1: "Integrated Services Digital Network (ISDN); Signalling System No.7; ISDN User Part (ISUP) version 3 for the international interface; Part 1: Basic services [ITU-T Recommendations Q.761 to Q.764 (1997), modified]". |
|-----|---|
| [4] | EN 300 356-2: "Integrated Services Digital Network (ISDN); Signalling System No.7; ISDN User Part (ISUP) version 3 for the international interface; Part 2: ISDN supplementary services [ITU-T Recommendation Q.730 (1997), modified]". |
| [5] | EN 300 403-1: "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 1: Protocol specification [ITU-T Recommendation Q.931 (1993), modified]". |

Throughout the text of ITU-T Recommendation Q.732, clause 7

Replace references as shown in table 1.

Table 1

| Reference in ITU-T Recommendation | Modified reference |
|-----------------------------------|--|
| Q.732, clause 7 | |
| ITU-T Recommendation Q.730 | ITU-T Recommendation Q.730 as modified by EN 300 356-2 [4] |
| ITU-T Recommendation Q.761 | ITU-T Recommendation Q.761 as modified by EN 300 356-1 [3] |
| ITU-T Recommendation Q.762 | ITU-T Recommendation Q.762 as modified by EN 300 356-1 [3] |
| ITU-T Recommendation Q.763 | ITU-T Recommendation Q.763 as modified by EN 300 356-1 [3] |
| ITU-T Recommendation Q.764 | ITU-T Recommendation Q.764 as modified by EN 300 356-1 [3] |
| ITU-T Recommendation Q.767 | ETS 300 121 [2] |
| ITU-T Recommendation Q.931 | ITU-T Recommendation Q.931 as modified by EN 300 403-1 [5] |
| i leh SI | ANDARD PREVIEW |

(standards.iteh.ai)

SIST EN 300 356-14 V3.1.3:2003

https://standards.iteh.ai/catalog/standards/sist/a2a2f6b4-e199-4628-b385-71311cdb38b6/sist-en-300-356-14-v3-1-3-2003

Annex ZA (informative): Coding of the compatibility information

ZA.1 Coding of the parameter compatibility information parameter

It is recommended that the parameter compatibility information for the call transfer number parameter should be coded as follows:

| | 0100 0 | 0101 | call transfer number. | |
|---|---------|-----------------------|---|--|
| b) | Instruc | struction indicators: | | |
| | bit | А | Transit at intermediate exchange indicator; | |
| | | 0 | transit interpretation; | |
| | bit | B: | Release call indicator; | |
| | | 0 | do not release call; | |
| | bit | C: | Send notification indicator; | |
| | | 0 | do not send notification; (standards.iteh.ai) | |
| | bit | D: | Discard message indicator; | |
| | | 0 | do not discard message (pass-0n), 356-14 V3.1.3:2003 https://standards.iteh.ai/catalog/standards/sist/a2a2f6b4-e199-4628-b385- | |
| | bit | E: | Discard parameter indicator 6/sist-en-300-356-14-v3-1-3-2003 | |
| | | 1 | discard parameter; | |
| | bits | GF: | Pass on not possible indicator; | |
| | | 10 | discard parameter; | |
| | bits | Л: | Broadband/narrowband interworking indicator; | |
| | | 00 | pass on. | |
| s recommended that the parameter compatibility information for the call transfer reference parame | | | | |

It is recommended that the parameter compatibility information for the call transfer reference parameter should be coded as follows:

a) Nth upgraded parameter:

a) Nth upgraded parameter:

- 0100 0011 call transfer reference.
- b) Instruction indicators:
 - bit A: Transit at intermediate exchange indicator;
 - 0 transit interpretation;
 - bit B: Release call indicator;
 - 0 do not release call;
 - bit C: Send notification indicator;
 - 0 do not send notification;