
**Liquefied natural gas (LNG) — Tanks
for on-board storage as a fuel for
automotive vehicles**

*Gaz naturel liquéfié (GNL) — Réservoirs pour le stockage à bord
comme carburant pour véhicules automobiles*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12991:2012

<https://standards.iteh.ai/catalog/standards/sist/8286cf97-356f-4c55-befc-7c427f7d97bd/iso-12991-2012>



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12991:2012

<https://standards.iteh.ai/catalog/standards/sist/8286cf97-356f-4c55-befc-7c427f7d97bd/iso-12991-2012>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Requirements	3
4.1 General requirements.....	3
4.2 Mechanical stresses.....	3
4.3 Thermal stresses.....	4
4.4 Materials.....	5
4.5 Design.....	5
4.6 Insulation.....	6
General requirements.....	6
4.7 Accessories.....	6
4.8 Manufacturing and assembly.....	7
5 Type tests	7
5.1 Approval of new designs.....	7
5.2 Inner tank burst pressure test.....	8
5.3 Holding time test.....	8
5.4 Maximum fuelling level test.....	8
5.5 Accessory type tests.....	8
6 Routine tests and inspection	8
6.1 General.....	8
6.2 Pressure test.....	9
6.3 Leak test.....	9
6.4 Verification of the dimensions.....	9
6.5 Destructive and non-destructive tests of welded joints.....	9
6.6 Visual inspection.....	10
7 Marking and labelling	10
7.1 Marking method.....	10
7.2 Inner tank markings.....	10
7.3 Outer jacket markings.....	10
7.4 Temporary markings for first fuelling.....	10
Annex A (normative) Fuel tank type tests	12
Annex B (normative) Accessory type tests	14
Bibliography	16

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12991 was prepared by Technical Committee ISO/TC 220, *Cryogenic vessels*.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 12991:2012](https://standards.iteh.ai/catalog/standards/sist/8286cf97-356f-4c55-befc-7c427f7d97bd/iso-12991-2012)

<https://standards.iteh.ai/catalog/standards/sist/8286cf97-356f-4c55-befc-7c427f7d97bd/iso-12991-2012>

Introduction

The fuel tanks described in this International Standard are intended to be used in conjunction with the fuelling system interface described in ISO 12617, which is under preparation.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 12991:2012](https://standards.iteh.ai/catalog/standards/sist/8286cf97-356f-4c55-befc-7c427f7d97bd/iso-12991-2012)

<https://standards.iteh.ai/catalog/standards/sist/8286cf97-356f-4c55-befc-7c427f7d97bd/iso-12991-2012>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12991:2012

<https://standards.iteh.ai/catalog/standards/sist/8286cf97-356f-4c55-befc-7c427f7d97bd/iso-12991-2012>

Liquefied natural gas (LNG) — Tanks for on-board storage as a fuel for automotive vehicles

1 Scope

This International Standard specifies the construction requirements for refillable fuel tanks for liquefied natural gas (LNG) used in vehicles as well as the testing methods required to ensure that a reasonable level of protection from loss of life and property resulting from fire and explosion is provided.

This International Standard is applicable to fuel tanks intended to be permanently attached to land vehicles but can be used as a guide for other mode of transport.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1176, *Road vehicles — Masses — vocabulary and codes*

ISO 1431-1, *Rubber, vulcanized or thermoplastic — Resistance to ozone cracking — Part 1: Static and dynamic strain testing*

ISO 2768-1, *General tolerances — Part 1: Tolerances for linear and angular dimensions without individual tolerance indications*

ISO 6957, *Copper alloys — Ammonia test for stress corrosion resistance*

ISO 9227, *Corrosion tests in artificial atmospheres — Salt spray tests*

ISO 21013-3, *Cryogenic vessels — Pressure-relief accessories for cryogenic service — Part 3: Sizing and capacity determination*

ISO 21014, *Cryogenic vessels — Cryogenic insulation performance*

ISO 21028-1, *Cryogenic vessels — Toughness requirements for materials at cryogenic temperature — Part 1: Temperatures below -80 degrees C*

ISO 21029-1:2004, *Cryogenic vessels — Transportable vacuum insulated vessels of not more than 1 000 litres volume — Part 1: Design, fabrication, inspection and tests*

ISO 23208, *Cryogenic vessels — Cleanliness for cryogenic service*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

accessory

device fixed directly to the inner tank or outer jacket of a fuel tank such as a pressure relief valve, shut-off valve, non-return valve or level gauge

3.2

boil-off management system

system that controls the boil-off of gas under normal conditions

3.3

burst pressure

pressure that causes the rupture of a pressure vessel subjected to a constant increase of pressure during a destructive test

3.4

design temperature

temperature of the inner tank, the outer jacket and all other accessories to which fabrication drawings, inspections and physical measurements such as volume are referred

3.5

fuel tank

vessel used for the storage of cryogenic liquefied natural gas (LNG) fuel

3.7

impermissible fault range

pressure range within which an unwanted event is to be expected

3.8

inner tank

part of the fuel tank that contains liquefied natural gas (LNG)

3.9

level gauge

device that measures the level of liquefied natural gas (LNG) in the fuel tank

3.10

maximum allowable working pressure

MAWP

maximum pressure to which a component is designed to be subjected to and which is the basis for determining the strength of the component under consideration

3.11

normal operating range

range planned for the process values

NOTE In the case of inner tanks, the normal operating range of the inner tank pressure is from 0 bar to the set pressure of the primary pressure relief valve, which is lower than or equal to the maximum allowable working pressure (MAWP) of the inner tank.

3.12

outer jacket

part of the fuel tank that encases the inner tank(s) and its insulation system

3.13

outer pressure

pressure acting on the outside of the inner tank or outer jacket

3.14

permissible fault range

range between the normal operating range and the impermissible fault range

3.15

pressure

pressure for which the value is equal to the algebraic difference between the absolute pressure and the atmospheric pressure

NOTE This is also known as gauge pressure.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12991:2012
<https://standards.iteh.ai/catalog/standards/sist/8286cf97-356f-4c55-befc-7c427f7d97bd/iso-12991-2012>

3.16**holding time**

time of the pressure increase in the inner tank measured from a starting pressure of 0 bar at the corresponding boiling point of liquefied natural gas (LNG) (-164° C) up to the maximum allowable working pressure (MAWP) of the inner tank

NOTE The holding time is a measure of the insulation performance of the fuel tank.

3.17**batch inner tank heads**

number (no more than 100) of tank heads produced by the same manufacturer, from the same material, and having the same dimensions

3.18**maximum mass**

a maximum authorized total mass, as defined in ISO 1176

4 Requirements**4.1 General requirements**

The fuel tank and its accessories shall function in a correct and safe way. It shall withstand and remain gas tight when subjected to the mechanical, thermal and chemical stresses specified in this International Standard.

iTeh STANDARD PREVIEW

4.2 Mechanical stresses (standards.iteh.ai)**4.2.1 Inner/outer pressure**

ISO 12991:2012

<https://standards.iteh.ai/catalog/standards/sist/8286cf97-356f-4c55-befc-7c427f7d97bd/iso-12991-2012>

4.2.1.1 Inner tank

The inner tank shall be designed to resist the following inner test pressure:

$$p_{\text{test}} = 1,3(\text{MAWP} + 1)$$

$$[p_{\text{test}} = 1,3(\text{MAWP} + 0,1)(\text{MPa})]$$

where

p_{test} is the test pressure, expressed in bar

MAWP is the maximum allowable working pressure of the inner tank, expressed in bar. The inner tank and its accessories shall be designed to resist an outer pressure of 1 bar.

4.2.1.2 Outer jacket

The outer jacket shall be designed to resist an outer pressure of 1 bar (see 4.5.2).

4.2.2 Accelerations**4.2.2.1 General**

The fuel tank and its accessories shall be mounted and protected so that the accelerations shown in Table 1 can be absorbed without structural damage to the fuel tank and its accessories. No uncontrolled release of LNG is permitted.

Table 1 — Accelerations

Vehicle categories	Accelerations
Vehicles of categories M1 and N1	20 g in the direction of travel
	8 g horizontally perpendicular to the direction of travel
Vehicles of categories M2 and N2	10 g in the direction of travel
	5 g horizontally perpendicular to the direction of travel
Vehicles of categories M3 and N3	6,6g in the direction of travel
	5 g horizontally perpendicular to the direction of travel
The vehicle categories include the following:	
— Category M1: Vehicles used for the transportation of passengers and comprising not more than eight seats in addition to the driver's seat.	
— Category M2: Vehicles used for the transportation of passengers, comprising more than eight seats in addition to the driver's seat, and having a maximum mass that does not exceed 5 000 kg.	
— Category M3: Vehicles used for the transportation of passengers, comprising more than eight seats in addition to the driver's seat, and having a maximum mass exceeding 5 000 kg.	
— Category N1: Vehicles used for the transportation of goods and having a maximum mass that does not exceed 3 500 kg	
— Category N2: Vehicles used for the transportation of goods and having a maximum mass exceeding 3 500 kg, but not exceeding 12 000 kg.	
— Category N3: Vehicles used for the transportation of goods and having a maximum mass exceeding 12 000 kg.	

(standards.iteh.ai)

4.2.2.2 Inner and outer support

When exposed to the accelerations described in Table 1, the stress in the support elements shall not exceed the minimum ultimate tensile strength of the material (R_m , calculated according with the linear stress model).

The allowable stress in the support elements may not have to be calculated if it can be demonstrated that the fuel tank supports the accelerations given in Table 1 without any structural damage to the inner tank or its supports.

Acceptable calculation methods include

- finite element,
- finite difference,
- boundary element, and
- established calculation method.

In these calculations static loads shall be substituted for static plus dynamic loads.

4.3 Thermal stresses

4.3.1 Design temperature

The design temperature of the inner tank, the outer jacket and the accessories shall be 20°C. In addition, the inner tank, the outer jacket and the accessories shall be designed to withstand a temperature range from the lowest to the highest possible operating temperatures that will be encountered in service.

4.3.2 Ambient temperature

The fuel tank shall be designed to withstand ambient temperatures ranging from -40°C to 85°C . If the fuel tank is to be installed in areas of internal heat sources such as the internal combustion engine compartment of a vehicle, the fuel tank shall be designed for an ambient temperature of 120°C , or a lower value if substantiated by calculations.

4.3.3 Operating temperature

The thermal stresses produced by the operating conditions shall be considered. The inner vessel and the other components that may be in contact with LNG shall be designed to operate at -196°C .

4.4 Materials

The materials of the fuel tank and its accessories shall be compatible, as applicable, with

- a) LNG, and
- b) other media and fluids found in a vehicle environment, such as coolants, brake fluid and battery acid.

Materials used at low temperatures shall meet the toughness requirements of ISO 21028-1. For non-metallic materials, low temperature suitability shall be validated by an experimental method, taking into account the service conditions.

The materials used for the outer jacket shall ensure the integrity of the insulation system and shall be made of austenitic stainless steel.

For the inner vessel if materials other than austenitic stainless steels are used it shall be ensured that the materials will resist all the in service fatigue load

A corrosion allowance does not need to be added for the inner tank. A corrosion allowance does not need to be added on other surfaces, if they are protected against corrosion.

For welded vessels, welds shall have properties equivalent to those specified for the parent material for all temperatures that the material may encounter.

4.5 Design

4.5.1 Design validation

Each type of vessel shall be validated in accordance with the design options specified in 10.1 of ISO 21029-1:2004 and in accordance with one of options given in 4.5.1.1 and 4.5.1.2.

4.5.1.1 Validation by calculation

This option requires calculation in accordance with 10.3 of ISO 21029-1:2004. Additional calculations are required to validate the design for accelerations in 4.2.2.

4.5.1.2 Validation by experiment method

This option requires validation in accordance with 10.4 of ISO 21029-1:2004 with the following modification; drop tests shall include a 9 m drop test of the fuel tank on the most critical area of the tank (other than the piping end) and a 3 m drop test on the piping end.

4.5.2 Inner tank and outer jacket

For the design of inner and outer tank the only acceptable options are

- the design is validated as per option 10.1.3 of ISO 21029-1:2004, especially the requirements of Table 3;