ETSI TR 136 913 V14.0.0 (2017-04)



Requirements for further advancements for Evolved Universal Terrestrial Radio Access (E-UTRA) (LTE-Advanced) (3GPP TR 36.913 version 14.0.0 Release 14) https://standards.iteh.ane

A GLOBAL INITIATIVE

Reference RTR/TSGR-0036913ve00 Keywords LTE

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from: http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommiteeSupportStaff.aspx

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.
All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP**TM and **LTE**TM are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Report (TR) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under http://webapp.etsi.org/key/queryform.asp.

Modal verbs terminology

In the present document "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the ETSt Drafting Rules (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intelle	ectual Property Rights	2
Forev	vord	2
Moda	ıl verbs terminology	2
Forev	vord	∠
1	Scope	5
2	References	
3	Definitions, symbols and abbreviations	
3.1	Definitions	
3.2	Symbols	
3.3	Abbreviations	
4	Introduction	5
5	Objective	<i>6</i>
6	Objective General requirements Capability-related requirements	8
	Contribution of the desired of the second of	
7 7.1	Capability-related requirements Peak Data Rate Latency C-plane latency U-Plane capacity U-Plane latency System performance requirements Spectrum efficiency Peak spectrum efficiency Average spectrum efficiency Cell edge user throughput VoIP capacity Mobility	٥
7.1	Latency	و
7.2.1	C-plane latency	8
7.2.1.1	C-plane capacity	
7.2.2	U-Plane latency	9
8	System morformon as magnine many states and seed all	
8.1	Spectrum officionay	 ر
8.1.1	Peak spectrum efficiency	د
8.1.2	Average spectrum efficiency	
8.1.3	Cell edge user throughput	10
8.1.4	VoIP capacity	11
8.2	Mobility	11
8.3	MobilityCoverage	11
8.4	Further Enhanced MBMS	11
8.5	Network synchronization	11
9	Deployment-related requirements	11
9.1	Deployment scenarios	11
9.2	Spectrum flexibility	
9.3	Spectrum deployment	
9.4	Co-existence and interworking with legacy RATs	
10	Requirements for E-UTRAN architecture and migration	
11	Radio Resource Management requirements	
12	Complexity requirements	
13	Cost-related requirements	
14	Service-related requirements	13
Anne	x A (informative): System performance evaluation model	1 4
A.1	System performance evaluation model	14
Anne	x B (informative): Change history	15
Histor	rv	16

Foreword

This Technical Report has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- Age control.

 Anne, i.e. technical

 Ally changes have been incorpo.

 All the standard standar the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

This document contains requirements for the further advancements for E-UTRA/E-UTRAN.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] (void)
- [2] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [3] 3GPP TR 25.913: "Requirements for Evolved UTRA (E-UTRA) and Evolved UTRAN (E-UTRA)
 - UTRAN)".
- [4] ITU-R Circular Letter 5/LCCE/2 on MT-Advanced
- [5] 3GPP TR 25.912: "Feasibility study for evolved Universal Terrestrial Radio Access (UTRA) and Universal Terrestrial Radio Access Network (UTRAN)".

3 Definitions, symbols and abbreviations

3.1 Definitions

Void

3.2 Symbols

Void

3.3 Abbreviations

For the purposes of the present document, the abbreviations defined in 3GPP TS 21.905 [2] and the following apply:

4 Introduction

At the 3GPP TSG RAN #39 meeting, the Study Item description on "Further Advancements for E-UTRA (LTE-Advanced)" was approved (RP-080137).

The justification of the Study Item was as follows;

IMT-Advanced is entering the phase of the process in ITU-R addressing the development of the terrestrial radio interface recommendations. To announce this stage of the process for IMT-Advanced, ITU-R has issued a Circular Letter(CL) to invite submission of candidate Radio Interface Technologies (RITs) or a set of RITs (SRITs) for IMT-Advanced. The key features of IMT-Advanced delineated in the CL are:

- a high degree of commonality of functionality worldwide while retaining the flexibility to support a wide range of services and applications in a cost efficient manner;
- compatibility of services within IMT and with fixed networks;
- capability of interworking with other radio access systems;
- high quality mobile services;
- user equipment suitable for worldwide use;
- user-friendly applications, services and equipment;
- worldwide roaming capability; and
- enhanced peak data rates to support advanced services and applications (100 Mbit/s for high and 1 Gbit/s for low mobility were established as targets for research).

The base line requirements for IMT-Advanced will be concluded in ITU-R WP 5D #2 (June 2008) and communicated in an Addendum to the Circular Letter in the July 2008 timeframe.

In the WRC07, the following spectrum bands were proposed as additions to the prior identified bands, and the parts of the existing and new bands are globally or regionally identified for IMT, which is the new root term to encompass both IMT-2000 and IMT-Advanced.

- 450 MHz band
- UHF band (698-960 MHz)
- 2.3 GHz band
- C-band(3400-4200 MHz)

- C-band(3400-4200 MHz)

In 3GPP, E-UTRA should be further evolved for the future releases in accordance with:

- 3GPP operator requirements for the evolution of E-UTRA
- The need to meet/exceed the IMT-Advanced capabilities.

Considering the above, 3GPP TSG-RAN should study further advancements for E-UTRA (LTE-Advanced) toward meeting:

- Requirements for IMT-Advanced and provide ITU-R with proposals of RITs or SRITs according to the defined ITU-R time schedule provided in the Circular Letter and its Addendums.
- 3GPP operators requirements for the evolution of E-UTRA

Objective 5

The objective of Further Advancements for E-UTRA is as follows;

- A) Define a framework for further advancements of E-UTRA and E-UTRAN (to be referred to as Advanced E-UTRA and Advanced EUTRAN considering:
 - The time schedule of ITU-R
 - That the work on Advanced E-UTRA and Advanced E-UTRAN must not introduce any delay to the completion of the Release 8 specification of E-UTRA and E-UTRAN

- That the general enhancements of specifications for Release 8 E-UTRA and E-UTRAN are maintained and progressed in a focused and efficient manner.
- B) Define requirements for Advanced E-UTRA and Advanced E-UTRAN based on the ITU-R requirements for IMT-Advanced as well as 3GPP operators own requirements for advancing Release 8 E-UTRA AND E-UTRAN considering:
 - E-UTRA radio technology and architecture improvements
 - Support for all radio modes of operation
 - Interworking with legacy RATs (scenarios and performance requirements)
 - Backward compatibility of Advanced E-UTRA and Advanced E-UTRAN with Release 8 E-UTRA and E-UTRAN i.e.
 - an Release 8 E-UTRA terminal can work in an Advanced E-UTRAN,
 - an Advanced E-UTRA terminal can work in an Release 8 E-UTRAN and
 - non-backward compatible elements could be considered based on RAN decision
 - Newly identified frequency bands and existing frequency bands, and their advantages and limitations, in particular, the consideration of the WRC-07 conclusions, to ensure that Advanced E-UTRA can accommodate radio channel bandwidths commensurate with the availability in parts of the world of wideband channels in the spectrum allocations (above 20 MHz) and at the same time being mindful on the need to accommodate those parts of the world where the spectrum allocations will not have availability of wideband channels
- C) Identify potential solutions, technologies for the Advanced E-UTRA and Advanced E-UTRAN. The study areas include:
 - Physical layer
 - Radio interface layer 2 and RRC
 - E-UTRAN architecture
 - RF, including Aspects of wider channel bandwidth than 20 MHz
 - Advanced system concepts
- D) To develop documents that will serve as a basis for the documentation to be submitted to ITU-R to provide the 3GPP proposals for IMT-Advanced:
 - 1) An "Early Proposal" submission that would be sent to ITU-R, to be agreed at RAN #41 (9-12 September 2008), for submission to WP 5D #3 (8-15 October 2008).
 - 2) A "Complete Technology" submission that would be sent to ITU-R, to be agreed at RAN #44 (26-29 May 2009), for submission to WP 5D #5 (planned for 10-17 June 2009).
 - 3) A "Final" submission to incorporate updates, additional specific details or feature additions, *and* the required self-evaluation that would be sent to ITU-R, to be agreed at RAN #45 (22-25 September 2009), for submission to WP 5D #6 (planned for 13-20 Oct 2009).
 - 3GPP should take note, that by ITU-R convention, the formal submission deadline for ITU-R meetings has been established as 16:00 hours UTC, seven calendar days prior to the start of the meeting.
- E) Make recommendations for future WIs
- F) For reference, the Circular Letter as received from the ITU-R (and future Addendums to the same) are annexed to this Work Item and should become an integral part of the WI.

6 General requirements

The following general requirements are valid for Advanced E-UTRA and Advanced E-UTRAN

- Advanced E-UTRA and Advanced E-UTRAN shall be an evolution of Release 8 E-UTRA and E-UTRAN
- All relevant requirement in [3] are valid also for Advanced E-UTRA and Advanced E-UTRAN
- Advanced E-UTRA and Advanced E-UTRAN shall meet or exceed IMT-Advanced requirements within the ITU-R time plan

The expectancy is that Advanced E-UTRA should provide substantially higher performance compared to what is expected to be the IMT-Advanced requirements in ITU-R. The values provided in clauses 7 and 8 have been expressed as preferred performance of Advanced E-UTRA. These values are recognised as being very ambitious, especially in light of the ITU-R time plan, and the performance evaluation results generated for LTE R8, but are adopted as long term target for Advanced E-UTRA"

7 Capability-related requirements

7.1 Peak Data Rate

The peak data rate is the maximum data rate to be supported from a system requirement viewpoint (i.e. not from radio performance requirement viewpoint) regardless of radio interface parameters such as the transmission bandwidth and antenna configuration.

Advanced E-UTRA should support significantly increased instantaneous peak data rates.

At a minimum, Advanced E-UTRA should support the key feature of IMT-Advanced which is stated in the Circular Letter from the ITU-R as "enhanced peak data rates to support advanced services and applications (100 Mbit/s for high and 1 Gbit/s for low mobility were established as targets for research)"

The system should target a downlink peak data rate of 1 Gbps and an uplink peak data rate of 500 Mbps.

7.2 Latency

7.2.1 C-plane latency

The overall C-Plane latency shall be significantly decreased compared to EPS Rel-8. The C-Plane latency takes into account RAN and CN latencies (excluding the transfer latency on the S1 interface) in unloaded conditions.

The target for transition time from Idle mode (with IP address allocated) to Connected mode is less than 50 ms including the establishment of the user plane (excluding the S1 transfer delay).

The target for the transition from a "dormant state" in Connected Mode (i.e. DRX substate in Connected Mode in E-UTRAN) is less than 10 ms (excluding the DRX delay).