ETSI TR 135 934 V14.0.0 (2017-04)



Universal Mobile Telecommunications System (UMTS);

Specification of the TUAK algorithm set:
A second example algorithm set for the 3GPP authentication and key generation functions f1, f1*, f2, f3, f4, f5 and f5*;
Document 4: Report on the design and evaluation (3GPP TR 35.934 version 14.0.0 Release 14)



Reference RTR/TSGS-0335934ve00 Keywords LTE,SECURITY,UMTS

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from: http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommiteeSupportStaff.aspx

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.
All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP**TM and **LTE**TM are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members
 GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Report (TR) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under http://webapp.etsi.org/key/queryform.asp.

Modal verbs terminology

In the present document "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the ETSI Deafting Rules (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

шеп	lectual Property Rights	
	word	
	al verbs terminology	
	word	
1	Scope	6
2	References	6
3	Definitions and abbreviations	
3.1	Definitions	
3.2	Abbreviations	
4	Structure of this report	
5	Background to the design and evaluation work	
6	Summary of algorithm requirements.	9
6.0	Introduction	
6.1	General requirements for 3GPP cryptographic functions and algorithms (as stated for MILENAGE)	9
6.2	Authentication and key agreement functions (as stated for MILENAGE)	9
6.2.0	Authentication and key agreement functions (as stated for MILENAGE) Introduction Implementation and operational considerations Type of algorithm 1	9
6.2.1	Implementation and operational considerations.	10
6.2.2	Type of algorithm	10
6.2.2.	1 fl	10
6.2.2.	$2 fl^*$	10
6.2.2.	3 t2 2 20 20 20 20 20 20 20 20 20 20 20 20	10
6.2.2.	4 f3	10
6.2.2.	5 f4 (8)	10
6.2.2.	6 f5	11
6.2.2.	,	11
	Tuak-specific requirements	11
6.3	D'Comme Com MI ENACE	11
6.3.1	Difference from MILENAGE	11
6.3.2	256-bit key support	11
6.3.3	Operator customization	11
6.3.4	Implementation and operational considerations.	
7	Overview of the Tuak design	
8	Design rationale	
8.0	Introduction	
8.1	Brand new design, or design based on an existing public algorithm?	13
8.2	Block cipher, stream cipher, MAC or hash function?	
8.3	Which hash function?	
8.4	What sort of Keccak function to use	
8.5	Keccak parameter selection	14
8.6	Security evaluation of Keccak	15
8.6.0	Introduction	15
8.6.1	What about the internet stories about NIST weakening SHA-3?	15
8.7	A note on IPR	16
8.7.1	Keccak IPR	
8.7.2	Tuak IPR	
8.8	Padding bits	
8.9	Flexible input and output sizes	
8.10	Operator customization	
	•	
9	Independent security and performance evaluation	
9.0	Introduction	
9.1	Independent security evaluation	
9.2	Independent SIM card performance evaluation	17

10	More no	otes on implementation and side channel attacks	18
10.1	Prote	ecting implementations against side channel attacks	18
10.2	Softw	vare implementation and the NIST SHA-3 standard	18
11	Conclus	sions	18
Annex A:		Change history	19
Histo	ry		20

Helps: Sandards iteliands in the sandards in the sandards iteliands iteliands iteliands

Foreword

This Technical Report has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- ance, i.e. technical ally changes have been incorporated by the standard standards and the standards a the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document (together with three accompanying documents, [8], [9] and [10] describes the design rationale, and presents evaluation results, on the Tuak algorithm set [5] – a second example set of algorithms which may be used as the authentication and key generation functions f1, f1*, f2, f3, f4, f5 and f5*, e.g. as an alternative to MILENAGE.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 33.102: "3G Security; Security Architecture", (available at http://www.3gpp.org/ftp/specs/html-info/33102.htm).
- [3] 3G TS 33.105 (V 3.4.0) (2000-07): "3G Security: Cryptographic Algorithm Requirements (Release 1999)".
- [4] 3GPP TS 35.206: "3G Security; Specification of the MILENAGE algorithm set: An example algorithm set for the 3GPP authentication and key generation functions f1, f1*, f2, f3, f4, f5 and f5*; Document 2: Algorithm specification", (available at http://www.3gpp.org/ftp/Specs/html-info/35206.htm).
- [5] 3GPP TS 35.231: "3G Security; Specification of the Tuak algorithm set: A second example algorithm set for the 3GPP authentication and key generation functions f1, f1*, f2, f3, f4, f5 and f5*; Document 1: Algorithm specification", (available at http://www.3gpp.org/ftp/Specs/html-info/35231.htm).
- [6] 3GPP TS 35.232: "3G Security; Specification of the Tuak algorithm set: A second example algorithm set for the 3GPP authentication and key generation functions f1, f1*, f2, f3, f4, f5 and f5*; Document 2: Implementers' Test Data", (available at http://www.3gpp.org/ftp/Specs/html-info/35232.htm).
- [7] 3GPP TS 35.233: "3G Security; Specification of the Tuak algorithm set: A second example algorithm set for the 3GPP authentication and key generation functions f1, f1*, f2, f3, f4, f5 and f5*; Document 3: Design Conformance Test Data", (available at http://www.3gpp.org/ftp/Specs/html-info/35233.htm).
- [8] "Security Assessment of Tuak Algorithm Set", Guang Gong, Kalikinkar Mandal, Yin Tan and Teng Wu, included as an accompanying document to the present report (available at http://www.3gpp.org/ftp/Specs/archive/35_series/35.935/SAGE_report/Secassesment.zip).
- [9] "Performance Evaluation of the Tuak algorithm in support of the ETSI SAGE standardisation group", Keith Mayes, included as an accompanying document to the present report (available at http://www.3gpp.org/ftp/Specs/archive/35 series/35.936/SAGE report/Perfevaluation.zip).
- [10] "Performance Evaluation of the Tuak algorithm in support of the ETSI SAGE standardisation group extension report", Keith Mayes, included as an accompanying document to the present report (available at http://www.3gpp.org/ftp/Specs/archive/35_series/35.936/SAGE_report/Perfevaluationext.zip).

[11]	"Note on side-channel attacks and their countermeasures", G. Bertoni, J. Daemen, M. Peeters, G. van Assche (available at http://keccak.noekeon.org/NoteSideChannelAttacks.pdf).
[12]	"Building power analysis resistant implementations of Keccak", G. Bertoni, J. Daemen, M. Peeters, G. van Assche (available at http://csrc.nist.gov/groups/ST/hash/sha-3/Round2/Aug2010/documents/papers/BERTONI_KeccakAntiDPA.pdf).
[13]	Wassenaar Arrangement on Export Controls for Conventional Arms and Dual-Use Goods and Technologies, http://www.wassenaar.org .
[14]	"Announcing Draft Federal Information Processing Standard (FIPS) 202, SHA-3 Standard: Permutation-Based Hash and Extendable-Output Functions, and Draft Revision of the Applicability Clause of FIPS 180-4, Secure Hash Standard, and Request for Comments", NIST, 28th May 2014, available at https://www.federalregister.gov/articles/2014/05/28/2014-12336/announcing-draft-federal-information-processing-standard-fips-202-sha-3-standard-permutation-based .
[15]	"Early Symmetric Crypto (ESC) seminar 2013" (available at https://www.cryptolux.org/mediawiki-esc2013/index.php/ESC_2013)
[16]	"The KECCAK sponge function family" (available at http://www.noekeon.org)
[17]	https://www.cdt.org/blogs/joseph-lorenzo-hall/2409-nist-sha-3
[18]	http://yro.slashdot.org/story/13/09/28/0219235/did-nist-cripple-sha-3
[19]	https://www.schneier.com/blog/archives/2013/10/will_keccak_sha-3.html
[20]	http://keccak.noekeon.org/yes_this_is_keccak.html

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

Keccak: algorithm selected as the winner of the SHA-3 competition

MILENAGE: previously designed example algorithm set for the 3GPP Authentication and Key Generation Functions

TOPc: value derived from TOP and K and used within the computations of the functions f1, f1*, f2, f3, f4, f5 and f5*

Tuak: newly designed example algorithm set for the 3GPP Authentication and Key Generation Functions. It should be pronounced like "too-ack"

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

AES Advanced Encryption Standard block cipher
AK Anonymity Key
AMF Algorithm Management Field
AuC Authentication Centre

CK Cipher Key

CPU Central Processing Unit

DEMA Differential Electromagnetic Analysis

DPA Differential Power Analysis

IC Integrated Circuit

IK Integrity Key

K Long lived subscriber unique key MAC Message Authentication Code

MAC-A MAC for normal authentication vectors MAC-S MAC for resynchronization vectors

MULTOS Multi-application smart card operating system
NIST National Institute of Standards and Technology

NSA National Security Agency NVM Non-Volatile Memory RAM Random Access Memory

RAND Random input parameter to authentication and key generation functions

RES Response value

RNC Radio Network Controller ROM Read-Only Memory

SAGE Security Algorithms Group of Experts

NOTE: This is an ETSI Technical Committee.

SHA-2 Secure Hash Algorithm already standardized by NIST
SHA-3 Secure Hash Algorithm soon to be standardized by NIST
TOP Tuak Operator Variant Algorithm Configuration Field

SEMA Simple Electromagnetic Analysis
SIM Subscriber Identity Module
SPA Simple Power Analysis
SQN Sequence Number

UICC Universal Integrated Circuit Card
USIM Universal Subscriber Identity Module

XMAC Expected MAC value

4 Structure of this report

The main content of the present document is organized as follows:

- Clause 5 and 6 give the requirements and background that were considered during the design of Tuak first
 recalling the functional and performance requirements that were used for MILENAGE, then noting some
 differences and additional points that apply for Tuak.
- Clause 7 gives a brief overview of the Tuak design.
- Clause 8 runs through choices made during the design of Tuak, and the reasons behind those choices.
- Clause 9 introduces independent assessments that have been carried out on the security and performance of Tuak. The full independent assessment reports are included as companion documents to this one.
- Clause 10 gives some further observations on software implementation and protection against side channel attacks.
- Clause 11 concludes with an overall assessment of Tuak's fitness for purpose.

Three further documents [8], [9] and [10] complete the present document, as explained in clause 9.

5 Background to the design and evaluation work

The 3rd Generation Partnership Project (3GPP) is a global initiative dedicated to the development of specifications for the next generations of cellular mobile systems. Integration of strong security services is an important feature of this system and the general security architecture is defined in ref. [2]. The implementation of these security services should be based on a variety of cryptographic functions/algorithms.

Out of the full algorithm suite, only the UMTS encryption algorithms (f8) and the UMTS integrity algorithms (f9) are fully standardized. f0 represents a random number generation algorithm, and has no standardization or interoperability

requirements at all. The remaining cryptographic functions for authentication and key agreement (fI - f5*) are allocated to the Authentication Centre (AuC) and the USIM; this means that the functions are proprietary to the home environment, and there is no need for formal standardization of these algorithms. However, there are good reasons to have a well trusted example set of functions available for this purpose, for use by operators that choose not to develop their own solutions. The MILENAGE algorithm set [4] was created to meet this need.

There are also good reasons to have a second trusted example set of $(fI - f5^*)$ algorithms available:

- To have a fallback already in place in case MILENAGE is ever compromised.
- In particular, for the embedded UICC, where it may be sensible to have two strong algorithms installed on the platform and available for selection by subsequently loaded USIM applications. This provides choice to operators; it also provides resilience against future cryptanalysis of either algorithm, in devices that may have a long lifetime in the field.

The Tuak algorithm set [5], [6] and [7] has been created to serve as this second trusted example algorithm set.

6 Summary of algorithm requirements

6.0 Introduction

When MILENAGE was created, the requirements specification was taken from [3]. Clauses 6.1 and 6.2 below reproduce the main requirements necessary to understand the present document. Clause 6.3 describes some new requirements that came into play when designing Tuak.

6.1 General requirements for 3GPP cryptographic functions and algorithms (as stated for MILENAGE)

The functions should be designed with a view to their continued use for a period of at least 20 years. Successful attacks with a workload significantly less than exhaustive key search through the effective key space should be impossible.

The designers of above functions should design algorithms to a strength that reflects the above qualitative requirements.

Legal restrictions on the use or export of equipment containing cryptographic functions may prevent the use of such equipment in certain countries.

It is the intention that UE and USIMs that embody such algorithms should be free from restrictions on export or use, in order to allow the free circulation of 3G terminals. Network equipment, including RNC and AuC, may be expected to come under more stringent restrictions. It is the intention that RNC and AuC that embody such algorithms should be exportable under the conditions of the Wassenaar Arrangement, see reference [13].

6.2 Authentication and key agreement functions (as stated for MILENAGE)

6.2.0 Introduction

The mechanisms for authentication and key agreement described in clause 6.3 of [2] require the following cryptographic functions:

- f1 The network authentication function;
- f1* The re-synchronization message authentication function;
- *f*2 The user authentication function;