

SLOVENSKI STANDARD
oSIST prEN 301 893 V1.8.5:2017
01-julij-2017

5 GHz RLAN - Harmonizirani standard, ki zajema bistvene zahteve člena 3.2 direktive 2014/53/EU

5 GHz RLAN - Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: [oSIST prEN 301 893 V1.8.5:2017](https://standards.iteh.ai/catalog/standards/sist/ecb63ac43-7610-4204-88cb-756d0ebcd5cc/osit-pr-en-301-893-v1-8-5-2017) **ETSI EN 301 893 V1.8.5 (2017-04)**
<https://standards.iteh.ai/catalog/standards/sist/ecb63ac43-7610-4204-88cb-756d0ebcd5cc/osit-pr-en-301-893-v1-8-5-2017>

ICS:

33.060.01	Radijske komunikacije na splošno	Radiocommunications in general
35.110	Omreževanje	Networking

oSIST prEN 301 893 V1.8.5:2017 **en**

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN 301 893 V1.8.5:2017

<https://standards.iteh.ai/catalog/standards/sist/ec63ac43-7b10-4204-88cb-756d0ebcd5cc/osist-pren-301-893-v1-8-5-2017>

Draft ETSI EN 301 893 V1.8.5 (2017-04)



**5 GHz RLAN;
Harmonised Standard covering the essential requirements
of article 3.2 of Directive 2014/53/EU**

[oSIST prEN 301 893 V1.8.5:2017](#)
<https://standards.iteh.ai/catalog/standards/sist/ec63ac43-7b10-4204-88cb-756d0ebcd5cc/osist-pren-301-893-v1-8-5-2017>

Reference

REN/BRAN-00230013

Keywords

access, broadband, LAN, layer 1, radio,
regulation, testing***ETSI***650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse N° 7303/88**iTeh STANDARD PREVIEW**
(standards.iteh.ai)

[oSIST prEN 301 893 V1.8.5:2017](#)
<https://standards.iteh.ai/catalog/standards/sist/ec63ac43-7b10-4204-88cb-756d0ebcd5cc/osit-pren-301-893-v1-8-5-2017>

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
oneM2M logo is protected for the benefit of its Members
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology.....	8
Introduction	8
1 Scope	10
2 References	10
2.1 Normative references	10
2.2 Informative references.....	10
3 Definitions, symbols and abbreviations	12
3.1 Definitions	12
3.2 Symbols	14
3.3 Abbreviations	15
4 Technical requirements specifications	15
4.1 Environmental profile.....	15
4.2 Conformance requirements	16
4.2.1 Centre frequencies	16
4.2.1.1 General	16
4.2.1.2 Definition	16
4.2.1.3 Limits	16
4.2.1.4 Conformance	16
4.2.2 Nominal Channel Bandwidth and Occupied Channel Bandwidth	16
4.2.2.1 Definition	16
4.2.2.2 Limits	16
4.2.2.3 Conformance	16
4.2.3 RF output power/Transmit Power Control (TPC) and power density	17
4.2.3.1 Definitions.....	17
4.2.3.1.1 RF Output Power	17
4.2.3.1.2 Transmit Power Control (TPC)	17
4.2.3.1.3 Power Density	17
4.2.3.2 Limits	17
4.2.3.2.1 General	17
4.2.3.2.2 Limits for RF output power and power density at the highest power level	17
4.2.3.2.3 Limit for RF output power at the lowest power level of the TPC range.....	18
4.2.3.3 Conformance	18
4.2.4 Transmitter unwanted emissions.....	18
4.2.4.1 Transmitter unwanted emissions outside the 5 GHz RLAN bands	18
4.2.4.1.1 Definition.....	18
4.2.4.1.2 Limits	18
4.2.4.1.3 Conformance	18
4.2.4.2 Transmitter unwanted emissions within the 5 GHz RLAN bands	19
4.2.4.2.1 Definition.....	19
4.2.4.2.2 Limits	19
4.2.4.2.3 Conformance	19
4.2.5 Receiver spurious emissions	19
4.2.5.1 Definition	19
4.2.5.2 Limits	20
4.2.5.3 Conformance	20
4.2.6 Dynamic Frequency Selection (DFS)	20
4.2.6.1 Introduction.....	20
4.2.6.1.1 General	20
4.2.6.1.2 Applicable frequency range.....	20
4.2.6.1.3 DFS operational modes	20
4.2.6.1.4 DFS operation.....	21
4.2.6.2 DFS technical requirements specifications	22

4.2.6.2.1	Applicability	22
4.2.6.2.2	Channel Availability Check.....	22
4.2.6.2.2.1	Definition	22
4.2.6.2.2.2	Limit	22
4.2.6.2.2.3	Conformance.....	23
4.2.6.2.3	Off-Channel CAC (Off-Channel Channel Availability Check).....	23
4.2.6.2.3.1	Definition.....	23
4.2.6.2.3.2	Limit	23
4.2.6.2.3.3	Conformance.....	23
4.2.6.2.4	In-Service Monitoring	23
4.2.6.2.4.1	Definition.....	23
4.2.6.2.4.2	Limit	23
4.2.6.2.4.3	Conformance.....	23
4.2.6.2.5	Channel Shutdown.....	23
4.2.6.2.5.1	Definition	23
4.2.6.2.5.2	Limit	24
4.2.6.2.5.3	Conformance.....	24
4.2.6.2.6	Non-Occupancy Period	24
4.2.6.2.6.1	Definition	24
4.2.6.2.6.2	Limit	24
4.2.6.2.6.3	Conformance.....	24
4.2.6.2.7	Uniform Spreading.....	24
4.2.6.2.7.1	Definition	24
4.2.6.2.7.2	Limit	25
4.2.7	Adaptivity (Channel Access Mechanism).....	25
4.2.7.1	Applicability.....	25
4.2.7.2	Definition	25
4.2.7.3	Requirements and limits.....	25
4.2.7.3.1	Frame Based Equipment.....	25
4.2.7.3.2	Load Based Equipment.....	26
4.2.7.3.3	Short Control Signalling Transmissions.....	28
4.2.7.3.3.1	Definition	28
4.2.7.3.3.2	Limits /standards.iteh.ai/catalog/standards/sist/ec63ac43-7b10-4204-88cb-75fd0ebcd5cc/osit-pren-301-893-v1.8-5-2017	28
4.2.7.4	Conformance	29
4.2.8	Receiver Blocking	29
4.2.8.1	Applicability.....	29
4.2.8.2	Definition	29
4.2.8.3	Performance Criteria	29
4.2.8.4	Limits	29
4.2.8.5	Conformance	29
4.2.9	User Access Restrictions	29
4.2.9.1	Definition	29
4.2.9.2	Requirement	30
4.2.10	Geo-location capability.....	30
4.2.10.1	Applicability.....	30
4.2.10.2	Definition	30
4.2.10.3	Requirements	30
4.2.10.4	Conformance	30
5	Testing for compliance with technical requirements.....	31
5.1	Environmental conditions for testing	31
5.1.1	Introduction.....	31
5.1.2	Normal test conditions	31
5.1.2.1	Normal temperature and humidity	31
5.1.2.2	Normal power source	31
5.1.3	Extreme test conditions.....	31
5.2	Interpretation of the measurement results	31
5.3	Definition of other test conditions	32
5.3.1	Test sequences and traffic load	32
5.3.1.1	General test transmission sequences	32
5.3.1.2	Test transmission sequences for DFS tests.....	32
5.3.2	Test channels	32

5.3.3	Antennas	33
5.3.3.1	Integrated and dedicated antennas.....	33
5.3.3.2	Transmit operating modes	34
5.3.3.2.1	Operating mode 1 (single antenna).....	34
5.3.3.2.2	Operating mode 2 (multiple antennas, no beamforming)	34
5.3.3.2.3	Operating mode 3 (multiple antennas, with beamforming)	34
5.3.4	Presentation of equipment	34
5.3.5	Conducted measurements, radiated measurements, relative measurements	34
5.4	Essential radio test suites.....	34
5.4.1	Product information	34
5.4.2	Carrier frequencies.....	36
5.4.2.1	Test conditions	36
5.4.2.2	Test methods	36
5.4.2.2.1	Conducted measurement.....	36
5.4.2.2.2	Radiated measurement.....	37
5.4.3	Occupied Channel Bandwidth	37
5.4.3.1	Test conditions	37
5.4.3.2	Test method.....	37
5.4.3.2.1	Conducted measurement.....	37
5.4.3.2.2	Radiated measurement.....	38
5.4.4	RF output power, Transmit Power Control (TPC) and power density.....	38
5.4.4.1	Test conditions	38
5.4.4.2	Test method.....	39
5.4.4.2.1	Conducted measurement.....	39
5.4.4.2.2	Radiated measurement.....	49
5.4.5	Transmitter unwanted emissions outside the 5 GHz RLAN bands.....	49
5.4.5.1	Test conditions.....	49
5.4.5.2	Test method.....	49
5.4.5.2.1	Conducted measurement.....	49
5.4.5.2.2	Radiated measurement.....	52
5.4.6	Transmitter unwanted emissions within the 5 GHz RLAN bands	52
5.4.6.1	Test conditions	52
5.4.6.2	Test method http://standards.iteh.ai/catalog/standards/sist/ec63ac43-7b10-4204-88cb-0d5cc/ossit-pren-301-893-v1-8-5-2017	52
5.4.6.2.1	Conducted measurement.....	52
5.4.6.2.2	Radiated measurement.....	53
5.4.7	Receiver spurious emissions	53
5.4.7.1	Test conditions	53
5.4.7.2	Test method.....	54
5.4.7.2.1	Conducted measurement.....	54
5.4.7.2.2	Radiated measurement.....	56
5.4.8	Dynamic Frequency Selection (DFS)	56
5.4.8.1	Test conditions	56
5.4.8.1.1	General	56
5.4.8.1.2	Selection of radar test signals	56
5.4.8.1.3	Test set-ups.....	56
5.4.8.2	Test method	58
5.4.8.2.1	Conducted measurement.....	58
5.4.8.2.2	Radiated measurement.....	65
5.4.9	Adaptivity (channel access mechanism)	65
5.4.9.1	Test conditions	65
5.4.9.2	Test method.....	65
5.4.9.2.1	Conducted measurements	65
5.4.9.2.2	Generic test procedure for measuring channel/frequency usage	67
5.4.9.2.3	Radiated measurements	68
5.4.10	Receiver Blocking	68
5.4.10.1	Test conditions	68
5.4.10.2	Test Method	68
5.4.10.2.1	Conducted measurements	68
5.4.10.2.2	Radiated measurements	70

Annex A (informative): Relationship between the present document and the essential requirements of Directive 2014/53/EU

Annex B (normative):	Test sites and arrangements for radiated measurements.....	73
B.1	Introduction	73
B.2	Radiation test sites.....	73
B.2.1	Open Area Test Site (OATS)	73
B.2.2	Semi Anechoic Room.....	74
B.2.3	Fully Anechoic Room (FAR)	75
B.2.4	Measurement Distance	76
B.3	Antennas.....	77
B.3.1	Introduction	77
B.3.2	Measurement antenna.....	77
B.3.3	Substitution antenna	77
B.4	Test fixture	77
B.4.1	Introduction	77
B.4.2	Description of the test fixture	78
B.4.3	Using the test fixture for relative measurements	78
B.5	Guidance on the use of radiation test sites	78
B.5.1	Introduction	78
B.5.2	Power supplies for the battery powered UUT	78
B.5.3	Site preparation	79
B.6	Coupling of signals.....	79
B.6.1	General	79
B.6.2	Data Signals.....	79
B.7	Interference Signal used for Adaptivity Tests.....	80
iTech STANDARD PREVIEW		
Annex C (normative):	Procedures for radiated measurements.....	81
C.1	Introduction	81
C.2	Radiated measurements in an OATS or SAR.....	81
C.3	Radiated measurements in a FAR	82
C.4	Substitution measurement	82
C.5	Guidance for testing technical requirements	82
C.5.1	Essential radio test suites and corresponding test sites.....	82
C.5.2	Guidance for testing Adaptivity (Channel Access Mechanism).....	83
C.5.2.1	Introduction.....	83
C.5.2.2	Measurement Set-up	83
C.5.2.3	Calibration of the measurement Set-up.....	83
C.5.2.4	Test method	84
C.5.3	Guidance for testing Receiver Blocking.....	84
C.5.3.1	Introduction.....	84
C.5.3.2	Measurement Set-up	84
C.5.3.3	Calibration of the measurement Set-up.....	84
C.5.3.4	Test method	85
Annex D (normative):	DFS parameters	86
Annex E:	Void	89
Annex F (informative):	Application form for testing.....	90
F.0	The right to copy	90
F.1	Introduction	90
F.2	Information as required by ETSI EN 301 893 (V1.9.1), clause 5.4.1	90
F.3	Additional information provided by the manufacturer.....	97
F.3.1	Modulation	97

F.3.2	Duty Cycle.....	97
F.3.3	About the UUT	98
F.3.4	List of ancillary and/or support equipment provided by the manufacturer.....	98
Annex G (informative):	Bibliography.....	99
Annex H (informative):	Change history	100
History		101

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN 301 893 V1.8.5:2017](#)
<https://standards.iteh.ai/catalog/standards/sist/ec63ac43-7b10-4204-88cb-756d0ebcd5cc/osist-pr-en-301-893-v1-8-5-2017>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Broadband Radio Access Networks (BRAN), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.2] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

ITEH STANDARD REVIEW
(standards.iteh.ai)

National transposition dates	
<small>oSIST prEN 301 893 V1.8.5:2017 https://standards.iteh.ai/catalog/standards/sist/ecb63ac43-7b10-4204-88cb-756d0ebcd5cc/osist-pren-301-893-v1-8-5-2017</small>	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

5 GHz wireless access systems (WAS) including RLAN equipment are used in wireless local area networks which provide high speed data communications in between devices connected to the wireless infrastructure. The present document also addresses ad-hoc networking where devices communicate directly with each other, without the use of a wireless infrastructure.

The spectrum usage conditions for equipment within the scope of the present document are set in the ECC Decision (04)08 [i.6] and the Commission Decision 2005/513/EC [i.7] as amended by the Commission Decision 2007/90/EC [i.8].

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN 301 893 V1.8.5:2017](#)
<https://standards.iteh.ai/catalog/standards/sist/ec63ac43-7b10-4204-88cb-756d0ebcd5cc/osist-pr-en-301-893-v1-8-5-2017>

1 Scope

The present document specifies technical characteristics and methods of measurements for 5 GHz wireless access systems (WAS) including RLAN equipment.

The present document also describes spectrum access requirements to facilitate spectrum sharing with other equipment.

These radio equipment are capable of operating in all or parts of the frequency bands given in table 1.

Table 1: Service frequency bands

Service frequency bands	
Transmit	5 150 MHz to 5 350 MHz
Receive	5 150 MHz to 5 350 MHz
Transmit	5 470 MHz to 5 725 MHz
Receive	5 470 MHz to 5 725 MHz

The present document covers the essential requirements of article 3.2 of Directive 2014/53/EU [i.1] under the conditions identified in annex A.

2 References

2.1 Normative references

Help STANDARD PREVIEW (standards.iteh.ai)

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found ~~to be publicly available in the~~ expected location might be found at http://docbox.etsi.org/Reference_standards.iteh.ai/catalog/standards/sist/ec63ac43-7b10-4204-88cb-756d0ebcd5cc/osist-pren-301-893-v1-8-5-2017

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] Void.
- [3] Void.
- [4] IEEE 802.11™-2016: "IEEE Standard for Information Technology - Telecommunications and information exchange between systems Local and metropolitan area networks - Specific requirements Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.3] ETSI EG 203 367 (V1.1.1) (06-2016): "Guide to the application of harmonised standards covering articles 3.1b and 3.2 of the Directive 2014/53/EU (RED) to multi-radio and combined radio and non-radio equipment".
- [i.4] ETSI TR 100 028-1 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1".
- [i.5] ETSI TR 100 028-2 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
- [i.6] ECC/DEC/(04)08: ECC Decision of 9 July 2004 on the harmonised use of the 5 GHz frequency bands for the implementation of Wireless Access Systems including Radio Local Area Networks (WAS/RLANs) (30/10/2009).
- [i.7] Commission Decision 2005/513/EC of 11 July 2005 on the harmonised use of radio spectrum in the 5 GHz frequency band for the implementation of Wireless Access Systems including Radio Local Area Networks (WAS/RLANs) ([standards.iteh.ai](http://standards.iteh.ai/standards/standards/sistc636c3-756d0ebcd5cc/0sist-pren-301-893-v1-8-5-2017))
- [i.8] Commission Decision 2007/90/EC of 12 February 2007 amending Decision 2005/513/EC on the harmonised use of radio spectrum in the 5 GHz frequency band for the implementation of Wireless Access Systems including Radio Local Area Networks (WAS/RLANs). ([standards.iteh.ai](http://standards.iteh.ai/standards/standards/sistc636c3-756d0ebcd5cc/0sist-pren-301-893-v1-8-5-2017))
- [i.9] ETSI TR 100 028 (all parts) (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.10] ETSI TR 102 273-2 (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 2: Anechoic chamber".
- [i.11] ETSI TR 102 273-3 (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 3: Anechoic chamber with a ground plane".
- [i.12] ETSI TR 102 273-4 (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 4: Open area test site".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in Directive 2014/53/EU [i.1] and the following apply:

5 GHz RLAN bands: total frequency range that consists of the 5 150 MHz to 5 350 MHz and the 5 470 MHz to 5 725 MHz sub-bands

adaptive equipment: equipment operating in an adaptive mode

adaptive mode: mechanism by which equipment can adapt to its environment by identifying other transmissions present in the band

ad-hoc mode: operating mode in which an RLAN device establishes a temporary wireless connection with other RLAN devices without a controlling network infrastructure

antenna array: two or more antennas connected to a single device and operating simultaneously

antenna assembly: combination of the antenna (integral or dedicated), its coaxial cable and if applicable, its antenna connector and associated switching components

NOTE 1: This term (antenna assembly) refers to an antenna connected to one transmit chain.

NOTE 2: The gain of an antenna assembly G in dBi, does not include the additional gain that may result out of beamforming. **iTeh STANDARD PREVIEW**

available channel: channel identified as available for immediate use as an *Operating Channel* ([standards.iteh.ai](https://standards.iteh.ai/catalog/standards/sist/ec63ac43-7b10-4204-88cb-590a6cda0001))

NOTE: *Usable Channels* whose nominal bandwidth falls completely within the band 5 150 MHz to 5 250 MHz can be considered as *Available Channels* without further testing.

<https://standards.iteh.ai/catalog/standards/sist/ec63ac43-7b10-4204-88cb-590a6cda0001>

beamforming gain: additional (antenna) gain realized by using beamforming techniques in smart antenna systems

NOTE: Beamforming gain as used in the present document does not include the gain of the antenna assembly.

burst: period during which radio waves are intentionally transmitted, preceded and succeeded by periods during which no intentional transmission is made

channel: minimum amount of spectrum used by a single RLAN device

NOTE: An RLAN device is permitted to operate (transmit/receive) in one or more adjacent or non-adjacent channels simultaneously.

EXAMPLE: For the purpose of the present document, an IEEE 802.11™ [4] device operating in a 40 MHz mode may be considered as operating in 2 adjacent 20 MHz channels simultaneously.

channel plan: combination of the centre frequencies and for each of the centre frequencies, the declared nominal bandwidth(s)

clear channel assessment: mechanism used by an equipment to identify other transmissions in the channel

combined equipment: any combination of non-radio equipment that requires a plug-in radio device to offer full functionality

dedicated antenna: antenna external to the equipment, using an antenna connector with a cable or a wave-guide and which has been designed or developed for one or more specific types of equipment

NOTE: It is the combination of dedicated antenna and radio equipment that is expected to be compliant with the regulations.

energy detect: mechanism used by an adaptive system to determine the presence of another device operating on the channel based on detecting the signal level of that other device

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

Frame Based Equipment (FBE): equipment where the transmit/receive structure is not directly demand-driven but has fixed timing

NOTE: I.e. it may be altered by configuration changes but there is always a minimum Idle Period following a transmit period.

host equipment: any equipment which has complete user functionality when not connected to the radio equipment part and to which the radio equipment part provides additional functionality and to which connection is necessary for the radio equipment part to offer functionality

integral antenna: antenna designed as a fixed part of the equipment (without the use of an external connector) which cannot be disconnected from the equipment by a user with the intent to connect another antenna

NOTE: An integral antenna may be fitted internally or externally. In the case where the antenna is external, a non-detachable cable or wave-guide can be used.

Listen Before Talk (LBT): mechanism by which an equipment applies clear channel assessment (CCA) before using the channel

Load Based Equipment (LBE): equipment where the transmit/receive structure is not fixed in time but demand-driven

master mode: mode which relates to the DFS functionality where the RLAN device uses a Radar Interference Detection function and controls the transmissions of RLAN devices operating in slave mode

NOTE: In this mode it is able to select a channel and initiate a network by sending enabling signals to other RLAN devices. A RLAN network always has at least one RLAN device operating in master mode when operating in the bands 5 250 MHz to 5 350 MHz and 5 470 MHz to 5 725 MHz.

multi-radio equipment: radio, host or combined equipment using more than one radio transceiver

operating channel: Available Channel on which the RLAN has started transmissions

NOTE: An Operating Channel becomes again an Available Channel if the RLAN stopped all transmissions on that channel and no radar signal was detected by the In-Service Monitoring.

plug-in radio device: radio equipment module intended to be used with or within host, combined or multi-radio equipment, using their control functions and power supply

receive chain: receiver circuit with an associated antenna

NOTE: Two or more receive chains are combined in a smart antenna system.

RLAN devices: 5 GHz high performance wireless access systems (WAS) including RLAN equipment

simulated radar burst: series of periodic radio wave pulses for test purposes

slave mode: mode which relates to the DFS functionality where the transmissions of the RLAN are under control of an RLAN device operating in master mode

NOTE: An RLAN device in slave mode may use a Radar Interference Detection function.

smart antenna systems: equipment that combines multiple transmit and/or receive chains with a signal processing function to increase the throughput and/or to optimize its radiation and/or reception capabilities

NOTE: These are techniques such as spatial multiplexing, beamforming, cyclic delay diversity, MIMO, etc.

stand-alone radio equipment: equipment that is intended primarily as communications equipment and that is normally used on a stand-alone basis

sub-band: portion of the 5 GHz RLAN bands

NOTE: See definition for "5 GHz RLAN bands".