



SLOVENSKI STANDARD

SIST ISO 6565:2014

01-januar-2014

Nadomešča:
SIST ISO 6565:2002

Tobak in tobačni proizvodi - Odpornost cigarete na vlek in upornost filtra - Standardni pogoji in merjenje

Tobacco and tobacco products - Draw resistance of cigarettes and pressure drop of filter rods - Standard conditions and measurement

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Tabac et produits du tabac - Résistance au tirage des cigarettes et perte de charge des bâtonnets-filtres - Conditions normalisées et mesurage

<https://standards.iteh.ai/catalog/standards/sist/8b28b90d-1a67-467a-bd7d-105b4bd681b/sist-iso-6565-2014>

Ta slovenski standard je istoveten z: ISO 6565:2011

ICS:

65.160

Tobak, tobačni izdelki in oprema

Tobacco, tobacco products and related equipment

SIST ISO 6565:2014

en,fr

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 6565:2014

<https://standards.iteh.ai/catalog/standards/sist/8b28b90d-1a67-467a-bd7d-105bf4bd681b/sist-iso-6565-2014>

INTERNATIONAL STANDARD

ISO
6565

Fourth edition
2011-10-01

Tobacco and tobacco products — Draw resistance of cigarettes and pressure drop of filter rods — Standard conditions and measurement

*Tabac et produits du tabac — Résistance au tirage des cigarettes et
perte de charge des bâtonnets-filtres — Conditions normalisées et
mesurage*

iTeh **STANDARD PREVIEW**
(standards.iteh.ai)

[SIST ISO 6565:2014](https://standards.iteh.ai/catalog/standards/sist/8b28b90d-1a67-467a-bd7d-105bf4bd681b/sist-iso-6565-2014)

<https://standards.iteh.ai/catalog/standards/sist/8b28b90d-1a67-467a-bd7d-105bf4bd681b/sist-iso-6565-2014>



Reference number
ISO 6565:2011(E)

© ISO 2011

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 6565:2014

<https://standards.iteh.ai/catalog/standards/sist/8b28b90d-1a67-467a-bd7d-105bf4bd681b/sist-iso-6565-2014>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2011

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction.....	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Test conditions	2
4.1 Test conditions common to cigarettes and filter rods	2
4.1.1 General	2
4.1.2 Air flow.....	2
4.1.3 Position.....	3
4.2 Conditions particular to cigarettes — Insertion of the test piece	3
4.3 Conditions particular to filter rods — Encapsulation	3
5 Instrument calibration.....	3
6 Procedure	3
6.1 Conditions common to vacuum and pressure instruments	3
6.2 Conditions particular to vacuum instruments	3
6.3 Conditions particular to pressure instruments (for filter rods only)	4
7 Expression of results	4
8 Precision	4
8.1 Interlaboratory test.....	4
8.2 Repeatability	4
8.3 Reproducibility	5
9 Test report.....	5
Annex A (normative) Calibration of pressure drop transfer standards	6
Annex B (informative) Results of an interlaboratory trial	14
Annex C (informative) Comparison of draw resistance or pressure drop measurement: Critical flow orifice instruments versus constant mass flow instruments	19
Bibliography.....	21

ISO 6565:2011(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 6565 was prepared by Technical Committee ISO/TC 126, *Tobacco and tobacco products*, Subcommittee SC 1, *Physical and dimensional tests*.

This fourth edition cancels and replaces the third edition (ISO 6565:2002), which has been technically revised.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 6565:2014](#)

<https://standards.iteh.ai/catalog/standards/sist/8b28b90d-1a67-467a-bd7d-105bf4bd681b/sist-iso-6565-2014>

Introduction

The draw resistance of cigarettes or the pressure drop of filter rods is a widespread and important concept both for product quality specifications and for analytical determinations by mechanical smoking.

Different procedures and apparatus are currently available for this determination. It has so far not been possible to standardize the complete description of the equipment to be used and the detailed procedure. Nevertheless, it has been possible to obtain broad consensus on the definitions to be adopted and the conditions that allow comparable determinations of this characteristic to be made. In order to achieve this, one of the main requirements is the use of transfer standards for the calibration of instruments (see Annex A).

In this International Standard, the results are given in pascals (Pa). For information, they are also given in millimetres water gauge (mmWG).

The values given previously in mmWG are converted into Pa using the following correction factor:

$$1 \text{ mmWG} = 9,806 \text{ 7 Pa}$$

For practical use, the values have been rounded.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 6565:2014](https://standards.iteh.ai/catalog/standards/sist/8b28b90d-1a67-467a-bd7d-105bf4bd681b/sist-iso-6565-2014)

<https://standards.iteh.ai/catalog/standards/sist/8b28b90d-1a67-467a-bd7d-105bf4bd681b/sist-iso-6565-2014>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 6565:2014](#)

<https://standards.iteh.ai/catalog/standards/sist/8b28b90d-1a67-467a-bd7d-105bf4bd681b/sist-iso-6565-2014>

Tobacco and tobacco products — Draw resistance of cigarettes and pressure drop of filter rods — Standard conditions and measurement

1 Scope

This International Standard describes a method for the measurement of the draw resistance of cigarettes and pressure drop of filter rods, and specifies the standard conditions applicable to such measurements.

It is applicable to cigarettes, filter rods and, by extension, to cylindrical tobacco products similar to cigarettes.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3402, *Tobacco and tobacco products — Atmosphere for conditioning and testing*

ISO 10185, *Tobacco and tobacco products — Vocabulary*

<https://standards.iteh.ai/catalog/standards/sist/8b28b90d-1a67-467a-bd7d-105bf4bd681b/sist-iso-6565-2014>

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 10185 and the following apply.

3.1

pressure drop

static pressure difference between the two ends of

- a test piece completely encapsulated in a measuring device such that no air can pass through the outer membrane (or wrapping); or
- a pneumatic circuit,

when it is traversed by an air flow under steady conditions in which the measured volumetric flow, under standard conditions, at the output end is 17,5 ml/s, as defined in ISO 3402

3.2

draw resistance

negative pressure which has to be applied to the output end, under test conditions (see ISO 3402), in order to sustain a volumetric flow of 17,5 ml/s, exiting at the output end, when the cigarette is encapsulated in a measurement device to a depth of approximately 9 mm, as defined in ISO 3308

NOTE 1 Any ventilation zones and the tobacco rod are exposed to the atmosphere.

NOTE 2 The concept of draw resistance can also be subjectively judged when a cigarette is smoked by a consumer/taste panel. Under such circumstances, draw resistance is not measured objectively because the conditions of the formal definition are not met.

ISO 6565:2011(E)**3.3****input end**

(cigarettes) that end of the test piece intended to be lit

3.4**output end**

that end opposite from the input end

3.5**standard direction of flow**

direction from the input end to the output end

NOTE In the case of a filter rod, the input end and the output end are defined by the direction of flow.

3.6**pressure drop transfer standard**

transfer standard for pressure drop measurement systems which is calibrated under standard ambient conditions and used under local ambient conditions

NOTE The form and properties of suitable transfer standards are given in Annex A.

3.7**dummy standard**

device with the same shape and similar form to a pressure drop transfer standard, for use in leak testing of calibration apparatus

NOTE A suitable dummy standard consists of a pressure drop transfer standard or a smooth metal tube of similar dimensions (see A.4.2.2).

iTeh STANDARD PREVIEW
(standards.iteh.ai)

3.8**reference standard**

pressure drop transfer standard against which other pressure drop transfer standards are compared

SIST ISO 6565:2014

<http://standards.iteh.ai/catalog/standards/sist/8b28b90d-1e67-4672-bd7d-105b4bd681b/sist-iso-6565-2014>

NOTE Such a reference standard is generally reserved for this purpose and is not used for the routine calibration of pressure drop measuring instruments.

3.9**monitor reference standard**

reference standard used to confirm the correctness of calibration of an instrument or measurement system

NOTE See A.4.2.3.4.

4 Test conditions**4.1 Test conditions common to cigarettes and filter rods****4.1.1 General**

The test conditions shall be constant and in agreement with the conditions under which the calibration was performed (see Clause 5).

NOTE The use of transfer standards for calibration enables measurements to be made under test conditions outside those described by ISO 3402.

4.1.2 Air flow

The air flow shall be from the input end in the standard direction of flow (see 3.5).

4.1.3 Position

The position of the test piece may be either horizontal or vertical, but products with cavities containing loose-fill material shall be positioned vertically.

4.2 Conditions particular to cigarettes — Insertion of the test piece

The output end of the test piece shall be inserted into a measurement device encapsulated to a depth of approximately 9 mm.

NOTE The intention is to achieve a good seal while not occluding any ventilation holes.

4.3 Conditions particular to filter rods — Encapsulation

The test piece shall be completely encapsulated in a measuring device so that no air can pass through the filter rod wrapping.

5 Instrument calibration

The instrument shall be calibrated before normal testing using transfer standards. This shall be done at least once per day. The calibration shall be carried out in accordance with the instrument manufacturer's instructions.

The instrument shall be recalibrated if the atmospheric conditions change by more than 2 °C for temperature, or by more than 5 % for relative humidity.

Each calibration of the instrument shall be recorded for later reference.

NOTE 1 To obtain the best accuracy, calibrate the instrument as close as possible to its full-scale deflection or at the maximum point of the range of values of the products to be tested.

NOTE 2 To check for air leaks that might have occurred during the calibration and to check the linearity of the measuring system, at least one intermediate value pressure drop standard should be used in order to obtain a mid-scale value.

NOTE 3 In addition to the mid-scale value, a calibration check can be made with a pressure drop standard that has a nominal pressure drop value close to the draw resistance or pressure drop of the test pieces to be measured.

6 Procedure

6.1 Conditions common to vacuum and pressure instruments

Record details of the instrument type and configuration, including measurement settling time, if this can be determined (see 6.2 and 6.3).

Insert the test piece (either manually or automatically) into the measuring device of the instrument. Read the value of the draw resistance or pressure drop and record it.

6.2 Conditions particular to vacuum instruments

Before reading the draw resistance or pressure drop, leave the test piece in the measuring device until the reading is steady.

NOTE Practice has shown that a settling time of 4 s to 6 s is normally sufficient.