

# INTERNATIONAL STANDARD

**Information technology – UPnP Device Architecture –  
Part 9-13: Imaging Device Control Protocol – Scan Service**

**ISO/IEC 29341-9-13:2008**  
<https://standards.iteh.ai/catalog/standards/sist/0ed9b84f-8d1e-411d-a81c-e7856cf30ddb/iso-iec-29341-9-13-2008>



**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2008 ISO/IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland  
Email: [inmail@iec.ch](mailto:inmail@iec.ch)  
Web: [www.iec.ch](http://www.iec.ch)

### **About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### **About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: [www.iec.ch/online\\_news/justpub](http://www.iec.ch/online_news/justpub)

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: [www.iec.ch/webstore/customerservice](http://www.iec.ch/webstore/customerservice)

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: [csc@iec.ch](mailto:csc@iec.ch)  
Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00



ISO/IEC 29341-9-13

Edition 1.0 2008-11

# INTERNATIONAL STANDARD

---

Information technology – UPnP Device Architecture –  
Part 9-13: Imaging Device Control Protocol – Scan Service  
(standards.iteh.ai)

ISO/IEC 29341-9-13:2008

<https://standards.iteh.ai/catalog/standards/sist/0ed9b84f-8d1e-411d-a81c-e7856cf30ddb/iso-iec-29341-9-13-2008>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE

S

---

ICS 35.200

ISBN 2-8318-1011-41

## CONTENTS

FOREWORD .....	5
ORIGINAL UPNP DOCUMENTS (informative) .....	7
<b>1 Overview and Scope .....</b>	<b>9</b>
<b>2 Service Modeling Definitions .....</b>	<b>10</b>
2.1 ServiceType .....	10
2.2 State Variables .....	10
2.2.1 <u>JobName</u> .....	11
2.2.2 <u>FailureCode</u> .....	11
2.2.3 <u>State</u> .....	12
2.2.4 <u>StateReason</u> .....	12
2.2.5 <u>ImageFormat</u> .....	12
2.2.6 <u>CompressionFactor</u> .....	12
2.2.7 <u>ImageType</u> .....	12
2.2.8 <u>Color Type and BitDepth</u> .....	13
2.2.9 <u>ColorSpace</u> .....	14
2.2.10 <u>UseFeeder</u> .....	14
2.2.11 <u>BaseName</u> .....	14
2.2.12 <u>AppendSideNumber</u> .....	14
2.2.13 <u>SideCount</u> .....	15
2.2.14 <u>SideNumber</u> .....	15
2.2.15 <u>Destination</u> .....	15
2.2.16 <u>Resolution</u> .....	15
2.2.17 <u>ScanLength</u> .....	15
2.2.18 <u>DeviceID</u> .....	16
2.2.19 <u>HeightLimit, WidthLimit, XValueLimit, YValueLimit</u> .....	16
2.2.20 <u>Timeout</u> .....	17
2.2.21 <u>ErrorTimeout</u> .....	17
2.2.22 <u>RegistrationID</u> .....	17
2.2.23 <u>JobID</u> .....	18
2.2.24 <u>DestinationID</u> .....	18
2.3 Eventing and Moderation .....	19
2.4 Action Set .....	20
2.4.1 (Void) StartScan(RegistrationIDIn, UseFeederIn, SideCountIn, JobNameIn, ResolutionIn, ImageXOffsetIn, ImageYOffsetIn, ImageWidthIn, ImageHeightIn, ImageFormatIn, CompressionFactorIn, ImageTypeIn, ColorTypeIn, BitDepthIn, ColorSpaceIn, BaseNameIn, AppendSideNumberIn, TimeoutIn, ActualTimeoutOut, JobIDOut, ActualWidthOut, ActualHeightOut ) .....	21
2.4.2 (Void) Start(JobIDIn, UseFeederIn, SideCountIn) .....	22
2.4.3 (Void) Stop(JobIDIn) .....	23
2.4.4 (Void) Abort(JobIDIn) .....	23
2.4.5 (Void) SetConfiguration(JobIDIn, JobNameIn, ResolutionIn, ImageXOffsetIn, ImageYOffsetIn, ImageWidthIn, ImageHeightIn, ImageFormatIn, CompressionFactorIn, ImageTypeIn, ColorTypeIn, BitDepthIn, ColorSpaceIn, BaseNameIn, AppendSideNumberIn, TimeoutIn, ActualTimeoutOut, ActualWidthOut, ActualHeightOut) .....	24
2.4.6 (Void) GetConfiguration(JobNameOut, ResolutionOut, ImageXOffsetOut, ImageYOffsetOut, ImageWidthOut, ImageHeightOut, ImageFormatOut, CompressionFactorOut, ImageTypeOut, ColorTypeOut, BitDepthOut, ColorSpaceOut, BaseNameOut, AppendSideNumberOut, TimeoutOut) .....	26
2.4.7 (Void) GetSideInformation(SideNumberOut, SideCountOut, ScanLengthOut) .....	26
2.4.8 (Void) GetDestination( JobIDIn, DestinationOut, DestinationIDOut ) .....	27
2.4.9 (Void) GetState( StateOut, StateReasonOut, FailureCodeOut ) .....	27
2.4.10 Common Error Codes .....	28
2.5 Theory of Operation .....	29

ITC STANDARD PREVIEW  
 (standards.iteh.ai)

ISO/IEC 29341-9-13:2008  
<https://standards.iteh.ai/catalog/standards/sist/0ed9b84f-8d1e-411d-a81c-2008>

2.5.1	<u>Sheet Size and Image Area</u> .....	29
2.5.2	Flow Example: Feeder-less, Button-less Scan Operation with Pull Image Transfer .....	30
2.5.3	Flow Example: Feeder-less Scan Operation with Pull Image Transfer .....	31
2.5.4	Flow Example: Feeder-less Scan Operation with Push Image Transfer .....	31
2.5.5	Flow Example: Scan Operation with Feeder and Pull Image Transfer .....	32
2.5.6	Flow Example: Scan Operation with Feeder and Push Image Transfer .....	32
2.5.7	Scanner Timeouts and Feeder Interactions .....	33
2.5.8	Scanner Buffer Functionality .....	37
2.5.9	Using XHTML-Print To Send An Image Directly To A Printer .....	37
2.5.10	BaseName, SideNumber, AppendSideNumber and Destination .....	37
2.5.11	Relationship between the Scan Service and the Feeder Service .....	38
2.5.12	Relationship between the Scan Service and the ExternalActivity Service .....	39
2.5.13	Extending Scanner Functionality .....	39
<b>3</b>	<b>XML Service Template for <u>Scan:1.0</u></b> .....	<b>40</b>
<b>4</b>	<b>Testing</b> .....	<b>51</b>
4.1	Syntax Testing .....	51
4.1.1	Issues .....	51
4.1.2	<i>StartScan</i> Syntax Test .....	51
<b>Annex A</b>	<b>(informative) Scan to Print using Multipart MIME</b> .....	<b>52</b>

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 29341-9-13:2008](https://standards.iteh.ai/catalog/standards/sist/0ed9b84f-8d1e-411d-a81c-e7856cf30ddb/iso-iec-29341-9-13-2008)

<https://standards.iteh.ai/catalog/standards/sist/0ed9b84f-8d1e-411d-a81c-e7856cf30ddb/iso-iec-29341-9-13-2008>

### LIST OF TABLES

Table 1: State Variables .....10

Table 1.1: allowedValueList for FailureCode .....11

Table 1.2: allowedValueList for ImageFormat .....12

Table 1.3: allowedValueList for ImageType.....13

Table 1.4: allowedValueList for ColorType .....13

Table 1.5: allowedValueList for BitDepth.....13

Table 1.6: Common Pixel Description Values .....13

Table 1.7: allowedValueList for ColorSpace.....14

Table 1.8: allowedValueList for UseFeeder.....14

Table 1.9: allowedValueList for BaseName.....14

Table 1.10: allowedValueList for AppendSideNumber .....14

Table 1.11: allowedValueRange for SideCount.....15

Table 1.12: allowedValueList for SideNumber.....15

Table 1.13: allowedValueList for Resolution.....15

Table 1.14: allowedValueRange for ScanLength .....15

Table 1.15: allowedValueRange for HeightLimit.....16

Table 1.16: allowedValueRange for WidthLimit.....16

Table 1.17: allowedValueRange for XValueLimit .....17

Table 1.18: allowedValueRange for YValueLimit .....17

Table 1.19: allowedValueRange for Timeout .....17

Table 2: Event Moderation.....19

Table 3: Actions .....20

Table 4: Arguments for StartScan .....21

Table 5: Arguments for Start .....22

Table 6: Arguments for Stop.....23

Table 7: Arguments for Abort .....23

Table 8: Arguments for SetConfiguration .....24

Table 9: Arguments for GetConfiguration.....26

Table 10: Arguments for GetSideInformation.....26

Table 11: Arguments for GetDestination .....27

Table 12: Arguments for GetState.....27

Table 13: Common Error Codes.....28

Table 14: Sheet and Image Area Dimensions.....29

Table 15: Scanner State Transition Table .....35

Table 16: Current State vs Service Actions .....36

Table 17: Destination Names .....38

STANDARD PREVIEW  
 (standards.iteh.ai)  
 ISO/IEC 29341-9-13:2008  
<https://standards.iteh.ai/catalog/standards/sist/0cd9b84f-8d1e-411d-a81c-770811111111/iso-iec-29341-9-13-2008>

# INFORMATION TECHNOLOGY – UPNP DEVICE ARCHITECTURE –

## Part 9-13: Imaging Device Control Protocol – Scan Service

### FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

IEC and ISO draw attention to the fact that it is claimed that compliance with this document may involve the use of patents as indicated below.

ISO and IEC take no position concerning the evidence, validity and scope of the putative patent rights. The holders of the putative patent rights have assured IEC and ISO that they are willing to negotiate free licences or licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of the putative patent rights are registered with IEC and ISO.

Intel Corporation has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Intel Corporation  
Standards Licensing Department  
5200 NE Elam Young Parkway  
MS: JFS-98  
USA – Hillsboro, Oregon 97124

Microsoft Corporation has informed IEC and ISO that it has patent applications or granted patents as listed below:

6101499 / US; 6687755 / US; 6910068 / US; 7130895 / US; 6725281 / US; 7089307 / US; 7069312 / US; 10/783 524 / US

Information may be obtained from:

Microsoft Corporation  
One Microsoft Way  
USA – Redmond WA 98052

Philips International B.V. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Philips International B.V. – IP&S  
High Tech campus, building 44 3A21  
NL – 5656 Eindhoven

NXP B.V. (NL) has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

NXP B.V. (NL)  
High Tech campus 60  
NL – 5656 AG Eindhoven

Matsushita Electric Industrial Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Matsushita Electric Industrial Co. Ltd.  
1-3-7 Shiromi, Chuoh-ku  
JP – Osaka 540-6139

Hewlett Packard Company has informed IEC and ISO that it has patent applications or granted patents as listed below:

5 956 487 / US; 6 170 007 / US; 6 139 177 / US; 6 529 936 / US; 6 470 339 / US; 6 571 388 / US; 6 205 466 / US

Information may be obtained from:

Hewlett Packard Company  
1501 Page Mill Road  
USA – Palo Alto, CA 94304

Samsung Electronics Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Digital Media Business, Samsung Electronics Co. Ltd.  
416 Maetan-3 Dong, Yeongtang-Gu,  
KR – Suwon City 443-742

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC and ISO shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 29341-9-13 was prepared by UPnP Implementers Corporation and adopted, under the PAS procedure, by joint technical committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

The list of all currently available parts of the ISO/IEC 29341 series, under the general title *Universal plug and play (UPnP) architecture*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.



## ORIGINAL UPnP DOCUMENTS (informative)

Reference may be made in this document to original UPnP documents. These references are retained in order to maintain consistency between the specifications as published by ISO/IEC and by UPnP Implementers Corporation. The following table indicates the original UPnP document titles and the corresponding part of ISO/IEC 29341:

UPnP Document Title	ISO/IEC 29341 Part
UPnP Device Architecture 1.0	ISO/IEC 29341-1
UPnP Basic:1 Device	ISO/IEC 29341-2
UPnP AV Architecture:1	ISO/IEC 29341-3-1
UPnP MediaRenderer:1 Device	ISO/IEC 29341-3-2
UPnP MediaServer:1 Device	ISO/IEC 29341-3-3
UPnP AVTransport:1 Service	ISO/IEC 29341-3-10
UPnP ConnectionManager:1 Service	ISO/IEC 29341-3-11
UPnP ContentDirectory:1 Service	ISO/IEC 29341-3-12
UPnP RenderingControl:1 Service	ISO/IEC 29341-3-13
UPnP MediaRenderer:2 Device	ISO/IEC 29341-4-2
UPnP MediaServer:2 Device	ISO/IEC 29341-4-3
UPnP AV Datastructure Template:1	ISO/IEC 29341-4-4
UPnP AVTransport:2 Service	ISO/IEC 29341-4-10
UPnP ConnectionManager:2 Service	ISO/IEC 29341-4-11
UPnP ContentDirectory:2 Service	ISO/IEC 29341-4-12
UPnP RenderingControl:2 Service	ISO/IEC 29341-4-13
UPnP ScheduledRecording:1	ISO/IEC 29341-4-14
UPnP DigitalSecurityCamera:1 Device	ISO/IEC 29341-5-1
UPnP DigitalSecurityCameraMotionImage:1 Service	ISO/IEC 29341-5-10
UPnP DigitalSecurityCameraSettings:1 Service	ISO/IEC 29341-5-11
UPnP DigitalSecurityCameraStillImage:1 Service	ISO/IEC 29341-5-12
UPnP HVAC_System:1 Device	ISO/IEC 29341-6-1
UPnP HVAC_ZoneThermostat:1 Device	ISO/IEC 29341-6-2
UPnP ControlValve:1 Service	ISO/IEC 29341-6-10
UPnP HVAC_FanOperatingMode:1 Service	ISO/IEC 29341-6-11
UPnP FanSpeed:1 Service	ISO/IEC 29341-6-12
UPnP HouseStatus:1 Service	ISO/IEC 29341-6-13
UPnP HVAC_SetpointSchedule:1 Service	ISO/IEC 29341-6-14
UPnP TemperatureSensor:1 Service	ISO/IEC 29341-6-15
UPnP TemperatureSetpoint:1 Service	ISO/IEC 29341-6-16
UPnP HVAC_UserOperatingMode:1 Service	ISO/IEC 29341-6-17
UPnP BinaryLight:1 Device	ISO/IEC 29341-7-1
UPnP DimmableLight:1 Device	ISO/IEC 29341-7-2
UPnP Dimming:1 Service	ISO/IEC 29341-7-10
UPnP SwitchPower:1 Service	ISO/IEC 29341-7-11
UPnP InternetGatewayDevice:1 Device	ISO/IEC 29341-8-1
UPnP LANDevice:1 Device	ISO/IEC 29341-8-2
UPnP WANDevice:1 Device	ISO/IEC 29341-8-3
UPnP WANConnectionDevice:1 Device	ISO/IEC 29341-8-4
UPnP WLANAccessPointDevice:1 Device	ISO/IEC 29341-8-5
UPnP LANHostConfigManagement:1 Service	ISO/IEC 29341-8-10
UPnP Layer3Forwarding:1 Service	ISO/IEC 29341-8-11
UPnP LinkAuthentication:1 Service	ISO/IEC 29341-8-12
UPnP RadiusClient:1 Service	ISO/IEC 29341-8-13
UPnP WANCableLinkConfig:1 Service	ISO/IEC 29341-8-14
UPnP WANCommonInterfaceConfig:1 Service	ISO/IEC 29341-8-15
UPnP WANDSLLinkConfig:1 Service	ISO/IEC 29341-8-16
UPnP WANEthernetLinkConfig:1 Service	ISO/IEC 29341-8-17
UPnP WANIPConnection:1 Service	ISO/IEC 29341-8-18
UPnP WANPOTSLinkConfig:1 Service	ISO/IEC 29341-8-19
UPnP WANPPPoEConnection:1 Service	ISO/IEC 29341-8-20
UPnP WLANConfiguration:1 Service	ISO/IEC 29341-8-21
UPnP Printer:1 Device	ISO/IEC 29341-9-1
UPnP Scanner:1.0 Device	ISO/IEC 29341-9-2
UPnP ExternalActivity:1 Service	ISO/IEC 29341-9-10
UPnP Feeder:1.0 Service	ISO/IEC 29341-9-11
UPnP PrintBasic:1 Service	ISO/IEC 29341-9-12
UPnP Scan:1 Service	ISO/IEC 29341-9-13
UPnP QoS Architecture:1.0	ISO/IEC 29341-10-1
UPnP QoSDevice:1 Service	ISO/IEC 29341-10-10
UPnP QoSManager:1 Service	ISO/IEC 29341-10-11
UPnP QoSPolicyHolder:1 Service	ISO/IEC 29341-10-12
UPnP QoS Architecture:2	ISO/IEC 29341-11-1
UPnP QOS v2 Schema Files	ISO/IEC 29341-11-2

<b>UPnP Document Title</b>	<b>ISO/IEC 29341 Part</b>
UPnP QosDevice:2 Service	ISO/IEC 29341-11-10
UPnP QosManager:2 Service	ISO/IEC 29341-11-11
UPnP QosPolicyHolder:2 Service	ISO/IEC 29341-11-12
UPnP RemoteUIClientDevice:1 Device	ISO/IEC 29341-12-1
UPnP RemoteUIServerDevice:1 Device	ISO/IEC 29341-12-2
UPnP RemoteUIClient:1 Service	ISO/IEC 29341-12-10
UPnP RemoteUIServer:1 Service	ISO/IEC 29341-12-11
UPnP DeviceSecurity:1 Service	ISO/IEC 29341-13-10
UPnP SecurityConsole:1 Service	ISO/IEC 29341-13-11

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 29341-9-13:2008](#)

<https://standards.iteh.ai/catalog/standards/sist/0ed9b84f-8d1e-411d-a81c-e7856cf30ddb/iso-iec-29341-9-13-2008>

# 1 Overview and Scope

This service definition is compliant with the UPnP Device Architecture version 1.0.

The Scan service represents the scan functionality of a scanner device. A control point may use this service to initiate a scan operation and receive images that represent the document in the scanner. The control point may pull the images using HTTP/GETs from the Destination URL or the service map push the images using HTTP/POSTs. The service has the following basic functional areas:

## Operation Functionality

The *StartScan*, *Start*, *Stop*, *Abort* and *SetConfiguration* actions are used to control the action of the scan service.

## Status Functionality

The *GetConfiguration*, *GetSideInformation*, *GetDestination* and *GetState* actions are used to query the current state of the scan service.

This service template does not address:

- *Faxing or Copying*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO/IEC 29341-9-13:2008

<https://standards.iteh.ai/catalog/standards/sist/0ed9b84f-8d1e-411d-a81c-e7856cf30ddb/iso-iec-29341-9-13-2008>

## 2 Service Modeling Definitions

### 2.1 ServiceType

A service that is compliant with this template is identified with the following service type: **urn:schemas-upnp-org:service:Scan:1**

### 2.2 State Variables

Table 1: State Variables

Variable Name	Req. or Opt. <sup>1</sup>	Data Type	Allowed Value <sup>2</sup>	Default Value <sup>2</sup>	Eng. Units
JobName	R	string	[device-setting   ...]	""	
FailureCode	R	string	[No Error   Jammed   Timeout Reached   ErredTimeout Reached   Destination Not Reachable]	No Error	
State	R	string	[Idle   Reserved   NotReady   Pending   Scanning   Finishing   Erred]	Idle	
StateReason	R	string			
ImageFormat	R	string	[device-setting   image/jpeg]	image/jpeg	
CompressionFactor	R	i4	-1-100	100	n/a
ImageType	R	string	[device-setting   Mixed]	Mixed	
ColorType	R	string	[device-setting   Color   Mono]	Color	
BitDepth	R	string	[device-setting   8]	8	bits
ColorSpace	R	string	[device-setting   sRGB]	sRGB	n/a
UseFeeder	R	string	[device-setting]	0 (false)	n/a
BaseName	R	string	[device-setting   buffer]	buffer	
AppendSideNumber	R	string	[device-setting[0]	0 (false)	n/a
SideCount	R	i4	[-1-1]	0	n/a
SideNumber	R	i4		1	n/a
Destination	R	string			
Timeout	R	i4	[-1   0 ]		seconds
ErrorTimeout	R	i4		vendor unique	seconds
Resolution	R	string	[device-setting]		Pixels

Variable Name	Req. or Opt. <sup>1</sup>	Data Type	Allowed Value <sup>2</sup>	Default Value <sup>2</sup>	Eng. Units
					Per Inch
ScanLength	R	i4	0 – vendor-defined	0	milli-inches
DeviceID	R	string			n/a
HeightLimit	R	i4			milli-inches
WidthLimit	R	i4			milli-inches
XValueLimit	R	i4	-1-vendor-defined	vendor-defined	milli-inches
YValueLimit	R	i4	-1-vendor-defined	vendor-defined	milli-inches
RegistrationID	R	ui4			
JobID	R	ui4	1 – vendor-defined		
DestinationID	R	ui4		0	

<sup>1</sup> R = Required, O = Optional, X = Non-standard.

<sup>2</sup> Values listed in this column are required. To specify standard optional values or to delegate assignment of values to the vendor, you must reference a specific instance of an appropriate table below.

(standards.iteh.ai)

### 2.2.1 JobName

This string allows the client to give the job a unique name. This is informational only. It can be used to identify the client or the purpose of the job. If the value is set to *device-setting* in the SetConfiguration or StartScan actions, then the value should not be changed.

### 2.2.2 FailureCode

A Failure Code indicates a failure, or error, that does not occur as an immediate result of an action and cannot be reported as part of the action response. Error Codes that occur during the execution of an action are not listed as allowed values of the FailureCode unless they can occur outside of the boundary of the action.

**Table 1.1: allowedValueList for FailureCode**

Value	Req. or Opt.
No Error	R
Jammed	R
Timeout Reached	R
ErredTimeout Reached	R
Destination not Reachable	R
... (Vendor specific error codes)	O

### 2.2.3 State

The current state of the scanner. The states are defined as follows:

- *Idle* – The scanner is not active
- *Reserved* – The scanner is reserved for use by a specific control point that has the correct RegistrationID. The RegistrationID value came from the ExternalActivity service.
- *NotReady* – The scanning is getting ready to scan.
- *Pending* - The scanner is currently processing a Scan job. It is waiting for client interaction (start action) or feeder interaction (loaded state) to complete
- *Scanning* – The scanner is currently scanning an image to the destination
- *Finishing* – The scanner has completed scanning all available sides and is waiting for the transfer of images to complete
- *Erred* – An error occurred during a scan operation. The scan service is waiting for the client to acknowledge the error by sending an Abort action.

### 2.2.4 StateReason

The StateReason string is used to augment the information given by the current state. This is especially helpful when in the NotReady state. In this case, the vendor should put information in this variable that tells the client what is going on (i.e. Calibrating, Warming Up, etc.).

### 2.2.5 ImageFormat

The format of the image to be returned. The list of allowed values may be a subset or superset of the given values. To send images to a printer, the application/vnd.pwg-xhtml-print format MUST be used with JPEG images embedded in an application/vnd.pwg-multiplexed document. See Using XHTML-Print To Send An Image Directly To A Printer on page 37 for more information about using the XHTML image type. If the value is set to *device-setting* in the SetConfiguration or StartScan actions, then the value should not be changed.

*NOTE: the ImageFormat value "application/vnd.pwg-xhtml-print+xml" exceeds the recommended maximum length of 31 characters for elements of an allowedValueList. A truncated version (application/vnd.pwg-xhtml-print) is used so that it will fit within that length.*

**Table 1.2: allowedValueList for ImageFormat**

Value	Req. or Opt.	Filename Suffix
device-setting	R	
image/jpeg	R	jpg
application/vnd.pwg-xhtml-print (Scan-to-Print)	O	xml
... (vendor defined)	O	

### 2.2.6 CompressionFactor

The measure of compression for compressed image formats. If the value is set to -1 (*device-setting*) in the SetConfiguration or StartScan actions, then the value should not be changed.

### 2.2.7 ImageType

The type of image to be scanned. If the value is set to *device-setting* in the SetConfiguration or StartScan actions, then the value should not be changed.

**Table 1.3: allowedValueList for ImageType**

Value	Req. or Opt.
device-setting	R
Mixed	R
Photo	O
Text	O
Graphics	O

### 2.2.8 Color Type and BitDepth

The type of the pixel used to represent the image is very dependent upon the ImageFormat. ColorType and BitDepth are used to describe the basic shape of the pixels. ColorType is used to describe whether the image is monochrome, color, or some sort of extended multi-plane pixel. The BitDepth value is used to describe the size of each part of a pixel. Since JPEG is the only required image format, the values for JPEG are given here. If vendors support additional image formats, then they should extend the allowed values to describe their formats (i.e. PNG-RGB-ALPHA, etc.).

**Table 1.4: allowedValueList for ColorType**

Value	Req. or Opt.
device-setting	R
Color	O
Mono	O

Note: Either *Color* or *Mono* should be given as an allowed value. Both are allowed, but at least one of them is required. The allowed value list can be extended or a subset of the list given here.

**Table 1.5: allowedValueList for BitDepth**

Value	Req. or Opt.
device-setting	R
8	R
12	O

The allowed value list may be extended as required.

#### 2.2.8.1 *Common Pixel Description Values*

The following examples show how to describe most JPEG variations:

**Table 1.6: Common Pixel Description Values**

Description	ColorType	BitDepth
8-bit Color JPEG	Color	8
8-bit Gray	Mono	8
12-bit Color	Color	12
PNG RGB with Alpha	PNG-RGB-ALPHA	8