

ETSI TS 102 366 V1.4.1 (2017-09)



Digital Audio Compression (AC-3, Enhanced AC-3) Standard

ITeH STANDARDS PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/4da5-4e52-b4b6-981b28526cb8/etsi-ts-102-366-v1-4-1-2017-09>

EBU

OPERATING EUROVISION

Reference

RTS/JTC-041

Keywords

audio, broadcasting, coding, digital

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.

© European Broadcasting Union 2017.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	17
Foreword.....	17
Modal verbs terminology.....	17
Introduction	18
1 Scope	21
2 References	21
2.1 Normative references	21
2.2 Informative references.....	21
3 Definitions and abbreviations.....	22
3.1 Definitions.....	22
3.2 Abbreviations	24
4 Bit stream syntax	27
4.1 Synchronization frame	27
4.2 Semantics of syntax specification.....	27
4.3 Syntax specification	28
4.3.0 AC-3_bit_stream and syncframe	28
4.3.1 syncinfo - Synchronization information	28
4.3.2 bsi - Bit stream information	28
4.3.3 audblk - Audio block	29
4.3.4 auxdata - Auxiliary data.....	32
4.3.5 errorcheck - Error detection code	32
4.4 Description of bit stream elements.....	32
4.4.0 Introduction.....	32
4.4.1 syncinfo - Synchronization information	32
4.4.1.1 syncword - Synchronization word - 16 bits.....	32
4.4.1.2 crc1 - Cyclic redundancy check 1 bit to 16 bits	32
4.4.1.3 fscod - Sample rate code - 2 bits	33
4.4.1.4 frmsizecod - Frame size code - 6 bits.....	33
4.4.2 bsi - Bit stream information	33
4.4.2.1 bsid - Bit stream identification - 5 bits.....	33
4.4.2.2 bsmod - Bit stream mode - 3 bits	33
4.4.2.3 acmod - Audio coding mode - 3 bits	33
4.4.2.4 cmixlev - Centre mix level - 2 bits.....	34
4.4.2.5 surmixlev - Surround mix level - 2 bits.....	34
4.4.2.6 dsurmod - Dolby® Surround mode - 2 bits.....	34
4.4.2.7 lfeon - Low frequency effects channel on - 1 bit.....	35
4.4.2.8 dialnorm - Dialogue normalization - 5 bits	35
4.4.2.9 compre - Compression gain word exists - 1 bit.....	35
4.4.2.10 compr - Compression gain word - 8 bits	35
4.4.2.11 langcode - Language code exists - 1 bit	35
4.4.2.12 langcod - Language code - 8 bits	35
4.4.2.13 audprodi2e - Audio production information exists - 1 bit.....	35
4.4.2.14 mixlevel - Mixing level - 5 bits.....	36
4.4.2.15 roomtyp - Room type - 2 bits	36
4.4.2.16 dialnorm2 - Dialogue normalization, Ch2 - 5 bits.....	36
4.4.2.17 compr2e - Compression gain word exists, Ch2 - 1 bit	36
4.4.2.18 compr2 - Compression gain word, Ch2 - 8 bits.....	36
4.4.2.19 langcod2e - Language code exists, Ch2 - 1 bit.....	36
4.4.2.20 langcod2 - Language code, Ch2 - 8 bits	36
4.4.2.21 audprodi2e - Audio production information exists, Ch2 - 1 bit	36
4.4.2.22 mixlevel2 - Mixing level, Ch2 - 5 bits	36
4.4.2.23 roomtyp2 - Room type, Ch2 - 2 bits.....	37
4.4.2.24 copyrightb - Copyright bit - 1 bit	37

4.4.2.25	origbs - Original bit stream - 1 bit.....	37
4.4.2.26	timecod1e, timecod2e - Time code (first and second) halves exists - 2 bits	37
4.4.2.27	timecod1 - Time code first half - 14 bits	37
4.4.2.28	timecod2 - Time code second half - 14 bits	37
4.4.2.29	addbsie - Additional bit stream information exists - 1 bit	37
4.4.2.30	addbsil - Additional bit stream information length - 6 bits	37
4.4.2.31	addbsi - Additional bit stream information - ((addbsil + 1) x 8) bits	37
4.4.3	audblk - Audio block	38
4.4.3.1	blksw[ch] - Block switch flag - 1 bit.....	38
4.4.3.2	dithflag[ch] - Dither flag - 1 bit.....	38
4.4.3.3	dynrng - Dynamic range gain word exists - 1 bit	38
4.4.3.4	dynrng - Dynamic range gain word - 8 bits.....	38
4.4.3.5	dynrng2e - Dynamic range gain word exists, Ch2 - 1 bit.....	38
4.4.3.6	dynrng2 - dynamic range gain word, Ch2 - 8 bits	38
4.4.3.7	cplstre - Coupling strategy exists - 1 bit.....	38
4.4.3.8	cplinu - Coupling in use - 1 bit.....	38
4.4.3.9	chincpl[ch] - Channel in coupling - 1 bit	38
4.4.3.10	phsflginu - Phase flags in use - 1 bit	38
4.4.3.11	cplbegf - Coupling begin frequency code - 4 bits	39
4.4.3.12	cplendf - Coupling end frequency code - 4 bits	39
4.4.3.13	cplbndstrec[sbnd] - Coupling band structure - 1 bit.....	39
4.4.3.14	cplcoe[ch] - Coupling coordinates exist - 1 bit	39
4.4.3.15	mstrecplco[ch] - Master coupling coordinate - 2 bits	40
4.4.3.16	cplcoexp[ch][bnd] - Coupling coordinate exponent - 4 bits.....	40
4.4.3.17	cplcomant[ch][bnd] - Coupling coordinate mantissa - 4 bits	40
4.4.3.18	phsflg[bnd] - Phase flag - 1 bit.....	40
4.4.3.19	rematstr - Rematrixing strategy - 1 bit	40
4.4.3.20	rematflg[rbnd] - Rematrix flag - 1 bit	40
4.4.3.21	cplexpstr - Coupling exponent strategy - 2 bits.....	40
4.4.3.22	chexpstr[ch] - Channel exponent strategy - 2 bits.....	41
4.4.3.23	lfeexpstr - Low frequency effects channel exponent strategy - 1 bit.....	41
4.4.3.24	chbwcod[ch] - Channel bandwidth code - 6 bits.....	41
4.4.3.25	cplabsexp - Coupling absolute exponent - 4 bits.....	41
4.4.3.26	cplexps[grp] - Coupling exponents - 7 bits.....	41
4.4.3.27	exps[ch][grp] - Channel exponents - 4 bits or 7 bits	41
4.4.3.28	gainrng[ch] - Channel gain range code - 2 bits	41
4.4.3.29	lfeexps[grp] - Low frequency effects channel exponents - 4 bits or 7 bits.....	41
4.4.3.30	baie - Bit allocation information exists - 1 bit.....	41
4.4.3.31	sdcycod - Slow decay code - 2 bits	41
4.4.3.32	fdycod - Fast decay code - 2 bits	42
4.4.3.33	sgaincod - Slow gain code - 2 bits.....	42
4.4.3.34	dbpbcod - dB per bit code - 2 bits	42
4.4.3.35	floorcod - Masking floor code - 3 bits.....	42
4.4.3.36	snroffste - SNR offset exists - 1 bit.....	42
4.4.3.37	csnroffst - Coarse SNR offset - 6 bits	42
4.4.3.38	cplfsnroffst - Coupling fine SNR offset - 4 bits	42
4.4.3.39	cplfgaincod - Coupling fast gain code - 3 bits.....	42
4.4.3.40	fsnroffst[ch] - Channel fine SNR offset - 4 bits	42
4.4.3.41	fgaincod[ch] - Channel fast gain code - 3 bits.....	42
4.4.3.42	lfefsnroffst - Low frequency effects channel fine SNR offset - 4 bits.....	42
4.4.3.43	lfefgaincod - Low frequency effects channel fast gain code - 3 bits	42
4.4.3.44	cplleake - Coupling leak initialization exists - 1 bit	42
4.4.3.45	cplfleak - Coupling fast leak initialization - 3 bits	43
4.4.3.46	cplslleak - Coupling slow leak initialization - 3 bits	43
4.4.3.47	deltbaie - Delta bit allocation information exists - 1 bit.....	43
4.4.3.48	cpldeltbae - Coupling delta bit allocation exists - 2 bits.....	43
4.4.3.49	deltbae[ch] - Delta bit allocation exists - 2 bits.....	43
4.4.3.50	cpldeltseg - Coupling delta bit allocation number of segments - 3 bits.....	43
4.4.3.51	cpldeltfst[seg] - Coupling delta bit allocation offset - 5 bits.....	43
4.4.3.52	cpldeltlen[seg] - Coupling delta bit allocation length - 4 bits	43
4.4.3.53	cpldeltba[seg] - Coupling delta bit allocation - 3 bits	43
4.4.3.54	deltseg[ch] - Channel delta bit allocation number of segments - 3 bits.....	44

4.4.3.55	deltoffst[ch][seg] - Channel delta bit allocation offset - 5 bits	44
4.4.3.56	deltlen[ch][seg] - Channel delta bit allocation length - 4 bits	44
4.4.3.57	deltba[ch][seg] - Channel delta bit allocation - 3 bits	44
4.4.3.58	skiple - Skip length exists - 1 bit	44
4.4.3.59	skipl - Skip length - 9 bits	44
4.4.3.60	skipfld - Skip field - (skipl x 8) bits	44
4.4.3.61	chmant[ch][bin] - Channel mantissas - 0 bits to 16 bits	44
4.4.3.62	cplmant[bin] - Coupling mantissas - 0 bits to 16 bits	45
4.4.3.63	lfemant[bin] - Low frequency effects channel mantissas - 0 bits to 16 bits	45
4.4.4	auxdata - Auxiliary data field	45
4.4.4.0	Introduction	45
4.4.4.1	auxbits - Auxiliary data bits - nauxbits bits	45
4.4.4.2	auxdatal - Auxiliary data length - 14 bits	46
4.4.4.3	auxdatae - Auxiliary data exists - 1 bit	46
4.4.5	errorcheck - Frame error detection field	46
4.4.5.1	crcsv - CRC reserved bit - 1 bit	46
4.4.5.2	crc2 - Cyclic redundancy check 2 - 16 bits	46
4.5	Bit stream constraints	46
5	Decoding the AC-3 bit stream	47
5.1	Introduction	47
5.2	Summary of the decoding process	47
5.2.1	Input bit stream	47
5.2.1.0	Introduction	47
5.2.1.1	Continuous or burst input	47
5.2.1.2	Byte or word alignment	47
5.2.2	Synchronization and error detection	48
5.2.3	Unpack BSI, side information	49
5.2.4	Decode exponents	50
5.2.5	Bit allocation	50
5.2.6	Process mantissas	50
5.2.7	Decoupling	50
5.2.8	Rematrixing	50
5.2.9	Dynamic range compression	50
5.2.10	Inverse transform	50
5.2.11	Window, overlap/add	51
5.2.12	Downmixing	51
5.2.13	PCM output buffer	51
5.2.14	Output PCM	51
6	Algorithmic details	51
6.0	Introduction	51
6.1	Exponent coding	51
6.1.1	Overview	51
6.1.2	Exponent strategy	52
6.1.3	Exponent decoding	53
6.2	Bit allocation	55
6.2.1	Overview	55
6.2.2	Parametric bit allocation	56
6.2.2.0	Introduction	56
6.2.2.1	Initialization	56
6.2.2.2	Exponent mapping into psd	57
6.2.2.3	psd integration	57
6.2.2.4	Compute excitation function	58
6.2.2.5	Compute masking curve	59
6.2.2.6	Apply delta bit allocation	60
6.2.2.7	Compute bit allocation	60
6.2.3	Bit allocation tables	61
6.3	Quantization and decoding of mantissas	65
6.3.1	Overview	65
6.3.2	Expansion of mantissas for asymmetric quantization ($6 \leq \text{bap} \leq 15$)	66
6.3.3	Expansion of mantissas for symmetrical quantization ($1 \leq \text{bap} \leq 5$)	66

6.3.4	Dither for zero bit mantissas ($bap = 0$)	66
6.3.5	Ungrouping of mantissas	68
6.4	Channel coupling.....	68
6.4.1	Overview	68
6.4.2	Sub-band structure for coupling.....	69
6.4.3	Coupling coordinate format	70
6.5	Rematrixing	70
6.5.1	Overview	70
6.5.2	Frequency band definitions.....	71
6.5.2.0	Introduction.....	71
6.5.2.1	Coupling not in use	71
6.5.2.2	Coupling in use, $cplbegf > 2$	71
6.5.2.3	Coupling in use, $2 \geq cplbegf > 0$	72
6.5.2.4	Coupling in use, $cplbegf = 0$	72
6.5.3	Encoding technique.....	72
6.5.4	Decoding technique	73
6.6	Dialogue normalization	73
6.7	Dynamic range compression	74
6.7.1	Overview	74
6.7.2	Dynamic range control; $dynrng$, $dynrng2$	74
6.7.2.1	Overview.....	74
6.7.2.2	Detailed implementation	75
6.7.3	Heavy compression; $compr$, $compr2$	76
6.7.3.1	Overview.....	76
6.7.3.2	Detailed implementation	76
6.8	Downmixing.....	77
6.8.0	Introduction.....	77
6.8.1	General downmix procedure.....	77
6.8.2	Downmixing into two channels	80
6.9	Transform equations and block switching	81
6.9.1	Overview	81
6.9.2	Technique	82
6.9.3	Decoder implementation.....	82
6.9.4	Transformation equations	82
6.9.4.1	512-sample IMDCT transform	82
6.9.4.2	256-sample IMDCT transforms.....	84
6.9.5	Channel gain range code.....	86
6.10	Error detection.....	87
6.10.0	Introduction.....	87
6.10.1	CRC checking.....	87
6.10.2	Checking bit stream consistency.....	88
7	Encoding the AC-3 bit stream.....	90
7.1	Introduction	90
7.2	Summary of the encoding process.....	90
7.2.1	Input PCM	90
7.2.1.1	Input word length.....	90
7.2.1.2	Input sample rate	90
7.2.1.3	Input filtering	90
7.2.2	Transient detection.....	91
7.2.3	Forward transform	93
7.2.3.1	Windowing.....	93
7.2.3.2	Time to frequency transformation.....	93
7.2.4	Coupling strategy.....	93
7.2.4.1	Basic encoder	93
7.2.4.2	Advanced encoder.....	93
7.2.5	Form coupling channel	93
7.2.5.1	Coupling channel	93
7.2.5.2	Coupling coordinates	94
7.2.6	Rematrixing	94
7.2.7	Extract exponents.....	94
7.2.8	Exponent strategy	94

7.2.9	Dither strategy	94
7.2.10	Encode exponents	94
7.2.11	Normalize mantissas	95
7.2.12	Core bit allocation.....	95
7.2.13	Quantize mantissas	95
7.2.14	Pack AC-3 syncframe	95
Annex A (normative): AC-3 bit streams in the MPEG-2 multiplex		96
A.0	Scope	96
A.1	Introduction	96
A.2	Detailed specification for System A (ATSC).....	96
A.2.1	Stream_type.....	96
A.2.2	Stream_id	96
A.2.3	Registration_descriptor	97
A.2.4	AC-3 audio_descriptor	97
A.2.5	ISO_639_language_code.....	100
A.2.6	STD audio buffer size.....	100
A.3	Specification for System B (DVB).....	101
A.4	PES constraints.....	101
A.4.0	Introduction	101
A.4.1	Encoding.....	101
A.4.2	Decoding	101
A.4.3	Byte-alignment	102
Annex B (informative): Void		103
Annex C (informative): AC-3 karaoke mode		104
C.0	Scope	104
C.1	Introduction	104
C.2	Detailed specification.....	104
C.2.1	Karaoke mode indication.....	104
C.2.2	Karaoke mode channel assignment	104
C.2.3	Reproduction of karaoke mode bit streams	105
C.2.3.0	Introduction.....	105
C.2.3.1	Karaoke-aware decoder	105
C.2.3.2	Karaoke-capable decoders	105
Annex D (normative): Alternate bit stream syntax.....		107
D.0	Scope	107
D.1	Specification.....	107
D.1.1	Indication of alternate bit stream syntax.....	107
D.1.2	Alternate bit stream syntax specification.....	107
D.1.3	Description of alternate syntax bit stream elements	108
D.1.3.0	Introduction.....	108
D.1.3.1	xbsi1e: Extra bit stream information #1 exists, 1 bit	108
D.1.3.2	dmixmod: Preferred stereo downmix mode, 2 bits	108
D.1.3.3	ltrcmixlev: Lt/Rt centre mix level, 3 bits	108
D.1.3.4	ltrtsurmixlev: Lt/Rt surround mix level, 3 bits.....	109
D.1.3.5	lorocmixlev: Lo/Ro centre mix level, 3 bits	109
D.1.3.6	lorosurmixlev: Lo/Ro surround mix level, 3 bits	110
D.1.3.7	xbsi2e: Extra bit stream information #2 exists, 1 bit	110
D.1.3.8	dsurexmod: Dolby® Surround EX® mode, 2 bits	110
D.1.3.9	dheadphonmod: Dolby® Headphone mode, 2 bits	110
D.1.3.10	adconvtyp: A/D converter type, 1 bit.....	111
D.1.3.11	xbsi2: Extra bit stream information, 8 bits.....	111

D.1.3.12	encinfo: Encoder information, 1 bit	111
D.2	Decoder processing	111
D.2.0	Introduction	111
D.2.1	Compliant decoder processing	111
D.2.1.1	Two-channel downmix selection	111
D.2.1.2	Two-channel downmix processing	111
D.2.1.3	Informational parameter processing	111
D.2.2	Legacy decoder processing	112
D.3	Encoder processing	112
D.3.0	Introduction	112
D.3.1	Encoder processing steps	112
D.3.1.1	Dynamic range overload protection processing	112
D.3.2	Encoder requirements	112
D.3.2.1	Legacy decoder support	112
D.3.2.2	Original bit stream syntax support	112
Annex E (normative):	Enhanced AC-3	113
E.0	Scope	113
E.1	Bit stream syntax and semantics specification	113
E.1.1	Indication of Enhanced AC-3 bit stream syntax	113
E.1.2	Syntax specification	113
E.1.2.0	E-AC-3_bit_stream and syncframe	113
E.1.2.1	syncinfo - Synchronization information	114
E.1.2.2	bsi - Bit stream information	114
E.1.2.3	audfrm - Audio frame	116
E.1.2.4	audblk - Audio block	118
E.1.2.5	auxdata - Auxiliary data	125
E.1.2.6	errorcheck - Error detection code	125
E.1.3	Description of Enhanced AC-3 bit stream elements	126
E.1.3.0	Introduction	126
E.1.3.1	bsi - Bit stream information	126
E.1.3.1.1	strmtyp - Stream type - 2 bits	126
E.1.3.1.2	substreamid - Substream identification - 3 bits	126
E.1.3.1.3	frmsiz - Frame size - 11 bits	127
E.1.3.1.4	fsco - Sample rate code - 2 bits	127
E.1.3.1.5	numblkscod - Number of audio blocks - 2 bits	127
E.1.3.1.6	bsid - Bit stream identification - 5 bits	127
E.1.3.1.7	chanmap - Custom channel map exists - 1 bit	127
E.1.3.1.8	chanmap - Custom channel map - 16 bits	128
E.1.3.1.9	mixmdate - Mixing Meta-data exists - 1 bit	128
E.1.3.1.10	lfemixlevcode - LFE mix level code exists - 1 bit	128
E.1.3.1.11	lfemixlevcod - LFE mix level code - 5 bits	128
E.1.3.1.12	pgmscle - Programme scale factor exists - 1 bit	129
E.1.3.1.13	pgmscl - Programme scale factor - 6 bits	129
E.1.3.1.14	pgmscl2e - Programme scale factor #2 exists - 1 bit	129
E.1.3.1.15	pgmscl2 - Programme scale factor #2 - 6 bits	129
E.1.3.1.16	extpgmscle - External programme scale factor exists - 1 bit	129
E.1.3.1.17	extpgmscl - External programme scale factor - 6 bits	129
E.1.3.1.18	mixdef - Mix control field length - 2 bits	129
E.1.3.1.19	premixcmpsel - Premix compression word select - 1 bit	129
E.1.3.1.20	drcsrc - Dynamic range control word source for the mixed output - 1 bit	130
E.1.3.1.21	premixcmpscl - Premix compression word scale factor - 3 bits	130
E.1.3.1.22	mixdeflen - Length of mixing parameter data field - 5 bits	130
E.1.3.1.23	mixdata - Mixing parameter data - (5 to 264) bits	130
E.1.3.1.24	mixdata2e - Mixing parameters for individual channel scaling exist - 1 bit	130
E.1.3.1.25	extpgmlscl - External programme left channel scale factor exists - 1 bit	130
E.1.3.1.26	extpgmlscl - External programme left channel scale factor - 4 bits	130
E.1.3.1.27	extpgmcscl - External programme centre channel scale factor exists - 1 bit	131
E.1.3.1.28	extpgmcscl - External programme centre channel scale factor - 4 bits	131

E.1.3.1.29	extpgmrscl - External programme right channel scale factor exists - 1 bit.....	131
E.1.3.1.30	extpgmrscl - External programme right channel scale factor - 4 bits.....	131
E.1.3.1.31	extpgmlsscl - External programme left surround channel scale factor exists - 1 bit	131
E.1.3.1.32	extpgmlsscl - External programme left surround channel scale factor - 4 bits.....	131
E.1.3.1.33	extpgmrsscl - External programme right surround channel scale factor exists - 1 bit.....	132
E.1.3.1.34	extpgmrsscl - External programme right surround channel scale factor - 4 bits	132
E.1.3.1.35	extpgmlfescle - External programme LFE channel scale factor exists - 1 bit	132
E.1.3.1.36	extpgmlfescle - External programme LFE channel scale factor - 4 bits	132
E.1.3.1.37	dmixscl - External programme downmix scale factor exists - 1 bit	132
E.1.3.1.38	dmixscl - External programme downmix scale factor - 4 bits.....	132
E.1.3.1.39	addche - Scale factors for additional external programme channels exist - 1 bit	132
E.1.3.1.40	extpgmaux1scl - External programme first auxiliary channel scale factor exists - 1 bit	132
E.1.3.1.41	extpgmaux1scl - External programme first auxiliary channel scale factor - 4 bits	133
E.1.3.1.42	extpgmaux2scl - External programme second auxiliary channel scale factor exists - 1 bit	133
E.1.3.1.43	extpgmaux2scl - External programme second auxiliary channel scale factor - 4 bits.....	133
E.1.3.1.44	mixdata3e - Mixing parameters for speech processing exist - 1 bit	133
E.1.3.1.45	spchdat - Speech enhancement processing data - 5 bits	133
E.1.3.1.46	addspchdate - Additional speech enhancement processing data exists - 1 bit.....	133
E.1.3.1.47	spchdat1 - Additional speech enhancement processing data - 5 bits.....	133
E.1.3.1.48	spchan1att - Speech enhancement processing attenuation data - 2 bits.....	133
E.1.3.1.49	addspchdat1e - Additional speech enhancement processing data exists - 1 bit.....	133
E.1.3.1.50	spchdat2 - Additional speech enhancement processing data - 5 bits.....	134
E.1.3.1.51	spchan2att - Speech enhancement processing attenuation data - 3 bits.....	134
E.1.3.1.52	mixdatafill - Mixdata field fill bits - 0 to 7 bits.....	134
E.1.3.1.53	paninfoe - Pan information exists - 1 bit.....	134
E.1.3.1.54	panmean - Pan mean direction index - 8 bits.....	134
E.1.3.1.55	paninfo - reserved - 6 bits.....	134
E.1.3.1.56	paninfo2e - Pan information exists - 1 bit.....	134
E.1.3.1.57	panmean2 - Pan mean direction index - 8 bits	134
E.1.3.1.58	paninfo2 - reserved - 6 bits.....	134
E.1.3.1.59	frmmixcfginfoe - Frame mixing configuration information exists - 1 bit.....	134
E.1.3.1.60	blkmixcfginfoe - Block mixing configuration information exists - 1 bit	134
E.1.3.1.61	blkmixcfginfo[blk] - Block mixing configuration information - 5 bits.....	135
E.1.3.1.62	infomdate - Informational metadata Exists - 1 bit.....	135
E.1.3.1.63	sourcefscl - Source sample rate code - 1 bit.....	135
E.1.3.1.64	convsync - Converter synchronization flag - 1 bit	135
E.1.3.1.65	blkid - Block identification - 1 bit.....	135
E.1.3.2	audfrm - Audio frame	135
E.1.3.2.1	expstre - Exponent strategy syntax enabled - 1 bit.....	135
E.1.3.2.2	ahte - Adaptive hybrid transform enabled - 1 bit	135
E.1.3.2.3	snroffststr - SNR offset strategy - 2 bits.....	135
E.1.3.2.4	transproce - Transient pre-noise processing enabled - 1 bit	136
E.1.3.2.5	blksw - Block switch syntax enabled - 1 bit.....	136
E.1.3.2.6	dithflage - Dither flag syntax enabled - 1 bit.....	136
E.1.3.2.7	bamode - Bit allocation model syntax enabled - 1 bit	136
E.1.3.2.8	frmfgaincode - Fast gain codes enabled - 1 bit.....	136
E.1.3.2.9	dbafld - Delta bit allocation syntax enabled - 1 bit.....	136
E.1.3.2.10	skipfld - Skip field syntax enabled - 1 bit.....	136
E.1.3.2.11	spxattene - Spectral extension attenuation enabled - 1 bit.....	136
E.1.3.2.12	frmcplexpstr - Frame based coupling exponent strategy - 5 bits.....	136
E.1.3.2.13	frmcchexpstr[ch] - Frame based channel exponent strategy - 5 bits	136
E.1.3.2.14	convexpstre - Converter exponent strategy exists - 1 bit.....	137
E.1.3.2.15	convexpstr[ch] - Converter channel exponent strategy - 5 bits	137
E.1.3.2.16	cplahinu - Coupling channel AHT in use - 1 bit	137
E.1.3.2.17	chahtinu[ch] - Channel AHT in use - 1 bit.....	137
E.1.3.2.18	lfehtinu - LFE channel AHT in use - 1 bit.....	137
E.1.3.2.19	frmcnsroffst - Frame coarse SNR offset - 6 bits.....	138
E.1.3.2.20	frmfnsroffst - Frame fine SNR offset - 4 bits	138
E.1.3.2.21	chintransproc[ch] - Channel in transient pre-noise processing - 1 bit	138
E.1.3.2.22	transprocloc[ch] - Transient location relative to start of frame - 10 bits	138
E.1.3.2.23	transprocclen[ch] - Transient processing length - 8 bits	138
E.1.3.2.24	chinspxatten[ch] - Channel in spectral extension attenuation processing - 1 bit.....	138

E.1.3.2.25	spxattencod[ch] - Spectral extension attenuation code - 5 bits.....	138
E.1.3.2.26	blkstrtinfor - Block start information exists - 1 bit	138
E.1.3.2.27	blkstrtinfor - Block start information - nblkstrtbits	138
E.1.3.2.28	firstspxcos[ch] - First spectral extension coordinates states - 1 bit	139
E.1.3.2.29	firstcplcos[ch] - First coupling coordinates states - 1 bit.....	139
E.1.3.2.30	firstcplleak - First coupling leak state - 1 bit.....	139
E.1.3.3	audblk - Audio block	139
E.1.3.3.1	spxstre - Spectral extension strategy exists - 1 bit.....	139
E.1.3.3.2	spxinu - Spectral extension in use - 1 bit.....	139
E.1.3.3.3	chinspx[ch] - Channel using spectral extension - 1 bit.....	139
E.1.3.3.4	spxstrtf - Spectral extension start copy frequency code - 2 bits	139
E.1.3.3.5	spxbegf - Spectral extension begin frequency code - 3 bits	139
E.1.3.3.6	spxendf - Spectral extension end frequency code - 3 bits	140
E.1.3.3.7	spxbndstrce - Spectral extension band structure exist - 1 bit	140
E.1.3.3.8	spxbndstrc[bnd] - Spectral extension band structure - 1 bit to 14 bits	140
E.1.3.3.9	spxcoe[ch] - Spectral extension coordinates exist - 1 bit	140
E.1.3.3.10	spxblend[ch] - Spectral extension blend - 5 bits	140
E.1.3.3.11	mstrspxco[ch] - Master spectral extension coordinate - 2 bits	141
E.1.3.3.12	spxcoexp[ch][bnd] - Spectral extension coordinate exponent - 4 bits.....	141
E.1.3.3.13	spxcomant[ch][bnd] - Spectral extension coordinate mantissa - 2 bits	141
E.1.3.3.14	ecplinu - Enhanced coupling in use - 1 bit	141
E.1.3.3.15	cplbndstrce - Coupling banding structure exist - 1 bit.....	141
E.1.3.3.16	ecplbegf - Enhanced coupling begin frequency code - 4 bits.....	142
E.1.3.3.17	ecplendf - Enhanced coupling end frequency code - 4 bits	142
E.1.3.3.18	ecplbndstrce - Enhanced coupling banding structure exists - 1 bit	142
E.1.3.3.19	ecplbndstrc[sbnd] - Enhanced coupling band (and sub-band) structure - 1 bit	142
E.1.3.3.20	ecplparam1e[ch] - Enhanced coupling parameters 1 exist - 1 bit.....	143
E.1.3.3.21	ecplamp[ch][bnd] - Enhanced coupling amplitude scaling - 5 bits	143
E.1.3.3.22	rsvdfldse - reserved fields exist - 1 bit.....	143
E.1.3.3.23	blkfsnroffst - Block fine SNR offset - 4 bits	143
E.1.3.3.24	fgaincode - Fast gain codes exist - 1 bit	143
E.1.3.3.25	convsnroffste - Converter SNR offset exists - 1 bit	143
E.1.3.3.26	convsnroffst - Converter SNR offset - 10 bits.....	144
E.1.3.3.27	chgaqmod[ch] - Channel gain adaptive quantization mode - 2 bits	144
E.1.3.3.28	chgaqgain[ch][n] - Channel gain adaptive quantization gain - 1 bit or 5 bits	144
E.1.3.3.29	pre_chmant[n][ch][bin] - Pre channel mantissas - 0 to 16 bits.....	144
E.1.3.3.30	cplgaqmod - Coupling channel gain adaptive quantization mode - 2 bits.....	144
E.1.3.3.31	cplgaqgain[n] - Coupling channel gain adaptive quantization gain - 1 bit or 5 bits	144
E.1.3.3.32	pre_cplmant[n][bin] - Pre coupling channel mantissas - 0 bits to 16 bits	144
E.1.3.3.33	lfegaqmod - LFE channel gain adaptive quantization mode - 2 bits	144
E.1.3.3.34	lfegaqgain[n] - LFE gain adaptive quantization gain - 1 bit or 5 bits.....	144
E.1.3.3.35	pre_lfemant[n][bin] - Pre LFE channel mantissas - 0 bits to 16 bits.....	144
E.2	Decoder processing	145
E.2.0	Introduction	145
E.2.1	Glitch-free switching between different stream types	145
E.2.2	Error detection and concealment	145
E.2.3	Modifications to previously defined parameters	145
E.2.3.0	Introduction.....	145
E.2.3.1	cplendf - Coupling end frequency code	145
E.2.3.2	nrematbd - Number of rematrixing bands.....	145
E.2.3.3	endmant - End mantissa	146
E.2.3.4	nchmant - Number of fbw channel mantissas	146
E.2.3.5	ncplgrps - Number of coupled exponent groups.....	146
E.2.4	Adaptive Hybrid Transform processing	147
E.2.4.1	Overview	147
E.2.4.2	Bit stream helper variables	147
E.2.4.3	Bit allocation.....	151
E.2.4.3.0	Introduction.....	151
E.2.4.3.1	Parametric bit allocation	151
E.2.4.3.2	Bit allocation tables.....	152
E.2.4.4	Quantization.....	153

E.2.4.4.0	Introduction.....	153
E.2.4.4.1	Vector quantization.....	153
E.2.4.4.2	Gain adaptive quantization.....	154
E.2.4.5	Transform equations.....	156
E.2.5	Enhanced channel coupling.....	157
E.2.5.1	Overview.....	157
E.2.5.2	Sub-band structure for enhanced coupling.....	157
E.2.5.3	Enhanced coupling tables.....	158
E.2.5.4	Enhanced coupling coordinate format.....	159
E.2.5.5	Enhanced coupling processing.....	159
E.2.5.5.0	Introduction.....	159
E.2.5.5.1	Amplitude parameter processing.....	160
E.2.5.5.2	Generate channel transform coefficients.....	160
E.2.6	Spectral extension processing.....	160
E.2.6.0	Introduction.....	160
E.2.6.1	Overview.....	161
E.2.6.2	Sub-band structure for spectral extension.....	161
E.2.6.3	Spectral extension coordinate format.....	162
E.2.6.4	High frequency transform coefficient synthesis.....	163
E.2.6.4.0	Introduction.....	163
E.2.6.4.1	Transform coefficient translation.....	163
E.2.6.4.2	Transform coefficient noise blending.....	163
E.2.6.4.2.0	Introduction.....	163
E.2.6.4.2.1	Blending factor calculation.....	164
E.2.6.4.2.2	Banded RMS energy calculation.....	164
E.2.6.4.2.3	Noise Scaling and Transform Coefficient Blending Calculation.....	165
E.2.6.4.2.4	Noise scaling and transform coefficient blending calculation.....	166
E.2.6.4.3	Blended transform coefficient scaling.....	167
E.2.7	Transient pre-noise processing.....	167
E.2.7.0	Introduction.....	167
E.2.7.1	Overview.....	167
E.2.7.2	Application of transient pre-noise processing data.....	167
E.2.8	Channel and programme extensions.....	169
E.2.8.0	Introduction.....	169
E.2.8.1	Overview.....	169
E.2.8.2	Decoding a single programme with greater than 5.1 channels.....	170
E.2.8.3	Decoding multiple programmes with up to 5.1 channels.....	170
E.2.8.4	Decoding a mixture of programmes with up to 5.1 channels and programmes with greater than 5.1 channels.....	171
E.2.8.5	Dynamic range compression for programmes containing greater than 5.1 channels.....	171
E.2.9	LFE downmixing decoder description.....	171
E.2.10	Control of Programme Mixing.....	172
E.2.10.1	Overview.....	172
E.2.10.2	pgmscl.....	172
E.2.10.3	extpgmscl.....	172
E.2.10.4	mixdef.....	173
E.2.10.5	mixdeflen.....	173
E.2.10.6	mixdata2e.....	173
E.2.10.7	extpgm(X)scl.....	173
E.2.10.8	dmixscl.....	174
E.2.10.9	panmean.....	174
E.3	AHT vector quantization tables.....	175
Annex F (normative):	AC-3 and Enhanced AC-3 bit streams in the ISO Base Media File Format.....	192
F.0	Scope.....	192
F.1	AC-3 and Enhanced AC-3 Track definition.....	192
F.2	AC-3 and Enhanced AC-3 Sample definition.....	193
F.3	AC3SampleEntry Box.....	196

F.3.0	Introduction	196
F.3.1	Syntax	196
F.3.2	Semantics	196
F.4	AC3SpecificBox	196
F.4.1	Syntax	196
F.4.2	Semantics	197
F.4.2.1	BoxHeader.Type - 32 bits	197
F.4.2.2	fscod - 2 bits	197
F.4.2.3	bsid - 5 bits	197
F.4.2.4	bsmod - 3 bits	197
F.4.2.5	acmod - 3 bits	197
F.4.2.6	lfeon - 1 bit	197
F.4.2.7	bit_rate_code - 5 bits	197
F.4.2.8	reserved - 5 bits	198
F.5	EC3SampleEntry Box	198
F.5.1	Syntax	198
F.5.2	Semantics	198
F.6	EC3SpecificBox	198
F.6.1	Syntax	198
F.6.2	Semantics	199
F.6.2.1	BoxHeader.Type - 32 bits	199
F.6.2.2	data_rate - 13 bits	199
F.6.2.3	num_ind_sub - 3 bits	199
F.6.2.4	fscod - 2 bits	199
F.6.2.5	bsid - 5 bits	199
F.6.2.6	reserved - 1 bit	200
F.6.2.7	asvc - 1 bit	200
F.6.2.8	bsmod - 3 bits	200
F.6.2.9	acmod - 3 bits	200
F.6.2.10	lfeon - 1 bit	200
F.6.2.11	reserved - 3 bits	200
F.6.2.12	num_dep_sub - 4 bits	200
F.6.2.13	chan_loc - 9 bits	200
F.6.2.14	reserved - variable	201
Annex G (normative):	Enhanced AC-3 bit streams in the MPEG-2 multiplex	202
Annex H (normative):	Extensible format for delivery of metadata	203
H.0	Scope	203
H.1	Overview	203
H.2	Container syntax and semantics specification	204
H.2.1	Syntax	204
H.2.1.1	emdf_sync - EMDF container synchronization information	204
H.2.1.2	emdf_container - EMDF container	204
H.2.1.2.0	emdf_container	204
H.2.1.2.1	variable_bits - variable bit-length field format	204
H.2.1.3	emdf_payload_config - EMDF payload configuration	205
H.2.1.4	emdf_protection - EMDF protection data	205
H.2.2	Semantics	205
H.2.2.1	emdf_sync - synchronization information	205
H.2.2.1.1	syncword - synchronization word - 16 bits	205
H.2.2.1.2	emdf_container_length - EMDF container length - 16 bits	205
H.2.2.2	emdf_container - EMDF metadata container structure	206
H.2.2.2.1	variable_bits(n) - variable-bit field encoding	206
H.2.2.2.2	emdf_version - EMDF syntax version - 2 bits / variable_bits(2)	206
H.2.2.2.3	key_id - authentication key identification - 3 bits	206
H.2.2.2.4	emdf_payload_id - EMDF payload identification - 5 bits	207
H.2.2.2.5	emdf_payload_size - size of EMDF payload - variable_bits(8)	207

H.2.2.3	emdf_payload_config - EMDF payload configuration data	207
H.2.2.3.1	smploffste - payload sample offset exists - 1 bit	207
H.2.2.3.2	smploffst - payload sample offset - 11 bits	207
H.2.2.3.3	duratione - payload duration data exists - 1 bit	207
H.2.2.3.4	duration - payload duration data - variable_bits(11)	207
H.2.2.3.5	groupide - payload group ID data exists - 1 bit	207
H.2.2.3.6	groupid - payload group ID - variable_bits(2)	208
H.2.2.3.7	codecdatæ - codec-specific data exists - 1 bit	208
H.2.2.3.8	discard_unknown_payload - discard unknown payload during transcode - 1 bit	208
H.2.2.3.9	create_duplicate - create duplicate payload during transcode - 1 bit	208
H.2.2.3.10	remove_duplicate - remove duplicate payload during transcode - 1 bit	208
H.2.2.3.11	payload_frame_aligned - payload to audio data frame alignment - 1 bit	208
H.2.2.3.12	priority - payload priority - 5 bit	208
H.2.2.3.13	proc_allowed - retain payload during transcoding - 2 bits	209
H.2.2.4	emdf_protection - EMDF container protection data	209
H.2.2.4.1	protection_length_primary - length of protection_bits_primary field - 2 bits	209
H.2.2.4.2	protection_length_secondary - length of protection_bits_secondary field - 2 bits	209
H.2.2.4.3	protection_bits_primary - primary EMDF container protection data - 8 to 128 bits	209
H.2.2.4.4	protection_bits_secondary - secondary EMDF container protection data - 0 to 128 bits	210
H.3	EMDF payload types	210
H.3.1	Payload ID 0x1 - programme loudness data	210
H.3.1.1	Overview	210
H.3.1.2	Syntax	210
H.3.1.3	Semantics	211
H.3.1.3.1	version - Version of loudness payload - 2 bits	211
H.3.1.3.2	dialchane - Dialogue presence data exists	211
H.3.1.3.3	dialchan - Dialogue present in channel - 3 bits	212
H.3.1.3.4	loudpractyp - Loudness measurement practice used - 4 bits	212
H.3.1.3.5	loudcorrdialgat - Dialogue-gated loudness correction applied - 1 bit	212
H.3.1.3.6	loudcorrtp - Type of loudness correction applied to programme - 1 bit	212
H.3.1.3.7	loudrelgate - Relative gated loudness data (ITU) exists - 1 bit	212
H.3.1.3.8	loudrelgat - Relative gated programme loudness (ITU) - 7 bits	212
H.3.1.3.9	loudspchgate - Speech-gated loudness data (ITU) exists - 1 bit	213
H.3.1.3.10	loudspchgat - Speech-gated programme loudness (ITU) - 7 bits	213
H.3.1.3.11	loudstrm3se - Short-term (3 second) loudness data exists - 1 bit	213
H.3.1.3.12	loudstrm3s - Short-term (3 second) programme loudness - 8 bits	213
H.3.1.3.13	truepke - True peak loudness data exists - 1 bit	213
H.3.1.3.14	truepk - True peak value - 8 bits	213
H.3.1.3.15	dmixloudoffste - Downmix loudness offset data exists - 1 bit	213
H.3.1.3.16	dmixloudoffst - Downmix loudness offset - 5 bits	213
H.3.1.3.17	prgmbndye - Programme boundary data exists - 1 bit	214
H.3.1.3.18	prgmbndy_bit - Programme boundary bit value - 1 bit	214
H.3.1.3.19	end_or_start - Programme boundary indicates end or start of programme - 1 bit	214
H.3.1.3.20	prgmbndyoffste - Programme boundary sample offset exists - 1 bit	214
H.3.1.3.21	prgmbndyoffst - Programme boundary sample offset - 11 bits	214
H.3.1.3.22	hrloudrelgate - High resolution relative gated loudness data (ITU) exists - 1 bit	214
H.3.1.3.23	hrloudrelgat - High resolution relative gated programme loudness (ITU) - 3 bits	215
H.3.1.3.24	hrloudspchgate - High resolution speech-gated loudness data (ITU) exists - 1 bit	215
H.3.1.3.25	hrloudspchgat - High resolution speech-gated programme loudness (ITU) - 3 bits	215
H.3.1.3.26	hrloudstrm3se - High resolution short-term (3 second) loudness data exists - 1 bit	215
H.3.1.3.27	hrloudstrm3s - High resolution short-term (3 second) loudness - 3 bits	215
H.3.1.3.28	hrtruepke - High resolution true peak loudness data exists - 1 bit	216
H.3.1.3.29	hrtruepk - High resolution true peak value - 3 bits	216
H.3.1.3.30	loudcorrdialgattyp - Dialog gating type used for loudness correction - 3 bits	216
H.3.1.3.31	extloudrelgate - Extended range relative gated loudness data (ITU) exists - 1 bit	216
H.3.1.3.32	extloudrelgat - Extended range relative gated loudness data (ITU) - 11 bits	217
H.3.1.3.33	extloudspchgate - Extended range speech-gated loudness data (ITU) exists - 1 bit	217
H.3.1.3.34	extloudspchgat - Extended range speech-gated loudness value - 11 bits	217
H.3.1.3.35	loudspchdialgattyp - Dialog gating type used for loudness measurement - 3 bits	217
H.3.1.3.36	extloudstrm3se - Extended range short-term (3 second) programme loudness exists - 1 bit	218
H.3.1.3.37	extloudstrm3s - Extended range short-term (3 second) programme loudness - 11 bits	218