



**SLOVENSKI STANDARD**  
**SIST EN 301 178 V2.2.2:2017**  
**01-junij-2017**

---

**Prenosne radiotelefonske naprave VHF za pomorske mobilne storitve, ki delujejo v območju VHF (samo za uporabo zunaj GMDSS) - Harmonizirani standard, ki zajema bistvene zahteve člena 3.2 direktive 2014/53/EU**

Portable Very High Frequency (VHF) radiotelephone equipment for the maritime mobile service operating in the VHF bands (for non-GMDSS applications only) - Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 301 178 V2.2.2:2017  
https://standards.iteh.ai/catalog/standards/sist/a269dca7-024d-4c41-8201-82df0441fdcf/sist-en-301-178-v2-2-2-2017](https://standards.iteh.ai/catalog/standards/sist/a269dca7-024d-4c41-8201-82df0441fdcf/sist-en-301-178-v2-2-2-2017)

**Ta slovenski standard je istoveten z: ETSI EN 301 178 V2.2.2 (2017-04)**

---

**ICS:**

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
47.020.70	Navigacijska in krmilna oprema	Navigation and control equipment

**SIST EN 301 178 V2.2.2:2017** en

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 301 178 V2.2.2:2017](https://standards.iteh.ai/catalog/standards/sist/a269dca7-024d-4c41-8201-82df0441fdcf/sist-en-301-178-v2-2-2-2017)

<https://standards.iteh.ai/catalog/standards/sist/a269dca7-024d-4c41-8201-82df0441fdcf/sist-en-301-178-v2-2-2-2017>

# ETSI EN 301 178 V2.2.2 (2017-04)



**Portable Very High Frequency (VHF) radiotelephone equipment  
for the maritime mobile service operating in the VHF bands  
(for non-GMDSS applications only);  
Harmonised Standard covering the essential requirements  
of article 3.2 of Directive 2014/53/EU**

STANDARD PREVIEW  
(GMDSS applications)  
SIST EN 301 178 V2.2.2:2017  
http://www.etsi.org/standards-store/catalogue.aspx?EN\_301\_178\_V2\_2\_2\_2017  
82df0441fdcf/sist-en-301-178-v2-2-2-2017

## Reference

---

REN/ERM-TG26-532C1

## Keywords

---

harmonised standard, maritime, radio, VHF**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 301 178 V2.2.2:2017

<https://standards.iteh.ai/catalog/standards/sist/a269dca7-024d-4c41-8201-82df0441bc3d/ETSI-ERM-TG26-532C1-2017>  
**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	7
Foreword.....	7
Modal verbs terminology.....	7
1 Scope .....	8
2 References .....	8
2.1 Normative references .....	8
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations .....	9
3.1 Definitions.....	9
3.2 Symbols.....	9
3.3 Abbreviations .....	10
4 General and operational requirements.....	10
4.1 Construction .....	10
4.2 Controls and indicators.....	11
4.3 Microphone and loudspeaker .....	11
4.4 Safety precautions .....	11
4.5 Labelling.....	12
5 Technical requirements specifications .....	12
5.1 Environmental profile.....	12
5.2 Conformance requirements .....	12
5.2.1 Switching time .....	12
5.2.2 Class of emission and modulation characteristics.....	12
6 General conditions of measurement.....	12
6.1 Arrangements for RF connections to the equipment.....	12
6.1.1 RF connections to integral antenna equipment.....	12
6.1.2 RF connection to equipment with a detachable antenna .....	13
6.2 Arrangements for test signals applied to the receiver input.....	13
6.3 Squelch.....	13
6.4 Normal test modulation .....	13
6.5 Artificial antenna.....	13
6.6 Arrangements for test signals applied to the transmitter input .....	13
6.7 Test channels.....	13
6.8 Test conditions, power sources and ambient temperatures.....	13
6.8.1 Normal and extreme test conditions.....	13
6.8.2 Test power source .....	14
6.9 Normal test conditions.....	14
6.9.1 Normal temperature and humidity .....	14
6.9.2 Normal power sources .....	14
6.9.2.1 Battery power source.....	14
6.9.2.2 Other power sources.....	14
6.10 Extreme test conditions .....	14
6.10.0 General.....	14
6.10.1 Extreme temperatures .....	14
6.10.2 Extreme values of test power sources .....	14
6.10.2.1 Battery power source.....	14
6.10.2.2 Other power sources.....	15
6.11 Procedure for tests at extreme temperatures.....	15
6.12 Reference bandwidths for spurious measurements.....	15
7 Environmental tests .....	15
7.1 Procedure.....	15
7.2 Performance check .....	15
7.3 Drop test.....	15

7.3.1	Definition.....	15
7.3.2	Method of measurement .....	16
7.3.3	Requirement.....	16
7.4	Temperature tests .....	16
7.4.1	Definition.....	16
7.4.2	Dry heat .....	16
7.4.2.1	Definition .....	16
7.4.2.2	Method of measurement.....	16
7.4.2.3	Requirement .....	16
7.4.3	Damp heat.....	16
7.4.3.1	Definition .....	16
7.4.3.2	Method of measurement.....	17
7.4.3.3	Requirement .....	17
7.4.4	Low temperature cycle.....	17
7.4.4.1	Definition .....	17
7.4.4.2	Method of measurement.....	17
7.4.4.3	Requirement .....	17
8	Transmitter .....	17
8.1	Frequency error .....	17
8.1.1	Definition.....	17
8.1.2	Method of measurement .....	17
8.1.3	Limits.....	18
8.2	Carrier power.....	18
8.2.1	Definitions .....	18
8.2.2	Method of measurement .....	18
8.2.3	Limits, Normal and extreme test conditions .....	18
8.3	Frequency deviation .....	18
8.3.1	Definition.....	18
8.3.2	Maximum permissible frequency deviation.....	18
8.3.2.1	Method of measurement.....	18
8.3.2.2	Limits .....	18
8.3.3	Reduction of frequency deviation at modulation frequencies above 3 kHz.....	19
8.3.3.1	Method of measurement.....	19
8.3.3.2	Limits .....	19
8.4	Sensitivity of the modulator, including microphone .....	20
8.4.1	Definition.....	20
8.4.2	Method of measurement .....	20
8.4.3	Limits.....	20
8.5	Audio frequency response .....	20
8.5.1	Definition.....	20
8.5.2	Method of measurement .....	20
8.5.3	Limit .....	20
8.6	Audio frequency harmonic distortion of the emission.....	21
8.6.1	Definition.....	21
8.6.2	Method of measurement .....	21
8.6.2.1	RF Coupling to the test demodulator .....	21
8.6.2.2	Normal test conditions .....	22
8.6.2.3	Extreme test conditions .....	22
8.6.3	Limits.....	22
8.7	Adjacent channel power .....	22
8.7.1	Definition.....	22
8.7.2	Method of measurement .....	22
8.7.3	Limits.....	23
8.8	Conducted spurious emissions conveyed to the antenna .....	23
8.8.1	Definition.....	23
8.8.2	Method of measurement .....	23
8.8.3	Limit .....	23
8.9	Cabinet radiation and conducted spurious emissions other than those conveyed to the antenna .....	23
8.9.1	Definitions .....	23
8.9.2	Method of measurement .....	23
8.9.3	Limits.....	24

8.10	Residual modulation of the transmitter .....	25
8.10.1	Definition .....	25
8.10.2	Method of measurement .....	25
8.10.3	Limit .....	25
8.11	Transient frequency behaviour of the transmitter .....	25
8.11.1	Definitions .....	25
8.11.2	Method of measurement .....	26
8.11.3	Limits .....	27
9	Receiver .....	29
9.1	Harmonic distortion and rated audio frequency output power .....	29
9.1.1	Definition .....	29
9.1.2	Methods of measurement .....	29
9.1.3	Limits .....	29
9.2	Audio frequency response .....	29
9.2.1	Definition .....	29
9.2.2	Method of measurement .....	29
9.2.3	Limits .....	30
9.3	Maximum usable sensitivity .....	30
9.3.1	Definition .....	30
9.3.2	Method of measurement .....	31
9.3.3	Limits .....	31
9.4	Co-channel rejection .....	31
9.4.1	Definition .....	31
9.4.2	Method of measurement .....	31
9.4.3	Limit .....	31
9.5	Adjacent channel selectivity .....	32
9.5.1	Definition .....	32
9.5.2	Method of measurement .....	32
9.5.3	Limits .....	32
9.6	Spurious response rejection .....	32
9.6.1	Definition .....	32
9.6.2	Method of measurement .....	32
9.6.3	Limit .....	33
9.7	Intermodulation response .....	33
9.7.1	Definition .....	33
9.7.2	Method of measurement .....	33
9.7.3	Limit .....	33
9.8	Blocking or desensitization .....	33
9.8.1	Definition .....	33
9.8.2	Method of measurement .....	33
9.8.3	Limit .....	34
9.9	Conducted spurious emissions .....	34
9.9.1	Definition .....	34
9.9.2	Method of measurement .....	34
9.9.3	Limit .....	34
9.10	Radiated spurious emissions .....	34
9.10.1	Definition .....	34
9.10.2	Method of measurements .....	34
9.10.3	Limit .....	35
9.11	Receiver noise and hum level .....	35
9.11.1	Definition .....	35
9.11.2	Method of measurement .....	35
9.11.3	Limit .....	36
9.12	Squelch operation .....	36
9.12.1	Definition .....	36
9.12.2	Method of measurement .....	36
9.12.3	Limits .....	36
9.13	Squelch hysteresis .....	37
9.13.1	Definition .....	37
9.13.2	Method of measurement .....	37
9.13.3	Limit .....	37

10	Testing for compliance with technical requirements.....	37
10.1	Environmental conditions for testing .....	37
10.2	Interpretation of the measurement results .....	37
<b>Annex A (informative):</b>	<b>Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b>	<b>39</b>
<b>Annex B (normative):</b>	<b>Measuring receiver for adjacent channel power measurement.....</b>	<b>41</b>
B.1	Power measuring receiver specification.....	41
B.1.0	General .....	41
B.1.1	IF filter .....	41
B.1.2	Attenuation indicator.....	42
B.1.3	rms value indicator .....	42
B.1.4	Oscillator and amplifier.....	42
<b>Annex C (informative):</b>	<b>Change history .....</b>	<b>43</b>
History .....		44

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 178 V2.2.2:2017](https://standards.iteh.ai/catalog/standards/sist/a269dca7-024d-4c41-8201-82df0441fdcf/sist-en-301-178-v2-2-2-2017)

<https://standards.iteh.ai/catalog/standards/sist/a269dca7-024d-4c41-8201-82df0441fdcf/sist-en-301-178-v2-2-2-2017>



## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.5] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

(standards.iteh.ai)

National transposition dates	
Date of latest announcement of this EN (doa):	31 July 2017
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2018
Date of withdrawal of any conflicting National Standard (dow):	31 January 2019

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# 1 Scope

The present document specifies technical characteristics and methods of measurements for equipment:

- 1) portable Very High Frequency (VHF) transceivers operating with 25 kHz channels;
- 2) portable Very High Frequency (VHF) transceivers operating with both 25 kHz and 12,5 kHz channels.

These radiotelephones are not providing maritime distress and safety communications functions (i.e. not forming part of the Global Maritime Distress and Safety System (GMDSS)) operating in certain frequency bands allocated to the maritime mobile service using either 25 kHz or 25 kHz and 12,5 kHz channels.

The present document covers the essential requirements of article 3.2 of Directive 2014/53/EU [i.2] under the conditions identified in annex A.

---

## 2 References

### 2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ITU Radio Regulations (2016), appendix 18: "Table of transmitting frequencies in the VHF maritime mobile band".
- [2] Recommendation ITU-T E.161 (2001): "Arrangement of digits, letters and symbols on telephones and other devices that can be used for gaining access to a telephone network".
- [3] Recommendation ITU-R M.493-14 (2015): "Digital selective-calling system for use in the maritime mobile service".
- [4] Recommendation ITU-R M.541-10 (2015): "Operational procedures for the use of digital selective-calling equipment in the maritime mobile service".
- [5] ETSI EN 300 225 (V1.5.1) (12-2015): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Technical characteristics and methods of measurement for survival craft portable VHF radiotelephone apparatus".
- [6] Recommendation ITU-T O.41 (10-1994): "Psophometer for use on telephone-type circuits".
- [7] Recommendation ITU-R M.1084-5 (03-2012): "Interim solutions for improved efficiency in the use of the band 156-174 MHz by stations in the maritime mobile service".
- [8] ETSI TS 103 052 (V1.1.1) (03-2011): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Recommendation ITU-R SM.332-4: "Selectivity of receivers".
- [i.2] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] ETSI TR 100 028 (all parts) (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.4] ETSI TR 100 028-2 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
- [i.5] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

---

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**block:** to inhibit a function by making it inaccessible from the user interface

**detachable antenna:** antenna fixed to the equipment by means of an antenna connector and detachable by the user

**G3E:** phase-modulation (frequency modulation with a pre-emphasis of 6 dB/octave) for speech

**integral antenna:** antenna that is permanently fixed to the equipment and not detachable by the user

**modulation index:** ratio between the frequency deviation and the modulation frequency

**performance check:** check of:

- the transmitter carrier power and frequency
- receiver sensitivity

### 3.2 Symbols

For the purposes of the present document, the following symbols apply:

dBA                      Relative to  $2 \times 10^{-5}$  Pa

### 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ad	amplitude difference
AIS	Automatic Identification System
DSC	Digital Selective Calling
emf	electromotive force
EUT	Equipment Under Test
fd	frequency difference
GMDSS	Global Maritime Distress and Safety System
IF	Intermediate Frequency
MPFD	Maximum Permissible Frequency Deviation
RBW	Reference Bandwidth
RF	Radio Frequency
rms	root mean square
SINAD	(Signal + Noise + Distortion)/(Noise + Distortion)
VHF	Very High Frequency

---

## 4 General and operational requirements

### 4.1 Construction

The manufacturer shall declare that compliance to the requirements of clause 4 is achieved and shall provide relevant documentation.

The mechanical and electrical construction and finish of the equipment shall conform in all respects to good engineering practice, and the equipment shall be suitable for use on board ships.

All controls shall be of sufficient size to enable the usual control functions to be easily performed and the number of controls should be the minimum necessary for simple and satisfactory operation.

All parts of the equipment to be checked during inspection or maintenance operations shall be readily accessible. The components shall be readily identifiable.

Technical documentation shall be supplied with the equipment.

The VHF maritime mobile service uses both single-frequency and two-frequency channels. For two-frequency channels there shall be a separation of 4,6 MHz between the transmitting frequency and the receiving frequency (see Radio Regulations, appendix 18 [1]).

The equipment, which can consist of more than one unit, shall be capable of operating on single frequency and two-frequency channels with manual control (simplex).

The equipment shall be of a colour which distinguishes it from the portable VHF equipment specified in clause 4.1 of ETSI EN 300 225 [5].

The equipment shall be able to operate on appropriate channels defined in ITU Radio Regulations, appendix 18 [1], noting in particular footnotes m) and e).

Additional VHF channels for maritime use outside those defined by appendix 18 to the ITU Radio Regulations [1] may also be provided where permitted by relevant administrations. These channels shall be clearly identified for use as relating to the relevant administration(s) and accessed through a positive action(s) for enabling use of these channel(s) but means shall be provided to block any or all of these additional channels if required by the relevant administration(s).

If 12,5 kHz channels are implemented in the equipment it shall be in accordance with Annex 4 of Recommendation ITU-R M.1084-5 [7].

The equipment shall be so designed that use of channel 70 for purposes other than DSC is prevented (see Recommendations ITU-R M.493-14 [3] and M.541-10 [4]), and that use of channels AIS1 and AIS2 for purposes other than AIS is prevented.

Scan or multiple watch may be provided but means shall be provided to block or unblock these functions.

If the equipment is fitted with an auxiliary antenna connector, simultaneous connection of both the auxiliary antenna and the normal antenna shall be prevented.

It shall not be possible to transmit while any frequency synthesizer used within the transmitter is out of lock.

It shall not be possible to transmit during channel switching operations.

## 4.2 Controls and indicators

The equipment shall have a channel selector and shall indicate the designator, as shown in ITU Radio Regulations, appendix 18 [1], of the channel at which the equipment is set. The channel designator shall be legible irrespective of the external lighting conditions.

Channel 16 shall be distinctively marked. Selection of channel 16, shall be preferably by readily accessible means (e.g. a distinctively marked key). Selection of channel 16 by any means shall automatically set the transmitter output power to maximum. This power level may subsequently be reduced by manual user control if required.

Where an input panel on the equipment for entering the digits 0 to 9 is provided, this shall conform to Recommendation ITU-T E.161 [2].

The equipment shall have the following additional controls and indicators:

- on/off switch for the equipment with a visual indication that the equipment is in operation;
- a manual, non-locking push to talk switch to operate the transmitter with a visual indication that the transmitter is activated and facilities to limit the transmission time to a maximum of 5 minutes. A short audible alarm and a visual indication may be provided to show when the transmission will be automatically terminated within the next 10 s. It shall be possible to reoperate the push to talk switch and reactivate the transmitter after a 10 s period;
- a switch for reducing transmitter output power to no more than 1 W where the RF output power is more than 1 W;
- an audio frequency power volume control;
- a squelch control;
- a visual indication that the transmitter is activated.

The equipment shall also meet the following requirements:

- the user shall not have access to any control which, if wrongly set, might impair the technical characteristics of the equipment.

## 4.3 Microphone and loudspeaker

The equipment shall be fitted with an integral microphone and an integral loudspeaker.

During transmission the receiver output shall be muted.

## 4.4 Safety precautions

Measures shall be taken to protect the equipment against the effects of overcurrent or overvoltage.

Measures shall be taken to prevent damage to the equipment that might arise from an accidental reversal of polarity of the electrical power source.

No damage to the equipment shall occur when the antenna terminals are placed on open circuit or short circuit while transmitting for a period of at least 5 minutes in each case.