



**ElectroMagnetic Compatibility (EMC) standard
for marine radio equipment and services;
Harmonised Standard for electromagnetic compatibility;
Part 6: Specific conditions for Earth Stations on board
Vessels operating in frequency bands above 3 GHz**

PREVIEW
https://standards.iteh.ai/catalog/standards/si/4-364f-4c43-bd3c-afe8282c4ecb/etsi-en-301-843-6-v2-2-0-17-11

Reference

REN/ERM-EMC-389

Keywords

EMC, harmonised standard, maritime, radio

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and LTE™ are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	6
3 Definitions, symbols and abbreviations	7
3.1 Definitions.....	7
3.2 Symbols.....	7
3.3 Abbreviations	8
4 General and operational requirements.....	8
4.1 Environmental profile.....	8
4.2 Arrangements for test signals	8
4.2.0 General.....	8
4.2.1 Arrangements for test signals at the input of the transmitter	9
4.2.2 Arrangements for test signals at the output of the transmitter	9
4.2.3 Arrangements for test signals at the input of the receiver	9
4.2.4 Arrangements for test signals at the output of the receiver	9
4.2.5 Arrangements for testing transmitter and receiver together (as a system)	9
4.3 Exclusion bands.....	9
4.4 Narrow band responses of receivers.....	9
4.5 Normal test modulation	9
5 Performance assessment.....	10
5.1 General	10
5.2 Equipment which can provide a continuous communication link	10
5.3 Equipment which does not provide a continuous communication link	10
5.4 Ancillary equipment.....	10
5.5 Equipment classification	10
5.6 Equipment configuration(s).....	10
6 Performance criteria	12
6.0 Performance criteria grades.....	12
6.1 Performance criteria A for continuous phenomena applied to transmitters and receivers.....	12
6.2 Performance criteria B for transient phenomena applied to transmitters and receivers	13
6.2.1 Performance criteria (B _A) for transient phenomena applied to a grade A EUT	13
6.2.2 Performance criteria (B _B) for transient phenomena applied to a grade B EUT	13
6.3 Performance criteria C applied to power supply failure	14
6.4 Performance check	14
6.5 Performance criteria for equipment which does not provide a continuous communication link.....	14
6.6 Performance criteria for ancillary equipment tested on a stand alone basis	14
7 Applicability overview	14
7.1 Emission.....	14
7.1.1 General.....	14
7.1.2 Special conditions	15
7.2 Immunity	15
7.2.1 General.....	15
7.2.2 Special conditions.....	15
Annex A (informative): Relationship between the present document and the essential requirements of Directive 2014/53/EU	16

Annex B (normative):	Examples of earth stations on board vessels in the scope of the present document	18
B.0	Definitions of Earth Stations on board Vessels equipment within the scope of the present document	18
B.1	Earth Stations on board Vessels operating in the 11 GHz, 12 GHz and 14 GHz frequency bands allocated to the Fixed Satellite Service (FSS)	18
B.2	Earth Stations on board Vessels operating in the 6/4 GHz frequency bands allocated to the Fixed Satellite Service (FSS).....	18
Annex C (informative):	Change history	20
History	21

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/e7b091e4-364f-4c43-bd3c-afe8282c4ee6/etsi-en-301-843-6-v2.2.1-2017-11>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.3] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 6 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document together with ETSI EN 301 843-1 [1], covers the assessment of Earth Stations on board Vessels (ESVs) transmitting above 3 GHz in the Fixed Satellite Service (FSS) as defined in annex A and ancillary equipment in respect of ElectroMagnetic Compatibility (EMC).

Technical specifications related to the antenna port and emissions from the enclosure port of Earth Stations on board Vessels are not included in the present document. Such technical specifications are found in the related product standards for the effective use of the radio spectrum.

The present document specifies the applicable test conditions, performance assessment, and performance criteria for Earth Stations on board Vessels and the associated ancillary equipment.

In case of differences (for instance concerning special conditions, definitions, abbreviations) between the present document and ETSI EN 301 843-1 [1], the provisions of the present document take precedence.

The electromagnetic environment used in the present document to develop the technical specifications encompasses the electromagnetic environment on board ships as identified in IEC EN 60945 [i.2].

NOTE: The relationship between the present document and essential requirements of article 3.1b of Directive 2014/53/EU [i.1] is given in annex A.

2 References

2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 301 843-1 (V2.2.0) (07-2017): "ElectroMagnetic Compatibility (EMC) standard for marine radio equipment and services; Harmonised Standard for electromagnetic compatibility; Part 1: Common technical requirements".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] IEC EN 60945 (2002) + Corrigendum 1 (2008): "Maritime navigation and radiocommunication equipment and systems - General requirements - Methods of testing and required test results".

- [i.3] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ETSI EN 301 843-1 [1] and the following apply:

above-deck unit: part of the ESV intended to be installed above deck, as declared by the manufacturer, or as indicated in the user documentation

NOTE 1: The above-deck unit usually comprises the following main parts:

- a) the antenna sub-system which converts the incident radiation field into a guided wave and vice versa;
- b) the Low Noise Block (LNB) down converter, which is a device that amplifies, with very low internal noise, the received signals in the Radio Frequency (RF) band and converts them to intermediate frequencies;
- c) the up-converter and the power amplifier which convert from the intermediate frequency to RF and amplify the low level RF signals for transmission through the antenna subsystem;
- d) the stabilization and tracking subsystems that ensure pointing of the antenna main beam towards the satellite within the required accuracy.

NOTE 2: The installation equipment (means of attachment) is outside the scope of the present document. However, the antenna structures and other components directly mounted on the antenna and forming an integral part of it, are subject to the specifications of the present document.

below-deck unit: is composed of that part of the ESV equipment which is not part of the above-deck unit

NOTE: This unit is installed inside the vessel and is connected to the above-deck unit. The connection cable between the above and below-deck units is considered part of the below-deck unit.

carrier-off state: ESV is in this state when it is authorized by the Centralized Control and Monitoring Functions (CCMF) to transmit, but when it does not transmit any signal

NOTE: The existence of a carrier-off state depends on the system of transmission used. For ESV designed for continuous transmission mode there may be no carrier-off state.

carrier-on state: ESV is in this state when it is authorized by the CCMF to transmit and when it transmits a signal

transmission disabled state: ESV is in this state when it is not authorized by the CCMF to transmit

transmission enabled state: ESV is in this state when it is authorized by the CCMF to transmit

3.2 Symbols

For the purposes of the present document, the following symbols apply:

emf	electromotive force
rms	root mean square
SINAD	(Signal + Noise + Distortion) / (Noise + Distortion)

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI EN 301 843-1 [1] and the following apply:

B _A	Performance criteria grade A
B _B	Performance criteria grade B
CCMF	Centralized Control and Monitoring Functions
EIRP	Equivalent Isotropically Radiated Power
EMC	ElectroMagnetic Compatibility
ESV	Earth Station on board a Vessel
EUT	Equipment Under Test
FSS	Fixed Satellite Service
IF	Intermediate Frequency
LNB	Low Noise Block converter
QTMA	Quality of Transmission Measurement Apparatus
RF	Radio Frequency

4 General and operational requirements

4.1 Environmental profile

For the purposes of the present document, the test conditions of ETSI EN 301 843-1 [1], clause 4, shall apply as appropriate. Further product type related test conditions for Earth Stations on board Vessels are specified in the present document.

For emission and immunity tests the normal test modulation, test arrangements, etc., as specified in the present document, clauses 4.1 to 4.5 shall apply.

For Earth Stations on board Vessels with or without ancillary equipment, and/or various telecommunication ports, the number of test configurations shall be determined. The assessment shall include sufficient representative configurations of the ESV to adequately exercise the equipment. These configurations shall be recorded in the test report.

In the following clauses, the Equipment Under Test (EUT) is an ESV with the selected configuration of ancillary equipment.

4.2 Arrangements for test signals

4.2.0 General

The provisions of ETSI EN 301 843-1 [1], clause 4.2 shall apply with the following modifications.

In order to measure the unwanted emissions and electromagnetic immunity under operational conditions, the following arrangements shall be provided by the manufacturer:

- a) the specific test equipment and/or procedures to put the ESV terminal in its normal operating mode, and providing the ESV with a receive signal to emulate the operational conditions of reception. This equipment shall control the EUT, when it is capable of transmission, so that it switches between the transmission disabled, carrier-on and carrier-off states;
- b) the specific Quality of Transmission Measurement Apparatus (QTMA). The QTMA shall also monitor and record the stability of the antenna tracking during testing.

For the measurement of the quality of transmission a communications link shall be established and the wanted input signal shall be applied to the Radio Frequency (RF) input of the receiver via the antenna.

4.2.1 Arrangements for test signals at the input of the transmitter

The provisions of ETSI EN 301 843-1 [1], clause 4.2.1 shall apply.

4.2.2 Arrangements for test signals at the output of the transmitter

The provisions of ETSI EN 301 843-1 [1], clause 4.2.2 shall apply.

4.2.3 Arrangements for test signals at the input of the receiver

The provisions of ETSI EN 301 843-1 [1], clause 4.2.3 shall apply with the following modification.

For tests on the receiver, due to the fact that for satellite earth stations the receive margin is considerably lower than 40 dB, the level of the signal received from the test transmitter shall be as close as possible to the normal operation level of the EUT receiver.

4.2.4 Arrangements for test signals at the output of the receiver

The provisions of ETSI EN 301 843-1 [1], clause 4.2.4 shall apply as appropriate.

4.2.5 Arrangements for testing transmitter and receiver together (as a system)

The provisions of ETSI EN 301 843-1 [1], clause 4.2.5 shall apply as appropriate. For ESVs that are normally able to transmit and receive simultaneously on different frequencies, no special arrangements for testing transmitter and receiver together are required.

4.3 Exclusion bands

There are no exclusion bands for ESVs at the operating frequencies. However an exclusion band(s) equal to the Intermediate Frequency (IF) bandwidth(s) $\pm 10\%$ may be declared by the manufacturer.

For the tests in the present document, the cable lengths between the above and below deck units should be the maximum lengths declared by the manufacturer. For maximum cable lengths longer than 10 m the tests may be performed with cables limited to 10 m.

4.4 Narrow band responses of receivers

Narrow band responses are not allowed for ESVs within the scope of the present document.

4.5 Normal test modulation

The provisions of ETSI EN 301 843-1 [1], clause 4.5 shall apply with the following modifications. The characteristics of the test signal (e.g. test patterns or message simulator or test voice signal) used for immunity testing shall be declared by the manufacturer.

5 Performance assessment

5.1 General

The provision of ETSI EN 301 843-1 [1], clause 5.1 shall apply. In addition the manufacturer shall provide the following information to be recorded in the test report:

- the dedicated grade (A or B) for the EUT in accordance with the information contained in the instructions accompanying the ESV (see ETSI EN 301 843-1 [1], clause 5.3).

5.2 Equipment which can provide a continuous communication link

The provisions of ETSI EN 301 843-1 [1], clause 5.2 shall apply.

5.3 Equipment which does not provide a continuous communication link

The provisions of ETSI EN 301 843-1 [1], clause 5.3 shall apply.

5.4 Ancillary equipment

The provisions of ETSI EN 301 843-1 [1], clause 5.4 shall apply.

5.5 Equipment classification

ESVs belong solely to the category of mobile marine radio equipment as defined in ETSI EN 301 843-1 [1], clause 5.5.

5.6 Equipment configuration(s)

For the purpose of measurements in the carrier-on state, the ESV shall be put in a continuous transmit mode or to the maximum burst rate where applicable. The ESV shall be operated at the highest normal operating Equivalent Isotropically Radiated Power (EIRP) or, if that is the maximum attainable, then 3 dB below such maximum.