

SLOVENSKI STANDARD
SIST EN 300 440 V2.2.1:2018
01-oktober-2018

Naprave kratkega dosega (SRD) - Radijska oprema, ki se uporablja v frekvenčnem območju od 1 GHz do 40 GHz - Harmonizirani standard za dostop do radijskega spektra

Short Range Devices (SRD) - Radio equipment to be used in the 1 GHz to 40 GHz frequency range - Harmonised Standard for access to radio spectrum

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 440 V2.2.1:2018](#)

Ta slovenski standard je istoveten z: <https://standards.iteh.ai/catalog/standards/sist/8e2776b0-03ba-437d-8b31-5055a81ac5a/sist-en-300-440-v2.2.1-2018> **ETSI EN 300 440 V2.2.1 (2018-07)**

ICS:

33.060.20	Sprejemna in oddajna oprema	Receiving and transmitting equipment
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

SIST EN 300 440 V2.2.1:2018

en

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 300 440 V2.2.1:2018

<https://standards.iteh.ai/catalog/standards/sist/8e2776b0-03ba-437d-8b31-3053a8ffac3a/sist-en-300-440-v2-2-1-2018>

ETSI EN 300 440 v2.2.1 (2018-07)



**Short Range Devices (SRD);
Radio equipment to be used in
the 1 GHz to 40 GHz frequency range;
Harmonised Standard for access to radio spectrum**

SIST EN 300 440 V2.2.1:2018
<https://standards.iteh.ai/catalog/standards/sist/8e2776b0-03ba-437d-8b31-3053a8ffac3a/sist-en-300-440-v2-2-1-2018>

Reference

REN/ERM-TG28-551

Keywords

harmonised standard, radio, SRD, testing

ETSI

650 Route des Lucioles
 F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
 Association à but non lucratif enregistrée à la
 Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW (standards.iteh.ai)

Important noticeSIST EN 300 440 V2.2.1:2018

<https://standards.iteh.ai/catalog/standards/sist/8e2776b0-03ba-437d-8b31-30d328fbc3a/sist-en-300-440-v2-2-1-2018>
 The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
 Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
 The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2018.
 All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and
 of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.
GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology.....	8
Introduction	9
1 Scope	10
2 References	11
2.1 Normative references	11
2.2 Informative references.....	11
3 Definitions, symbols and abbreviations	12
3.1 Definitions.....	12
3.2 Symbols	14
3.3 Abbreviations	14
4 Technical requirements specifications	15
4.1 Environmental profile.....	15
4.2 Transmitter requirements	15
4.2.1 Transmitter measurement requirements.....	15
4.2.1.1 Applicability.....	15
4.2.1.2 Methods of measurement and limits for transmitter parameters	15
4.2.2 Equivalent isotropically radiated power (e.i.r.p.) (Pre STANDARD PREVIEW standards.iteh.ai)	16
4.2.2.1 Applicability.....	16
4.2.2.2 Description	16
4.2.2.3 Method of measurement.....	16
4.2.2.3.0 General requirements.....	16
4.2.2.3.1 Non spread spectrum transmitters with a -6 dB bandwidth of up to 20 MHz and spread spectrum transmitters with channel bandwidth of up to 40 MHz ^{137d-8b31-}	16
4.2.2.3.2 Transmitters other than those defined in clause 4.2.2.3.10.18.....	17
4.2.2.4 Limits	18
4.2.2.5 Conformance	18
4.2.3 Permitted range of operating frequencies	18
4.2.3.1 Applicability.....	18
4.2.3.2 Description	19
4.2.3.3 Method of measurement.....	19
4.2.3.4 Method of measurement for equipment using FHSS modulation	19
4.2.3.5 Limits	20
4.2.4 Unwanted emissions in the spurious domain	20
4.2.4.1 Applicability.....	20
4.2.4.2 Description	20
4.2.4.3 Method of measurement.....	20
4.2.4.3.0 General Requirements	20
4.2.4.3.1 Conducted spurious emission	21
4.2.4.3.2 Method of measurement - cabinet spurious radiation.....	21
4.2.4.3.3 Method of measurement - radiated spurious emission	22
4.2.4.3.4 Additional requirements for equipment employing FHSS modulation	23
4.2.4.4 Limits	23
4.2.4.5 Conformance	23
4.2.5 Duty cycle.....	23
4.2.5.1 Applicability.....	23
4.2.5.2 Description	23
4.2.5.3 Method of measurement.....	24
4.2.5.4 Limits	24
4.2.5.5 Conformance	25
4.2.6 Additional requirements for FHSS equipment.....	25
4.2.6.1 Applicability.....	25
4.2.6.2 Description	25

4.2.6.3	Method of measurement.....	25
4.2.6.4	Limits	25
4.2.6.5	Conformance	25
4.3	Receiver requirements.....	25
4.3.1	Receiver category	25
4.3.2	General performance criteria	26
4.3.3	Adjacent channel selectivity	26
4.3.3.1	Applicability.....	26
4.3.3.2	Description.....	26
4.3.3.3	Method of measurement.....	26
4.3.3.4	Limits	27
4.3.3.5	Conformance	27
4.3.4	Blocking or desensitization.....	27
4.3.4.1	Applicability.....	27
4.3.4.2	Description	27
4.3.4.3	Methods of measurement	27
4.3.4.4	Limits	28
4.3.4.5	Conformance	29
4.3.5	Spurious radiations	29
4.3.5.1	Applicability.....	29
4.3.5.2	Description	29
4.3.5.3	Method of measurement for spurious radiation.....	29
4.3.5.3.0	General Requirements	29
4.3.5.3.1	Method of measurement conducted spurious components	29
4.3.5.3.2	Method of measurement cabinet radiation.....	30
4.3.5.3.3	Method of measurement radiated spurious components.....	30
4.3.5.4	Limits	31
4.3.5.5	Conformance	31
4.4	Spectrum access techniques	31
4.4.1	Applicability	31
4.4.2	Listen Before Talk (LBT)	31
4.4.2.0	General.....	31
4.4.2.1	LBT timing parameters https://standards.iteh.ai/catalog/standards/sist-en-300-440-v2-2-1-2018	32
4.4.2.1.1	Minimum transmitter off-time.....	32
4.4.2.1.2	LBT minimum listening time	32
4.4.2.1.3	Acknowledge transmissions	33
4.4.2.1.4	Maximum transmitter on-time.....	33
4.4.2.1.5	Declaration of LBT parameters	33
4.4.2.1.6	Manual and event driven devices	33
4.4.2.2	Receiver LBT threshold and transmitter max on-time	33
4.4.2.2.0	Applicability	33
4.4.2.2.1	Descriptions	34
4.4.2.2.2	Method of measurements.....	34
4.4.2.2.3	Limits	34
4.4.2.2.4	Conformance	35
4.4.3	Detect And Avoid techniques (DAA).....	35
4.4.3.1	General requirements	35
4.4.4	Adaptive Frequency Agility (AFA)	35
4.4.4.1	General requirements	35
4.5	2,45 GHz RFID systems.....	36
4.6	GBSAR systems	36
4.6.1	Effective radiated power	36
4.6.2	Permitted range of operating frequencies	36
4.6.3	DAA threshold.....	36
4.6.3.0	General requirements	36
4.6.3.1	DAA timing parameters	36
4.6.3.1.1	Minimum listen time	36
4.6.3.1.2	Minimum listen time after detection.....	36
4.6.3.1.3	Maximum transmitter on-time.....	36
4.6.3.1.4	Minimum transmitter off-time	36
4.6.4	Antenna pattern.....	36

5	Testing for compliance with technical requirements.....	36
5.1	Environmental conditions for testing	36
5.2	Presentation of equipment for testing purposes.....	37
5.2.0	General.....	37
5.2.1	Choice of model for testing	37
5.2.2	Testing of equipment with alternative power levels	37
5.2.3	Testing of equipment that does not have an external 50 Ω RF connector (integral antenna equipment)	37
5.2.3.1	Equipment with an internal permanent or temporary antenna connector or using a dedicated test fixture	37
5.2.3.2	Equipment with a temporary antenna connector	38
5.2.4	Testing of devices using duty cycle	38
5.3	Mechanical and electrical design.....	38
5.3.1	General.....	38
5.3.2	Void	38
5.3.3	Transmitter shut-off facility	38
5.3.4	Receiver mute or squelch.....	38
5.4	Auxiliary test equipment	38
5.5	Test power source.....	39
5.5.0	General.....	39
5.5.1	External test power source	39
5.5.2	Internal test power source	39
5.6	Normal test conditions.....	39
5.6.1	Normal temperature and humidity	39
5.6.2	Normal test power source	39
5.6.2.1	Mains voltage	39
5.6.2.2	Battery power sources	40
5.6.2.3	Other power sources	40
5.7	Extreme test conditions	40
5.7.1	Extreme temperatures	40
5.7.1.1	Procedure for tests at extreme temperatures.....	40
5.7.1.1.0	General	40
5.7.1.1.1	Procedure for equipment designed for continuous operation	40
5.7.1.1.2	Procedure for equipment designed for intermittent operation	40
5.7.1.2	Extreme temperature ranges	41
5.7.2	Extreme test source voltages.....	41
5.7.2.1	Mains voltage	41
5.7.2.2	Battery power sources	41
5.7.2.3	Power sources using other types of batteries.....	41
5.7.2.4	Other power sources.....	41
5.8	General conditions.....	42
5.8.1	Normal test signals and test modulation	42
5.8.1.0	General	42
5.8.1.1	Normal test signals for data.....	42
5.8.2	Artificial antenna	42
5.8.3	Test fixture.....	43
5.8.3.0	General	43
5.8.3.1	Validation of the test-fixture in the temperature chamber	44
5.8.3.2	Mode of use.....	45
5.8.4	Test sites and general arrangements for radiated measurements	46
5.8.5	Measuring receiver	46
5.9	Interpretation of the measurement results	46
5.9.0	General.....	46
5.9.1	Measurement uncertainty is greater than maximum acceptable uncertainty.....	47
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU.....	48
Annex B (normative):	EU wide harmonised national radio interfaces from 1 GHz to 40 GHz	50
Annex C (informative):	National Radio Interfaces not EU wide harmonised	51

Annex D (informative):	Selection of technical parameters	53
D.1	Introduction	53
D.2	Receiver parameters	53
Annex E (normative):	Radiated measurements	54
E.1	General requirements for measurements involving the use of radiated fields.....	54
E.2	Test Sites	55
E.2.1	Outdoor test site	55
E.2.2	Indoor test site	56
E.2.3	Shielded anechoic test site.....	57
E.2.3.0	General.....	57
E.2.3.1	Influence of parasitic reflections in anechoic chambers	57
E.2.3.2	Calibration of the shielded RF anechoic chamber	57
E.3	Antennas.....	59
E.3.1	Test antenna.....	59
E.3.2	Substitution antenna	59
E.3.3	Artificial antenna.....	59
E.4	Test Practice and Auxiliary Test Equipment.....	60
E.5	Measuring distance.....	60
E.5.0	General	60
E.5.1	Standard position.....	60
E.5.2	Auxiliary cables.....	60
iTeh STANDARD PREVIEW		
Annex F (normative):	General description of measurement methods.....	61
(standards.iteh.ai)		
F.0	General	61
F.1	Conducted measurements.....	61
F.2	Radiated measurements.....	61
F.3	Radiated measurement for receivers	62
Annex G (normative):	Power limits for RFID systems operating in the 2,45 GHz band	63
G.1	Power limits and frequency band	63
G.1.0	General requirements	63
G.1.1	Additional requirements for 2,45 GHz 4 W e.i.r.p. indoor RFID equipment.....	63
G.1.2	Spectrum mask	64
Annex H (informative):	Example of implementation for restriction of 4 W RFID to in-building use only.....	65
Annex I (normative):	Limits for GBSAR operating in the frequency range 17,1 GHz to 17,3 GHz	67
I.1	Introduction	67
I.2	Effective radiated power (e.i.r.p.).....	67
I.2.1	Definition	67
I.2.2	Method of measurement.....	67
I.2.3	Limits	67
I.3	Permitted range of operating frequencies.....	67
I.3.1	Definition	67
I.3.2	Method of measurement.....	67
I.3.3	Limits	68
I.4	Principles of Detection And Avoid (DAA)	68
I.4.0	General	68
I.4.1	DAA test set-up	68

I.4.2	Test signals	69
I.4.3	DAA threshold	69
I.4.3.1	Definition	69
I.4.3.2	Method of measurement	69
I.4.3.3	Limit	70
I.4.4	DAA timing parameters	70
I.4.4.1	Minimum listen Time	70
I.4.4.1.1	Definition	70
I.4.4.1.2	Method of measurement	70
I.4.4.1.3	Limit for minimum listen time	71
I.4.4.2	Minimum listen time after detection	71
I.4.4.2.1	Definition	71
I.4.4.2.2	Method of measurement	71
I.4.4.2.3	Limit	72
I.4.4.3	Maximum transmitter on-time	72
I.4.4.3.1	Definition	72
I.4.4.3.2	Method of measurement	72
I.4.4.3.3	Limit	73
I.4.4.4	Minimum transmitter off-time	73
I.4.4.4.1	Definition	73
I.4.4.4.2	Method of measurement	73
I.4.4.4.3	Limit	74
I.5	Antenna pattern	74
I.5.1	Definition	74
I.5.2	Method of measurements	74
I.5.3	Limits	76
iTeh STANDARD PREVIEW		
Annex J (informative):	Bibliography	77
Annex K (informative):	Change History	78
History	SIST EN 300 440 V2.2.1:2018 https://standards.iteh.ai/catalog/standards/sist/8e2776b0-03ba-437d-8b31-3053a8ffac3a/sist-en-300-440-v2-2-1-2018	79

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.6] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].<https://standards.iteh.ai/catalog/standards/sist/8e2776b0-03ba-437d-8b31-3053a8ffac3a/sist-en-300-440-v2-2-1-2018>

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

National transposition dates	
Date of adoption of this EN:	16 July 2018
Date of latest announcement of this EN (doa):	31 October 2018
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 April 2019
Date of withdrawal of any conflicting National Standard (dow):	30 April 2020

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document aims at providing requirements to demonstrate that the SRD devices to be used for the following equipment types can be presumed to conform to the essential requirements of article 3.2 of Directive 2014/53/EU [i.1] under the conditions identified in Annex A.

The present document aims to describe performance requirements and conformance test procedures for licence exempt Short Range Devices (SRDs) intending to use frequency bands within the range of 1 GHz to 40 GHz.

Equipment aiming to be covered by the present document may operate on a specific frequency or may be channel agile and operate on a number of different frequencies.

The present document is structured as follows:

- Clause 2 provides references.
- Clause 3 provides definitions of terms and abbreviations used.
- Clause 4 provides technical requirements specifications.
- Clause 5 provides conditions for testing for compliance with technical requirements.
- Annex A (informative): Relationship between the present document and the essential requirements of Directive 2014/53/EU.
- Annex B (normative): EU wide harmonised national radio interfaces from 1 GHz to 40 GHz.
- Annex C (informative): National Radio Interfaces not EU wide harmonised.
- Annex D (informative): Selection of technical parameters.
- Annex E (normative): Radiated measurements.
- Annex F (normative): General description of measurement methods.
- Annex G (normative): Power limits for RFID systems operating in the 2,45 GHz band.
- Annex H (informative): Example of implementation for restriction of 4 W RFID to in-building use only.
- Annex I (normative): Limits for GBSAR operating in the frequency range 17,1 GHz to 17,3 GHz.
- Annex J (informative): Bibliography.
- Annex K (informative): Change History.
- History.

1 Scope

The present document specifies technical characteristics and methods of measurements for the following equipment types:

- 1) Non specific Short Range Devices, including alarms, telecommand, telemetry, data transmission in general, etc.
- 2) Radio Frequency IDentification (RFID) devices.
- 3) Radiodetermination devices including detection, movement and alert applications.

These radio equipment types are capable of operating in the permitted frequency bands within the 1 GHz to 40 GHz range as specified in table 1:

- 1) with either a Radio Frequency (RF) output connection and dedicated antenna or an integral antenna;
- 2) for all types of modulation;
- 3) with or without speech.

Table 1 shows a list of the frequency bands as designated by the European Commission Decisions on Short Range Devices [i.5] and the CEPT/ERC Recommendation 70-03 [i.2] as known at the date of publication of the present document.

Table 1: Short Range Devices within the 1 GHz to 40 GHz permitted frequency bands

Item	Frequency Bands	Standard	Applications	Notes
Transmit and Receive	2 400 MHz to 2 483,5 MHz	SIST EN 300 440-1 (2018-07)	Non-specific short range devices	
Transmit and Receive	2 400 MHz to 2 483,5 MHz		Radiodetermination devices	
Transmit and Receive	(a) 2 446 MHz to 2 454 MHz		Radio Frequency Identification (RFID) devices	See Annex G
Transmit and Receive	(b) 2 446 MHz to 2 454 MHz	https://standards.etsi.org/catalog/standards/850/827/000-3ba-437d-8b31-3053-a80fc3a/ist-en-300-440-1-1-2018	Radio Frequency Identification (RFID) devices	See Annex G
Transmit and Receive	5 725 MHz to 5 875 MHz		Non-specific short range devices	
Transmit and Receive	9 200 MHz to 9 500 MHz		Radiodetermination devices	
Transmit and Receive	9 500 MHz to 9 975 MHz		Radiodetermination devices	
Transmit and Receive	10,5 GHz to 10,6 GHz		Radiodetermination devices	
Transmit and Receive	13,46 GHz to 14,0 GHz		Radiodetermination devices	
Transmit and Receive	17,1 GHz to 17,3 GHz		Radiodetermination devices	See Annex I
Transmit and Receive	24,00 GHz to 24,25 GHz		Non-specific short range devices and radiodetermination devices	

NOTE: (a) and (b) refer to two different operational restrictions for different power levels in the same frequency band.

NOTE 1: It should be noted that not all frequency bands in table 1 are implemented in all European countries.

Annex B provides an overview of radio interfaces which are harmonised in the European Union. Annex C provides an overview of national radio interfaces not harmonised in the European Union. at date of publication.

NOTE 2: In addition, it should be noted that other frequency bands may be available in a country within the frequency range 1 GHz to 40 GHz covered by the present document. See the European Commission Decisions on Short Range Devices [i.5] and the CEPT ERC Recommendation 70-03 [i.2] as implemented through National Radio Interfaces (NRI) and additional NRI as relevant.

NOTE 3: On non-harmonised parameters, national administrations may impose certain conditions such as the type of modulation, frequency, channel/frequency separations, maximum transmitter radiated power, duty cycle, and the inclusion of an automatic transmitter shut-off facility, as a condition for the issue of an individual or general licence, or as a condition for the issuing of Individual Rights for use of spectrum or General Authorization, or as a condition for use "under licence exemption" as it is in most cases for Short Range Devices.

The present document covers fixed stations, mobile stations and portable stations.

Applications using Ultra Wide Band (UWB) technology are not covered by the present document.

NOTE 4: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.6] is given in Annex A.

2 References

2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] CISPR 16-1-1 (2015): "Specification for radio disturbance and immunity measuring apparatus and methods; Part 1-1: Radio disturbance and immunity measuring apparatus - Measuring apparatus".
- [2] CISPR 16-1-4 (2010): "Specification for radio disturbance and immunity measuring apparatus and methods; Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements".
*iTek STANDARD REVIEW
(standards.iteh.ai)*
- [3] CISPR 16-1-5 (2014): "Specification for radio disturbance and immunity measuring apparatus and methods; Part 1-5: Radio disturbance and immunity measuring apparatus - Antenna calibration sites and reference test sites for 5 MHz to 18 GHz".
*SIST EN 300 440 V2.2.1:2018
http://standards.iteh.ai/catalog/standards/it/837/660-03ba-437d-8b31-3053a8ffac3a/sist-en-300-440-v2-2-1-2018*
- [4] Recommendation ITU-T O.41 (1994): "Psophometer for use on telephone-type circuits".
- [5] Recommendation ITU-T O.153 (1992): "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [6] Commission Implementing Decision (EU) 2017/1483 of 8 August 2017 amending Decision 2006/771/EC on harmonisation of the radio spectrum for use by short-range devices and repealing Decision 2006/804/EC.

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC (RE-Directive).
- [i.2] CEPT/ERC Recommendation 70-03: "Relating to the use of Short Range Devices (SRD)".
- [i.3] Recommendation ITU-R SM.1755: "Characteristics of ultra-wideband technology".

- [i.4] ETSI TR 100 028 (V1.4.1) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.5] Commission Decision 2013/752/EC on harmonization of the radio spectrum for use by short-range devices as amended by subsequent Commission Decisions.
- [i.6] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.7] Recommendation ITU-R SM.329-12 (2012): "Unwanted emissions in the spurious domain".
- [i.8] CEPT/ERC/Recommendation 74-01E: "Unwanted emissions in the spurious domain".
- [i.9] R&TTE Subclasses of Class1 Equipment December 2014: Publication in accordance with Article 1(3) of Commission Decision 2000/299/EC (Version December 2014).
- [i.10] ETSI EG 203 336 (V1.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".

3 Definitions, symbols and abbreviations

3.1 Definitions

iTeh STANDARD PREVIEW

For the purposes of the present document, the following terms and definitions apply:

adjacent channels: two channels offset from the nominal channel by the nominal channel bandwidth

alarm: use of radio communication for indicating an alarm condition at a distant location
<https://standards.iteh.ai/catalog/standards/sist/8e2776b0-03ba-437d-8b31-3033c53c1a18>

alternate adjacent channels: two channels offset from the nominal channel by double the channel bandwidth




Figure 1: Adjacent and alternate adjacent channel definitions

NOTE: For equipment to be used in a frequency band where channelization is not defined by regulation, the channel spacing of the equipment is defined by the manufacturer.

artificial antenna: non-radiating dummy load

assigned frequency band: frequency band within which the device is authorized to operate and to perform the intended function of the equipment

chip: unit of modulation used in Direct Sequence Spread Spectrum (DSSS) modulation

chip rate: number of chips per second in DSSS

conducted measurements: measurements which are made using a direct connection to the equipment under test

cumulative on-time (T_{on_cum}): sum of T_{on} , within T_{obs}

dedicated antenna: removable antenna supplied and tested with the radio equipment, designed as an indispensable part of the equipment

Direct Sequence Spread Spectrum (DSSS): form of modulation where a combination of data to be transmitted and a code sequence (chip sequence) is used to directly modulate a carrier, e.g. by phase shift keying

NOTE: The chip rate determines the occupied bandwidth.

Duty Cycle (DC): ratio expressed as a percentage, of the cumulative duration of transmissions T_{on_cum} within an observation interval T_{obs} . $DC = \left(\frac{T_{on_cum}}{T_{obs}} \right)_{F_{obs}}$ on an observation bandwidth F_{obs}

equivalent isotropically radiated power: maximum radiated power of the transmitter and its antenna

fixed station: equipment intended for use in a fixed location

Frequency Hopping Spread Spectrum (FHSS): spread spectrum technique in which the transmitter signal occupies a number of frequencies in time, each for some period of time, referred to as the dwell time

NOTE: Transmitter and receiver follow the same frequency hop pattern. The number of hop positions and the bandwidth per hop position determine the occupied bandwidth.

identification system: equipment consisting of a transmitter(s), receiver(s) (or a combination of the two) and an antenna(s) to identify objects by means of a transponder

integral antenna: permanent fixed antenna, which may be built-in, designed as an indispensable part of the equipment

mobile station: equipment normally fixed in a vehicle or used as a transportable station

observation bandwidth (F_{obs}): bandwidth in which the energy of an equipment is considered for the purposes of assessing transmission timings
<https://standards.itech.ai/catalog/standards/sist/8e2776b0-03ba-437d-8b31-3053a8ffac3a/sist-en-300-440-v2-2-1-2018>

observation period (T_{obs}): reference interval of time

occupied bandwidth: width of a frequency band such that, below the lower and above the upper frequency limits the mean powers emitted are each equal to 0,5 % of the total mean power of a given emission

off-time (Toff): time duration between two successive transmissions

on-time (Ton): duration on a Transmission Operating Channel (OC)

Operating Channel (OC): frequency range in which the transmission from the equipment occurs; defined by two frequency edges values: F_{low} and F_{high}

Operating Channel Width (OCW): bandwidth between the two frequencies F_{low} and F_{high} channel

operating frequency: nominal frequency at which equipment is operated; this is also referred to as the operating centre frequency

NOTE: Equipment may be able to operate at more than one operating frequency.

operating frequency range: range of operating frequencies over which the equipment can be adjusted through tuning, switching or reprogramming

out-of-band emissions: emission on a frequency or frequencies outside the occupied bandwidth which results from the modulation process, but excluding spurious emissions

portable station: equipment intended to be carried, attached or implanted

radiated measurements: measurements which involve the absolute measurement of a radiated field