



**Transport and Traffic Telematics (TTT);
Dedicated Short Range Communication (DSRC)
transmission equipment (500 kbit/s / 250 kbit/s)
operating in the 5 795 MHz to 5 815 MHz frequency band;
Part 2: Harmonised Standard for access to radio spectrum;
Sub-part 2: On-Board Units (OBU)**

PREVIEW
https://standards.10000.com/standards/etsi/en-300-674-2-2-19-06
4cef-940f-add80c24

ReferenceREN/ERM-TG37-272

Keywordsdata, DSRC, harmonised standard, radio,
regulation, RTTT, testing

ETSI650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	9
3 Definition of terms, symbols and abbreviations.....	9
3.1 Terms.....	9
3.2 Symbols.....	11
3.3 Abbreviations	13
4 Technical requirements specifications	14
4.1 General characteristics	14
4.1.1 OBU sets.....	14
4.1.2 Uplink sub-carrier frequencies.....	14
4.1.3 Carrier frequencies.....	14
4.1.4 Modulation.....	14
4.2 Environmental conditions.....	15
4.2.1 Environmental profile	15
4.2.2 Power supply	15
4.3 Conformance requirements	15
4.3.1 Transmitter requirements	15
4.3.1.1 Transmitter spectrum mask	15
4.3.1.2 Maximum equivalent isotropically radiated power	15
4.3.1.3 Transmitter frequency error	16
4.3.1.4 Transmitter unwanted emissions	16
4.3.2 Receiver requirements	16
4.3.2.1 Receiver unwanted emissions in the spurious domain	16
4.3.2.2 Sensitivity	17
4.3.2.3 Receiver selectivity	17
4.3.2.3.1 General	17
4.3.2.3.2 Receiver spurious response rejection and adjacent channel rejection	17
4.3.2.3.3 Receiver blocking.....	18
4.3.2.3.4 Co-channel rejection.....	18
4.3.3 Antennas	18
5 Testing for compliance with technical requirements.....	19
5.1 Environmental conditions for testing	19
5.2 Interpretation of the measurement results	19
5.3 Radio test suites.....	20
5.3.1 Transmitter parameters	20
5.3.1.1 Transmitter spectrum mask	20
5.3.1.1.1 General	20
5.3.1.1.2 Radiated measurements	20
5.3.1.1.3 Conducted measurements	22
5.3.1.2 Maximum equivalent isotropically radiated power	23
5.3.1.2.1 General	23
5.3.1.2.2 Radiated measurement.....	24
5.3.1.2.3 Conducted measurement.....	25
5.3.1.3 Transmitter frequency error	25
5.3.1.3.1 General	25
5.3.1.3.2 Radiated measurements	26
5.3.1.3.3 Conducted measurements	26
5.3.1.4 Transmitter unwanted emissions	27
5.3.1.4.1 General	27

5.3.1.4.2	Radiated measurement.....	27
5.3.2	Receiver parameters.....	28
5.3.2.1	Receiver unwanted emissions in the spurious domain	28
5.3.2.1.1	General	28
5.3.2.1.2	Radiated measurement.....	28
5.3.2.2	Sensitivity	29
5.3.2.2.1	General	29
5.3.2.2.2	Radiated measurements	29
5.3.2.2.3	Conducted measurements	29
5.3.2.3	Receiver selectivity	30
5.3.2.3.1	General	30
5.3.2.3.2	Unwanted signal characteristics	30
5.3.2.3.3	Measurement of receiver selectivity in OBU boresight.....	30
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	32
Annex B (normative):	Basics on testing	33
B.1	General conditions.....	33
B.1.1	Thermal balance	33
B.1.2	Test signals	33
B.1.3	Test sites.....	34
B.1.3.1	Shielded anechoic chamber.....	34
B.1.3.2	Open area test site	35
B.1.3.3	Test fixture.....	35
B.1.4	General requirements for RF cables	36
B.1.5	Conducted measurements.....	37
B.1.5.1	One antenna connector arrangement.....	37
B.1.5.2	Two antenna connectors arrangement.....	38
B.1.5.3	Test site requirements	38
B.1.5.4	Site preparation for conducted measurements.....	38
B.1.5.4.1	Monochromatic signals.....	38
B.1.5.4.2	Modulated signals	38
B.1.6	Radiated measurements	39
B.1.6.1	One antenna arrangement	39
B.1.6.2	Two antennas arrangement	40
B.1.6.3	Test site requirements	41
B.1.6.3.1	Measurement distances	41
B.1.6.3.2	Free-space wave propagation	41
B.1.6.4	Test and substitution antennas	42
B.1.6.5	Site preparation for radiated OBU measurements	42
B.1.6.5.1	Monochromatic signals	42
B.1.6.5.2	Modulated signals	44
B.1.6.5.3	Arrangement for OBU transmitter unwanted emissions measurement	45
B.1.6.5.4	Arrangement for OBU receiver selectivity measurement	47
B.2	Instruments	49
B.2.1	Receiving device	49
B.2.2	RF power sensor.....	49
B.2.3	Combiner.....	50
B.3	Power of modulated RSU carrier	50
B.4	Bit error ratio measurements	51
B.4.1	Basics	51
B.4.2	BER measurement.....	51
B.4.3	FER measurement	51
B.4.3.1	Mathematical expressions.....	51
B.4.3.2	Equipment.....	52
B.4.3.3	Procedure.....	52
Annex C (normative):	Environmental profile	53

C.1	General Requirements	53
C.2	Mandatory environmental conditions.....	53
C.3	Additional environmental conditions	53
Annex D (informative):	Maximum Measurement Uncertainty.....	54
Annex E (informative):	Bibliography.....	55
Annex F (informative):	Change History	56
History		57

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/baf2b2ad-5fbd-4cef-940f-add80c24578a/etsi-en-300-674-2-2-v2.2.1-2019-06>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.3] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 2, sub-part 2 of a multi-part deliverable covering Transport and Traffic Telematics (TTT); Dedicated Short Range Communication (DSRC) transmission equipment (500 kbit/s / 250 kbit/s) operating in the 5 795 MHz to 5 815 MHz frequency band, as identified below:

Part 1: "General characteristics and test methods for Road Side Units (RSU) and On-Board Units (OBU)";

Part 2: "Harmonised Standard for access to radio spectrum";

Sub-part 1: "Road Side Units (RSU)";

Sub-part 2: "On-Board Units (OBU)".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are **NOT** allowed in ETSI deliverables except when used in direct citation.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/baf2b2ad-5fbd-4cef-940f-add80c24578a/etsi-en-300-674-2-2-v2.2.1-2019-06>

1 Scope

The present document specifies technical characteristics and methods of measurements for Transport and Traffic Telematics (TTT) systems:

- with a Radio Frequency (RF) output connection and specified antenna or with an integral antenna;
- for data transmission only;
- operating in the 5 795 MHz to 5 815 MHz frequency band.

The applicability of the present document covers only the On Board Units (OBU).

The present document complies with the Commission Implementing Decision 2017/1483/EU [i.4] and CEPT/ERC Recommendation 70-03 [i.6].

The present document applies to the following radio equipment types operating in all or in part of the following service frequency bands given in table 1.

Table 1: Frequency bands and centre frequencies f_{TX} allocated for DSRC

	Pan European Service Frequencies	National Service Frequencies
Channel 1	5,795 GHz to 5,800 GHz, $f_{TX} = 5,7975$ GHz	
Channel 2	5,800 GHz to 5,805 GHz, $f_{TX} = 5,8025$ GHz	
Channel 3		5,805 GHz to 5,810 GHz, $f_{TX} = 5,8075$ GHz
Channel 4		5,810 GHz to 5,815 GHz, $f_{TX} = 5,8125$ GHz

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.2] is given in annex A.

2 References

2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] CEN EN 12253 (2004): "Road transport and traffic telematics - Dedicated short-range communication - Physical layer using microwave at 5,8 GHz".
- [2] ISO 14906 (2018): "Electronic fee collection -- Application interface definition for dedicated short-range communication".
- [3] CEPT/ERC Recommendation 74-01E (2011): "Unwanted emissions in the spurious domain".
- [4] CEN EN 13372 (2004): "Road Transport and Traffic Telematics (RTTT) - Dedicated short-range communication - Profiles for RTTT applications".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TS 103 052 (V1.1.1) (03-2011): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".
- [i.2] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.4] Commission Implementing Decision (EU) 2017/1483 of 8 August 2017 amending Decision 2006/771/EC on harmonisation of the radio spectrum for use by short-range devices and repealing Decision 2006/804/EC".
- [i.5] Void.
- [i.6] CEPT/ERC Recommendation 70-03 (May 2018): "Relating to the use of Short Range Devices (SRD)".
- [i.7] ETSI TR 102 273-2 (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 2: Anechoic chamber".
- [i.8] ETSI TR 102 273-6 (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 6: Test fixtures".
- [i.9] IEC 60721-3-4 (1995) including Amendment 1 (1996): "Classification of environmental conditions - Part 3: Classification of groups of environmental parameters and their severities - Section 4: Stationary use at non-weather protected locations".
- [i.10] IEC 60721-3-5 (1997): "Classification of environmental conditions - Part 3: Classification of groups of environmental parameters and their severities - Section 5: Ground vehicle installations".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in Directive 2014/53/EU [i.2] and the following apply:

adjacent channel: channel at a distance of 5 MHz relative to the centre frequency, i.e. in the channel at the next upper or lower centre frequency within the frequency band allocated for DSRC (see table 3)

bit: acronym for "binary digit" which can have one out of two possible values

EXAMPLE: 0/1, or +1/-1, or low/high.

bit rate: in a bit stream, the number of bits occurring per unit time, usually expressed in bits per second

boresight: direction of maximum radiation of a directional antenna

NOTE: If boresight cannot be determined unambiguously, then boresight may be declared by the manufacturer.

carrier frequency: frequency f_{TX} to which the RSU transmitter is tuned

NOTE: In DSRC, the carrier frequency is in the centre of a channel, see table 3 of the present document.

carrier signal or carrier: harmonic signal whose nominal single frequency f_{TX} can vary within a range specified by the carrier frequency tolerance and which is capable of being modulated by a second, symbol-carrying signal

channel: continuous part of the radio-frequency spectrum to be used for a specified emission or transmission

NOTE: A radio-frequency channel may be defined by two specified limits, or by its centre frequency and its bandwidth, or any equivalent indication. It is often designated by a sequential number. A radio-frequency channel may be time-shared in order to allow radio communication in both directions by simplex operation. The term "channel" is sometimes used to denote two associated radio-frequency channels, each of which is used for one of two directions of transmission, i.e. in fact a telecommunication circuit.

co-channel: transmission using the same channel (frequency band of 5 MHz width)

cross-polar discrimination (XPD): the ratio P_{LHCP} / P_{RHCP} of power P_{LHCP} of the left hand circular polarized wave to the power P_{RHCP} of the right hand circular wave when the total power of the transmitted wave is $P_{LHCP} + P_{RHCP}$

downlink: transmission in direction from RSU to OBU

ellipticity of polarization: ratio of the polarization main axes of an elliptic polarized radio wave

EXAMPLE: The ellipticity of circular polarized radio waves is one.
The ellipticity of linear polarized waves is infinity.

environmental profile: range of environmental conditions

equivalent isotropically radiated power: signal power fed into an ideal loss-less antenna radiating equally in all directions that generates the same power flux at a reference distance as the one generated by a signal fed into the antenna under consideration in a predefined direction within its far field region

integral antenna: antenna, with or without a connector, designed as an indispensable part of the equipment

OBU sleep mode: optional mode for battery powered OBUs that allows to save battery power

NOTE: In this mode, the OBU can only detect the presence of a DSRC downlink signal to initiate under certain defined conditions a transition to the stand-by mode.

OBU stand-by mode: mode, in which the OBU is capable of receiving DSRC downlink signals, but is never transmitting

operating frequency: nominal frequency at which equipment is operated; also referred to as the operating centre frequency

NOTE: Equipment may be able to operate at more than one operating frequency.

out-of-band emissions: emissions on a frequency or frequencies immediately outside the necessary bandwidth which results from the modulation process and which cannot be reduced without affecting the corresponding transmission of information, but excluding spurious emissions (see also CEPT/ERC Recommendation 74-01E [3])

polarization: locus of the tip of the electrical field vector in a plane perpendicular to the direction of transmission

EXAMPLE: Horizontal and vertical linear polarization
Left and right hand circular polarization.

Portable Equipment (PE): generally intended to be self-contained, free standing and portable

NOTE: A PE would normally consist of a single module, but may consist of several interconnected modules. It is powered by one or more internal batteries.

radiated measurements: measurements which involve the measurement of a radiated electromagnetic field

spurious emissions: emission on a frequency, or frequencies, which are outside an exclusion band of $\pm 2,5$ times the channel spacing around the selected centre frequency f_{Tx} , and the level of which may be reduced without affecting the corresponding transmission of information

NOTE: Spurious emissions include harmonic emissions, parasitic emissions, intermodulation products and frequency conversion products but exclude out-of-band emissions (see also CEPT/ERC Recommendation 74-01E [3]).

uplink: transmission in direction from OBU to RSU

3.2 Symbols

For the purposes of the present document, the following symbols apply:

A_{CW}	Amplitude of CW signal
A_{mod}	Amplitude of modulated signal
ATN_{AT2}	Attenuation of attenuator AT2
ATN_{BLN}	Attenuation of balun BLN
ATN_{CA1}	Attenuation of coaxial cable 1
BER	Bit error ratio
C_F	Number of frames transmitted
C_E	Number of erroneous frames received
d	Distance between phase centres of transmitting and receiving antenna
$d_{displace}$	Horizontal displacement of TTA and RTA antenna phase centres
d_{F1}	Distance from transmitting antenna to first Fresnel ellipse
d_{F2}	Distance from first Fresnel ellipse to receiving antenna
D_{fb}	Distance between neighbouring ferrite beads
D_i	Directivity relative to an isotropic radiator
$D_{0,TA}$	Largest linear dimension of test antenna
$D_{0,EUT}$	Largest linear dimension of EUT antenna
$EIRP_{max}$	Maximum e.i.r.p. of RSU
$EIRP_{MaxObuTx}$	Maximum e.i.r.p. generated by the OBU in a single side band
$EIRP_{ObuTx}$	e.i.r.p. generated by the OBU within a single side band
$EIRP_{OBU}$	e.i.r.p. generated by the OBU antenna
$EIRP_{TSM}$	e.i.r.p. referred to transmitter spectrum mask
Δf_{RSU}	Frequency error of RSU
Δf_s	Sub-carrier frequency error
f	Frequency
f_c	Centre frequency of receiving device or of MSS2 used for calibration
FER	Frame error ratio
f_{ObuTx}	Actual centre frequency of the lower and upper side band of the OBU uplink channel
f_{MSS1}	Frequency of MSS1
f_{offset}	Offset frequency
f_s	Nominal OBU sub-carrier frequency
f_{Tx}	Nominal RSU carrier frequency
$f_{Tx,actual}$	Actual centre frequency of the downlink carrier
f_u	Nominal centre frequency of unwanted signal
f_{u1}, f_{u2}	Centre frequencies of unwanted signal
G_c	Conversion gain
G_{corr}	Correction gain
$G_{OBU,Rx}$	Gain of OBU receiving antenna
$G_{OBU,Tx}$	Gain of OBU transmitting antenna

G_{RSA}	Gain of receiving substitution antenna
G_{TA}	Gain of test antenna
G_{TSA}	Gain of transmitting substitution antenna
$G_{\text{RSU,Tx}}$	Gain of RSU transmitting antenna
k	Expansion factor (coverage factor)
$\lg(\cdot)$	Logarithm to the base ten
m	Modulation index
Mc	Location of the OBU antenna phase centre
N	Total number of transmitted bits within a single frame
P_{CW}	Power of CW signal
P_{D11a}	Power limit for communication (upper)
P_{D11b}	Power limit for communication (lower)
P_{inc}	Incident signal power as received by an ideal isotropical receiving antenna
$P_{\text{inc,scan}}$	Incident signal power obtained from a scanning process
$P_{\text{inc,dBm}}$	P_{inc} in dBm
P_{LHCP}	Signal power of left hand circular polarized wave
P_{max}	Maximum signal power
P_{mod}	Power of modulated signal
P_{MMS1}	Output signal power of MSS1
P_{MMS2}	Output signal power of MSS2
P_{ObuRx}	Incident signal power to OBU, referred to an ideal isotropical receiving antenna
P_{pol}	Signal power of wave with corresponding polarization
P_{v}	Signal power of wave featuring vertical polarization
P_{h}	Signal power of wave featuring horizontal polarization
P_{PM1}	Signal power measured by the power meter 1
P_{ref}	Reference signal power limit in Watt
$P_{\text{ref,dBm}}$	Reference signal power limit in dBm
P_{reTx}	Retransmitted signal power
P_{RSA}	Signal power obtained from receiving substitution antenna
P_{RHCP}	Signal power of right hand circular polarized wave
P_{ssb}	Signal power within single side band
P_{sens}	Sensitivity of receiver
P_{spurious}	Signal power of spurious signal
P_{tot}	Sum of signal power $P_1 + P_2$, or $P_1 + P_2 + \dots + P_5$, whichever applies
$P_{\text{tot,dBm}}$	P_{tot} in dBm
P_{TSM}	Transmitter spectrum mask
P_{u}	Power of unwanted signal at OBU antenna
$P_{\text{u max}}$	Unwanted signal power limit at OBU antenna
P_{w}	Signal power of wanted signal
P_0	Reference signal power of 1 mW corresponding to 0 dBm
RBW	Resolution bandwidth
T_{CW}	Duration of CW signal
T_{mod}	Duration of modulated signal
$V_{\text{max}}, V_{\text{min}}$	Maximal amplitude of modulated output signal of RSU caused by data bit 1, or 0
α	Tilt angle of test antenna
α_{displace}	Displacement angle between TTA and RTA
θ	Angle relative to OBU boresight indicating worst case direction
θ°	Value of θ measured in degree
λ	Wavelength
ρ_{RSA}	Reflection coefficient at antenna connector of the receiving substitution antenna
ρ_{TSA}	Reflection coefficient at antenna connector of the transmitting substitution antenna

3.3 Abbreviations

For the purposes of the present document the abbreviations given in CEN EN 12253 [1] and the following apply:

ASG	Arbitrary Signal Generator
AT1	ATtenuator 1
AT2	ATtenuator 2
BER	Bit Error Ratio
BLN	BaLuN
BST	Beacon Service Table
CA	Corresponding Antenna
CC	Coaxial Circulator
CRC	Cyclic Redundancy Checking
CW	Continuous Wave
DSRC	Dedicated Short Range Communication
e.i.r.p.	equivalent isotropically radiated power

NOTE: Also called EIRP, eirp, E.I.R.P.

EC	European Community
EUT	Equipment Under Test
FCCA	Ferrited Coaxial CAble
FCCA1	Ferrited Coaxial CAble 1
FER	Frame Error Ratio
LHCP	Left Hand Circular Polarized
LOS	Line-Of-Sight
LP	Linear Polarized
M _{centre}	Centre point between phase centres of TTA and RTA
MSS1	Monochromatic Signal Source 1
MSS2	Monochromatic Signal Source 2
n.a.	not applicable
OBU	On Board Unit
PE	Portable Equipment
PM1	Power Meter 1
RBW	Resolution BandWidth
RD	Receiving Device
RF	Radio Frequency
RRxA	RSU Receiving Antenna
RSA	Receiving Substitution Antenna
RSU	Road Side Unit
RTA	Receiving Test Antenna
RTTT	Road Transport and Traffic Telematics
RTxA	RSU Transmitting Antenna
Rx	Receiver
SMS1	Signal or Message Source 1
SR	Special Report
SSB	Single Side Band
TA	Test Antenna
TM1	Test Message 1
TS1	Test Signal 1
TS2	Test Signal 2
TSA	Transmitting Substitution Antenna
TSM	Transmitter Spectrum Mask
TTA	Transmitting Test Antenna
Tx	Transmitter
VBW	Video Band Width
VST	Vehicle Service Table
VSWR	Voltage Standing Wave Ratio
XP	Cross Polarized
XPD	Cross-Polar Discrimination