

**SLOVENSKI STANDARD**  
**oSIST prEN 300 338-8 V1.0.0:2022**  
**01-januar-2022**

---

**Tehnične karakteristike in merilne metode za naprave, ki generirajo, oddajajo in sprejemajo digitalni selektivni klic (DSC) v pomorski mobilni storitvi, ki deluje v območju MF, MF/HF oziroma VHF - 8. del: Omogočanje radijske opreme DSC z možnostmi daljinskega upravljanja**

Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service - Part 8: Enabling DSC radio equipment with remote control capabilities

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

<https://standards.iteh.ai/catalog/standards/sist/fl4462f8-a6cd-4e62-81d6-ea21e702f294/osist-pren-300-338-8-v1-0-0-2022>

**Ta slovenski standard je istoveten z: ETSI EN 300 338-8 V1.0.0 (2021-11)**

---

**ICS:**

33.060.20	Sprejemna in oddajna oprema	Receiving and transmitting equipment
47.020.70	Navigacijska in krmilna oprema	Navigation and control equipment

**oSIST prEN 300 338-8 V1.0.0:2022**      **en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[oSIST prEN 300 338-8 V1.0.0:2022](https://standards.iteh.ai/catalog/standards/sist/f14462f8-a6cd-4e62-81d6-ea21e702f294/osist-pren-300-338-8-v1-0-0-2022)

<https://standards.iteh.ai/catalog/standards/sist/f14462f8-a6cd-4e62-81d6-ea21e702f294/osist-pren-300-338-8-v1-0-0-2022>

Draft **ETSI EN 300 338-8** V1.0.0 (2021-11)



**Technical characteristics and methods of measurement  
for equipment for generation, transmission  
and reception of Digital Selective Calling (DSC)  
in the maritime MF, MF/HF and/or VHF mobile service;  
Part 8: Enabling DSC radio equipment  
with remote control capabilities**

---

**Reference**

DEN/ERM-TGMAR-087-8

---

**Keywords**

DSC, GMDSS, maritime, radio, SAR

**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.  
All rights reserved.

# Contents

Intellectual Property Rights .....	5
Foreword.....	5
Modal verbs terminology.....	5
1 Scope .....	6
2 References .....	6
2.1 Normative references .....	6
2.2 Informative references.....	6
3 Definition of terms, symbols and abbreviations.....	7
3.1 Terms.....	7
3.2 Symbols.....	8
3.3 Abbreviations .....	8
4 General requirements .....	9
4.1 General .....	9
4.2 Interfaces .....	9
4.2.1 General.....	9
4.2.2 Physical connection .....	10
4.2.3 Ethernet protocols.....	10
4.2.4 Audio interfaces.....	10
4.2.5 Sentences to support on the interface.....	10
5 DSC remote control communication .....	14
5.1 Introduction .....	14
5.2 Use of AC0, AC1, AC2, AC3, AC4 and AC5.....	14
5.3 Use of AO1, AO2, AO3, AO4 and AO5 .....	14
5.4 Use of AP0, AP1, AP2, AP3, AP4 and AP5 .....	15
5.5 Use of AI1 to AI9.....	15
5.6 Use of AUQ.....	15
5.7 Use of DCR Device Capability Report.....	15
6 Remote control in standby, DSC and non-DSC automated procedures .....	15
6.1 General .....	15
<b>Annex A (normative): Sentences to support DSC remote control.....</b>	<b>16</b>
A.1 Introduction .....	16
A.1.1 AP0 - Automated Procedure Configuration Status.....	16
A.1.2 AP1 - Sending Distress Automated Procedure Status VHF and MF/HF.....	18
A.1.3 AP2 - Receiving Distress Automated Procedure Status VHF and MF/HF.....	21
A.1.4 AP3 - Sending Non-Distress Automated Procedure Status .....	24
A.1.5 AP4 - Receiving Non-Distress Automated Procedure Status .....	28
A.1.6 AP5 - Communications Automated Procedure Status .....	31
A.1.7 AO1 - Automated procedure Options - Sending Own Distress .....	34
A.1.8 AO2 - Automated procedure Options - Receiving Distress .....	36
A.1.9 AO3 - Automated procedure Options - Sending Non-Distress .....	37
A.1.10 AO4 - Automated procedure Options - Receiving Non-Distress .....	39
A.1.11 AO5 - Automated procedure Options - Communications .....	40
A.1.12 AC0 - Command Radio Settings .....	42
A.1.13 AC1 - Automated procedure Command - Sending Own Distress .....	45
A.1.14 AC2 - Automated procedure Command - Receiving Distress.....	47
A.1.15 AC3 - Automated procedure Command - Sending Non-Distress.....	51
A.1.16 AC4 - Automated procedure Command - Receiving Non-Distress.....	53
A.1.17 AC5 - Automated procedure Command - Communications .....	55
A.1.18 AI1 - Automated procedure Initiate - Sending Own Distress.....	57
A.1.19 AI2 - Initiate All ships urgency and safety (VHF) - Frequency .....	60
A.1.20 AI3 - Automated procedure Initiate - Geographical area urgency and safety (MF/HF) - Frequency.....	61
A.1.21 AI4 - Initiate Individual Urgency and safety (VHF/MF/HF) - Frequency .....	64

A.1.22	AI5 - Initiate Individual Urgency and safety - Position/Test.....	67
A.1.23	AI6 - Initiate Routine Group - Frequency .....	69
A.1.24	AI7 - Initiate Routine Individual- Frequency/Data .....	71
A.1.25	AI8 - Automated procedure Initiate DROBOSE .....	74
A.1.26	AI9 - Initiate Communications Call .....	78
A.1.27	AUQ - Automatic Procedure Query .....	79
A.1.28	AAS - Audible Alert Sound Status and Control.....	82
A.1.29	DCR - Device Capability Report.....	84
A.1.30	FSC - Frequency Status and Command.....	88
<b>Annex B (informative): Traffic simulation .....</b>		<b>91</b>
B.1	General guide .....	91
B.2	Traffic load scenarios .....	92
B.2.1	6 simultaneous procedures .....	92
B.2.2	61162-1 4800 baud interfaces .....	93
B.2.3	61162-450 traffic shaping .....	93
History .....		94

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN 300 338-8 V1.0.0:2022](https://standards.iteh.ai/catalog/standards/sist/fl4462f8-a6cd-4e62-81d6-ea21e702f294/osist-pren-300-338-8-v1-0-0-2022)

<https://standards.iteh.ai/catalog/standards/sist/fl4462f8-a6cd-4e62-81d6-ea21e702f294/osist-pren-300-338-8-v1-0-0-2022>

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

ITEH STANDARD PREVIEW  
(standards.iteh.ai)

# Foreword

oSIST prEN 300 338-8 V1.0.0:2022

This draft European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document is part 8 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.1].

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# 1 Scope

The present document states minimum requirements for GMDSS radiocommunication equipment using Digital Selective Calling (DSC) Class A [2], with the capability to fully operate handling of the automated procedures defined in part 2 of this multi-part deliverable, see ETSI EN 300 338-2 [2] from a remote position such as a central HMI.

In addition other proprietary control interfaces may apply to support full remote control of other DSC EQUIPMENT functions.

Such proprietary control interfaces (whether based on proprietary IEC 61162-1 [3] sentences or other protocols) are not part of the present document, and may co-exist with the requirements in the present document.

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Recommendation ITU-R M.493-15: "Digital selective-calling system for use in the maritime mobile service".  
<https://standards.iteh.ai/catalog/standards/sist/fl4462f8-a6cd-4e62-81d6-21e702f294/osist-prn-300-338-8-v1-0-0-2022>
- [2] ETSI EN 300 338-2: "Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service; Part 2: Class A DSC".
- [3] IEC 61162-1 edition 5 (2016): "Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 1: Single talker and multiple listeners".
- [4] IEC 61162-2: "Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 2: Single talker and multiple listeners, high-speed transmission".
- [5] IEC 61162-450 edition 2 (2018): "Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 450: Multiple talkers and multiple listeners - Ethernet interconnection".

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EN 300 338-1: "Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service; Part 1: Common requirements".



- [i.2] IEC 61097-3 edition 2 (2017): "Global maritime distress and safety system (GMDSS) - Part 3: Digital selective calling (DSC) equipment - Operational and performance requirements, methods of testing and required results".
- [i.3] IEC 61162-460 edition 2 (2018): "Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 460: Multiple talkers and multiple listeners - Ethernet interconnection - Safety and security".
- [i.4] NMEA 0183: "Standard for Interfacing Marine Electronic Devices".
- [i.5] ETSI EN 300 338-7: "Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service; Part 7: Implementation of Bridge Alert Management (BAM) in DSC radio equipment".
- [i.6] ETSI EN 301 925: "Radiotelephone transmitters and receivers for the maritime mobile service operating in VHF bands; Technical characteristics and methods of measurement".
- [i.7] ETSI EN 300 373-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Maritime mobile transmitters and receivers for use in the MF and HF bands; Part 1: Technical characteristics and methods of measurement".
- [i.8] ITU Radio Regulations (2020).
- [i.9] Recommendation Recommendation Recommendation ITU-R-M.541-10 (10/2015): "Operational procedures for the use of digital selective-calling equipment in the maritime mobile service".
- [i.10] Recommendation ITU-R M.1084-5 (03/2012): "Interim solutions for improved efficiency in the use of the band 156-174 MHz by stations in the maritime mobile service".
- [i.11] IMO Resolution A.803(19): "Performance Standards for Shipborne VHF Radio Installations Capable of Voice Communication and Digital Selective Calling".
- [i.12] IMO Resolution A.804(19): "Performance Standards for Shipborne MF Radio Installations Capable of Voice Communication and Digital Selective Calling".
- [i.13] IMO Resolution A.806(19): "Performance Standards for Shipborne MF/HF Radio Installations Capable of Voice Communication, Narrow-Band Direct Printing and Digital Selective Calling".
- [i.14] MSC/Circular.862: "Clarifications of Certain Requirements in IMO Performance Standards for GMDSS Equipment".
- [i.15] IEC 62320-2:2016: "Maritime navigation and radiocommunication equipment and systems - Automatic identification system (AIS) - Part 2: AIS AtoN Stations - Operational and performance requirements, methods of testing and required test results".

---

## 3 Definition of terms, symbols and abbreviations

### 3.1 Terms

For the purposes of the present document, the terms given in ETSI EN 300 338-1 [i.1] and the following apply:

**acknowledged:** automated procedure it indicates that the objective of the initial DSC message has been achieved

**activation:** initial triggering of the MoB device i.e. both parts of the two step procedure are performed

**active mode:** activated mode, transmitting in an emergency situation

**distress alert:** name given to the single distress DSC message with the format symbol 112

**distress DSC message:** DSC message or acknowledgement containing the distress information

**distress information:** symbols within a DSC message describing a distress situation consisting of the MMSI of the vessel in distress, the nature of distress, the position of the vessel in distress, the UTC time of that position and the mode of subsequent communication

**non distress DSC message:** DSC messages or acknowledgements that do not have the format specifier or category of "distress"

## 3.2 Symbols

Void.

## 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AAS	Audible Alert Sound
ACn	AC0, AC1, AC2, AC3, AC4 or AC5 sentence
AIn	AI1, AI2, AI3, AI4, AI5, AI6, AI7, AI8, AI9 sentence
AIS	Automatic Indetification System
ALC	Cyclic Alert List
ALF	BAM Alert Details
AOn	AO1, AO2, AO3, AO4 or AO5 sentence
AP	Automated procedure
APn	AP0, AP1, AP2, AP3, AP4 or AP5 sentence
ARQ	Automatic Request Query
ASCII	Americal Standard Communications Indication
AUQ	Automated Query Procedure
BIT	Binary Digit
CAM	Central Alert Mechanism
CD	NMEA indicator for DSC
CIRM	Comite International Radio-Maritime
CSTDMA	Carrier Sense Time Division Multiple Access
CUL	Cyclic Procedure List
DCR	Device Capability Report
DROBOSE	Distress Relay On Behalf Of Someone Else
DSC	Digital Selective Calling
DSE	Expanded Digital Selective Calling
ECDIS	Electronic Chart Display and Information Systems
ECI	Enhanced Caller Information EN European Standard
EPFS	Electronic Position Fixing System
EPIRB	Electronic Position Indicating Radio Beacon
EPV	Equipment Property Value
ERM	European Radio Management
FATDMA	Manually Managed AIS TDMA access for AtoN and Base Stations
FEC	Forward Error Correction
FSC	Frequency Status and Command
FSI	Frequency Set information
FSS	Frequency Selection Set
GMDSS	Global Maritime Distress and Safety System
GNSS	Global Navigation Satellite System
GPS	Global Positioning System
HBT	Heartbeat
HF	High Frequency
HMI	Human Manual Intervention
IEC	Internation Electronic Commission
IMO	International Maritime Organisaton
IN	NMEA indicator for Integrated Navigation
ITU	International Telecommunication Union
ITU-R	International Telecommunication Union - Radio
LSB	Least Significant Bit

MF	Medium Frequency
MF/HF	Medium Frequencies/High Frequencies [Radio Frequencies]
MHZ	MegaHertz (Frequency indication)
MMSI	Maritime Mobile Service Identity
MOB	Man Over Board
MSB	Most Significant Bit
MSC	Maritime Safety Committee (IMO)
NAK	Negative acknowledgment
NBDP	Narrow Band Direct Printing
NMEA	National Marine Electronics Association
NW	North West point of Geographical Area Location
OK	Accepted
RATDMA	Random Access AIS TDMA for Class 'A' network entry
SFI	Scanning Frequency information
SNGF	Serial Network Gateway Function SNMP Server Network Management Protocol
TAG	Advanced Communications for NMEA networks
TCP/IP	Transmission Control Packet/Internet Protocol
TX/RX	Transmitter/Receiver or Transceiver
UDP	Unaddressed Data Packet
UTC	Universal Time Co-ordinated
VDL	VHF Data Link
VHF	Very High Frequency
VoIP	Voice over IP

---

## 4 General requirements

### 4.1 General

For safety reasons the remote control facility is a functional extension to, not a substitution of, any facilities as required in ETSI EN 300 338-2 [2]. Full compliance with ETSI EN 300 338-2 [2] shall be required.

The remote protocol described in the current document shall support the concept of the automated procedures defined in ITU Recommendation ITU-R M.493-15 [1]. This will enable the simultaneous overview of several active automated procedures on a larger display, as well as supporting distribution of target states to navigation instruments.

The signalling interface defined is also suitable to exploit for testing purposes.

The evolution of new radio performance standards and carriage requirements may initially require only parts of the interface functionality. It shall be possible for the manufacturer to state and document partial compliance to the present document. E.g:

- Sentences supported.
- Features supported:
  - Information only. Document supported fields of status sentences to reflect radio state - selected from Table 1.
  - Radio control. Document supported fields of control and status sentences - selected from Table 1 and Table 2.

## 4.2 Interfaces

### 4.2.1 General

Data interfaces for remote control purposes shall be compatible with at least one of IEC 61162-1 [3], IEC 61162-2 [4] and IEC 61162-450 [5]. The manufacturer shall specify which alternative of IEC 61162 ([3], [4] or [5]) the physical interface supports.

## 4.2.2 Physical connection

The general required interface may be:

- physically part of the individual equipment/function; or
- connected using a proprietary interface to an external unit supporting the required interfaces towards the remote controller system (e.g. being part of a larger system).

In both configurations, compliance to the present document shall be demonstrated as a whole presented on the required interfaces (clause 4.2.1).

## 4.2.3 Ethernet protocols

The IEC 61162-1 [3] sentences sent over the Ethernet [5] are using the UDP multicast datagrams.

Other protocols/logical connections may exist on the same physical connection (including TCP/IP or SNMP) if the equipment supports these layers.

The traffic limitations and requirements shall be kept as specified in IEC 61162-450 [5] (see annex B).

## 4.2.4 Audio interfaces

Audio interfaces for the remote support of subsequent communications in a DSC automated procedure or communication in a non-DSC communication automated procedure may be accomplished by the analog interfaces as defined in the equipment standards ETSI EN 301 925 [i.6] and ETSI EN 300 373-1 [i.7], but alternative digital audio interfaces shall be allowed (e.g. VoIP).

The manufacturer shall declare the audio interface to use for testing.

## 4.2.5 Sentences to support on the interface

For remote display and/or command purposes and test purposes the equipment shall be capable of transmitting and receiving the sentences (see IEC 61162-1 [3] and annex A) as defined in Table 1 and Table 2.

Connection of, or failure within any connected equipment, shall not affect the required performance of the DSC equipment.

**Table 1: Remote control sentences transmitted by the DSC equipment**

Mnemonic	Interface	Name	Comment
AP0	Automated Procedure Configuration Status	Config status	Report status of parameters available in standby mode
AP1 <sup>a</sup>	Remote display status or allowed command of Sending Distress automated procedure	Automated Procedure Status and available control	Report status of the ITU procedure Support for Recommendation ITU-R M.493-15 [1], annexes 3 and 4
AP2 <sup>a</sup>	Remote display status or allowed command of Receiving Distress automated procedure	Automated Procedure Status and available control	Report status of the ITU procedure Support for Recommendation ITU-R M.493-15 [1], annexes 3 and 4
AP3 <sup>a</sup>	Remote display status or allowed command of Sending non-distress automated procedure	Automated Procedure Status and available control	Report status of the ITU procedure Support for Recommendation ITU-R M.493-15 [1], annexes 3 and 4

Mnemonic	Interface	Name	Comment
AP4 <sup>a</sup>	Remote display status or allowed command of Receiving non-distress automated procedure	Automated Procedure Status and available control	Report status of the ITU procedure Support for Recommendation ITU-R M.493-15 [1], annexes 3 and 4
AP5 <sup>a</sup>	Remote display status or allowed command of communication automated procedure	Automated Procedure Status and available control	Report status of the ITU procedure Support for Recommendation ITU-R M.493-15 [1], annexes 3 and 4
AO1	Available options in sending own distress procedure	Reports options in the current state of the procedure.	
AO2	Available options in receiving distress procedure	Reports options in the current state of the procedure.	
AO3	Available options in sending non distress procedure	Reports options in the current state of the procedure.	
AO4	Available options in receiving non distress procedure	Reports options in the current state of the procedure.	
AO5	Available options in communications procedure <a href="https://standards.iteh.ai/catalog/standards-citeId/6044519-a66d-4e62-81d6-ea21e702f294/osist-pren-300338-8-v1-0-0-2022">https://standards.iteh.ai/catalog/standards-citeId/6044519-a66d-4e62-81d6-ea21e702f294/osist-pren-300338-8-v1-0-0-2022</a>	Reports options in the current state of the procedure.	
CUL <sup>a</sup>	Remote display or command	Cyclic Procedure List	Control proper operation of the ITU procedure Support for Recommendation ITU-R M.493-15 [1], annexes 3 and 4
DSC <sup>b</sup> DSE ECI <sup>a</sup>	Remote display or command	Digital selective calling information	Report a received DSC call detail information
EPV	Remote display or command	Equipment property value	Report equipment property values
FSS <sup>a</sup>	Remote display or command	Frequency selection set	Report setting of radio frequency
HBT	Remote display or command	Heartbeat	Integrity test
NAK	Remote display or command	Negative acknowledge ment	Used to inform commander about refusal to set equipment property values

Mnemonic	Interface	Name	Comment
OCC <sup>a</sup>	Remote display or command	Occupation Control	Control possible multiple command sources Support for Recommendation ITU-R M.493-15 [1], annexes 3 and 4
SFI	Remote display or command	Scanning frequency information	Report scanning frequency of DSC
DCR	Device Capability Report	Class of DSC and mdes frequencies available	Functionality available.
NOTE a: See annex A.			
NOTE b: Test Requirement.			

Table 2: Remote control sentences received by the DSC equipment

Mnemonic	Interface	Name	Comment
AC0	Remote command of Automated Procedure Configuratio	Config command	Setting of parameters available in standby mode
AC1 <sup>a</sup>	Remote control commands for Sending Distress automated procedure	Automated Procedure Control	Used to control the ITU procedure Support for Recommendation ITU-R M.493-15 [1] annexes 3 and 4
AC2 <sup>a</sup>	Remote control commands for Receiving Distress automated procedure	Automated Procedure Control	Used to control the ITU procedure Support for Recommendation ITU-R M.493-15 [1] annexes 3 and 4
AC3 <sup>a</sup>	Remote control commands for Sending non-distress automated procedure	Automated Procedure Control	Used to control the ITU procedure Support for Recommendation ITU-R M.493-15 [1] annexes 3 and 4
AC4 <sup>a</sup>	Remote control commands for Receiving non-distress automated procedure	Automated Procedure Control	Used to control the ITU procedure Support for Recommendation ITU-R M.493-15 [1] annexes 3 and 4
AC5 <sup>a</sup>	Remote control commands for communication automated procedure	Automated Procedure Control	Used to control the ITU procedure Support for Recommendation ITU-R M.493-15 [1] annexes 3 and 4
AI1	Automated procedure Initiate - Sending Own Distress. This is a command sentence	Automated Procedure Start	Used to initiate the ITU procedure Support for Recommendation ITU-R M.493-15 [1] annexes 3 and 4
AI2	Initiate All ships urgency and safety (VHF) - Frequency	Automated Procedure Start	Used to initiate the ITU procedure Support for Recommendation ITU-R M.493-15 [1] annexes 3 and 4

Mnemonic	Interface	Name	Comment
AI3	Initiate Geographical area urgency and safety (MF/HF)	Automated Procedure Start	Used to initiate the ITU procedure Support for Recommendation ITU-R M.493-15 [1] annexes 3 and 4
AI4	Initiate Individual Urgency and safety (VHF/MF/HF) - Frequency/Position	Automated Procedure Start	Used to initiate the ITU procedure Support for Recommendation ITU-R M.493-15 [1] annexes 3 and 4
AI5	Initiate Individual Urgency and safety- Test	Automated Procedure Start	Used to initiate the ITU procedure Support for Recommendation ITU-R M.493-15 [1] annexes 3 and 4
AI6	Initiate Routine Group - Frequency	Automated Procedure Start	Used to initiate the ITU procedure Support for Recommendation ITU-R M.493-15 [1] annexes 3 and 4
AI7	Initiate Routine Individual-Frequency/Position/Data	Automated Procedure Start	Used to initiate the ITU procedure Support for Recommendation ITU-R M.493-15 [1] annexes 3 and 4
AI8	Automated procedure Initiate DROBOSE	Automated Procedure Start	Used to initiate the ITU procedure Support for Recommendation ITU-R M.493-15 [1] annexes 3 and 4
AI9	Initiate Communications Call	Automated Procedure Start	Used to initiate the ITU procedure Support for Recommendation ITU-R M.493-15 [1] annexes 3 and 4
AAS	Audible Alert Sound Status and Control, This is a command sentence	Config of Alert sounds.	
AUQ <sup>a</sup>	DSC Automated procedure query information	Automated Procedure Query	Used to query for details of an automated DSC procedure
FSS <sup>a</sup>	Remote display or command	Frequency selection set	Used to control radio frequency
HBT	Remote display or command	Heartbeat	Integrity test
SFI	Remote display or command	Scanning frequency information	Used to set scanning frequencies of DSC
NOTE a: See annex A.			