



**Broadcast Sound Receivers;  
Part 4: DAB broadcast sound service;  
Harmonised Standard for access to radio spectrum**

[ETSI EN 303 345-4 V1.1.1 \(2021-03\)](https://standards.iteh.ai/catalog/standards/sist/8e2bb1a5-c744-4543-a17d-8a7d5471434c/etsi-en-303-345-4-v1-1-1-2021-03)

<https://standards.iteh.ai/catalog/standards/sist/8e2bb1a5-c744-4543-a17d-8a7d5471434c/etsi-en-303-345-4-v1-1-1-2021-03>

---

**Reference**DEN/ERM-TG17-154

---

**Keywords**broadcast, digital, harmonised standard, radio,  
receiver**ETSI**650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

---

**Important notice**

---

<https://standards.iteh.ai/catalog/standards/sist/8e2bb1a5-c744-4543-a17d-8a7d0c114349/etsi-en-303-345-4-v1-1-1-2021-03>  
The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	5
Foreword.....	5
Modal verbs terminology.....	6
Introduction .....	6
1 Scope .....	7
2 References .....	7
2.1 Normative references .....	7
2.2 Informative references.....	7
3 Definition of terms, symbols and abbreviations.....	8
3.1 Terms.....	8
3.2 Symbols.....	8
3.3 Abbreviations .....	8
4 Technical requirements specifications .....	9
4.1 Test signal configurations .....	9
4.2 Sensitivity.....	9
4.2.1 Definition.....	9
4.2.2 Limits.....	9
4.2.3 Conformance.....	10
4.3 Adjacent channel selectivity and blocking .....	10
4.3.1 Definition.....	10
4.3.2 Limits.....	10
4.3.3 Conformance.....	11
4.4 Unwanted emissions in the spurious domain.....	11
4.4.1 Definition.....	11
4.4.2 Limits.....	11
4.4.3 Conformance.....	11
5 Testing for compliance with technical requirements.....	11
5.1 Environmental conditions for testing .....	11
<b>Annex A (informative): Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b>	<b>12</b>
<b>Annex B (informative): Development of the present document.....</b>	<b>13</b>
B.1 Introduction .....	13
B.2 Relevance .....	13
B.3 Receiver parameters under article 3.2 .....	13
B.3.1 General .....	13
B.3.2 Receiver sensitivity .....	13
B.3.3 Receiver co-channel rejection .....	14
B.3.4 Receiver selectivity .....	14
B.3.4.1 General.....	14
B.3.4.2 Single signal selectivity .....	14
B.3.4.2.1 Receiver adjacent signal selectivity (adjacent channel selectivity) .....	14
B.3.4.2.2 Receiver spurious response rejection .....	14
B.3.4.3 Receiver multiple signal selectivity .....	14
B.3.4.3.1 Receiver blocking .....	14
B.3.4.3.2 Receiver radio-frequency intermodulation.....	15
B.3.4.3.3 Receiver adjacent signal selectivity (adjacent channel selectivity).....	15
B.3.4.4 Other receiver effects.....	15
B.3.4.4.1 Receiver dynamic range.....	15
B.3.4.4.2 Reciprocal mixing.....	15

B.3.4.4.3	Desensitization .....	15
B.3.5	Receiver unwanted emissions in the spurious domain .....	16
<b>Annex C (informative):</b>	<b>Change History .....</b>	<b>17</b>
History .....		18

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ETSI EN 303 345-4 V1.1.1 \(2021-03\)](https://standards.iteh.ai/catalog/standards/sist/8e2bb1a5-c744-4543-a17d-8a7d5471434c/etsi-en-303-345-4-v1-1-1-2021-03)

<https://standards.iteh.ai/catalog/standards/sist/8e2bb1a5-c744-4543-a17d-8a7d5471434c/etsi-en-303-345-4-v1-1-1-2021-03>

---

## Intellectual Property Rights

### Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

### Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

## Foreword

This final draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Vote phase of the ETSI standards EN Approval Procedure. (standards.iteh.ai)

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.2] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 4 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

The present document has a number of test data files that are contained in archive en\_30334501v010101p0.zip which accompanies ETSI EN 303 345-1 [1].

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

## Introduction

The present document provides the necessary limits and conformance requirements for radio receivers to meet the essential requirements of article 3.2 of Directive 2014/53/EU [i.1] for the DAB sound broadcast service and is used with reference to ETSI EN 303 345-1 [1], which describes the generic requirements and test methods.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ETSI EN 303 345-4 V1.1.1 \(2021-03\)](#)

<https://standards.iteh.ai/catalog/standards/sist/8e2bb1a5-c744-4543-a17d-8a7d5471434c/etsi-en-303-345-4-v1-1-1-2021-03>

---

# 1 Scope

The present document specifies the test signal configuration and the limits for sensitivity, selectivity, blocking and unwanted emissions in the spurious domain for devices that receive DAB broadcast sound services.

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.1] is given in annex A.

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 303 345-1 (V1.1.1) (06-2019): "Broadcast Sound Receivers; Part 1: Generic requirements and measuring methods"
- [2] ETSI EN 300 401 (V2.1.1) (01-2017): "Radio Broadcasting Systems; Digital Audio Broadcasting (DAB) to mobile, portable and fixed receivers" (2021-03)
- [3] EN 55032:2015: "Electromagnetic compatibility of multimedia equipment - Emission Requirements" (produced by CENELEC).

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.3] AES17: "AES standard method for digital audio engineering - Measurement of digital audio equipment".
- [i.4] ETSI EG 203 336 (V1.1.1) (08-2015): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".

- [i.5] ITU GE06: "Final Acts RRC-06".
- [i.6] Recommendation ITU-R BS.1660-7 (10/2015): "Technical basis for planning of terrestrial digital sound broadcasting in the VHF band".
- [i.7] Recommendation ITU-R SM.332-4 (07/1978): "Selectivity of Receivers".

## 3 Definition of terms, symbols and abbreviations

### 3.1 Terms

For the purposes of the present document, the terms given in Directive 2014/53/EU [i.1] and the following apply:

**integral antenna:** antenna which is detachable from the equipment without the use of any tools, and not using a 50  $\Omega$  or 75  $\Omega$  external connector

NOTE: A device that uses a supplied earphone as the antenna has an integral antenna.

### 3.2 Symbols

For the purposes of the present document, the following symbols apply:

**dBFS:** decibels relative to Full Scale in accordance with AES17 [i.3]

**dBm:** decibels relative to 1 mW of power

**dB $\mu$ V/m:** decibels relative to 1  $\mu$ V/m

STANDARD PREVIEW  
(standards.iteh.ai)

### 3.3 Abbreviations

ETSI EN 303 345-4 V1.1.1 (2021-03)

[https://standards.iteh.ai/catalog/standards/sist/8e2bb1a5-c744-4543-a17d-](https://standards.iteh.ai/catalog/standards/sist/8e2bb1a5-c744-4543-a17d-8a7d5471434c/etsi-en-303-345-4-v1-1-1-2021-03)

[8a7d5471434c/etsi-en-303-345-4-v1-1-1-2021-03](https://standards.iteh.ai/catalog/standards/sist/8e2bb1a5-c744-4543-a17d-8a7d5471434c/etsi-en-303-345-4-v1-1-1-2021-03)

For the purposes of the present document, the following abbreviations apply:

AAC	Advanced Audio Coding
ACS	Adjacent Channel Selectivity
ADC	Analogue to Digital Converter
AM	Amplitude Modulation
DAB	Digital Audio Broadcasting
DDC	Direct Digital Conversion
EEP	Equal Error Protection
EEP-3A	Equal Error Protection profile 3A
EFTA	European Free Trade Association
ETI	Ensemble Transport Interface
EU	European Union
ITU-R	International Telecommunications Union - Radiocommunications sector
LO	Local Oscillator
NZIF	Near-Zero Intermediate Frequency
OFDM	Orthogonal Frequency Division Modulation
RED	Radio Equipment Directive
RF	Radio Frequency
VHF	Very High Frequency



## 4 Technical requirements specifications

### 4.1 Test signal configurations

The generated DAB signals (wanted and unwanted) and the blocking signal shall be in accordance in table 1.

**Table 1: DAB configuration**

Parameter	DAB signals		AM signal
	Wanted	Unwanted	Blocking
Audio modulation	Service label: "Sine+" 1 kHz tone at a level of -3 dBFS mono, 128 kbit/s AAC, EEP-3A	Any DAB ensemble without the "Sine+" service	1 kHz tone
Other modulation parameters	DAB signal to ETSI EN 300 401 [2], clause 15	DAB signal to ETSI EN 300 401 [2], clause 15	80 % depth

NOTE: Level is defined in accordance with AES17 [i.3].

ETI files providing the required DAB test signals are available at [https://docbox.etsi.org/Broadcast/Open/PRODUCT-STREAM\\_V1.2.zip](https://docbox.etsi.org/Broadcast/Open/PRODUCT-STREAM_V1.2.zip): PRODUCT-STREAM-01\_V1.2.eti can be used for the wanted signal and PRODUCT-STREAM-02\_V1.2.eti can be used for the unwanted signal. An arbitrary waveform file producing the blocking signal is available in archive en\_30334501v010101p0.zip which accompanies ETSI EN 303 345-1 [1].

### 4.2 Sensitivity

**ITeH STANDARD PREVIEW**  
(standards.iteh.ai)

#### 4.2.1 Definition

The receiver sensitivity is the minimum wanted signal level required to provide a given level of audio quality.

[ETSI EN 303 345-4 V1.1.1 \(2021-03\)](https://standards.iteh.ai/catalog/standards/sist/8e2bb1a5-c744-4543-a17d-8a7d5471434c/etsi-en-303-345-4-v1-1-1-2021-03)

#### 4.2.2 Limits

<https://standards.iteh.ai/catalog/standards/sist/8e2bb1a5-c744-4543-a17d-8a7d5471434c/etsi-en-303-345-4-v1-1-1-2021-03>

The limits for sensitivity specified in table 2 shall apply. Each figure quoted is the required level of wanted signal which provides a given level of audio quality. The audio impairment criterion relevant for these tests is clean audio: that is 10 seconds of audio without impairments (e.g. no muting, clicks, warbles or squeaks).

**Table 2: DAB sensitivity requirements**

De-modulation	Tuned frequency band	Wanted signal centre frequency (MHz)	Required sensitivity limit	
			Conducted (dBm)	Radiated (dB $\mu$ V/m)
DAB	VHF band III	202,928	-94	37 (see note)

NOTE: For products with an integral antenna, the requirement is relaxed to 50 dB $\mu$ V/m.

### 4.2.3 Conformance

Conformance tests as defined in ETSI EN 303 345-1 [1], clause 5.3.4.2 shall be carried out. The wanted signal generator shall be set to produce a signal according to table 1 at the centre frequency according to table 2. The required sensitivity level shall be as indicated in table 2. If the impairment criterion given in clause 4.2.2 is met then the receiver has passed the sensitivity requirement.

## 4.3 Adjacent channel selectivity and blocking

### 4.3.1 Definition

The adjacent channel selectivity is a measure of the capability of the receiver to receive a wanted modulated signal without exceeding a given degradation due to the presence of an unwanted signal which differs in frequency from the wanted signal by an amount equal to the adjacent channel separation. The wanted and unwanted signals are of the same modulation type.

The blocking ratio at a given frequency separation, is a measure of the capability of the receiver to receive a wanted modulated signal without exceeding a given degradation due to the presence of an unwanted input signal.

In order to provide effective use of spectrum, devices shall be able to demodulate the tuned signal in the presence of similar signals in adjacent channels. In addition, testing shall also be performed to check the ability of the receiver to work effectively with interfering signals at a greater separation from the wanted signal (blocking).

The channel spacings specified in table 3 shall apply.

**Table 3: Channel spacing for adjacent channel selectivity and blocking**

Demodulation	Tuned frequency band	Unwanted frequency (N = 1, 2, 3)	Unwanted frequency (blocking)
DAB	VHF band III	$\pm N \times 1\,712$ kHz	$\pm 12$ MHz

ETSI EN 303 345-4 V1.1.1 (2021-03)

<https://standards.iteh.ai/catalog/standards/sist/8e2bb1a5-c744-4543-a17d-8a7d5471434c/etsi-en-303-345-4-v1-1-1-2021-03>

### 4.3.2 Limits

The limits for selectivity and blocking specified in table 4 shall apply with the channel spacings given in table 3. Each figure quoted is the minimum acceptable level of unwanted signal, relative to that of the wanted signal, which provides a given level of audio quality. The audio impairment criterion relevant for these tests is clean audio: that is 10 seconds of audio without impairments (e.g. no muting, clicks, warbles or squeaks).

**Table 4: Adjacent channel selectivity and blocking requirements**

De-modulation	Tuned frequency band	C Wanted signal centre frequency (MHz)	C Wanted signal level		Required I/C ratio (see notes 1 and 2)			
			Conducted (dBm)	Radiated (dB $\mu$ V/m)	N = 1 (dB)	N = 2 (dB)	N = 3 (dB)	Blocking (dB)
DAB	VHF band III	202,928	-70	61	35	40	45	40

NOTE 1: The frequency of the interferer shall be calculated using the channel spacing data in table 3 for each of the 6 defined adjacent channels  $N = \{-3, -2, -1, +1, +2, +3\}$  and the two blocking offsets. Each row of table 4 thus defines 8 individual tests.

NOTE 2: The minimum level of I for the relevant level of impairment is calculated by adding the I/C ratio to the wanted C level.