



**Broadcast Sound Receivers;  
Part 5: DRM broadcast sound service;  
Harmonised Standard for access to radio spectrum**

*Standard for Access to Radio Spectrum  
Full standard  
https://standards.iteh.ai/catalog/standards/etsi/303-345-5-v1-1-2020-02*

---

**Reference**DEN/ERM-TG17-155

---

---

**Keywords**broadcast, digital, harmonised standard, radio,  
receiver

---

**ETSI**650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	5
Foreword.....	5
Modal verbs terminology.....	6
Introduction .....	6
1 Scope .....	7
2 References .....	7
2.1 Normative references .....	7
2.2 Informative references.....	7
3 Definition of terms, symbols and abbreviations.....	8
3.1 Terms.....	8
3.2 Symbols.....	8
3.3 Abbreviations .....	8
4 Technical requirements specifications .....	9
4.1 Test signal configurations .....	9
4.2 Sensitivity.....	9
4.2.1 Definition.....	9
4.2.2 Limits.....	10
4.2.3 Conformance.....	10
4.3 Adjacent channel selectivity and blocking .....	10
4.3.1 Definition.....	10
4.3.2 Limits.....	11
4.3.3 Conformance.....	11
5 Testing for compliance with technical requirements.....	11
5.1 Environmental conditions for testing .....	11
5.2 Interpretation of the measurement results .....	12
<b>Annex A (informative): Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b>	<b>13</b>
<b>Annex B (informative): Development of the present document.....</b>	<b>14</b>
B.1 Introduction .....	14
B.2 Relevance .....	14
B.3 Receiver parameters under article 3.2 .....	14
B.3.1 General .....	14
B.3.2 Receiver sensitivity .....	14
B.3.3 Receiver co-channel rejection .....	15
B.3.4 Receiver selectivity .....	15
B.3.4.1 General.....	15
B.3.4.2 Single signal selectivity .....	15
B.3.4.2.1 Receiver adjacent signal selectivity (adjacent channel selectivity).....	15
B.3.4.2.2 Receiver spurious response rejection .....	15
B.3.4.3 Receiver multiple signal selectivity .....	15
B.3.4.3.1 Receiver blocking .....	15
B.3.4.3.2 Receiver radio-frequency intermodulation.....	16
B.3.4.3.3 Receiver adjacent signal selectivity (adjacent channel selectivity).....	16
B.3.4.4 Other receiver effects.....	16
B.3.4.4.1 Receiver dynamic range .....	16
B.3.4.4.2 Reciprocal mixing .....	16
B.3.4.4.3 Desensitization .....	16
B.3.5 Receiver unwanted emissions in the spurious domain .....	17

**Annex C (informative): Change History .....18**  
History .....19

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/2938b57d-6fba-4359-a90f-de2ccc45e35d/etsi-en-303-345-5-v1.1.1-2020-02>

---

## Intellectual Property Rights

### Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

### Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

## Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.2] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 5 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

The present document has a number of test data files that are contained in archive en\_30334501v010101p0.zip which accompanies ETSI EN 303 345-1 [1].

<b>Proposed national transposition dates</b>	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

---

## Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

## Introduction

The present document provides the necessary limits and conformance requirements for radio receivers to meet the essential requirements of article 3.2 of Directive 2014/53/EU [i.1] for the DRM sound broadcast service and is used with reference to ETSI EN 303 345-1 [1], which describes the generic requirements and test methods.

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/2938b57d-6fba-4359-a90f-de2ccc45e35d/etsi-en-303-345-5-v1.1.1-2020-02>

---

# 1 Scope

The present document specifies the test signal configuration and the limits for sensitivity, selectivity and blocking for devices that receive DRM broadcast sound services.

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.1] is given in annex A.

---

## 2 References

### 2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 303 345-1 (V1.1.1) (06-2019): "Broadcast Sound Receivers; Part 1: Generic requirements and measuring methods".
- [2] ETSI ES 201 980 (V4.1.1) (01-2014): "Digital Radio Mondiale (DRM); System Specification".

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.3] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.4] ETSI TR 100 028-2 (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
- [i.5] AES17: "AES standard method for digital audio engineering - Measurement of digital audio equipment".

- [i.6] ETSI EG 203 336 (V1.1.1) (08-2015): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.7] ITU GE75: "Final Acts of the Regional Administrative LF/MF Broadcasting Conference (Regions 1 and 3)".
- [i.8] ITU GE84: "Final Acts of the Regional Administrative Radio Conference for the Planning of the VHF Sound Broadcasting (Region 1 and part of Region 3)".
- [i.9] ITU GE06: "Final Acts RRC-06".
- [i.10] Recommendation ITU-R BS.1615-1 (05/2011): "Planning parameters' for digital sound broadcasting at frequencies below 30 MHz".
- [i.11] Recommendation ITU-R BS.1660-7 (10/2015): "Technical basis for planning of terrestrial digital sound broadcasting in the VHF band".
- [i.12] Recommendation ITU-R SM.332-4 (07/1978): "Selectivity of Receivers".
- [i.13] CENELEC EN 55032:2015: "Electromagnetic compatibility of multimedia equipment - Emission Requirements".

---

## 3 Definition of terms, symbols and abbreviations

### 3.1 Terms

For the purposes of the present document, the terms given in Directive 2014/53/EU [i.1] and the following apply:

**adjacent channel selectivity:** measure of the capability of the receiver to receive a wanted modulated signal without exceeding a given degradation due to the presence of an unwanted signal which differs in frequency from the wanted signal by an amount equal to the adjacent channel separation

**blocking:** measure of the capability of the receiver to receive a wanted modulated signal without exceeding a given degradation due to the presence of an unwanted input signal which differs in frequency from the wanted signal by a specified amount

**sensitivity:** minimum wanted signal level required to provide a given level of audio quality

### 3.2 Symbols

For the purposes of the present document, the following symbols apply:

**dBFS:** decibels relative to Full Scale in accordance with AES17 [i.5]

**dBm:** decibels relative to 1 mW of power

**dB $\mu$ V/m:** decibels relative to 1  $\mu$ V/m

### 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AAC	Advanced Audio Coding
ACS	Adjacent Channel Selectivity
ADC	Analogue to Digital Converter
AM	Amplitude Modulation
DDC	Direct Digital Conversion
DRM	Digital Radio Mondiale
EFTA	European Free Trade Association



EMCD	ElectroMagnetic Compatibility Directive
EU	European Union
HF	High Frequency
ITU-R	International Telecommunications Union - Radiocommunications sector
LF	Low Frequency
LO	Local Oscillator
MF	Medium Frequency
MSC	Main Service Channel
NZIF	Near-Zero Intermediate Frequency
OFDM	Orthogonal Frequency Division Modulation
RED	Radio Equipment Directive
RF	Radio Frequency
RM	Robustness Mode
VHF	Very High Frequency

## 4 Technical requirements specifications

### 4.1 Test signal configurations

The generated DRM signals (wanted and unwanted) and the blocking signal shall be in accordance in table 1.

**Table 1: DRM configuration**

Parameter	DRM signals						AM signal Blocking
	Wanted			Unwanted			
<b>Audio coding</b>	Service label: "Sine 1 kHz" 1 kHz tone at a level of -3 dBFS Coding: mono AAC at maximum permitted rate			Service label: "Sine 2 kHz" 2 kHz tone at a level of -3 dBFS Coding: mono AAC at maximum permitted rate			1 kHz tone
<b>Frequency band</b>	LF/MF	HF	VHF	LF/MF	HF	VHF	
<b>Channel coding parameters</b>	RM flag	0	0	1	0	0	1
	protection level	1	1	2	1	1	2
	MSC mode	0	0	0	0	0	0
	interleaver depth	1	1	0	1	1	0
	robustness mode	B	B	E	B	B	E
spectrum occupancy	2	3	0	2	3	0	
<b>Other modulation Parameters</b>	DRM signal to ETSI ES 201 980 [2], clause 8			DRM signal to ETSI ES 201 980 [2], clause 8			80 % depth

NOTE: Level is defined in accordance with AES17 [i.5].

An arbitrary waveform file producing the blocking signal is available in archive en\_30334501v010101p0.zip which accompanies ETSI EN 303 345-1 [1].

### 4.2 Sensitivity

#### 4.2.1 Definition

The receiver sensitivity is the minimum wanted signal level required to provide a given level of audio quality.