



DRAFT INTERNATIONAL STANDARD ISO/DIS 12345

ISO/TC 22/SC 7

Secretariat: DIN

Voting begins on
2010-12-14

Voting terminates on
2011-05-14

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Diesel engines — Cleanliness assessment of fuel injection equipment

Moteurs diesels — Évaluation de la propreté de l'équipement d'injection

[Revision of first edition (ISO 12345:2002)]

ICS 43.060.40

ITeH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<http://standards.iteh.ai/catalog/standards/sist/1584cbf3-b21-4f4b-aac7-b591b898d0ab/iso-12345-2013>

In accordance with the provisions of Council Resolution 15/1993 this document is circulated in the English language only.

Conformément aux dispositions de la Résolution du Conseil 15/1993, ce document est distribué en version anglaise seulement.

To expedite distribution, this document is circulated as received from the committee secretariat. ISO Central Secretariat work of editing and text composition will be undertaken at publication stage.

Pour accélérer la distribution, le présent document est distribué tel qu'il est parvenu du secrétariat du comité. Le travail de rédaction et de composition de texte sera effectué au Secrétariat central de l'ISO au stade de publication.

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/1584cbf3-bb21-4f4b-aac7-b591b898d0ab/iso-12345-2013>

Copyright notice

This ISO document is a Draft International Standard and is copyright-protected by ISO. Except as permitted under the applicable laws of the user's country, neither this ISO draft nor any extract from it may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission being secured.

Requests for permission to reproduce should be addressed to either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Reproduction may be subject to royalty payments or a licensing agreement.

Violators may be prosecuted.

Contents

Page

Foreword	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Test apparatus	3
4.1 General	3
4.2 Pressure source	3
4.3 Verification high-pressure pipe assembly	4
4.4 Verification test injector	4
4.5 Collecting vessel	4
4.6 Verification rail	4
4.7 Equipment for contamination measurement	4
4.8 Test fluid	6
4.9 Clean-up filter	7
4.10 Pressure gauge	7
5 Procedure	7
5.1 General	7
5.2 High-pressure supply pumps (common rail)	8
5.3 Unit injectors	9
5.4 Fuel injection pumps	10
5.5 Common rail fuel injectors	11
5.6 Fuel injectors (Nozzle holder assemblies)	13
5.7 High-pressure fuel injection pipes	14
5.8 Rails	16
5.9 Low-pressure systems	20
6 Sample analysis	21
6.1 General	21
6.2 Gravimetric analysis	21
6.3 Particle size distribution	21
6.4 Largest particle size	21
7 Reporting results	22
7.1 Principle of fuel injection equipment cleanliness code	22
7.2 Examples of fuel injection equipment cleanliness code usage	23
8 Designation	24
Annex A (informative) Typical test equipment for measuring fuel injection equipment cleanliness	25
A.1 General	25
A.2 Basic principle of test equipment	25
A.3 Test equipment for syringe or hand flushing test	27
A.4 Test rig components for high-pressure supply pumps (test pump running by hand)	28
A.5 Rail pressure vessel flushing test (dynamic procedure)	29
Annex B (informative) Rail low pressure flushing test	30
Annex C (normative) Procedure for verifying test equipment initial cleanliness	31
C.1 Initial cleanliness verification procedures	31
C.2 Blank test	31
C.3 Criteria for acceptance	32
Annex D (informative) Determination of flushing parameters for rail pressure vessel flushing test	34

D.1 Blowhole and particle collection point..... 34
D.2 Different flushing configurations to avoid blowholes and particle collection points 34
Bibliography 36

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/1584cbf3-bb21-4f4b-aae7-b591b898d0ab/iso-12345-2013>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12345 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 7, *Injection equipment and filters for use on road vehicles*.

This second edition cancels and replaces the first edition (ISO 12345:2002), which has been technically revised.

Annex C forms a normative part of this International Standard. Annexes A, B and D are for information only.

Introduction

Modern fuel injection systems contain many closely controlled clearances and rely on the fuel-flowing characteristics of small orifices; thus they require the close control of sources of contamination in order to maintain the operational performance demanded of them throughout their design life. To this end, such systems are designed with integral fuel-filtration equipment, which reduces the amount of potentially damaging debris that could enter the system from external sources.

However, contamination of the fuel injection system can also occur internally, from system use or wear, from equipment servicing, or as a result of the original supplier's manufacturing and assembly processes. The focus of this International Standard is on the latter source of contamination, and is thus concerned with the assessment of the cleanliness of the fuel injection equipment as originally supplied to the engine manufacturer.

Fuel injection systems comprise a number of components. Traditional systems contain low pressure elements (fuel tank, pipe-work, filters, lift pump, etc.), a fuel injection pump, high-pressure pipes and fuel injectors, located within the engine cylinder head.

During the preparation of this International Standard, the importance of care in the handling and measurement of contamination samples was clearly recognized. Moreover, the low levels of contaminant with fuel injection equipment makes this a particularly difficult task. For this International Standard to be used meaningfully - as an indicator of component cleanliness and a driver towards higher quality standards - extreme attention to detail is required of the user. Verification requirements for the test equipment used are therefore emphasized, in detail.

It is not always clear what level and type of cleanliness would be beneficial for improved performance and life on a cost-effective basis. The actual quantitative levels can only be set in relation to other parameters, agreed between the manufacturer, supplier and user. This International Standard provides a set of procedures for evaluating the cleanliness of fuel injection equipment and a framework for a common measurement and reporting.

Diesel engines — Cleanliness assessment of fuel injection equipment

1 Scope

This International Standard specifies cleanliness assessment procedures for evaluating the amount of debris, found within the clean side of diesel fuel injection assemblies, which could lead to a reduction in the system's operational effectiveness.

While other International Standards e.g. ISO 16232 series relate to cleanliness of components used in Road Vehicle fluid circuits, this Standard is focussed on diesel fuel injection assemblies as supplied to diesel engine manufacturers or the service market.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3722, *Hydraulic fluid power – Fluid sample containers – Qualifying and controlling cleaning methods*

ISO 4008-1, *Road Vehicles – Fuel injection pump testing – Part 1: Dynamic conditions*

ISO 4113, *Road Vehicles – Calibration fluid for diesel injection equipment*

ISO 4788, *Laboratory glassware – Graduated measuring cylinders*

ISO 7440-1, *Road vehicles – Fuel injection equipment testing – Part 1: Calibrating nozzle and holder assemblies*

ISO 8535-1, *Compression ignition engines – Steel tubes for high pressure fuel injection pipes – Part 1: Requirements for seamless cold drawn single wall tubes*

ISO 8984-1, *Diesel engines – Testing of fuel injectors – Part 1: Hand lever operated testing and setting apparatus*

ISO 14644-1, *Clean room and associated controlled environments – classification of air cleanliness*

ISO 16232-6, *Road vehicles — Cleanliness of components of fluid circuits — Part 6: Particle mass determination by gravimetric analysis*

ISO 16232-7, *Road vehicles — Cleanliness of components of fluid circuits — Part 7: Particle sizing and counting by microscopic analysis*

ISO 16232-9, *Road vehicles — Cleanliness of components of fluid circuits — Part 9: Particle sizing and counting by automatic light extinction particle counter*

SAE J 1549, *Diesel fuel injection pump – Validation of calibrating nozzle holder assemblies*

3 Terms and definitions

For the purpose of this International Standard, the following terms and definitions apply:

NOTE For terms and definitions given in ISO 4006, ISO 7876-1 to ISO 7876-5 and ISO 7967-7: see Bibliography.

3.1 Fuel injection equipment cleanliness code FIECC

alpha-numeric code representing the distribution of particles by size and/or weight.

3.2 Cleanliness level CL

amount and/or nature of contaminant present on the controlled surfaces and/or in controlled volumes of a component

NOTE The term may apply to the presumed, specified or measured extent of contamination.

3.3 Cleanliness specification CS

a document that specifies the cleanliness level CL required for a given component along with the agreed inspection method

3.4 Reynolds number Re

dimensionless parameter expressing the ratio between the inertia and viscous forces in a flowing fluid, given by the formula

$$Re = \frac{U \times l}{\nu}$$

where:

U is the mean axial fluid velocity across the defined area, expressed in millimetres per seconds

l is the characteristic dimension of the system over which the flow occurs, expressed in millimetres

[for pipes $l = d$ (pipe bore diameter)]

ν is the kinematic viscosity of the fluid, expressed in square millimetres per second [centistokes].

3.5 Blank Test

Analysis carried out with the same operating conditions as on the test component but without the component or the component being a “clean” master sample used only for this purpose.

NOTE The blank test allows quantification of the contamination brought in from the environment, process or materials used.

3.6 Blank value/ level

Result obtained from the blank test

4 Test apparatus

4.1 General

Typical test equipments recommended for measuring fuel-injection equipment cleanliness are described in Annex A. Following are details of specific apparatus that may be used.

4.2 Pressure source

4.2.1 General

Take different forms for different tests, as described in the following subclauses.

4.2.2 Fuel injection pump test bench

A single cylinder inline pump as specified in SAE J1549 and a test bench as specified in ISO 4008-1.

4.2.3 Hand-lever-operated testing and setting apparatus

A testing apparatus as described in ISO 8984-1.

4.2.4 High-pressure pulsating flow rig

A pressure source capable of achieving:

- a) a flow rate which will generate a turbulent flow in the pipes ($Re > 4000$) for a period of $30\text{ s} \pm 1\text{ s}$, while pulsating the flow between zero and this value at a frequency of 0,2 Hz to 1 Hz, followed by
- b) a flush at $1,4\text{ MPa} \pm 0,1\text{ MPa}$ constant pressure for $15\text{ s} \pm 1\text{ s}$.

4.2.5 Verification low pressure pump

A plunger or diaphragm-type pump having a flow rate of approximately twice the rated value for the component under test at a pressure of at least 2 MPa.

The verification low-pressure pump shall be cleaned to the cleanliness level CL in accordance with Annex C and carefully stored with proper cover in a clean environment.

4.2.6 Verification high pressure delivery pump

For testing of high-pressure pipes with open ends, having a flow rate capable of generating a Reynolds number in the pipes of $Re > 4000$. A pressure capability of $3\text{ MPa} \pm 0,1\text{ MPa}$ is considered suitable.

The verification high-pressure delivery pump shall be cleaned to the cleanliness level CL in accordance with Annex C and carefully stored with proper cover in a clean environment.

4.2.7 Pressure vessel

Used as pressure source, shall be able to supply a testing pressure of at least 0,5 Mpa (=5 bar) and to produce a turbulent flow inside the rail (recommended flow rate at least 2,5 l/min)

4.2.8 Flushing pump

For testing of rails with open ends, having a flow rate of at least 0,1 l/min. For this pump a pressure capability of up to $0,1\text{ MPa} \pm 0,01\text{ MPa}$ is considered suitable.

4.3 Verification high-pressure pipe assembly

600 mm long, of tube ISO 8535-1 S-2-6-2 1 P 0 (see ISO 8535-1)¹⁾ and suitable for the component under test.

Stainless steel tubing should be used because of its resistance to rust and corrosion contamination. The verification high-pressure pipe assembly shall be cleaned to the cleanliness level CL in accordance with Annex C and carefully stored with proper cover in a clean environment

4.4 Verification test injector

In accordance with ISO 7440-1, fitted with an orifice plate of orifice diameter 2,5 mm.

The inlet edge filter shall be removed, while the pintle end may be removed to improve the particle passage. The nozzle opening pressure shall be set to $20,7^{+0,3}_{-0}$ MPa.

4.5 Collecting vessel

Which may be necessary for collecting test fluid downstream from the tested equipment at a flow rate different from that passing through the particle counter, the contamination monitor or the membrane filter.

The collecting vessel may be used for storing test fluid before transfer fluid samples to laboratory for analysis. A cylindrical stainless steel or glass reservoir with a conical bottom should be used for facilitating further particle collection.

4.6 Verification rail

Needed to establish the cleanliness level CL for the whole rail cleanliness test apparatus.

For the verification the verification rail shall be cleaned to the blank value in accordance with Annex C and carefully stored with proper cover in a clean environment.

4.7 Equipment for contamination measurement

4.7.1 General

Involving the application of two specific techniques for evaluating the level of contamination:

gravimetric analysis;

microscopic examination

Each requires the following specific laboratory apparatus.

4.7.2 Gravimetric analysis apparatus

NOTE For gravimetric analysis see ISO 16232-6.

4.7.2.1 Non-ventilated drying oven

Capable of maintaining a temperature of $80\text{ °C} \pm 2\text{ °C}$.

¹⁾ Use of stainless steel tubing is recommended to resist rust and corrosion contamination.

4.7.2.2 Filter holder

Comprising

- glass funnel of at least 300 ml capacity with suitably calibrated volumetric graduations (e.g. 25 ml \pm 2 ml),
- suitable cover for the funnel (e.g. petri dish),
- clamping device,
- suitable base to support the membrane filter, and
- a means of dissipating any static electricity generated during the filtering process.

4.7.2.3 Vacuum flask

Suitable for the filter holder and of capacity enabling it to hold the entire volume of sample liquid without refilling.

4.7.2.4 Vacuum device

Able to generate a vacuum of 86,6 kPa (gauge).

4.7.2.5 Solvent dispenser (syringe)

A pressurized vessel that discharges solvent through an in-line filter membrane with a pore size of not greater than 1 μ m.

4.7.2.6 Tweezers

Flat-bladed (non-serrated, blunt tips), and of stainless steel.

4.7.2.7 Graduated cylinders

For measuring out the volume of test liquid, to an accuracy that should be in accordance with ISO 4788. Alternatively, a sample bottle calibrated with suitable volumetric graduations may be used, in which case the accuracy of graduation should be \pm 2 %.

4.7.2.8 Sample bottles

Of 250 ml nominal capacity, preferably flat-bottomed and wide-mouthed, with a screw cap containing a suitable internal polymeric seal.

4.7.2.9 Plastic film

0,05 mm thick x 50 mm x 50 mm, placed between the sample bottle cap and neck if the cap does not have an internal seal. The film shall be compatible with both the cleaning and sample liquids.

4.7.2.10 Filter membranes

Preferred 25 or 47 mm in diameter, white, without grids, and compatible with the fluid to be analysed and with the rinsing chemicals. Reference membranes shall have a recommended pore size of between 5 and 8 μ m. The pore size used shall be stated.

4.7.2.11 Petri dishes

Of glass and 150 mm diameter.

4.7.2.12 Analytical balance

Of at least 0,05 mg accuracy.

4.7.2.13 Alpha-ray ioniser

To be used to prevent collection of dust during the weighing operation, placed under the balance scale incorporating the filter and projecting from beneath it.

4.7.2.14 Air dryer

4.7.2.15 Collecting vessel

A vessel with a vacuum device connecting, to be used to collect test fluid

4.7.3 Microscopic analysis apparatus

NOTE For microscopic analysis see ISO 16232-7.

4.7.3.1 Filter membrane

Compatible with the sample liquid and any solvents or chemicals used in the processes. Normally, the membrane shall be of 25 or 47 mm diameter, white, with grids (each grid square width side 3,08 mm ± 0,05 mm and equal to 1 % of the effective filtration area), and with a pore size < 8 µm, used for manual counting down to 2 µm. A 47 mm diameter white, membrane without grids and with a pore size of < 8 µm should be used for image analysis. Membranes of different diameters may be used.

4.8 Test fluid

4.8.1 General

Test fluids are described in the following clauses, depending on the test being conducted.

(see 5.2.2.1, 5.3.2, 5.4.2, 5.5.2.1, 5.5.3.1, 5.6.2.1, 5.7.2.1, 5.7.3.1, 5.7.4.1, 5.8.1, 5.8.3.1, 5.8.4.2, 5.9.2)

4.8.2 Calibration fluid

Test oil in accordance with ISO 4113, pre-filtered on a maximum of 1,0 µm cartridge filter, unless otherwise specified.

4.8.3 Solvent, aliphatic hydrocarbon

Pre-filtered using a maximum of 1,0 µm, single-membrane nylon filter, which shall not leave any residue when vaporized, as residuals can influence the weighing results, shall have a minimum flash point of 38 °C, in order to fulfil normal working environment safety aspects, shall not have any aromatic components that could enter the atmosphere when vaporized, and shall have a boiling point not higher than 200 °C.