UDC 661.419:620.1 Ref. No. : ISO/R 909-1968(E)

ISO

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION

ISO RECOMMENDATION R 909

HYDROCHLORIC ACID FOR INDUSTRIAL USE

ITCH STANDARD PREVIEW

DETERMINATION OF IRON CONTENT

(standards.itch.ai)

2,2'-bipyridyl spectrophotometric method

ISO/R 909:1968 https://standards.iteh.ai/catalog/standards/sist/5652e71d-3560-49c3-86b6-a0b2db36ec94/iso-r-909-1968

1st EDITION
December 1968

COPYRIGHT RESERVED

The copyright of ISO Recommendations and ISO Standards belongs to ISO Member Bodies. Reproduction of these documents, in any country, may be authorized therefore only by the national standards organization of that country, being a member of ISO.

For each individual country the only valid standard is the national standard of that country.

Printed in Switzerland

Also issued in French and Russian. Copies to be obtained through the national standards organizations.

BRIEF HISTORY

The ISO Recommendation R 909, Hydrochloric acid for industrial use – Determination of iron content – 2,2'-bipyridyl spectrophotometric method, was drawn up by Technical Committee ISO/TC 47, Chemistry, the Secretariat of which is held by the Ente Nazionale Italiano di Unificazione (UNI).

Based on detailed work on this question carried out by the Technical Committee, a Draft ISO Recommendation was adopted in 1965.

In June 1967, this Draft ISO Recommendation (No. 1179) was circulated to all the ISO Member Bodies for enquiry. It was approved, subject to a few modifications of an editorial nature, by the following Member Bodies:

Austria i Teh	STANDARD PREV	South Africa, Rep. of
Belgium	Ireland	Spain
Bulgaria	(standsraerds.iteh.ai)	Switzerland
Chile	Italy	Thailand
Cuba	Japan 000-1068	Turkey
Czechoslovakia	Korea, Dem. P. Rep. of ds. iteh. ai/cataley sandards set 100 200 100 100 100 100 100 100 100 100	U.A.R
France France	Korea, Dem. P. Rep. of ds. iteh.ai/catalog stands sist/5652e71d-350 a0b2db36ec94/ncara909-1968	United Kingdom
Germany	a0b2dbnew Zealand 909-1968	U.S.S.R.
Hungary	Poland	Yugoslavia
ICAITI*	Portugal	
India	Romania	

No Member Body opposed the approval of the Draft.

The Draft ISO Recommendation was then submitted by correspondence to the ISO Council which decided, in December 1968, to accept it as an ISO RECOMMENDATION.

^{*} Instituto Centroamericano de Investigación y Tecnología Industrial (Costa Rica, Guatemala, Honduras, Nicaragua, El Salvador, Panama).

HYDROCHLORIC ACID FOR INDUSTRIAL USE

DETERMINATION OF IRON CONTENT

2,2'-bipyridyl spectrophotometric method

iTeh STANDARD PREVIEW (standards.iteh.ai) 1. SCOPE

ISO/R 909:1968

This ISO Recommendation describes a 2,2 bipyridyl spectrophotometric method for the determination of the iron content of hydrochloric acid for industrial use.

2. FIELD OF APPLICATION

The method is applicable to the determination of iron content, expressed as Fe greater than 1 p.p.m.

3. PRINCIPLE

Evaporation of the test portion, taking up by means of hydrochloric acid and reduction of iron (III) by means of hydroxylammonium chloride.

Formation of an iron (II) - 2,2'-bipyridyl complex in a buffered medium (pH value between 4.5 and 6).

Photometric measurement of the coloured complex at a wavelength of about 522 nm.

4. REAGENTS

Distilled water or water of equivalent purity should be used in the test.

- 4.1 Hydrochloric acid, approximately N solution.
- 4.2 Hydroxylammonium chloride, 100 g/l solution.

Dissolve 10 g of hydroxylammonium chloride (NH₂OH.HCl) in water and dilute to 100 ml.

4.3 Ammonium acetate, 300 g/l solution.

Dissolve 30 g of ammonium acetate (CH₃COONH₄) in water and dilute to 100 ml.

4.4 2,2'-bipyridyl, 10 g/l hydrochloric acid solution.

Dissolve 1 g of 2.2 bipyridyl in 10 ml of approximately N hydrochloric acid solution and dilute to 100 ml.

(standards.iteh.ai)

4.5 Iron standard solution, containing 2.00 g/l of Fe. 1968

Weigh, to the nearest 4 mg, 7.022 g of iron (II) set ammonium sulphate hexahydrate and place in a beaker of suitable capacity. Add 50 ml of 100 g/I sulphuric acid solution (about 2 N) and transfer quantitatively to a 500 ml one-mark volumetric flask. Dilute to the mark and mix thoroughly.

1 ml of this standard solution contains 2.00 mg of Fe.

4.6 Iron standard solution, containing 0.20 g/l of Fe.

Transfer 50.0 ml of the iron standard solution (4.5) to a 500 ml one-mark volumetric flask, add 5 ml of 100 g/l sulphuric acid solution (about 2 N), dilute to the mark and mix thoroughly.

1 ml of this standard solution contains 0.20 mg of Fe.

The solution should be prepared just before use.

4.7 Iron standard solution, containing 0.010 g/l of Fe.

Transfer 50.0 ml of the iron standard solution (4.6) to a 1000 ml one-mark volumetric flask, dilute to the mark and mix thoroughly.

1 ml of this standard solution contains 10 μ g of Fe.

The solution should be prepared just before use.

5. APPARATUS

Ordinary laboratory apparatus and

- 5.1 Weighing pipette, capacity 60 ml approximately, with ground-glass stopper.
- 5.2 Spectrophotometer.

6. PROCEDURE

6.1 Test portion

Fill the weighing pipette (5.1) with the test sample and weigh by difference to the nearest 10 mg, a portion of approximately 50 g. Transfer the test portion to a beaker of suitable capacity (250 ml for example).

6.2 Blank test

At the same time as the analysis, carry out a blank test using the same procedure and quantities of all reagents employed in the test. DARD PREVIEW

6.3 Preparation of calibrated curve ndards.iteh.ai)

6.3.1 Preparation of standard matching solutions for the spectrophotometric measurement with 1 cm cell. Into each of a series of eleven 100 ml one-mark volumetric flasks, place the quantities of standard iron solution (4.7) indicated in the following Table:

Standard iron solution (4.7)	Corresponding to Fe
ml	μg
01)	0
5.0	50
10.0	100
15.0	150
20.0	200
25.0	250
30.0	300
35.0	350
40.0	400
45.0	450
50.0	500

¹⁾ Compensation solution

Add to each volumetric flask an amount of water sufficient to dilute to approximately 50 ml, then 2 ml of the hydrochloric acid solution (4.1), 2 ml of the hydroxylammonium chloride solution (4.2) and after 5 minutes, 5 ml of the ammonium acetate solution (4.3) and 1 ml of the 2,2'—bipyridyl solution (4.4). Dilute to the mark, mix thoroughly and wait 10 minutes.

- 6.3.2 Spectrophotometric measurement. Carry out the measurement on the spectrophotometer (5.2) at a wavelength of about 522 nm, adjusting the instrument to zero optical density using as reference the compensation solution.
- 6.3.3 Preparation of the calibration chart. Prepare a calibration chart having for example the iron content in microgrammes per 100 ml of the standard matching solution as abscissae and the corresponding values of optical density as ordinates.

6.4 Determination

6.4.1 Preparation of sample solution. Place the beaker containing the test portion (6.1) on a boiling water bath and carefully evaporate to dryness.

Cool, take up with 2 ml of the hydrochloric acid solution (4.1), 25 ml of water and heat to facilitate the dissolution. Transfer quantitatively to a 100 ml one-mark volumetric flask, dilute to the mark, mix and filter if necessary.

6.4.2 Colour development. Transfer an aliquot of the sample solution (6.4.1) containing between 50 and 500 μg of iron, to a 100 ml one-mark volumetric flask. Dilute to approximately 50 ml if necessary, then add successively 2 ml of the hydrochloric acid solution (4.1), 2 ml of the hydroxylammonium chloride solution (4.2) and, after 5 minutes, 5 ml of the ammonium acetate solution (4.3) and 1 ml of the 2.2 bipyridyl solution (4.4). Dilute to the mark, mix and wait 10 minutes.

6.4.3 Spectrophotometric measurement. Carry out the spectrophotometric measurement according to the procedure of clause 6.3.2, adjusting the instrument to zero optical density using as reference the blank test solution (6.2)/standards/sist/5652e71d-3560-49c3-86b6-

a0b2db36ec94/iso-r-909-1968

7. EXPRESSION OF RESULTS

By reference to the calibration chart (see clause 6.3.3), determine the iron content corresponding to the spectrophotometric measurement.

The iron content, expressed as Fe, is given as a percentage, by mass, by the following formula:

$$\frac{A \times 100 \times 100}{V \times E}$$

where

A is the mass, in grammes, of iron determined in the aliquot of sample solution,

V is the volume, in millilitres, of the sample solution taken for the colour reaction,

E is the mass, in grammes, of the test portion.

8. TEST REPORT

Give the following particulars:

- (a) the reference of the method used,
- (b) the results and the method of expression used,
- (c) any unusual features noted during the determination,
- (d) any operation not included in this ISO Recommendation or regarded as optional.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/R 909:1968 https://standards.iteh.ai/catalog/standards/sist/5652e71d-3560-49c3-86b6-a0b2db36ec94/iso-r-909-1968

iTeh STANDARD PREVIEW (standards.iteh.ai)

This page intentionally left blank ISO/R 909:1968

https://standards.iteh.ai/catalog/standards/sist/5652e71d-3560-49c3-86b6-a0b2db36ec94/iso-r-909-1968