



Designation: D7243 – 06a

Standard Guide for Measuring the Saturated Hydraulic Conductivity of Paper Industry Sludges¹

This standard is issued under the fixed designation D7243; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 Paper industry sludges are industrial by-products derived from wastewater treatment operations at plants associated with the manufacturing of paper. These sludges typically consist of clay and organic matter. They may also contain low levels of inorganic and organic contaminants and can be rich in microbes. Traditionally, paper industry sludges have been disposed in municipal solid waste landfills or solid waste monofills. However, in the interest of sustainability, applications are being developed where sludges can be used beneficially. One application is using sludge to construct hydraulic barriers (for example, for use in a landfill cap). Such applications generally require that the hydraulic conductivity of the sludge be measured.

1.2 Compacted paper industry sludges generally behave like soils and are amenable to geotechnical testing methods. However, several of their attributes require special attention during testing. Compacted industry sludges generally are highly compressible due to their organic component. Thus, their hydraulic conductivity can be more sensitive to the effective stress and hydraulic gradient applied during testing than most soils. The microbes in paper sludge can also produce gas during testing, confounding testing methods.

1.3 This guide is intended to supplement ASTM D5084, Test Methods for Measurement of Hydraulic Conductivity of Saturated Porous Materials Using a Flexible Wall Permeameter. The purpose of the guide is to provide additional guidance on issues relevant to testing sludges using Test Methods D5084. The guide applies to specimens compacted in the laboratory using procedures such as those described in Test Methods D698 and D1557 or undisturbed specimens collected from the field using procedures such as Practice D1587 or Practice D7015.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate*

and determine the applicability of regulatory limitations prior to use. This standard contains a hazards section regarding the use of biocides (Section 10).

1.5 *This guide offers an organized collection of information or a series of options and does not recommend a specific course of action. This document cannot replace education or experience and should be used in conjunction with professional judgment. Not all aspects of this guide may be applicable in all circumstances. This ASTM standard is not intended to represent or replace the standard of care by which the adequacy of a given professional service must be judged, nor should this document be applied without consideration of a project's many unique aspects. The word "Standard" in the title of this document means only that the document has been approved through the ASTM consensus process.*

2. Referenced Documents

2.1 ASTM Standards:²

- D653 Terminology Relating to Soil, Rock, and Contained Fluids
- D698 Test Methods for Laboratory Compaction Characteristics of Soil Using Standard Effort (12 400 ft-lbf/ft³ (600 kN-m/m³))
- D1557 Test Methods for Laboratory Compaction Characteristics of Soil Using Modified Effort (56,000 ft-lbf/ft³ (2,700 kN-m/m³))
- D1587 Practice for Thin-Walled Tube Sampling of Soils for Geotechnical Purposes
- D2216 Test Methods for Laboratory Determination of Water (Moisture) Content of Soil and Rock by Mass
- D3740 Practice for Minimum Requirements for Agencies Engaged in Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction
- D5084 Test Methods for Measurement of Hydraulic Conductivity of Saturated Porous Materials Using a Flexible Wall Permeameter
- D7015 Practices for Obtaining Intact Block (Cubical and

¹ This guide is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.04 on Hydrologic Properties and Hydraulic Barriers.

Current edition approved Nov. 1, 2006. Published April 2007. Originally approved in 2006. Last previous edition approved in 2006 as D7243-06. DOI: 10.1520/D7243-06A.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

Cylindrical) Samples of Soils
D7100 Test Method for Hydraulic Conductivity Compatibility Testing of Soils with Aqueous Solutions

3. Terminology

3.1 *Definitions*—For common definitions of other terms in this standard, see Terminology **D653**.

3.1.1 *paper industry sludge*—porous solid material derived from clarification of water during wastewater treatment operations at plants producing paper and similar materials. Also referred to as paper sludge, papermill sludge, fiber clay, paper clay, or sludge.

3.1.2 *head loss, h_L or h* —the change in total head of water across a given distance.

3.1.2.1 *Discussion*—Typically the change in total head is across the influent and effluent lines connected to the permeameter, while the given distance is typically the length of the test specimen.

3.1.3 *permeameter*—the apparatus (cell) containing the test specimen in a hydraulic conductivity test.

3.1.3.1 *Discussion*—The apparatus in this case is typically a triaxial-type cell with all of its components (top and bottom specimen caps, stones, and filter paper; membrane; chamber; top and bottom plates; valves; etc.). However, the cell generally does not have a loading piston.

3.1.4 *hydraulic conductivity, k* —the rate of discharge of water under laminar flow conditions through a unit cross-sectional area of porous medium under a unit hydraulic gradient and standard temperature conditions (20°C).

3.1.4.1 *Discussion*—The term *coefficient of permeability* (or *permeability*) is often used instead of *hydraulic conductivity*, but *hydraulic conductivity* is used exclusively in this standard. These terms are synonymous.

4. Significance and Use

4.1 This guide is intended to supplement the methods and procedures described in Test Methods **D5084**. When following the recommendations in this guide to test paper sludges, all assumptions and limitations described in Test Methods **D5084** apply.

4.2 This guide only applies to hydraulic conductivity tests on paper industry sludges where one-dimensional laminar flow of water is imposed using a flexible-wall permeameter.

4.3 The hydraulic conductivity of sludges, and other porous materials, generally decreases as the degree of water saturation decreases. This guide applies only to water-saturated sludge containing negligible amounts of gas.

4.4 This guide applies only to permeation of paper industry sludges with water. Information on testing porous materials with liquids other than water can be found in Test Method **D7100**.

4.5 The hydraulic conductivity of paper sludge measured in the laboratory following Test Methods **D5084** and the recommendations in this guide may or may not be comparable to the hydraulic conductivity of in-place sludge. The issue has not been fully investigated. Therefore, the results should be applied to field situations with caution and by qualified personnel.

NOTE 1—The quality of the result produced when using the recommen-

dations in this guide depends on the competence of the personnel performing the testing and the suitability of the equipment and facilities that are employed. Agencies that meet the criteria of Practice **D3740** are generally considered capable of competent and objective testing, sampling, inspection, etc. Users of this guide are cautioned that compliance with Practice **D3740** does not in itself ensure reliable results. Reliable results depend on many factors; Practice **D3740** provides a means of evaluating some of those factors.

5. Reagents

5.1 *Permeant Water:*

5.1.1 Selection of the permeant water should follow the instructions in Section 6 of Test Methods **D5084**. Comparative testing has been conducted to assess whether the hydraulic conductivity of sludge is sensitive to the type of water used for testing. Tests conducted by Nelson and Benson³ indicate that essentially the same hydraulic conductivity is obtained if hydraulic conductivity tests on paper sludge are conducted with tap water, deionized water, 0.005 M CaCl₂, 0.01 M CaCl₂, or 0.01 M CaSO₄. These permeant waters should be considered equivalent when testing paper sludge.

5.1.2 In some cases, a biocide may be added to the permeant water to prevent generation of gases associated with microbial activity. Testing conducted previously³ suggests that biocides do not alter the hydraulic conductivity of paper sludges when used at concentrations recommended by the manufacturer. However, comprehensive testing has not been conducted to assess how all biocides affect the hydraulic conductivity of paper sludges (for example, through chemical interactions with the solid phase). If chemical interactions are a concern, an assessment can be made with side-by-side testing using an alternative method to prevent gas generation.

6. Procedures to Minimize Gas Generation

6.1 Gases generated by microbial activity can confound hydraulic conductivity testing of paper sludges. Indications of gas generation include: (1) inability to meet the termination criteria in Test Methods **D5084** for steady hydraulic conductivity and continuity (section 9.5 in Test Methods **D5084**), (2) flow in the influent system in the opposite direction of the applied hydraulic gradient, and (3) outflow much greater than inflow. This section describes how to deal with gas generation.

6.2 Gas generation can be minimized or eliminated by preventing or minimizing microbial activity or by applying elevated backpressure.

6.2.1 Microbial activity can be minimized by temperature control or through the use of biocides.

6.2.1.1 Temperature control consists of placing the permeameter containing the test specimen in a chamber where the temperature is greater than 0°C and no more than 4°C. A kitchen refrigerator works well for this purpose. The temperature of the chamber should be controlled to within ±1°C and must be maintained above 0°C at all times. At lower temperatures, the effects of temperature on the viscosity and density of

³ Nelson, M., and Benson, C., "Laboratory Hydraulic Conductivity Testing Protocols for Paper Sludges Used for Hydraulic Barriers," *Technical Bulletin No. 848*, National Council for Air and Stream Improvement, Research Triangle Park, NC, 2002.