
**Information technology — Open Systems
Interconnection — The Directory:
Selected attribute types**

*Technologies de l'information — Interconnexion de systèmes ouverts
(OSI) — L'annuaire: Types d'attributs sélectionnés*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 9594-6:2008](https://standards.iteh.ai/catalog/standards/sist/969648af-2440-4886-bfc9-8dcc61240d1a/iso-iec-9594-6-2008)

<https://standards.iteh.ai/catalog/standards/sist/969648af-2440-4886-bfc9-8dcc61240d1a/iso-iec-9594-6-2008>

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 9594-6:2008](https://standards.iteh.ai/catalog/standards/sist/969648af-2440-4886-bfc9-8dcc61240d1a/iso-iec-9594-6-2008)

<https://standards.iteh.ai/catalog/standards/sist/969648af-2440-4886-bfc9-8dcc61240d1a/iso-iec-9594-6-2008>



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published by ISO in 2009

Published in Switzerland

CONTENTS

	<i>Page</i>
Foreword	v
Introduction	vi
SECTION 1 – GENERAL	1
1 Scope	1
2 Normative references	1
2.1 Identical Recommendations International Standards	1
2.2 Other references	2
2.3 ISO/IEC Standards	2
3 Definitions	3
4 Abbreviations	3
5 Conventions	3
SECTION 2 – SELECTED ATTRIBUTE TYPES	4
6 Definition of selected attribute types	4
6.1 System attribute types	4
6.2 Labelling attribute types	4
6.3 Geographical Attribute Types	7
6.4 Organizational attribute types	8
6.5 Explanatory attribute types	9
6.6 Postal Addressing attribute types	10
6.7 Telecommunications Addressing attribute types	12
6.8 Preferences attribute types	15
6.9 OSI Application attribute types	15
6.10 Relational attribute types	16
6.11 Domain attribute types	17
6.12 Attributes applications using tag-based identification	17
6.13 Notification attributes	18
SECTION 3 – MATCHING RULES	23
7 String preparation	23
7.1 Transcode	23
7.2 Map	23
7.3 Normalize	23
7.4 Prohibit	23
7.5 Check bidi	24
7.6 Insignificant Character Removal	24
8 Definition of matching rules	24
8.1 String matching rules	24
8.2 Syntax-based matching rules	27
8.3 Time matching rules	30
8.4 First component matching rules	31
8.5 Word matching rules	31
8.6 Approximate Matching Rules	34
8.7 Special Matching Rules	34
8.8 Zonal Match	34
SECTION 4 – CONTEXTS	38
9 Definition of Context Types	38
9.1 Language Context	38
9.2 Temporal Context	38
9.3 Locale Context	41
9.4 LDAP Attribute Option Context	41

	<i>Page</i>
Annex A – Selected attribute types in ASN.1.....	43
Annex B – Summary of attribute types	61
Annex C – Upper bounds.....	62
Annex D – Alphabetical index of attributes, matching rules and contexts	63
Annex E – Examples for zonal match matching rules	65
Annex F – ASN.1 module from ITU-T Rec. X.660 ISO/IEC 9834-1	67
Annex G – Tag-based applications as they relate to these Directory Specifications	68
G.1 The concept of a tag-based application	68
G.2 RFID example	68
G.3 DIT structure for entries representing object identifier components	70
Annex H – Amendments and corrigenda.....	72

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 9594-6:2008](https://standards.iteh.ai/catalog/standards/sist/969648af-2440-4886-bfc9-8dcc61240d1a/iso-iec-9594-6-2008)
<https://standards.iteh.ai/catalog/standards/sist/969648af-2440-4886-bfc9-8dcc61240d1a/iso-iec-9594-6-2008>

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 9594-6:2008 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology, Subcommittee SC 6, Telecommunications and information exchange between systems*, in collaboration with ITU-T. The identical text is published as ITU-T Rec. X.520 (11/2008).

This sixth edition cancels and replaces the fifth edition (ISO/IEC 9594-6:2005), which has been technically revised.

[ISO/IEC 9594-6:2008](https://standards.iteh.ai/catalog/standards/sist/969648ef-2440-4886-bf9-8dccc61240d1a/iso-iec-9594-6-2008)

ISO/IEC 9594 consists of the following parts, under the general title *Information technology — Open Systems Interconnection — The Directory*:

- *Part 1: Overview of concepts, models and services*
- *Part 2: Models*
- *Part 3: Abstract service definition*
- *Part 4: Procedures for distributed operation*
- *Part 5: Protocol specifications*
- *Part 6: Selected attribute types*
- *Part 7: Selected object classes*
- *Part 8: Public-key and attribute certificate frameworks*
- *Part 9: Replication*
- *Part 10: Use of systems management for administration of the Directory*

Introduction

This Recommendation | International Standard, together with other Recommendations | International Standards, has been produced to facilitate the interconnection of information processing systems to provide directory services. A set of such systems, together with the directory information that they hold, can be viewed as an integrated whole, called the *Directory*. The information held by the Directory, collectively known as the Directory Information Base (DIB), is typically used to facilitate communication between, with or about objects such as application entities, people, terminals, and distribution lists.

The Directory plays a significant role in Open Systems Interconnection, whose aim is to allow, with a minimum of technical agreement outside of the interconnection standards themselves, the interconnection of information processing systems:

- from different manufacturers;
- under different managements;
- of different levels of complexity; and
- of different ages.

This Recommendation | International Standard defines a number of attribute types which may be found useful across a range of applications of the Directory, as well as a number of standard attribute syntaxes and matching rules. One particular use for many of the attributes defined herein is in the formation of names, particularly for the classes of object defined in ITU-T Rec. X.521 | ISO/IEC 9594-7.

This Recommendation | International Standard provides the foundation frameworks upon which industry profiles can be defined by other standards groups and industry forums. Many of the features defined as optional in these frameworks may be mandated for use in certain environments through profiles. This sixth edition technically revises and enhances, but does not replace, the fifth edition of this Recommendation | International Standard. Implementations may still claim conformance to the fifth edition. However, at some point, the fifth edition will not be supported (i.e., reported defects will no longer be resolved). It is recommended that implementations conform to this sixth edition as soon as possible.

This sixth edition specifies versions 1 and 2 of the Directory protocols.

The first and second editions specified only version 1. Most of the services and protocols specified in this edition are designed to function under version 1. However some enhanced services and protocols, e.g., signed errors, will not function unless all Directory entities involved in the operation have negotiated version 2. Whichever version has been negotiated, differences between the services and between the protocols defined in the six editions, except for those specifically assigned to version 2, are accommodated using the rules of extensibility defined in ITU-T Rec. X.519 | ISO/IEC 9594-5.

Annex A, which is an integral part of this Recommendation | International Standard, provides the ASN.1 notation for the complete module which defines the attributes, attribute syntaxes, and matching rules.

Annex B, which is not an integral part of this Recommendation | International Standard, provides a table of attribute types, for easy reference.

Annex C, which is not an integral part of this Recommendation | International Standard, provides an example of upper bounds value constraints.

Annex D, which is not an integral part of this Recommendation | International Standard, lists alphabetically the attributes and matching rules defined in this Directory Specification.

Annex E, which is not an integral part of this Recommendation | International Standard, gives examples relevant to the definition of zonal matching.

Annex F, which is not an integral part of this Recommendation | International Standard, provides a copy of an ASN.1 module specified in ITU-T Rec. X.660 | ISO/IEC 9834-1.

Annex G, which is not an integral part of this Recommendation | International Standard, provides a short tutorial on ID-based applications.

Annex H, which is not an integral part of this Recommendation | International Standard, lists the amendments and defect reports that have been incorporated to form this edition of this Recommendation | International Standard.

**INTERNATIONAL STANDARD
ITU-T RECOMMENDATION**

**Information technology – Open Systems Interconnection –
The Directory: Selected attribute types**

SECTION 1 – GENERAL

1 Scope

This Recommendation | International Standard defines a number of attribute types and matching rules which may be found useful across a range of applications of the Directory.

Attribute types and matching rules fall into three categories, as described below.

Some attribute types and matching rules are used by a wide variety of applications or are understood and/or used by the Directory itself.

NOTE – It is recommended that an attribute type or matching rule defined in this Recommendation | International Standard be used, in preference to the generation of a new one, whenever it is appropriate for the application.

Some attribute types and matching rules are internationally standardized, but are application-specific. These are defined in the standards associated with the application concerned.

Any administrative authority can define its own attribute types and matching rules for any purpose. These are not internationally standardized, and are available to others beyond the administrative authority which created them only by bilateral agreement.

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

2 Normative references

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

2.1 Identical Recommendations | International Standards

- ITU-T Recommendation X.200 (1994) | ISO/IEC 7498-1:1994, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model.*
- ITU-T Recommendation X.500 (2008) | ISO/IEC 9594-1:2008, *Information technology – Open Systems Interconnection – The Directory: Overview of concepts, models and services.*
- ITU-T Recommendation X.501 (2008) | ISO/IEC 9594-2:2008, *Information technology – Open Systems Interconnection – The Directory: Models.*
- ITU-T Recommendation X.509 (2008) | ISO/IEC 9594-8:2008, *Information technology – Open Systems Interconnection – The Directory: Public-key and attribute certificate frameworks.*
- ITU-T Recommendation X.511 (2008) | ISO/IEC 9594-3:2008, *Information technology – Open Systems Interconnection – The Directory: Abstract service definition.*
- ITU-T Recommendation X.518 (2008) | ISO/IEC 9594-4:2008, *Information technology – Open Systems Interconnection – The Directory: Procedures for distributed operation.*
- ITU-T Recommendation X.519 (2008) | ISO/IEC 9594-5:2008, *Information technology – Open Systems Interconnection – The Directory: Protocol specifications.*
- ITU-T Recommendation X.521 (2008) | ISO/IEC 9594-7:2008, *Information technology – Open Systems Interconnection – The Directory: Selected object classes.*
- ITU-T Recommendation X.525 (2008) | ISO/IEC 9594-9:2008, *Information technology – Open Systems Interconnection – The Directory: Replication.*

- ITU-T Recommendation X.530 (2008) | ISO/IEC 9594-10:2008, *Information technology – Open Systems Interconnection – The Directory: Use of systems management for administration of the Directory.*
- ITU-T Recommendation X.660 (2008) | ISO/IEC 9834-1:2008, *Information technology – Open Systems Interconnection – Procedures for the operation of OSI Registration Authorities: General procedures and top arcs of the ASN.1 Object Identifier tree.*
- ITU-T Recommendation X.667 (2008) | ISO/IEC 9834-8:2008, *Information technology – Open Systems Interconnection – Procedures for the operation of OSI Registration Authorities: Generation and registration of Universally Unique Identifiers (UUIDs) and their use as ASN.1 object identifier components.*
- ITU-T Recommendation X.668 (2008) | ISO/IEC 9834-9:2008, *Information technology – Open Systems Interconnection – Procedures for the operation of OSI Registration Authorities: Registration of object identifier arcs for applications and services using tag-based identification.*
- ITU-T Recommendation X.680 (2008) | ISO/IEC 8824-1:2008, *Information technology – Abstract Syntax Notation One (ASN.1): Specification of basic notation.*
- ITU-T Recommendation X.681 (2008) | ISO/IEC 8824-2:2008, *Information technology – Abstract Syntax Notation One (ASN.1): Information object specification.*
- ITU-T Recommendation X.682 (2008) | ISO/IEC 8824-3:2008, *Information technology – Abstract Syntax Notation One (ASN.1): Constraint specification.*
- ITU-T Recommendation X.683 (2008) | ISO/IEC 8824-4:2008, *Information technology – Abstract Syntax Notation One (ASN.1): Parameterization of ASN.1 specifications.*

2.2 Other references

- ITU-T Recommendation E.123 (2001), *Notation for national and international telephone numbers, e-mail addresses and Web addresses.*
- ITU-T Recommendation E.164 (2005), *The international public telecommunication numbering plan.*
- ITU-T Recommendation F.1 (1998), *Operational provisions for the international public telegram service.*
- CCITT Recommendation F.31 (1988), *Telegram retransmission system.*
- CCITT Recommendation F.401 (1992), *Message handling services: Naming and addressing for public message handling services.*
- ITU-T Recommendation T.30 (2005), *Procedures for document facsimile transmission in the general switched telephone network.*
- ITU-T Recommendation T.62 (1993), *Control procedures for teletex and Group 4 facsimile services.*
- ITU-T Recommendation X.121 (2000), *International numbering plan for public data networks.*
- ITU-T Recommendation Y.2213 (2008), *NGN service requirements and capabilities for network aspects of applications and services using tag-based identification.*
- ISO 3166-1:2006, *Codes for the representation of names of countries and their subdivisions – Part 1: Country codes.*
- ISO 3166-3:2006, *Codes for the representation of names of countries and their subdivisions – Part 3: Code for formerly used names of countries.*
- ISO 639-2:1998, *Codes for the representation of names of languages – Part 2: Alpha-3 code.*
- ISO/IEC 9945-3:2003, *Information technology – Portable Operating System Interface (POSIX) – Part 3: Shell and Utilities.*
- IETF RFC 3377 (2002), *Lightweight Directory Access Protocol (v3): Technical Specification.*
- IETF RFC 3454 (2002), *Preparation of Internationalized Strings (stringprep).*
- The Unicode Consortium. *The Unicode Standard, Version 4.0*, defined by: *The Unicode Standard, Version 4.0* (Reading, MA, Addison-Wesley, 2003. ISBN 0-321-18578-1).
- *Unicode Standard Annex #15: Unicode Normalization Forms*, by Mark Davis and Martin Dürst. An integral part of *The Unicode Standard, Version 4.0*.

2.3 ISO/IEC Standards

- ISO/IEC 10646:2003, *Information technology – Universal Multiple-Octet Coded Character Set (UCS).*

3 Definitions

For the purposes of this Recommendation | International Standard, the following definitions apply:

The following terms are defined in ITU-T Rec. X.501 | ISO/IEC 9594-2:

- a) *attribute type*;
- b) *object class*;
- c) *matching rule*;
- d) *context*.

4 Abbreviations

For the purposes of this Recommendation | International Standard, the following abbreviations apply:

LDAP	Lightweight Directory Access Protocol
RFID	Radio Frequency Identification
UII	Unique Item Identifier
URL	Uniform Resource Locator
URN	Uniform Resource Name
UUID	Universally Unique Identifier

5 Conventions

The term "Directory Specification" (as in "this Directory Specification") shall be taken to mean ITU-T Rec. X.520 | ISO/IEC 9594-6. The term "Directory Specifications" shall be taken to mean the X.500-series Recommendations and all parts of ISO/IEC 9594.

This Directory Specification uses the term *first edition systems* to refer to systems conforming to the first edition of the Directory Specifications, i.e., the 1988 edition of the series of CCITT X.500 Recommendations and the ISO/IEC 9594:1990 edition.

This Directory Specification uses the term *second edition systems* to refer to systems conforming to the second edition of the Directory Specifications, i.e., the 1993 edition of the series of ITU-T X.500 Recommendations and the ISO/IEC 9594:1995 edition.

This Directory Specification uses the term *third edition systems* to refer to systems conforming to the third edition of the Directory Specifications, i.e., the 1997 edition of the series of ITU-T X.500 Recommendations and the ISO/IEC 9594:1998 edition.

This Directory Specification uses the term *fourth edition systems* to refer to systems conforming to the fourth edition of the Directory Specifications, i.e., the 2001 editions of ITU-T Recs X.500, X.501, X.511, X.518, X.519, X.520, X.521, X.525, and X.530, the 2000 edition of ITU-T Rec. X.509, and parts 1-10 of the ISO/IEC 9594:2001 edition.

This Directory Specification uses the term *fifth edition systems* to refer to systems conforming to the fifth edition of the Directory Specifications, i.e., the 2005 edition of the series of ITU-T X.500 Recommendations and the ISO/IEC 9594:2005 edition.

This Directory Specification uses the term *sixth edition systems* to refer to systems conforming to the sixth edition of the Directory Specifications, i.e., the 2008 edition of the series of ITU-T X.500 Recommendations and the ISO/IEC 9594:2008 edition.

This Directory Specification presents ASN.1 notation in the bold Helvetica typeface. When ASN.1 types and values are referenced in normal text, they are differentiated from normal text by presenting them in the bold Helvetica typeface. The names of procedures, typically referenced when specifying the semantics of processing, are differentiated from normal text by displaying them in bold Times. Access control permissions are presented in italicized Times.

If the items in a list are numbered (as opposed to using "-" or letters), then the items shall be considered steps in a procedure.

Attribute types, matching rules and context types are defined in this Recommendation | International Standard by use of the **ATTRIBUTE**, **MATCHING-RULE** and **CONTEXT** information object classes defined in ITU-T Rec. X.501 | ISO/IEC 9594-2.

Examples of the use of the attribute types are described using an informal notation, where attribute type and value pairs are represented by an acronym for the attribute type, followed by an equals sign ("="), followed by the example value for the attribute.

SECTION 2 – SELECTED ATTRIBUTE TYPES

6 Definition of selected attribute types

This Directory Specification defines a number of attribute types which may be found useful across a range of applications of the Directory.

Many of the attribute types defined in this Directory Specification are based on a common ASN.1 syntax:

```
UnboundedDirectoryString ::= CHOICE {
    teletexString      TeletexString (SIZE(1..MAX)),
    printableString    PrintableString (SIZE (1..MAX)),
    bmpString          BMPString (SIZE (1..MAX)),
    universalString    UniversalString (SIZE (1..MAX)),
    utf8String         UTF8String (SIZE (1..MAX)) }
```

A few attribute types are based on the following syntax:

```
DirectoryString { INTEGER : maxSize } ::= CHOICE {
    teletexString      TeletexString (SIZE (1..maxSize)),
    printableString    PrintableString (SIZE (1..maxSize)),
    bmpString          BMPString (SIZE (1..maxSize)),
    universalString    UniversalString (SIZE (1..maxSize)),
    utf8String         UTF8String (SIZE (1..maxSize)) }
```

NOTE – The above syntaxes are also used in other parts of these Directory Specifications.

Some implementations of the Directory may not support **UniversalString**, **BMPString**, or **UTF8String**, and may not be able to generate, match, shadow, or display attributes with these syntax types.

6.1 System attribute types

6.1.1 Knowledge Information

The *Knowledge Information* attribute type specifies a human readable accumulated description of knowledge mastered by a specific DSA.

NOTE – This attribute is now obsolete.

```
knowledgeInformation ATTRIBUTE ::= {
    WITH SYNTAX          UnboundedDirectoryString
    EQUALITY MATCHING RULE caselgnoreMatch
    ID                   id-at-knowledgeInformation }
```

6.2 Labelling attribute types

These attributes type are concerned with information about objects which has been explicitly associated with the objects by a labelling process.

6.2.1 Name

The *Name* attribute type is the attribute supertype from which string attribute types typically used for naming may be formed.

```
name ATTRIBUTE ::= {
    WITH SYNTAX          UnboundedDirectoryString
    EQUALITY MATCHING RULE caselgnoreMatch
    SUBSTRINGS MATCHING RULE caselgnoreSubstringsMatch
    ID                   id-at-name }
```

6.2.2 Common Name

The *Common Name* attribute type specifies an identifier of an object. A Common Name is not a directory name; it is a (possibly ambiguous) name by which the object is commonly known in some limited scope (such as an organization) and conforms to the naming conventions of the country or culture with which it is associated.

An attribute value for common name is a string chosen either by the person or organization it describes or the organization responsible for the object it describes for devices and application entities. For example, a typical name of a person in an English-speaking country comprises a personal title (e.g., Mr., Ms., Rd, Professor, Sir, Lord), a first name, middle name(s), last name, generation qualifier (if any, e.g., Jr.) and decorations and awards (if any, e.g., QC).

Examples

CN = "Mr. Robin Lachlan McLeod BSc(Hons) CEng MIEE";

CN = "Divisional Coordination Committee";

CN = "High Speed Modem".

Any variants should be associated with the named object as separate and alternative attribute values.

Other common variants should also be admitted, e.g., use of a middle name as a preferred first name; use of "Bill" in place of "William", etc.

```
commonName ATTRIBUTE ::= {
    SUBTYPE OF          name
    WITH SYNTAX         UnboundedDirectoryString
    ID                  id-at-commonName }
```

6.2.3 Surname

The *Surname* attribute type specifies the linguistic construct which normally is inherited by an individual from the individual's parent or assumed by marriage, and by which the individual is commonly known.

An attribute value for Surname is a string, e.g., "McLeod".

```
surname ATTRIBUTE ::= {
    SUBTYPE OF          name
    WITH SYNTAX         UnboundedDirectoryString
    ID                  id-at-surname }
```

6.2.4 Given Name

The *Given Name* attribute type specifies the linguistic construct which is normally given to an individual by the individual's parent, or is chosen by the individual, or by which the individual is commonly known.

An attribute value for Given Name is a string, e.g., "David", or "Jean Paul".

```
givenName ATTRIBUTE ::= {
    SUBTYPE OF          name
    WITH SYNTAX         UnboundedDirectoryString
    ID                  id-at-givenName }
```

6.2.5 Initials

The *Initials* attribute type contains the initials of some or all of an individual's names, but not the surname(s).

An attribute value for Initials is a string, e.g., "D" or "D." or "J.P.".

```
initials ATTRIBUTE ::= {
    SUBTYPE OF          name
    WITH SYNTAX         UnboundedDirectoryString
    ID                  id-at-initials }
```

6.2.6 Generation Qualifier

The *Generation Qualifier* attribute type contains a string which is used to provide generation information to qualify an individual's name.

An attribute value for Generation Qualifier is a string, e.g., "Jr." or "II".

```
generationQualifier ATTRIBUTE ::= {
    SUBTYPE OF                               name
    WITH SYNTAX                               UnboundedDirectoryString
    ID                                         id-at-generationQualifier }
```

6.2.7 Unique Identifier

The *Unique Identifier* attribute type specifies an identifier which may be used to distinguish between object references when a distinguished name has been reused. It may be, for example, an encoded object identifier, certificate, date, timestamp, or some other form of certification on the validity of the distinguished name.

An attribute value for Unique Identifier is a bit string.

```
uniqueIdentifier ATTRIBUTE ::= {
    WITH SYNTAX                               UniquelIdentifier
    EQUALITY MATCHING RULE                   bitStringMatch
    ID                                       id-at-uniqueIdentifier }
```

UniquelIdentifier ::= BIT STRING

6.2.8 DN Qualifier

The *DN Qualifier* attribute type specifies disambiguating information to add to the relative distinguished name of an entry. It is intended to be used for entries held in multiple DSAs which would otherwise have the same name, and that its value be the same in a given DSA for all entries to which this information has been added.

```
dnQualifier ATTRIBUTE ::= {
    WITH SYNTAX                               PrintableString
    EQUALITY MATCHING RULE                   caseIgnoreMatch
    ORDERING MATCHING RULE                   caseIgnoreOrderingMatch
    SUBSTRINGS MATCHING RULE                 caseIgnoreSubstringsMatch
    ID                                       id-at-dnQualifier }
```

6.2.9 Serial Number

The *Serial Number* attribute type specifies an identifier, the serial number of an object.

An attribute value for Serial Number is a printable string.

```
serialNumber ATTRIBUTE ::= {
    WITH SYNTAX                               PrintableString (SIZE (1..MAX))
    EQUALITY MATCHING RULE                   caseIgnoreMatch
    SUBSTRINGS MATCHING RULE                 caseIgnoreSubstringsMatch
    ID                                       id-at-serialNumber }
```

6.2.10 Pseudonym

The *Pseudonym* attribute type specifies a pseudonym for an object. It is used for naming an object when it is to be made clear that its name is a pseudonym.

```
pseudonym ATTRIBUTE ::= {
    SUBTYPE OF                               name
    WITH SYNTAX                               UnboundedDirectoryString
    ID                                         id-at-pseudonym }
```

6.2.11 Universal Unique Identifier Pair

The *Universal Unique Identifier Pair* attribute type specifies a pair of Universal Unique Identifiers (UUID), as specified in ITU-T Rec. X.667 | ISO/IEC 9834-8. The pair collectively represents an issuer/subject relationship, the nature of which is outside the scope of this Directory Specification. The initial UUID in the pair represents the issuer, and the trailing UUID in the pair represents the subject of the issuer/subject relationship. An example of such a relationship is a user account.

```
uUIDPair ATTRIBUTE ::= {
    WITH SYNTAX                               UUIDPair
    EQUALITY MATCHING RULE                   uUIDPairMatch
    ID                                       id-at-uuidpair }
```

```

UUIDPair ::= SEQUENCE {
    issuerUUID    UUID,
    subjectUUID   UUID }

```

```

UUID ::= OCTET STRING (SIZE(16))    -- UUID format only

```

6.3 Geographical Attribute Types

These attribute types are concerned with geographical positions or regions with which objects are associated.

6.3.1 Country Name

The *Country Name* attribute type specifies a country. When used as a component of a directory name, it identifies the country in which the named object is physically located or with which it is associated in some other important way.

An attribute value for country name is a string chosen from ISO 3166-1 alpha-2 or ISO 3166-3 alpha-2.

```

countryName ATTRIBUTE ::= {
    SUBTYPE OF          name
    WITH SYNTAX         CountryName
    SINGLE VALUE       TRUE
    ID                  id-at-countryName }

```

```

CountryName ::= PrintableString (SIZE(2))    -- ISO 3166-1/3 alpha-2 codes only

```

6.3.2 Locality Name

The *Locality Name* attribute type specifies a locality. When used as a component of a directory name, it identifies a geographical area or locality in which the named object is physically located or with which it is associated in some other important way.

An attribute value for Locality Name is a string, e.g., L = "Edinburgh".

```

localityName ATTRIBUTE ::= {
    SUBTYPE OF          name
    WITH SYNTAX         UnboundedDirectoryString
    ID                  id-at-localityName }

```

The *Collective Locality Name* attribute type specifies a locality name for a collection of entries.

```

collectiveLocalityName ATTRIBUTE ::= {
    SUBTYPE OF          localityName
    COLLECTIVE         TRUE
    ID                  id-at-collectiveLocalityName }

```

6.3.3 State or Province Name

The *State or Province Name* attribute type specifies a state or province. When used as a component of a directory name, it identifies a geographical subdivision in which the named object is physically located or with which it is associated in some other important way.

An attribute value for State or Province Name is a string, e.g., S = "Ohio".

```

stateOrProvinceName ATTRIBUTE ::= {
    SUBTYPE OF          name
    WITH SYNTAX         UnboundedDirectoryString
    ID                  id-at-stateOrProvinceName }

```

The *Collective State or Province Name* attribute type specifies a state or province name for a collection of entries.

```

collectiveStateOrProvinceName ATTRIBUTE ::= {
    SUBTYPE OF          stateOrProvinceName
    COLLECTIVE         TRUE
    ID                  id-at-collectiveStateOrProvinceName }

```

6.3.4 Street Address

The *Street Address* attribute type specifies a site for the local distribution and physical delivery in a postal address, i.e., the street name, place, avenue, and the house number. When used as a component of a directory name, it identifies the street address at which the named object is located or with which it is associated in some other important way.

An attribute value for Street Address is a string, e.g., "Arnulfstraße 60".

```
streetAddress ATTRIBUTE ::= {
    WITH SYNTAX                               UnboundedDirectoryString
    EQUALITY MATCHING RULE                   caselgnoreMatch
    SUBSTRINGS MATCHING RULE                 caselgnoreSubstringsMatch
    ID                                        id-at-streetAddress }
```

The *Collective Street Address* attribute type specifies a street address for a collection of entries.

```
collectiveStreetAddress ATTRIBUTE ::= {
    SUBTYPE OF                               streetAddress
    COLLECTIVE                               TRUE
    ID                                        id-at-collectiveStreetAddress }
```

6.3.5 House Identifier

The *House Identifier* attribute type specifies a linguistic construct used to identify a particular building, for example a house number or house name relative to a street, avenue, town or city, etc.

An attribute value for House Identifier is a string, e.g., "14".

```
houseIdentifier ATTRIBUTE ::= {
    WITH SYNTAX                               UnboundedDirectoryString
    EQUALITY MATCHING RULE                   caselgnoreMatch
    SUBSTRINGS MATCHING RULE                 caselgnoreSubstringsMatch
    ID                                        id-at-houseIdentifier }
```

6.4 Organizational attribute types

These attribute types are concerned with organizations and can be used to describe objects in terms of organizations with which they are associated.

6.4.1 Organization Name

The *Organization Name* attribute type specifies an organization. When used as a component of a directory name, it identifies an organization with which the named object is affiliated.

An attribute value for **OrganizationName** is a string chosen by the organization (e.g., O = "Scottish Telecommunications plc"). Any variants should be associated with the named Organization as separate and alternative attribute values.

```
organizationName ATTRIBUTE ::= {
    SUBTYPE OF                               name
    WITH SYNTAX                               UnboundedDirectoryString
    ID                                        id-at-organizationName }
```

The *Collective Organization Name* attribute type specifies an organization name for a collection of entries.

```
collectiveOrganizationName ATTRIBUTE ::= {
    SUBTYPE OF                               organizationName
    COLLECTIVE                               TRUE
    ID                                        id-at-collectiveOrganizationName }
```

6.4.2 Organizational Unit Name

The *Organizational Unit Name* attribute type specifies an organizational unit. When used as a component of a directory name, it identifies an organizational unit with which the named object is affiliated.

The designated organizational unit is understood to be part of an organization designated by an **organizationName** attribute. It follows that if an Organizational Unit Name attribute is used in a directory name, it shall be associated with an **organizationName** attribute.

An attribute value for Organizational Unit Name is a string chosen by the organization of which it is part (e.g., OU = "Technology Division"). Note that the commonly used abbreviation "TD" would be a separate and alternative attribute value.

Example

O = "Scottel", OU = "TD"

```

organizationalUnitName ATTRIBUTE ::= {
    SUBTYPE OF
    WITH SYNTAX
    ID
    name
    UnboundedDirectoryString
    id-at-organizationalUnitName }

```

The *Collective Organizational Unit Name* attribute type specifies an organizational unit name for a collection of entries.

```

collectiveOrganizationalUnitName ATTRIBUTE ::= {
    SUBTYPE OF
    COLLECTIVE
    ID
    organizationalUnitName
    TRUE
    id-at-collectiveOrganizationalUnitName }

```

6.4.3 Title

The *Title* attribute type specifies the designated position or function of the object within an organization.

An attribute value for Title is a string.

Example

T = "Manager, Distributed Applications"

```

title ATTRIBUTE ::= {
    SUBTYPE OF
    WITH SYNTAX
    ID
    name
    UnboundedDirectoryString
    id-at-title }

```

6.5 Explanatory attribute types

These attribute types are concerned with explanations (e.g., in a natural language) of something about an object.

6.5.1 Description

The *Description* attribute type specifies text that describes the associated object.

For example, the object "Standards Interest" might have the associated description "distribution list for exchange of information about intra-company standards development".

An attribute value for Description is a string.

```

description ATTRIBUTE ::= {
    WITH SYNTAX
    EQUALITY MATCHING RULE
    SUBSTRINGS MATCHING RULE
    ID
    UnboundedDirectoryString
    caseIgnoreMatch
    caseIgnoreSubstringsMatch
    id-at-description }

```

6.5.2 Search Guide

The *Search Guide* attribute type specifies information of suggested search criteria which may be included in some entries expected to be a convenient base-object for the search operation, e.g., country or organization.

Search criteria consist of an optional identifier for the type of object sought and combinations of attribute types and logical operators to be used in the construction of a filter. It is possible to specify for each search criteria item the matching level, e.g., approximate match.

The Search Guide attribute may recur to reflect the various types of requests, e.g., search for a Residential Person or an Organizational Person, which may be fulfilled from the given base-object where the Search Guide is read.

```

searchGuide ATTRIBUTE ::= {
    WITH SYNTAX
    ID
    Guide
    id-at-searchGuide }

```

```

Guide ::= SET {
    objectClass [0] OBJECT-CLASS.&id OPTIONAL,
    criteria [1] Criteria }

```

```

Criteria ::= CHOICE {
    type [0] Criterialtem,
    and [1] SET OF Criteria,
    or [2] SET OF Criteria,
    not [3] Criteria }

```