

SLOVENSKI STANDARD
SIST EN 303 402 V2.1.2:2017

01-november-2017

Pomorski mobilni oddajniki in sprejemniki za uporabo v radiofrekvenčnih pasovih MF in HF - Harmonizirani standard, ki zajema bistvene zahteve členov 3.2 in 3.3(g) direktive 2014/53/EU

Maritime mobile transmitters and receivers for use in the MF and HF bands -
Harmonised Standard covering the essential requirements of articles 3.2 and 3.3(g) of
Directive 2014/53/EU

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 303 402 V2.1.2:2017](#)

<https://standards.iteh.ai/catalog/standards/sist/f9e5b4e2-2c91-4456-9ae0-8a2b339fc19/sist-en-303-402-v2-1-2-2017>

Ta slovenski standard je istoveten z: ETSI EN 303 402 V2.1.2 (2017-09)

ICS:

| | | |
|-----------|--------------------------------|--------------------------------------|
| 33.060.20 | Sprejemna in oddajna oprema | Receiving and transmitting equipment |
| 47.020.70 | Navigacijska in krmilna oprema | Navigation and control equipment |

SIST EN 303 402 V2.1.2:2017

en

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 303 402 V2.1.2:2017

<https://standards.iteh.ai/catalog/standards/sist/f9e5b4e2-2e91-4456-9ae0-8a2b339f3c19/sist-en-303-402-v2-1-2-2017>

ETSI EN 303 402 v2.1.2 (2017-09)



**Maritime mobile transmitters and receivers
for use in the MF and HF bands;
Harmonised Standard covering the essential requirements
of articles 3.2 and 3.3(g) of Directive 2014/53/EU**

STANDARD PREVIEW
SIST EN 303 402 V2.1.2:2017
<https://standards.iteh.ai/catalog/standards/sist/f9e5b4e2-2e91-4456-9ae0-8a2b339f3c19/sist-en-303-402-v2-1-2-2017>

Reference

REN/ERM-TG26-520C1

Keywords

harmonised standard, maritime, radio, regulation,
telephony***ETSI***650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse 06 N° 7303/88**iTeh STANDARD PREVIEW**
(standards.iteh.ai)***Important notice***SIST EN 303 402 V2.1.2:2017

<https://standards.iteh.ai/catalog/standards/sist/9e5b4e2-2e91-4456-9ae0-8920339bc19/sist-en-303-402-v2-1-2-2017>
 The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
 Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
 The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.
 All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and
 of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.
GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

| | |
|--|----|
| Intellectual Property Rights | 8 |
| Foreword..... | 8 |
| Modal verbs terminology..... | 8 |
| 1 Scope | 9 |
| 2 References | 9 |
| 2.1 Normative references | 9 |
| 2.2 Informative references..... | 10 |
| 3 Definitions, symbols and abbreviations | 11 |
| 3.1 Definitions..... | 11 |
| 3.2 Symbols..... | 11 |
| 3.3 Abbreviations | 12 |
| 4 General requirements | 12 |
| 4.1 Environmental profile..... | 12 |
| 4.2 General, operational and technical requirements..... | 12 |
| 4.2.1 Testing of requirements | 12 |
| 4.2.2 General requirements | 12 |
| 4.2.2.1 Composition | 12 |
| 4.2.2.1.1 DSC requirements | 12 |
| 4.2.2.1.2 Audio frequencies interfaces | 13 |
| 4.2.2.1.3 DSC Interface | 13 |
| 4.2.2.1.4 Digital input panels..... | 13 |
| 4.2.2.1.5 GNSS receiver antenna | 13 |
| 4.2.2.2 Construction | 13 |
| 4.2.2.3 Controls and indicators | 14 |
| 4.2.2.3.1 General | 14 |
| 4.2.2.3.2 Illumination | 14 |
| 4.2.2.4 Labelling | 14 |
| 4.2.2.4.1 General | 14 |
| 4.2.2.4.2 Distress frequencies | 14 |
| 4.2.2.5 Protection against mishandling | 15 |
| 4.2.3 Operational requirements | 15 |
| 4.2.3.1 Frequency bands | 15 |
| 4.2.3.1.1 Operating bands | 15 |
| 4.2.3.1.2 MF band | 15 |
| 4.2.3.1.3 HF bands..... | 15 |
| 4.2.3.2 Classes of emission | 16 |
| 4.2.4 Warming up period | 16 |
| 4.2.4.1 Time | 16 |
| 4.2.4.2 Heaters | 16 |
| 4.2.4.3 Heating circuits | 16 |
| 4.2.4.4 Delay | 16 |
| 4.2.5 Technical requirements | 16 |
| 4.2.5.1 Distress controls | 16 |
| 4.2.5.2 Telephony transmit control | 16 |
| 4.2.5.3 Misuse | 16 |
| 4.2.5.4 Control panel priority..... | 17 |
| 4.2.5.5 Manual gain control and Automatic Gain Control (AGC) | 17 |
| 4.2.5.6 Output indication..... | 17 |
| 4.2.5.7 DSC operation..... | 17 |
| 4.2.5.8 Synthesizer lock | 17 |
| 4.2.5.9 Channel switching | 17 |
| 5 Test conditions, power sources and ambient temperatures | 17 |
| 5.1 General | 17 |
| 5.2 Test power source..... | 17 |

| | | |
|-----------|--|----|
| 5.3 | Normal test conditions..... | 18 |
| 5.3.1 | Normal temperature and humidity | 18 |
| 5.3.2 | Normal test power source | 18 |
| 5.3.2.1 | Mains voltage and frequency | 18 |
| 5.3.2.2 | Secondary battery power sources | 18 |
| 5.3.2.3 | Other power sources..... | 18 |
| 5.4 | Extreme test conditions | 18 |
| 5.4.1 | Extreme temperature tests..... | 18 |
| 5.4.2 | Extreme values of test power source | 18 |
| 5.4.2.1 | Mains voltage and mains frequency | 18 |
| 5.4.2.2 | Secondary battery power sources | 18 |
| 5.4.2.3 | Other power sources..... | 19 |
| 6 | General conditions of measurement..... | 19 |
| 6.1 | Artificial antennas | 19 |
| 6.1.1 | Transmitters | 19 |
| 6.1.2 | Receivers | 19 |
| 6.2 | Standard test signals | 19 |
| 6.2.1 | Test signals applied to the receiver input | 19 |
| 6.2.1.1 | Sources | 19 |
| 6.2.1.2 | Levels | 19 |
| 6.2.2 | Normal test signals..... | 20 |
| 6.2.2.1 | General | 20 |
| 6.2.2.2 | Class of emission J3E..... | 20 |
| 6.2.2.3 | Class of emission F1B..... | 20 |
| 6.2.3 | Choice of testing frequencies..... | 20 |
| 6.2.4 | Exclusion bands for emissions testing..... | 20 |
| 6.2.4.1 | Transmitter exclusion bands | 20 |
| 6.2.4.2 | Receiver exclusion bands | 20 |
| 6.2.5 | Reference bandwidths for spurious measurements (standards.iteh.ai) | 20 |
| 7 | Environmental tests | 21 |
| 7.1 | Introduction | 21 |
| 7.2 | Procedure | 21 |
| 7.3 | Performance check | 21 |
| 7.4 | Temperature tests | 21 |
| 7.4.1 | Definition..... | 21 |
| 7.4.2 | Dry heat | 22 |
| 7.4.2.1 | Method of measurement..... | 22 |
| 7.4.2.1.1 | Internally mounted equipment..... | 22 |
| 7.4.2.1.2 | Externally mounted equipment..... | 22 |
| 7.4.2.2 | Requirement | 22 |
| 7.4.3 | Damp heat | 22 |
| 7.4.3.1 | Method of measurement..... | 22 |
| 7.4.3.2 | Requirement | 23 |
| 7.4.4 | Low temperature cycle..... | 23 |
| 7.4.4.1 | Method of measurement..... | 23 |
| 7.4.4.1.1 | Internally mounted equipment..... | 23 |
| 7.4.4.1.2 | Externally mounted equipment..... | 23 |
| 7.4.4.2 | Requirement | 23 |
| 7.5 | Vibration test | 23 |
| 7.5.1 | Definition..... | 23 |
| 7.5.2 | Method of measurement | 24 |
| 7.5.3 | Requirements | 24 |
| 7.6 | Corrosion test | 24 |
| 7.6.1 | Applicability | 24 |
| 7.6.2 | Definition..... | 24 |
| 7.6.3 | Method of measurement | 24 |
| 7.6.4 | Requirements | 25 |
| 7.7 | Rain test..... | 25 |
| 7.7.1 | Applicability | 25 |
| 7.7.2 | Method of measurement | 25 |

| | | |
|---------|--|----|
| 7.7.3 | Requirements | 26 |
| 8 | Transmitter | 26 |
| 8.1 | Frequency error | 26 |
| 8.1.1 | Definition..... | 26 |
| 8.1.2 | Method of measurement | 26 |
| 8.1.3 | Limit | 27 |
| 8.2 | Output power and intermodulation products | 27 |
| 8.2.1 | Definition..... | 27 |
| 8.2.2 | Method of measurement | 27 |
| 8.2.3 | Limits..... | 28 |
| 8.2.3.1 | Output power in the range 1 606,5 kHz to 4 000 kHz for all modulation modes..... | 28 |
| 8.2.3.2 | Output power in the range 4 MHz to 27,5 MHz for all modulation modes..... | 28 |
| 8.2.3.3 | Intermodulation products for SSB telephony modes..... | 28 |
| 8.2.3.4 | Difference of power of B-state frequency and Y-state frequency | 28 |
| 8.2.3.5 | Output spectrum..... | 29 |
| 8.3 | Power of out-of-band emissions of SSB telephony | 29 |
| 8.3.1 | Definition..... | 29 |
| 8.3.2 | Method of measurement | 29 |
| 8.3.3 | Limits..... | 30 |
| 8.4 | Power of conducted spurious emissions of SSB telephony | 30 |
| 8.4.1 | Definition..... | 30 |
| 8.4.2 | Method of measurement | 30 |
| 8.4.3 | Limits..... | 30 |
| 8.5 | Carrier suppression | 30 |
| 8.5.1 | Definition..... | 30 |
| 8.5.2 | Method of measurement | 31 |
| 8.5.3 | Limit | 31 |
| 8.6 | Unwanted frequency modulation | 31 |
| 8.6.1 | Definition..... | 31 |
| 8.6.2 | Method of measurement | 31 |
| 8.6.3 | Limit | 31 |
| 8.7 | Sensitivity of the microphone and the 600 Ω line inputs for SSB telephony | 31 |
| 8.7.1 | SIST EN 303-402-V2.1.2:2017 | 31 |
| 8.7.2 | Definition..... | 31 |
| 8.7.3 | Method of measurement | 32 |
| 8.7.3 | Limit | 32 |
| 8.8 | Automatic level control and/or limiter for SSB telephony | 32 |
| 8.8.1 | Definition..... | 32 |
| 8.8.2 | Method of measurement | 32 |
| 8.8.3 | Limit | 33 |
| 8.9 | Audio frequency response of SSB telephony | 33 |
| 8.9.1 | Definition..... | 33 |
| 8.9.2 | Method of measurement | 33 |
| 8.9.3 | Limit | 33 |
| 8.10 | Residual hum and noise power for telephony | 34 |
| 8.10.1 | Definition..... | 34 |
| 8.10.2 | Method of measurement | 34 |
| 8.10.3 | Limit | 34 |
| 8.11 | Residual frequency modulation on DSC | 35 |
| 8.11.1 | Definition..... | 35 |
| 8.11.2 | Method of measurement | 35 |
| 8.11.3 | Limit | 35 |
| 8.12 | Continuous operation on telephony | 35 |
| 8.12.1 | Definition..... | 35 |
| 8.12.2 | Method of measurement | 35 |
| 8.12.3 | Limits..... | 35 |
| 8.13 | Protection of transmitter | 35 |
| 8.13.1 | Definition..... | 35 |
| 8.13.2 | Method of measurement | 36 |
| 8.13.3 | Requirements | 36 |
| 8.14 | Transmitter radiated spurious emissions | 36 |
| 8.14.1 | Definition..... | 36 |

| | | |
|---------|---|----|
| 8.14.2 | Method of measurement | 36 |
| 8.14.3 | Limits..... | 37 |
| 9 | Receiver..... | 37 |
| 9.1 | Receiver spurious emissions..... | 37 |
| 9.1.1 | Definition..... | 37 |
| 9.1.2 | Method of measurement | 37 |
| 9.1.2.1 | Conducted antenna port measurement | 37 |
| 9.1.2.2 | Radiated measurement | 37 |
| 9.1.3 | Limits..... | 38 |
| 9.2 | Maximum usable sensitivity..... | 38 |
| 9.2.1 | Definition..... | 38 |
| 9.2.2 | Method of measurement | 38 |
| 9.2.3 | Limits..... | 39 |
| 9.3 | Adjacent signal selectivity..... | 39 |
| 9.3.1 | Definition..... | 39 |
| 9.3.2 | Method of measurement | 39 |
| 9.3.3 | Limits..... | 40 |
| 9.4 | Blocking or desensitization..... | 40 |
| 9.4.1 | Definition..... | 40 |
| 9.4.2 | Method of measurement | 40 |
| 9.4.3 | Limits..... | 41 |
| 9.5 | Intermodulation response | 41 |
| 9.5.1 | Definition..... | 41 |
| 9.5.2 | Method of measurement | 41 |
| 9.5.2.1 | Class of emission J3E..... | 41 |
| 9.5.2.2 | Class of emission F1B analogue..... | 41 |
| 9.5.2.3 | Class of Emission FB digital..... | 42 |
| 9.5.3 | Limits..... | 42 |
| 9.6 | Spurious response rejection ratio..... | 42 |
| 9.6.1 | Definition..... | 42 |
| 9.6.2 | Method of measurement | 42 |
| 9.6.3 | Limits..... | 43 |
| 9.7 | Receiver frequency error | 44 |
| 9.7.1 | Definition..... | 44 |
| 9.7.2 | Method of measurement | 44 |
| 9.7.3 | Limit | 44 |
| 9.8 | Unwanted frequency modulation | 44 |
| 9.8.1 | Definition..... | 44 |
| 9.8.2 | Method of measurement | 44 |
| 9.8.3 | Limit | 45 |
| 9.9 | Pass band | 45 |
| 9.9.1 | Definition..... | 45 |
| 9.9.2 | Method of measurement | 45 |
| 9.9.3 | Limits..... | 45 |
| 9.10 | Reciprocal mixing | 45 |
| 9.10.1 | Definition..... | 45 |
| 9.10.2 | Method of measurement | 45 |
| 9.10.3 | Limit | 46 |
| 9.11 | Harmonic content in output | 46 |
| 9.11.1 | Definition..... | 46 |
| 9.11.2 | Method of measurement | 46 |
| 9.11.3 | Limits..... | 46 |
| 9.12 | Audio frequency intermodulation..... | 46 |
| 9.12.1 | Definition..... | 46 |
| 9.12.2 | Method of measurement | 46 |
| 9.12.3 | Limit | 46 |
| 9.13 | Internally generated spurious signals | 47 |
| 9.13.1 | Definition..... | 47 |
| 9.13.2 | Method of measurement | 47 |
| 9.13.3 | Limits..... | 47 |
| 9.14 | AGC efficiency | 47 |

| | | |
|-------------------------------|---|-----------|
| 9.14.1 | Definition..... | 47 |
| 9.14.2 | Method of measurement | 47 |
| 9.14.2.1 | General..... | 47 |
| 9.14.2.2 | Settings..... | 47 |
| 9.14.2.3 | Increase in Signal-to-Noise Ratio (SNR) | 47 |
| 9.14.3 | Limits..... | 47 |
| 9.15 | AGC time constants (attack and recovery time)..... | 48 |
| 9.15.1 | Definition..... | 48 |
| 9.15.2 | Method of measurement | 48 |
| 9.15.3 | Limits..... | 48 |
| 9.16 | Protection of input circuits | 48 |
| 9.16.1 | Definition..... | 48 |
| 9.16.2 | Method of measurement | 48 |
| 9.16.3 | Requirement..... | 48 |
| 10 | Testing for compliance with technical requirements..... | 49 |
| 10.1 | Environmental conditions for testing | 49 |
| 10.2 | Interpretation of the measurement results | 49 |
| Annex A (informative): | Relationship between the present document and the essential requirements of Directive 2014/53/EU | 50 |
| Annex B (informative): | Bibliography | 52 |
| Annex C (informative): | Change history | 53 |
| History | | 54 |

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 303 402 V2.1.2:2017](#)
<https://standards.iteh.ai/catalog/standards/sist/f9e5b4e2-2e91-4456-9ae0-8a2b339f3c19/sist-en-303-402-v2-1-2-2017>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.12] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in tables A.1 and A.2 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document replaces ETSI EN 300 373-2 [i.10] and ETSI EN 300 373-3 [i.11].

| National transposition dates | |
|--|------------------|
| Date of latest announcement of this EN (doa): | 31 December 2017 |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 30 June 2018 |
| Date of withdrawal of any conflicting National Standard (dow): | 30 June 2019 |

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document specifies technical characteristics and methods of measurements for radio transmitters and receivers, for use on vessels, operating in either the Medium Frequency (MF) only or in the Medium and High Frequency (MF/HF) bands allocated in the International Telecommunications Union (ITU) Radio Regulations [i.9], to the Maritime Mobile Service (MMS).

The present document refers to equipment for one or more of the following:

- Single SideBand (SSB) modulation for telephony transmission and reception (J3E);
- Frequency Shift Keying (FSK) or SSB modulation of a keyed sub-carrier to transmit and receive Digital Selective Calling (DSC) signals.

The present document also refers to radio equipment with either an integrated or external DSC controller.

The requirements in the present document are applicable to receivers for operating on all frequencies in the bands 1 606,5 kHz to 4 000 kHz or 1 606,5 kHz to 27,5 MHz as allocated in the ITU Radio Regulations [i.9], to the MMS.

Other spot frequency receivers should meet all the requirements of the present document and other relevant standards as applicable for the frequencies and modes provided.

If the equipment, or parts of it, are designed in such a manner that they can be used for other categories of maritime radiocommunication (e.g. Morse telegraphy or NBDP - ETSI ETS 300 067 [i.4]), those parts of the equipment should fulfil the relevant requirements of the appropriate standards for the service(s) in question e.g. ETSI ETS 300 067 [i.4].

The present document covers the essential requirements of article 3.2 and article 3.3(g) of Directive 2014/53/EU [i.1] under the conditions identified in annex A.

ITU STANDARD PREVIEW (standards.iteh.ai)

2 References

[SIST EN 303 402 V2.1.2:2017](#)

<https://standards.iteh.ai/catalog/standards/sist/f9e5b4e2-2e91-4456-9ae0-02d1302c10/sist-en-303-402-v2-1-2-2017>

2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 103 052 (V1.1.1) (03-2011): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".
- [2] ITU Recommendation E.161 (02-2001): "Arrangement of digits, letters and symbols on telephones and other devices that can be used for gaining access to a telephone network".
- [3] ETSI EN 300 338-4 (V1.2.1) (02-2017): "Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service; Part 4: Class E DSC".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] ETSI TR 100 028-1 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1".
- [i.3] ETSI TR 100 028-2 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
- [i.4] ETSI ETS 300 067 (11-1990): "Radio Equipment and Systems (RES); Radiotelex equipment operating in the maritime MF/HF service; Technical Characteristics and methods of measurement".
- [i.5] Recommendation ITU-R SM.332-4 (07-1978): "Selectivity of receivers".
- [i.6] Recommendation ITU-R SM.326-7 (11-1998): "Determination and measurement of the power of amplitude-modulated radio transmitters".
- [i.7] ISO 3791 (1976): "Office machines and data processing equipment - Keyboard layouts for numeric applications".
SIST EN 303 402 V2.1.2:2017
<https://standards.itel.ai/catalog/standards/sist/fe5b4e22e914456-9ae0-8a2b339f3c19/sist-en-303-402-v2-1-2-2017>
- [i.8] CENELEC EN 60945 (2002): "Maritime navigation and radiocommunication equipment and systems - General requirements - Methods of testing and required test results".
- [i.9] ITU Radio Regulations (2016).
- [i.10] ETSI EN 300 373-2 (V1.2.1) (12-2009): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Maritime mobile transmitters and receivers for use in the MF and HF bands; Part 2: Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive".
- [i.11] ETSI EN 300 373-3 (V1.2.1) (12-2009): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Maritime mobile transmitters and receivers for use in the MF and HF bands; Part 3: Harmonized EN covering essential requirements under article 3.3(e) of the R&TTE Directive; Equipment with integrated or associated equipment for Class E Digital Selective Calling (DSC)".
- [i.12] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.13] CENELEC EN 60945 4th edition (2002): "Maritime navigation and radiocommunication equipment and systems - General requirements - Methods of testing and required test results".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document the following terms and definitions apply:

assigned frequency: centre of the frequency band assigned to a station

carrier frequency: frequency to which the transmitter or receiver is tuned

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

spurious emission: emission on a frequency, or frequencies, which are outside the necessary bandwidth and the level of which may be reduced without affecting the corresponding transmission of information

NOTE: Spurious emissions include harmonic emissions, parasitic emissions, intermodulation products and frequency conversion products but exclude out-of-band emissions (ITU Radio Regulations [i.9]).

standard output power: output power of the receiver measured across a resistor equal to the nominal value of the load impedance as declared by the manufacturer

NOTE: Standard output power is 1 mW for earphone reception, 500 mW for loudspeaker reception and 0 dBm into 600 Ω for the audio line outputs.

3.2 Symbols

iTeh STANDARD PREVIEW

(standards.iteh.ai)

For the purposes of the present document, the symbols given in the ITU Radio Regulations [i.9] and the following apply:

| | SIST EN 303 402 V2.1.2:2017 https://standards.iteh.ai/catalog/standards/sist/f9e5b4e2-2e91-4456-9ae0-8a2b339f3c19/sist-en-303-402-v2-1-2-2017 |
|------------|--|
| dB | decibel |
| dBm | dBmilliwatt |
| dB μ V | dBmicrovolt |
| F1B | frequency modulation, single channel containing quantized or digital information without the use of a modulating sub-carrier, telephony for automatic reception |
| g | gram |
| h | hour |
| Hz | hertz |
| J2B | SSB, suppressed carrier, single channel containing quantized or digital information with the use of a modulating sub-carrier, telephony for automatic reception |
| J3E | SSB, suppressed carrier, single channel containing analogue information, telephony |
| k | kilo |
| kHz | kilohertz |
| kPa | kilopascal |
| l | litre |
| m | meter |
| MHz | megahertz |
| min | minute |
| mm | millimeter |
| ms | millisecond |
| mW | milliwatt |
| NaCl | sodium chloride |
| Ω | ohm |
| pF | picofarad |
| s | second |
| V | volt |
| W | watt |

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| | |
|-------|--|
| AGC | Automatic Gain Control |
| BER | Bit Error Rate |
| CSP | Channel Spacing |
| DC | Direct Current |
| DSC | Digital Selective Calling |
| emf | electromotive force |
| EN | European Norm |
| EUT | Equipment Under Test |
| FM | Frequency Modulation |
| FSK | Frequency Shift Keying |
| GNSS | Global Navigation Satellite System |
| ISO | International Standards Organization |
| ITU | International Telecommunications Union |
| MF | Medium Frequency |
| MF/HF | Medium and High Frequency |
| MMS | Maritime Mobile Service |
| NBDP | Narrowband Direct Printing |
| PEP | Peak Envelope Power |
| RBW | Reference BandWidth |
| RF | Radio Frequency |
| RMS | Root Mean Square |
| SINAD | Signal plus Noise plus Distortion to Noise plus Distortion |
| SNR | Signal-to-Noise Ratio |
| SSB | Single Side Band |

ITEH STANDARD PREVIEW
(standards.iteh.ai)

4 General requirements

SIST EN 303 402 V2.1.2:2017
<https://standards.iteh.ai/catalog/standards/sist/f9e5b4e2-2e91-4456-9ae0-8a2b339f3c19/sist-en-303-402-v2-1-2-2017>

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer, but as a minimum, shall be that specified in the test conditions contained in the present document. The equipment shall comply with all the technical requirements of the present document which are identified as applicable in annex A at all times when operating within the boundary limits of the declared operational environmental profile.

4.2 General, operational and technical requirements

4.2.1 Testing of requirements

There are no defined tests for the requirements in clause 4.2. The availability of the specified controls shall be verified by visual inspection.

4.2.2 General requirements

4.2.2.1 Composition

4.2.2.1.1 DSC requirements

The equipment shall contain either:

- a dedicated watchkeeping receiver for the DSC decoder;

- a DSC encoder;
- a DSC decoder; and
- an integral GNSS receiver providing locating function;

Or:

- a dedicated DSC controller interface as specified in clause 4.2.2.1.3.

4.2.2.1.2 Audio frequencies interfaces

The following inputs and outputs applicable to the type of equipment shall be provided:

a) transmitters:

- SSB Telephony:
 - 600 Ω earth free audio input;
 - microphone input;

b) receivers:

- SSB Telephony:
 - 600 Ω earth free audio output;
 - earphone output;
 - speaker output.

Audio processing may be applied to audio outputs for handset, external speaker, etc., but shall not affect line level audio interfaces. Where audio processing is activated it shall be assessed. The acoustic speech recognition is equal to, or better than without audio processing enabled under receive conditions at sensitivity level.

https://standards.iteh.ai/catalog/standards/sist/19e5b4e2-2e91-4456-9ae0-

8a2b339f3c19/sist-en-303-402-v2-1-2-2017

4.2.2.1.3 DSC Interface

If the equipment does not have an integrated DSC controller then, the equipment shall have a dedicated interface for an external DSC controller compliant with ETSI EN 300 338-4 [3].

Other interfaces than those described in this clause may be provided but shall not in any case have an impact which will degrade the performance of the equipment.

4.2.2.1.4 Digital input panels

Where a digital input panel with the digits "0" to "9" is provided, the digits shall be arranged to conform to one of the options described in clause 3 of Recommendation ITU-T E.161 [2]. However, where an alphanumeric keyboard layout is provided, the digits "0" to "9" may, alternatively, be arranged to conform to ISO 3791 [i.7].

4.2.2.1.5 GNSS receiver antenna

The integrated GNSS receiver shall have the possibility to connect an external antenna.

4.2.2.2 Construction

The attention of the manufacturer is drawn to CENELEC EN 60945 [i.8] which offers guidelines on the construction and ergonomic details for equipment intended to be used on board vessels.

All controls shall be of sufficient size to enable the usual control functions to be easily performed and the number of controls should be the minimum necessary for simple and satisfactory operation.

Adequately detailed operating instructions shall be provided with the equipment.