
**Petroleum, petrochemical and natural gas
industries — Fired heaters for general
refinery service**

*Industries du pétrole, de la pétrochimie et du gaz naturel —
Réchauffeurs à brûleurs pour usage général dans les raffineries*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 13705:2012

<https://standards.iteh.ai/catalog/standards/sist/cfb75800-71e2-4dc9-ac22-0d20fe12f912/iso-13705-2012>



iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 13705:2012

<https://standards.iteh.ai/catalog/standards/sist/cfb75800-71e2-4dc9-ac22-0d20fe12f912/iso-13705-2012>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction.....	vi
1 Scope	1
2 Normative references	1
3 Terms, definitions, abbreviated terms and symbols	4
3.1 Terms and definitions	4
3.2 Abbreviated terms and symbols	11
4 General	12
4.1 Pressure design code	12
4.2 Regulations	12
4.3 Heater nomenclature	12
5 Proposals	16
5.1 Purchaser's responsibilities	16
5.2 Vendor's responsibilities	16
5.3 Documentation	16
5.4 Final reports	18
6 Design considerations	18
6.1 Process design	18
6.2 Combustion design	19
6.3 Mechanical design	19
7 Tubes	20
7.1 General	20
7.2 Extended surface	21
7.3 Materials	22
8 Headers	22
8.1 General	22
8.2 Plug headers	23
8.3 Return bends	24
8.4 Materials	24
9 Piping, terminals and manifolds	25
9.1 General	25
9.2 Allowable movement and loads	26
9.3 Materials	28
10 Tube supports	28
10.1 General	28
10.2 Loads and allowable stress	29
10.3 Materials	30
11 Refractories and insulation	31
11.1 General	31
11.2 Brick and tile construction	32
11.3 Castable construction	33
11.4 Ceramic-fibre construction	33
11.5 Multi-component lining construction	35
11.6 Materials	35
12 Structures and appurtenances	36
12.1 General	36

12.2	Structures	36
12.3	Header boxes, doors and ports	37
12.4	Ladders, platforms and stairways	37
12.5	Materials	38
13	Stacks, ducts and breeching	39
13.1	General	39
13.2	Design considerations	39
13.3	Design methods	41
13.4	Static design	41
13.5	Wind-induced vibration design	42
13.6	Materials	43
14	Burners and auxiliary equipment	43
14.1	Burners	43
14.2	Sootblowers	48
14.3	Fans and drivers	48
14.4	Dampers and damper controls for stacks and ducts	48
15	Instrument and auxiliary connections	49
15.1	Flue gas and air	49
15.2	Process fluid temperature	50
15.3	Auxiliary connections	50
15.4	Tube-skin thermocouples	51
15.5	Access to connections	51
16	Shop fabrication and field erection	51
16.1	General	51
16.2	Structural-steel fabrication	52
16.3	Coil fabrication	53
16.4	Painting and galvanizing	54
16.5	Refractories and insulation	54
16.6	Preparation for shipment	55
16.7	Field erection	56
17	Inspection, examination and testing	56
17.1	General	56
17.2	Weld examination	57
17.3	Castings examination	57
17.4	Examination of other components	58
17.5	Testing	59
Annex A (informative) Equipment data sheets		
		61
Annex B (informative) Purchaser's checklist		
		90
Annex C (informative) Proposed shop-assembly conditions		
		94
Annex D (normative) Stress curves for use in the design of tube-support elements		
		96
Annex E (normative) Centrifugal fans for fired-heater systems		
		111
Annex F (normative) Air preheat systems for fired process heaters		
		128
Annex G (informative) Measurement of efficiency of fired process heaters		
		186
Annex H (informative) Stack design		
		254
Annex I (informative) Measurement of noise from fired-process heaters		
		264
Bibliography		
		300

iTeh STANDARD PREVIEW

(standards.iteh.ai)

ISO 13705:2012

[https://standards.iteh.ai/catalog/standards/sist/cfb75800-71e2-4dc9-ac22-](https://standards.iteh.ai/catalog/standards/sist/cfb75800-71e2-4dc9-ac22-0d20fe12f912/iso-13705-2012)

[0d20fe12f912/iso-13705-2012](https://standards.iteh.ai/catalog/standards/sist/cfb75800-71e2-4dc9-ac22-0d20fe12f912/iso-13705-2012)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 13705 was prepared by Technical Committee ISO/TC 67, *Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries*, Subcommittee SC 6, *Processing equipment and systems*.

This third edition cancels and replaces the second edition (ISO 13705:2006), which has been technically revised.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
<https://standards.iteh.ai/catalog/standards/sist/cfb75800-71e2-4dc9-ac22-0d20fe12f912/iso-13705-2012>

Introduction

Users of this International Standard should be aware that further or differing requirements may be needed for individual applications. This International Standard is not intended to inhibit a vendor from offering, or the purchaser from accepting, alternative equipment or engineering solutions for the individual application. This may be particularly applicable where there is innovative or developing technology. Where an alternative is offered, the vendor should identify any variations from this International Standard and provide details.

In International Standards, the SI system of units is used. Where practical in this International Standard, US Customary (USC) units are included in brackets for information.

A bullet (●) at the beginning of a clause or subclause indicates that either a decision is required or further information is to be provided by the purchaser. This information should be indicated on data sheets (see examples in Annex A) or stated in the enquiry or purchase order. Decisions should be indicated on a checklist (see example in Annex B).

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 13705:2012

<https://standards.iteh.ai/catalog/standards/sist/cfb75800-71e2-4dc9-ac22-0d20fe12f912/iso-13705-2012>

Petroleum, petrochemical and natural gas industries — Fired heaters for general refinery service

1 Scope

This International Standard specifies requirements and gives recommendations for the design, materials, fabrication, inspection, testing, preparation for shipment, and erection of fired heaters, air heaters (APHs), fans and burners for general refinery service.

This International Standard is not intended to apply to the design of steam reformers or pyrolysis furnaces.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1461, *Hot dip galvanized coatings on fabricated iron and steel articles — Specifications and test methods*

ISO 1940-1:2003, *Mechanical vibration — Balance quality requirements for rotors in a constant (rigid) state — Part 1: Specification and verification of balance tolerances*

ISO 8501-1, *Preparation of steel substrates before application of paints and related products — Visual assessment of surface cleanliness — Part 1: Rust grades and preparation grades of uncoated steel substrates and of steel substrates after overall removal of previous coatings*

ISO 10684, *Fasteners — Hot dip galvanized coatings*

ISO 13704, *Petroleum, petrochemical and natural gas industries — Calculation of heater-tube thickness in petroleum refineries*

ISO 15649, *Petroleum and natural gas industries — Piping*

IEC 60079 (all parts), *Electrical apparatus for explosive gas atmospheres*

EN 10025-2:2004¹, *Hot rolled products of structural steels — Part 2: Technical delivery conditions for non-alloy structural steels*

ABMA Standard 9², *Load Ratings and Fatigue Life for Ball Bearings*

AMCA 210³, *Laboratory Methods of Testing Fans for Aerodynamic Performance Rating*

AMCA 801:2001, *Industrial Process/Power Generation Fans — Specifications and Guidelines*

¹ European Committee for Standardization (CEN), Rue de Stassart 36, B-1050 Brussels, Belgium.

² American Bearing Manufacturers Association, 2025 M. Street, NW, Suite 800, Washington, DC 20036, USA.

³ Air Movement and Control Association, 30 West University Drive, Arlington Heights, IL 60004, USA.

ISO 13705:2012(E)

ASME B 17.1⁴, *Keys and Keyseats*

ASME *Boiler and Pressure Vessel Code, Section VIII, Pressure Vessels*

ASTM A 36⁵, *Standard Specification for Carbon Structural Steel*

ASTM A 53, *Standard Specification for Pipe, Steel, Black and Hot-Dipped, Zinc-Coated, Welded and Seamless*

ASTM A 105, *Standard Specification for Carbon Steel Forgings for Piping Applications*

ASTM A 106, *Standard Specification for Seamless Carbon Steel Pipe for High-Temperature Service*

ASTM A 123, *Standard Specification for Zinc (Hot-Dip Galvanized) Coatings on Iron and Steel Products*

ASTM A 143, *Standard Practice for Safeguarding Against Embrittlement of Hot-Dip Galvanized Structural Steel Products and Procedure for Detecting Embrittlement*

ASTM A 153, *Standard Specification for Zinc Coating (Hot-Dip) on Iron and Steel Hardware*

ASTM A 181, *Standard Specification for Carbon Steel Forgings, for General-Purpose Piping*

ASTM A 182, *Standard Specification for Forged or Rolled Alloy and Stainless-Steel Pipe Flanges, Forged Fittings, and Valves and Parts for High-Temperature Service*

ASTM A 192, *Standard Specification for Seamless Carbon Steel Boiler Tubes for High-Pressure Service*

ASTM A 193, *Standard Specification for Alloy-Steel and Stainless Steel Bolting for High-Temperature or High-Pressure Service and Other Special Purpose Applications*

ASTM A 194, *Standard Specification for Carbon and Alloy Steel Nuts for Bolts for High-Pressure or High-Temperature Service, or Both*

ASTM A 209, *Standard Specification for Seamless Carbon-Molybdenum Alloy-Steel Boiler and Superheater Tubes*
<https://standards.iteh.ai/catalog/standards/sist/cfb75800-71e2-4dc9-ac22-9420514912/sc/13705-2012>

ASTM A 210, *Standard Specification for Seamless Medium-Carbon Steel Boiler and Superheater Tubes*

ASTM A 213, *Standard Specification for Seamless Ferritic and Austenitic Alloy-Steel Boiler, Superheater, and Heat-Exchanger Tubes*

ASTM A 216, *Standard Specification for Steel Castings, Carbon, Suitable for Fusion Welding, for High-Temperature Service*

ASTM A 217, *Standard Specification for Steel Castings, Martensitic Stainless and Alloy, for Pressure-Containing Parts, Suitable for High-Temperature Service*

ASTM A 234, *Standard Specification for Piping Fittings of Wrought Carbon Steel and Alloy Steel for Moderate and High Temperature Service*

ASTM A 240, *Standard Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications*

ASTM A 242, *Standard Specification for High-Strength Low-Alloy Structural Steel*

ASTM A 283, *Standard Specification for Low and Intermediate Tensile Strength Carbon Steel Plates*

ASTM A 297, *Standard Specification for Steel Castings, Iron-Chromium and Iron-Chromium-Nickel, Heat Resistant, for General Application*

ASTM A 307, *Standard Specification for Carbon Steel Bolts and Studs, 60 000 PSI Tensile Strength*

⁴ American Society of Mechanical Engineers, 3 Park Avenue, New York, NY 10017, USA.

⁵ American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959, USA.

- ASTM A 312, *Standard Specification for Seamless, Welded, and Heavily Cold Worked Austenitic Stainless Steel Pipes*
- ASTM A 320, *Standard Specification for Alloy Steel and Stainless Steel Bolting Materials for Low-Temperature Service*
- ASTM A 325, *Standard Specification for Structural Bolts, Steel, Heat Treated, 120/105 ksi Minimum Tensile Strength*
- ASTM A 335, *Standard Specification for Seamless Ferritic Alloy-Steel Pipe for High-Temperature Service*
- ASTM A 351, *Standard Specification for Castings, Austenitic, for Pressure-Containing Parts*
- ASTM A 376, *Standard Specification for Seamless Austenitic Steel Pipe for High-Temperature Central-Station Service*
- ASTM A 384, *Standard Practice for Safeguarding Against Warpage and Distortion During Hot-Dip Galvanizing of Steel Assemblies*
- ASTM A 385, *Standard Practice for Providing High-Quality Zinc Coatings (Hot-Dip)*
- ASTM A 387, *Standard Specification for Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum*
- ASTM A 403, *Standard Specification for Wrought Austenitic Stainless Steel Piping Fittings*
- ASTM A 447, *Standard Specification for Steel Castings, Chromium-Nickel-Iron Alloy (25-12 Class), for High-Temperature Service*
- ASTM A 560, *Standard Specification for Castings, Chromium-Nickel Alloy*
- ASTM A 572, *Standard Specification for High-Strength, Low-Alloy Columbium-Vanadium Structural Steel*
- ASTM A 608, *Standard Specification for Centrifugally Cast Iron-Chromium-Nickel High-Alloy Tubing for Pressure Application at High Temperatures*
- ASTM B 366, *Standard Specification for Factory-Made Wrought Nickel and Nickel Alloy Fittings*
- ASTM B 407, *Standard Specification for Nickel-Iron-Chromium Alloy Seamless Pipe and Tube*
- ASTM B 564, *Standard Specification for Nickel Alloy Forgings*
- ASTM B 633, *Standard Specification for Electrodeposited Coatings of Zinc on Iron and Steel*
- ASTM C 27, *Standard Classification of Fireclay and High-Alumina Refractory Brick*
- ASTM C 155, *Standard Classification of Insulating Firebrick*
- ASTM C 332, *Standard Specification for Lightweight Aggregates for Insulating Concrete*
- ASTM C 401, *Standard Classification of Alumina and Alumina-Silicate Castable Refractories*
- ASTM C 612, *Standard Specification for Mineral Fiber Block and Board Thermal Insulation*
- AWS⁶ D 1.1, *Structural Welding Code — Steel*
- AWS D 14.6, *Specification for Welding of Rotating Elements of Equipment*
- NFPA 70⁷, *National Electrical Code*
- SSPC SP 6/NACE No 3⁸, *Commercial Blast Cleaning*

6 American Welding Society, 550 NW Le Jeune Road, Miami, FL 33126, USA.

7 National Fire Protection Association, 1 Batterymarch Park, Quincy, MA 02269-9101, USA.

8 The Society for Protective Coatings, 40, 24th Street, Pittsburg, PA 15222-4643, USA.

3 Terms, definitions, abbreviated terms and symbols

For the purposes of this document, the following terms and definitions apply.

NOTE Terms and definitions related to centrifugal fans are given in Annex E.

3.1 Terms and definitions

3.1.1

air heater

air preheater

APH

heat transfer apparatus through which combustion air is passed and heated by a medium of higher temperature, such as combustion products, steam or other fluid

3.1.2

anchor

tieback

metallic or refractory device that holds the refractory or insulation in place

3.1.3

arch

flat or sloped portion of the heater radiant section opposite the floor

3.1.4

atomizer

device used to reduce a liquid fuel oil to a fine mist, using steam, air or mechanical means

3.1.5

backup layer

refractory layer behind the hot-face layer

iTeh STANDARD PREVIEW
(standards.iteh.ai)
<https://standards.iteh.ai/catalog/standards/sist/cfb75800-71e2-4dc9-ac22-0d20fe12f912/iso-13705-2012>
ISO 13705:2012

3.1.6

balanced-draught heater

heater that uses forced-draught fans to supply combustion air and induced-draught fans to remove flue gases

3.1.7

breeching

heater section where flue gases are collected after the last convection coil for transmission to the stack or the outlet ductwork

3.1.8

bridgewall

gravity wall

wall that separates two adjacent heater zones

3.1.9

bridgewall temperature

temperature of flue gas leaving the radiant section

3.1.10

burner

device that introduces fuel and air into a heater at the desired velocities, turbulence and concentration to establish and maintain proper ignition and combustion

NOTE Burners are classified by the type of fuel fired, such as oil, gas, or a combination of gas and oil, which may be designated as "dual fuel" or "combination".

3.1.11**butterfly damper**

single-blade damper, which pivots about its centre

3.1.12**casing**

metal plate used to enclose the fired heater

3.1.13**castable**

insulating concrete poured or gunned in place to form a rigid refractory shape or structure

3.1.14**ceramic fibre**

fibrous refractory insulation which can be in the form of refractory ceramic fibre (RCF) or man-made vitreous fibre (MMVF)

NOTE Applicable forms include bulk, blanket, board, modules, paper, coatings, pumpables and vacuum-formed shapes.

3.1.15**convection section**

portion of the heater in which the heat is transferred to the tubes primarily by convection

3.1.16**corbel**

projection from the refractory surface generally used to prevent flue gas from bypassing the tubes of the convection section if they are on a staggered pitch

3.1.17**corrosion allowance**

material thickness added to allow for material loss during the design life of the component

3.1.18**corrosion rate**

rate of reduction in the material thickness due to chemical attack from the process fluid or flue gas or both

3.1.19**crossover**

interconnecting piping between any two heater-coil sections

3.1.20**damper**

device for introducing a variable resistance in order to regulate the flow of flue gas or air

3.1.21**direct-APH**

heat exchanger that transfers heat directly between the flue gas and the combustion air

NOTE A regenerative APH uses heated rotating elements and a recuperative design uses stationary tubes, plates or cast-iron elements to separate the two heating media.

3.1.22**draught**

negative pressure (vacuum) of the air and/or flue gas measured at any point in the heater

3.1.23**draught loss**

pressure drop (including buoyancy effect) through duct conduits or across tubes and equipment in air and flue gas systems

3.1.24

duct

conduit for air or flue gas flow

3.1.25

fuel efficiency

total heat absorbed divided by the total input of heat derived from the combustion of fuel only (lower heating value basis)

NOTE This definition excludes sensible heat of the fuels and applies to the net amount of heat exported from the unit.

3.1.26

thermal efficiency

total heat absorbed divided by the total input of heat derived from the combustion of fuel plus sensible heats from air, fuel and any atomizing medium

3.1.27

erosion

reduction in material thickness due to mechanical attack from a fluid

3.1.28

excess air

amount of air above the stoichiometric requirement for complete combustion

NOTE Excess air is expressed as a percentage.

3.1.29

extended surface

heat-transfer surface in the form of fins or studs attached to the heat-absorbing surface

3.1.30

extension ratio

ratio of total outside exposed surface to the outside surface of the bare tube

iTech STANDARD PREVIEW
(standards.iteh.ai)
<https://standards.iteh.ai/catalog/standards/sist/cfb75800-71e2-4dc9-ac22-431100000000/iso-13705-2012>

3.1.31

flue gas

gaseous product of combustion including excess air

3.1.32

forced-draught heater

heater for which combustion air is supplied by a fan or other mechanical means

3.1.33

fouling allowance

factor to allow for a layer of residue that increases the pressure drop

NOTE 1 This residue is usually a build-up of coke or scale on the inner surface of a coil.

NOTE 2 The fouling allowance is used in calculating the fouled pressure drop.

3.1.34

fouling resistance

factor used to calculate the overall heat transfer coefficient

NOTE The inside fouling resistance is used to calculate the maximum metal temperature for design. The external fouling resistance is used to compensate the loss of performance due to deposits on the external surface of the tubes or extended surface.

3.1.35**guillotine
isolation blind**

single-blade device used to isolate equipment or heaters

3.1.36**header
return bend**

cast or wrought fitting shaped in a 180° bend and used to connect two or more tubes

3.1.37**header box**

internally insulated compartment, separated from the flue gas stream, which is used to enclose a number of headers or manifolds

NOTE Access is afforded by means of hinged doors or removable panels.

3.1.38**heat absorption**

total heat absorbed by the coils, excluding any combustion air preheat

3.1.39**average heat flux density**

heat absorbed divided by the exposed heating surface of the coil section

NOTE Average flux density for an extended-surface tube is indicated on a bare surface basis with extension ratio noted.

3.1.40**maximum heat flux density**

maximum local rate of heat transfer in the coil section

3.1.41**total heat release**

heat liberated from the specified fuel, using the lower heating value of the fuel

3.1.42**volumetric heat release**

heat released (net) divided by the net volume of the radiant section, excluding the coils and refractory dividing walls

3.1.43**higher heating value****gross heating value**

total heat obtained from the combustion of a specified fuel at 15 °C (60 °F)

3.1.44**lower heating value****net heating value**

higher heating value minus the latent heat of vaporization of the water formed by combustion of hydrogen in the fuel

3.1.45**hot-face layer**

refractory layer exposed to the highest temperatures in a multilayer or multi-component lining

3.1.46**hot-face temperature**

temperature of the refractory surface in contact with the flue gas or heated combustion air

3.1.47

indirect APH

fluid-to-air heat-transfer device

NOTE The heat transfer can be accomplished by using a heat-transfer fluid, process stream or utility stream that has been heated by the flue gas or other means. A heat pipe APH uses a vaporizing/condensing fluid to transfer heat between the flue gas and air.

3.1.48

induced-draught heater

heater that uses a fan to remove flue gases and to maintain a negative pressure in the heater to induce combustion air without a forced-draught fan

3.1.49

interface temperature

calculated temperature between each layer of multilayer or multi-component refractory construction

3.1.50

jump over

interconnecting pipework within a heater coil section

3.1.51

louvre damper

damper consisting of several blades, each of which pivots about its centre and is linked to the other blades for simultaneous operation

3.1.52

manifold

chamber for the collection and distribution of fluid to or from multiple parallel flow paths

3.1.53

man-made vitreous fibre

MMVF

synthetic amorphous glass insulation fibre, based on a calcium, magnesium and silicate chemistry, that has enhanced solubility in body fluids

iTeh STANDARD PREVIEW
(standards.iteh.ai)
ISO 13705:2012
<https://standards.iteh.ai/catalog/standards/sist/cfb75800-71e2-4dc9-ac22-0d20fe12f912/iso-13705-2012>

3.1.54

metal fibre reinforcement

stainless-steel needles added to castable for improved toughness and durability

3.1.55

monolithic lining

single-component lining system

3.1.56

mortar

refractory-material preparation used for laying and bonding refractory bricks

3.1.57

multi-component lining

refractory system consisting of two or more layers of different refractory types

NOTE Examples of refractory types are castable, insulating firebrick, firebrick, block, board and ceramic fibre.

3.1.58

multilayer lining

refractory system consisting of two or more layers of the same refractory type

3.1.59

natural-draught heater

heater in which a stack effect induces the combustion air and removes the flue gases

3.1.60**normal heat release**

design heat absorption of the heater divided by the calculated fuel efficiency

3.1.61**pass
stream**

flow circuit consisting of one or more tubes in series

3.1.62**pilot**

small burner that provides ignition energy to light the main burner

3.1.63**plenum
windbox**

chamber surrounding the burners that is used to distribute air to the burners or reduce combustion noise

3.1.64**plug header**

cast return bend provided with one or more openings for the purpose of inspection or mechanical tube cleaning

3.1.65**pressure design code**

recognized pressure vessel standard specified or agreed by the purchaser

EXAMPLE ASME Boiler and Pressure Vessel Code, Section VIII

3.1.66**pressure drop**

difference between the inlet and the outlet static pressures between termination points, excluding the static differential head

3.1.67**primary air**

portion of the total combustion air that first mixes with the fuel

3.1.68**protective coating**

corrosion-resistant material applied to a metal surface

EXAMPLE

Coating on casing plates behind porous refractory materials to protect against sulfur in the flue gases.

3.1.69**radiant section**

portion of the heater in which heat is transferred to the tubes primarily by radiation

3.1.70**radiation loss
setting loss**

heat lost to the surroundings from the casing of the heater and the ducts and auxiliary equipment (when heat recovery systems are used)

3.1.71**secondary air**

air supplied to the fuel to supplement primary air