

Designation: F1600 - 95a(Reapproved 2007)

Standard Terminology Relating to Bioremediation¹

This standard is issued under the fixed designation F1600; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

- 1.1 This terminology defines the terminology used in test methods, specifications, guides, and practices related to bioremediation technology.
- 1.2 These definitions are written to ensure that standards related to bioremediation technology are understood and interpreted properly.

2. Referenced Documents

2.1 ASTM Standards:²

F873 Guide for Incinerating Oil Spill Wastes at Temporary Field Locations (Withdrawn 2010)³

F1481 Guide for Ecological Considerations for the Use of Bioremediation in Oil Spill Response—Sand and Gravel Beaches (Withdrawn 2010)³

3. Terminology

3.1 Definitions:

aerobes—organisms that require air or free oxygen for growth.

F1481

anaerobes—organisms that grow in the absence of air or oxygen and do not use molecular oxygen in respiration.

7148

arctic—the biogeographic realm that comprises the tundra and treeless grounds lying north of the timberline in the Northern hemisphere or south of the timberline in the Southern hemisphere.

bioaugmentation—the addition of microorganisms (predominantly bacteria) to increase the biodegradation rate of target pollutants.

F1481

¹ This terminology is under the jurisdiction of ASTM Committee F20 on Hazardous Substances and Oil Spill Response and is the direct responsibility of Subcommittee F20.24 on Bioremediation.

biodegradation—the chemical alteration and breakdown of a substance, usually to smaller products caused by microorganisms or their enzymes.

F1481

bioremediation—the enhancement of biodegradation.

bioremediation agents—inorganic and organic compounds and microorganisms that enhance biological degradation processes, predominantly microbial.

F1481

biostimulation—the addition of microbial nutrients, oxygen, heat, or water, or some combination thereof, to enhance the rate of biodegradation of target pollutants by indigenous species (predominantly bacteria and fungi).

buffer—a solution of partially ionized acids or bases capable of reducing pH changes in the presence of added alkalis or acids.

carcinogen—cancer-causing agent.

culture—controlled inoculation, growth, and harvesting of known microorganisms.

decomposers—microorganisms, predominantly bacteria and fungi, that convert complex organic matter into simpler organic and inorganic molecules.

disinfectants—physical and chemical agents used for inactivating or destroying microorganisms.

ecosystem—organisms and the surrounding environment combined in a community that is self-supporting.F1481

effluent—the liquid discharge from a process.

end product—the chemical compound resulting from a particular metabolic process.

enrichment culture—a liquid culture that enhances the growth of a given type of organism.

landfill—a land disposal technique that uses excavated pits to contain the oil spill waste material. The waste is placed in the excavation, covered over, and left to degrade.

leachate—the liquid residue from the migration of environmental pollutants mediated by surface or ground water.

marine—relating to the ocean.

F1481

Current edition approved April 1, 2007. Published May 2007. Originally approved in 1995. Last previous edition approved in 2001 as F1600 - 95a (2001). DOI: 10.1520/F1600-95AR07.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website

³ The last approved version of this historical standard is referenced on www.astm.org.



medium—the material that supports the growth and reproduction of microorganisms.

mesophile—an organism with an optimum growth temperature range of 20 to 45°C.

metabolic pathway—the sequence of biochemical reactions that allows conversion for carbon or energy assimilation.

microbes—microscopic organisms, including algae, bacteria, fungi, protozoa, and viruses.

mineralization—the microbial-mediated breakdown of organic materials into inorganic materials.

mutagen—a substance that increases the normal mutation rate.

nutrient—a substance that supports organismal growth. F1481

pathogens—organisms that are capable of causing disease.

petri plate—a dish designed to contain solid growth medias.

plasmids—independently-replicating extrachromosomal genetic material.

recalcitrant—a substance that is resistant to microbial degradation.

terrestrial—consisting of land, as distinguished from water.

toxicity—the property of a material, or combination of materials, to adversely affect organisms.

tropical—the region lying between the tropics of Cancer and Capricorn.

tundra—the vast, treeless, nearly level plains of the arctic regions.

viability—the ability to grow and reproduce.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the ASTM website (www.astm.org/COPYRIGHT/).

Document Preview

ASTM F1600-95a(2007)

/catalog/standards/astm/d5636ea3-752d-49ea-b415-4b1a92b04a3a/astm-f1600-95a-2007