

# ETSI TS 123 280 V14.3.0 (2017-10)



**LTE;**  
**Common functional architecture**  
**to support mission critical services;**  
**Stage 2**  
**(3GPP TS 23.280 version 14.3.0 Release 14)**



---

Reference

RTS/TSGS-0623280ve30

---

Keywords

LTE

---

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at  
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M** logo is protected for the benefit of its Members.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	9
1 Scope .....	10
2 References .....	10
3 Definitions, symbols and abbreviations .....	11
3.1 Definitions .....	11
3.2 Symbols.....	12
3.3 Abbreviations .....	12
4 Introduction .....	13
5 Assumptions and architectural requirements.....	14
5.1 Assumptions .....	14
5.1.1 Service continuity .....	14
5.1.2 Trust domain.....	14
5.2 Architectural requirements .....	14
5.2.1 General architectural requirements .....	14
5.2.2 Roaming requirements .....	15
5.2.3 UE-to-network relay MC service requirements .....	15
5.2.4 MC service user profile requirements .....	15
5.2.5 MC service group affiliation and MC service group de-affiliation .....	15
5.2.6 GCS AS requirements for the MC services .....	16
5.2.7 Bearer management .....	17
5.2.7.0 General .....	17
5.2.7.1 MBMS bearer management .....	17
5.2.7.2 EPS bearer considerations .....	18
5.2.8 External applications access to services in a MC system.....	18
6 Involved business relationships.....	18
7 Functional model .....	21
7.1 General .....	21
7.2 Description of the planes .....	21
7.3 Functional model description .....	21
7.3.1 On-network functional model .....	21
7.3.2 Off-network functional model .....	24
7.4 Functional entities description.....	25
7.4.1 General.....	25
7.4.2 Application plane.....	25
7.4.2.1 General .....	25
7.4.2.2 Common services core .....	25
7.4.2.2.1 Configuration management client.....	25
7.4.2.2.2 Configuration management server.....	26
7.4.2.2.3 Group management client.....	26
7.4.2.2.4 Group management server.....	26
7.4.2.2.5 Identity management client .....	26
7.4.2.2.6 Identity management server.....	26
7.4.2.2.7 Key management client .....	26
7.4.2.2.8 Key management server .....	26
7.4.2.2.9 Location management client.....	27
7.4.2.2.10 Location management server .....	27
7.4.2.3 MC service .....	27
7.4.2.3.1 MC service client.....	27
7.4.2.3.2 MC service server.....	27

7.4.2.3.3	MC service user database .....	27
7.4.3	Signalling control plane .....	27
7.4.3.1	SIP entities .....	27
7.4.3.1.1	Signalling user agent .....	27
7.4.3.1.2	SIP AS .....	27
7.4.3.1.3	SIP core .....	28
7.4.3.1.3.1	General.....	28
7.4.3.1.3.2	Local inbound / outbound proxy.....	28
7.4.3.1.3.3	Registrar finder .....	28
7.4.3.1.3.4	Registrar / application service selection.....	29
7.4.3.2	SIP database .....	29
7.4.3.2.1	General .....	29
7.4.3.2.2	SIP database logical functions.....	30
7.4.3.3	HTTP entities .....	30
7.4.3.3.1	HTTP client .....	30
7.4.3.3.2	HTTP proxy.....	30
7.4.3.3.3	HTTP server .....	31
7.5	Reference points .....	31
7.5.1	General reference point principle.....	31
7.5.2	Application plane.....	31
7.5.2.1	General .....	31
7.5.2.2	Reference point CSC-1 (between the identity management client and the identity management server) .....	31
7.5.2.3	Reference point CSC-2 (between the group management client and the group management server for configuration while UE is on-network) .....	31
7.5.2.4	Reference point CSC-3 (between the MC service server and the group management server).....	31
7.5.2.5	Reference point CSC-4 (between the configuration management client and the configuration management server for configuration while UE is on-network) .....	32
7.5.2.6	Reference point CSC-5 (between the MC service server and the configuration management server) .....	32
7.5.2.7	Reference point CSC-7 (between the group management servers).....	32
7.5.2.8	Reference point CSC-8 (between the key management server and the key management client).....	32
7.5.2.9	Reference point CSC-9 (between the key management server and the MC service server) .....	32
7.5.2.10	Reference point CSC-10 (between the key management server and the group management server) .....	33
7.5.2.11	Reference point CSC-11 (between the configuration management client and the configuration management server for configuration while UE is off-network).....	33
7.5.2.12	Reference point CSC-12 (between the group management client and the group management server for configuration while UE is off-network).....	33
7.5.2.13	Reference point CSC-13 (between the configuration management server and the MC service user database) .....	33
7.5.2.14	Reference point CSC-14 (between the location management client and the location management server) .....	33
7.5.2.15	Reference point CSC-15 (between the location management server and the MC service server) .....	33
7.5.3	Signalling control plane .....	34
7.5.3.1	General .....	34
7.5.3.2	Reference point SIP-1(between the signalling user agent and the SIP core).....	34
7.5.3.3	Reference point SIP-2 (between the SIP core and the SIP AS).....	34
7.5.3.4	Reference point SIP-3 (between the SIP core and SIP core).....	34
7.5.3.5	Reference point HTTP-1 (between the HTTP client and the HTTP proxy).....	35
7.5.3.6	Reference point HTTP-2 (between the HTTP proxy and the HTTP server).....	35
7.5.3.7	Reference point HTTP-3 (between the HTTP proxy and HTTP proxy) .....	35
7.5.3.8	Reference point AAA-1 (between the SIP database and the SIP core) .....	35
8	Identities .....	35
8.1	Application plane .....	35
8.1.1	Mission Critical user identity (MC ID).....	35
8.1.2	MC service user identity (MC service ID).....	35
8.1.3	MC service group identity (MC service group ID).....	36
8.1.3.1	General .....	36
8.1.3.2	MC service group ID management (off-network operation).....	36
8.2	SIP signalling control plane.....	37

8.3	Relationship between identities in different planes .....	37
8.3.1	Relationship between MC service ID and public user identity .....	37
8.3.2	Relationship between MC service group ID and public service identity .....	38
9	Application of functional model to deployments .....	38
9.1	General .....	38
9.2	Architecture model and deployment scenarios for on-network operations .....	39
9.2.1	On-network architectural model .....	39
9.2.1.1	On-network architectural model diagram .....	39
9.2.1.2	Application services layer .....	39
9.2.1.2.1	Overview .....	39
9.2.1.2.2	Common services core .....	39
9.2.1.2.3	MC services .....	40
9.2.1.3	SIP core .....	40
9.2.1.4	EPS .....	40
9.2.1.5	UE 1 .....	40
9.2.1.6	UE 2 .....	40
9.2.2	Deployment scenarios .....	40
9.2.2.1	Administration of MC service, SIP core and EPS .....	40
9.2.2.1.1	General .....	40
9.2.2.1.2	Common administration of all planes .....	41
9.2.2.1.3	MC service provider separate from SIP core and EPS .....	41
9.2.2.1.4	MC service provider administers SIP core, separate from EPS .....	42
9.2.2.1.5	SIP core partially administered by both PLMN operator and MC service provider .....	43
9.2.2.1.6	PLMN operator administers SIP core with SIP identities administered by MC service provider .....	43
9.2.2.2	MC service user database, SIP database and HSS .....	44
9.2.2.3	Control of bearers by SIP core and MC service server .....	47
9.2.2.3.1	General .....	47
9.2.2.3.2	Control of bearers by SIP core .....	47
9.2.2.3.3	Control of bearers by MC service server .....	47
9.3	Architecture model for off-network operations .....	48
9.3.1	Off-network architectural model diagram .....	48
9.3.2	UE 3 .....	48
9.3.3	UE 4 .....	49
9.3.4	Offline common services server .....	49
9.4	Architecture model for roaming .....	49
10	Procedures and information flows .....	49
10.1	MC service configuration .....	49
10.1.1	General .....	49
10.1.2	Information flows for MC service configuration .....	50
10.1.2.1	Store group configuration request .....	50
10.1.2.2	Store group configuration response .....	51
10.1.2.3	Get group configuration request .....	51
10.1.2.4	Get group configuration response .....	51
10.1.2.5	Subscribe group configuration request .....	51
10.1.2.6	Subscribe group configuration response .....	52
10.1.2.7	Notify group configuration request .....	52
10.1.2.8	Notify group configuration response .....	52
10.1.3	MC service UE configuration data .....	52
10.1.3.1	General .....	52
10.1.3.2	Procedures .....	52
10.1.3.3	Structure of UE configuration data .....	53
10.1.4	MC service user profile .....	53
10.1.4.1	General .....	53
10.1.4.2	Information flows for MC service user profile .....	54
10.1.4.2.1	Get MC service user profile request .....	54
10.1.4.2.2	Get MC service user profile response .....	54
10.1.4.2.3	Notification for MC service user profile data update .....	54
10.1.4.2.4	Get updated MC service user profile data request .....	55
10.1.4.2.5	Get updated MC service user profile data response .....	55

10.1.4.2.6	Update MC service user profile data request.....	55
10.1.4.2.7	Update MC service user profile data response .....	55
10.1.4.2.8	Update pre-selected MC service user profile request .....	55
10.1.4.2.9	Update pre-selected MC service user profile response .....	56
10.1.4.2.10	Update selected MC service user profile request.....	56
10.1.4.2.11	Update selected MC service user profile response .....	56
10.1.4.3	MC service user obtains the MC service user profile(s) from the network.....	56
10.1.4.4	MC service user receives updated MC service user profile data from the network.....	57
10.1.4.5	MC service user updates MC service user profile data to the network .....	58
10.1.4.6	Updating the pre-selected MC service user profile .....	59
10.1.4.7	Updating the selected MC service user profile for an MC service.....	60
10.1.5	MC service group configuration management.....	62
10.1.5.1	Store group configurations at the group management server .....	62
10.1.5.2	Retrieve group configurations at the group management client.....	62
10.1.5.3	Subscription and notification for group configuration data.....	63
10.1.5.4	Structure of group configuration data .....	64
10.1.5.5	Dynamic data associated with a group .....	64
10.2	Group management (on-network) .....	65
10.2.1	General.....	65
10.2.2	Information flows for group management .....	65
10.2.2.1	Group creation request .....	65
10.2.2.2	Group creation confirmation response .....	65
10.2.2.3	Group regroup request (group management client – group management server) .....	65
10.2.2.4	Group regroup response (group management server – group management client).....	66
10.2.2.5	Group regroup teardown request.....	66
10.2.2.6	Group regroup teardown response .....	66
10.2.2.7	Group creation notify .....	66
10.2.2.8	Group regroup notify.....	67
10.2.2.9	Group regroup teardown notify.....	67
10.2.2.10	Group regroup teardown notification.....	67
10.2.2.11	Group regroup teardown notification response .....	67
10.2.2.12	Group regroup request (group management server – group management server).....	68
10.2.2.13	Group regroup response (group management server – group management server).....	68
10.2.2.14	Group regroup notification.....	68
10.2.2.15	Group regroup notification response.....	68
10.2.2.16	Group information query request .....	68
10.2.2.17	Group information query response.....	69
10.2.2.18	Group membership update request.....	69
10.2.2.19	Group membership update response .....	69
10.2.2.20	Group membership notification .....	69
10.2.3	Group creation .....	70
10.2.4	Group regrouping.....	71
10.2.4.1	Temporary group formation - group regrouping within an MC system .....	71
10.2.4.2	Temporary group formation involving multiple MC systems.....	72
10.2.4.3	Temporary group tear down involving multiple group host servers .....	74
10.2.5	Membership and affiliation list query .....	76
10.2.5.1	General .....	76
10.2.5.2	Procedure .....	76
10.2.6	Group membership .....	76
10.2.6.1	Group membership notification .....	76
10.2.6.2	Group membership update by authorized user.....	77
10.3	Pre-established session (on-network) .....	78
10.3.1	General.....	78
10.3.2	Procedures.....	79
10.3.2.1	General .....	79
10.3.2.2	Pre-established session establishment .....	79
10.3.2.3	Pre-established session modification .....	80
10.3.2.4	Pre-established session release.....	81
10.4	Simultaneous session (on-network).....	82
10.4.1	General.....	82
10.5	Use of UE-to-network relay .....	82
10.5.1	UE-to-network relay service authorization.....	82

10.5.2	UE-to-network relay MC service.....	83
10.6	General user authentication and authorization for MC services.....	83
10.7	Use of MBMS transmission .....	84
10.7.1	General.....	84
10.7.2	Information flows for MBMS transmission.....	84
10.7.2.1	MBMS bearer announcement.....	84
10.7.2.2	MBMS listening status report .....	84
10.7.2.3	MBMS suspension reporting instruction.....	85
10.7.2.4	Discover bearer request.....	85
10.7.2.5	Discover bearer response .....	85
10.7.2.6	Media distribution request.....	86
10.7.2.7	Media distribution response .....	86
10.7.2.8	Identify multicast participants request .....	86
10.7.2.9	Remove call from bearer request .....	87
10.7.3	Procedures for MBMS usage.....	87
10.7.3.1	Use of pre-established MBMS bearers.....	87
10.7.3.1.1	General .....	87
10.7.3.1.2	Procedure.....	87
10.7.3.2	Use of dynamic MBMS bearer establishment.....	89
10.7.3.3	Switching from MBMS bearer to unicast bearer.....	90
10.7.3.4	Use of MBMS bearer for application level control signalling .....	91
10.7.3.4.1	Description .....	91
10.7.3.4.2	Procedure.....	91
10.7.3.5	MBMS bearer announcement over MBMS bearer.....	92
10.7.3.5.1	Description .....	92
10.7.3.5.2	Procedure.....	92
10.7.3.6	MBMS bearer quality detection.....	94
10.7.3.6.1	Description .....	94
10.7.3.6.2	Procedure.....	94
10.7.3.7	Service continuity in MBMS scenarios.....	95
10.7.3.7.1	General .....	95
10.7.3.7.2	Service continuity when moving from one MBSFN to another .....	95
10.7.3.7.3	Service continuity with a UE-to-Network relay .....	97
10.7.3.8	MBMS suspension notification.....	98
10.7.3.8.1	Description .....	98
10.7.3.8.2	Procedure.....	98
10.7.3.9	Multi-server bearer coordination.....	99
10.7.3.9.1	General .....	99
10.7.3.9.2	Procedures .....	100
10.8	Affiliation and de-affiliation to/from MC service group(s).....	103
10.8.1	General.....	103
10.8.2	Information flows .....	103
10.8.2.1	MC service group affiliation request.....	103
10.8.2.2	MC service group affiliation request (MC service server – MC service server).....	103
10.8.2.3	MC service group affiliation response .....	103
10.8.2.4	MC service group affiliation response (MC service server – MC service server) .....	104
10.8.2.5	Group affiliation status update .....	104
10.8.2.6	MC service group de-affiliation request.....	104
10.8.2.7	MC service group de-affiliation request (MC service server – MC service server).....	104
10.8.2.8	MC service group de-affiliation response .....	105
10.8.2.9	MC service group de-affiliation response (MC service server – MC service server) .....	105
10.8.2.10	Group de-affiliation status update .....	105
10.8.2.11	MC service group affiliation change request.....	105
10.8.2.12	MC service group affiliation change response .....	106
10.8.3	Affiliation .....	106
10.8.3.1	MC service group affiliation procedure .....	106
10.8.3.2	Affiliation to MC service group(s) defined in partner MC service system .....	107
10.8.3.2.1	Functional description .....	107
10.8.3.2.2	Procedure.....	107
10.8.4	De-affiliation from MC service group(s).....	109
10.8.4.1	General .....	109
10.8.4.2	MC service group de-affiliation procedure .....	109



10.8.4.3	De-affiliation from MC service group(s) defined in partner MC service system.....	110
10.8.5	Remote change of affiliation.....	111
10.8.5.1	Remote change of affiliation for groups defined in primary MC service system.....	111
10.8.5.1.1	Authorized user remotely changes another MC service user's affiliated MC service group(s) – mandatory mode .....	111
10.8.5.1.2	Authorized user remotely changes another MC service user's affiliated MC service group(s) – negotiated mode.....	113
10.8.5.2	Remote change of affiliation for groups defined in partner MC service system.....	114
10.8.5.2.1	Authorized user remotely changes another MC service user's affiliated MC service group(s) defined in partner MC service system – mandatory mode .....	114
10.9	Location management (on-network) .....	116
10.9.1	General.....	116
10.9.2	Information flows for location information .....	116
10.9.2.1	Location reporting configuration .....	116
10.9.2.2	Location information report .....	117
10.9.2.3	Location information request .....	117
10.9.2.4	Location reporting trigger .....	117
10.9.2.5	Location information subscription request.....	118
10.9.2.6	Location information subscription response .....	118
10.9.2.7	Location information notification .....	118
10.9.3	Procedure .....	119
10.9.3.1	Event-triggered location reporting procedure .....	119
10.9.3.2	On-demand location reporting procedure.....	120
10.9.3.3	Client-triggered location reporting procedure .....	120
10.9.3.4	Location reporting cancel procedure.....	121
10.9.3.5	Location information subscription procedure .....	122
10.9.3.6	Usage of location information procedure.....	122
10.9.3.6.1	Event-trigger location information notification procedure.....	122
10.9.3.6.2	On-demand usage of location information procedure.....	123
10.10	Emergency Alert .....	123
10.10.1	On-network emergency alert.....	123
10.10.1.1	General .....	123
10.10.1.2	MC service emergency alert.....	124
10.10.1.2.1	MC service emergency alert initiation.....	124
10.10.1.2.2	MC service emergency state cancel.....	126
10.10.2	Off-network emergency alert.....	128
10.10.2.1	General.....	128
10.10.2.2	MC service emergency alert.....	128
10.10.2.2.1	Emergency alert initiation .....	128
10.10.2.2.2	Emergency state cancel .....	129
<b>Annex A (normative): Configuration data for MC services.....</b>		<b>131</b>
A.1	General .....	131
A.2	MC service UE configuration data.....	132
A.3	MC service user profile configuration data.....	132
A.4	Group configuration data.....	132
A.5	MC service configuration data .....	137
A.6	Initial MC service UE configuration data .....	137
<b>Annex B (informative): Service continuity for MC service .....</b>		<b>139</b>
B.1	Service continuity between on-network MC service and UE-to-network relay MC service .....	139
<b>Annex C (informative): Change history .....</b>		<b>142</b>
History .....		145

---

# Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

**PREVIEW**  
iTech STANDARD  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/553f56d6-0e34-42f5-a4f4-9f02107b8ee/etsi-ts-123-280-v14.3.0-2017-10>

---

# 1 Scope

This document specifies the common functional architecture, procedures and information flows needed to support mission critical services including the common services core architecture.

The corresponding service requirements are defined in 3GPP TS 22.179 [2], 3GPP TS 22.280 [3], 3GPP TS 22.281 [4] and 3GPP TS 22.282 [5].

The present document is applicable primarily to mission critical services using E-UTRAN access based on the EPC architecture defined in 3GPP TS 23.401 [17]. Certain MC service functions such as dispatch and administrative functions could also be supported via non-3GPP access networks but no additional functionality is specified to support non-3GPP access.

The common functional architecture to support mission critical services can be used for public safety applications and also for general commercial applications e.g. utility companies and railways.

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 22.179: "Mission Critical Push to Talk (MCPTT) over LTE; Stage 1".
- [3] 3GPP TS 22.280: "Mission Critical Services Common Requirements (MCCoRe); Stage 1".
- [4] 3GPP TS 22.281: "Mission Critical Video services over LTE".
- [5] 3GPP TS 22.282: "Mission Critical Data services over LTE".
- [6] 3GPP TS 23.002: "Network Architecture".
- [7] 3GPP TS 23.179: "Functional architecture and information flows to support mission critical communication services; Stage 2".
- [8] 3GPP TS 23.203: "Policy and charging control architecture".
- [9] 3GPP TS 23.228: "IP Multimedia Subsystem (IMS); Stage 2".
- [10] 3GPP TS 23.237: "IP Multimedia Subsystem (IMS) Service Continuity; Stage 2".
- [11] 3GPP TS 23.246: "Multimedia Broadcast/Multicast Service (MBMS); Architecture and functional description".
- [12] 3GPP TS 23.281: "Functional architecture and information flows to support Mission Critical Video (MCVideo); Stage 2".
- [13] 3GPP TS 23.282: "Functional architecture and information flows to support Mission Critical Data (MCData); Stage 2".
- [14] 3GPP TS 23.303: "Proximity-based services (ProSe); Stage 2".
- [15] 3GPP TS 23.335: "User Data Convergence (UDC); Technical realization and information flows".

- [16] 3GPP TS 23.379: "Functional architecture and information flows to support Mission Critical Push To Talk (MCPTT); Stage 2".
- [17] 3GPP TS 23.401: "General Packet Radio Service (GPRS) enhancements for Evolved Universal Terrestrial Radio Access Network (E-UTRAN) access".
- [18] 3GPP TS 23.468: "Group Communication System Enablers for LTE (GCSE\_LTE); Stage 2".
- [19] 3GPP TS 29.283: "Diameter Data Management Applications".
- [20] 3GPP TS 33.179: "Security of Mission Critical Push-To-Talk (MCPTT)".
- [21] 3GPP TS 36.300: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2".
- [22] IETF RFC 5245 (April 2010): "Interactive Connectivity Establishment (ICE): A Protocol for Network Address Translator (NAT) Traversal for Offer/Answer Protocols".
- [23] GSMA PRD IR.92 v10.0: "IMS Profile for Voice and SMS".
- [24] GSMA PRD IR.88 v15.0: "LTE and EPC Roaming Guidelines".
- [25] 3GPP TS 33.180: "Security of the mission critical service".

---

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

**Active MC service user profile:** The MC service user profile that is currently used by an MC service client of an MC service user while receiving MC service.

**Location:** The current physical location of the MC service UE.

**MC service:** A generic name for any one of the three mission critical services: either MCPTT, or MCVideo, or MCDData.

**MC service affiliated group member:** An MC service user who has indicated an interest in a particular MC service group and has been accepted to participate in MC service group communication for that MC service group.

**MC service client:** A generic name for the client application function of a specific MC service. MC service client could be replaced by MCPTT client, or MCVideo client, or MCDData client depending on the context.

**MC service group:** A defined set of MC service users with associated communication dispositions (e.g. media restrictions, default priority and commencement directions) configured for the use with one or more MC services.

**MC service group affiliation:** A mechanism by which an MC service user's MC service(s) communication interest in one or more MC service groups is determined.

**MC service group call:** A mechanism by which an MC service user can make a one-to-many MC service(s) transmission to other users that are members of MC service group(s).

**MC service group de-affiliation:** A mechanism by which an MC service user's MC service(s) communication interest in one or more MC service groups is removed.

**MC service group home system:** The mission critical system where the MC service group is defined.

**MC service group host MC service server:** The MC service server within a mission critical system which provides centralised support for a particular MC service of an MC service group defined in a MC service group home system.

**MC service group member:** An MC service user, whose MC service ID is listed in a particular MC service group.

**MC service ID:** A generic name for the user ID of a mission critical user within a specific MC service. MC service ID could be replaced by MCPTT ID, or MCVideo ID, or MCDData ID depending on the context.

**MC service server:** A generic name for the server application function of a specific MC service. MC service server could be replaced by MCPTT server, MCVideo server, or MCDData server depending on the context.

**MC service user:** An authorized user, who can use an MC service UE to participate in one or more MC services.

**MC service user profile:** The set of information associated to an MC service user that allows that user to employ one or more MC services in a given role and from a given MC service UE.

**MC service UE:** A UE that can be used to participate in one or more MC services.

**MC user:** A user, identified by an MC ID, who, after authorization, obtains mission critical service(s).

**Mission critical system:** The collection of applications, services, and enabling capabilities required to provide a single mission critical service or multiple mission critical services to one or more mission critical organizations.

**Pre-selected MC service user profile:** The MC service user profile that is to be selected as the active MC service user profile through configuration, and applicable for an authenticated MC service user upon MC service authorization.

**Selected MC service user profile:** The MC service user profile that is to be selected as the active MC service user profile for an MC service upon request by an MC service user.

For the purposes of the present document, the following terms given in 3GPP TS 22.280 [3] apply

**Mission Critical**  
**Mission Critical Applications**  
**Mission Critical Organization**  
**Mission Critical Service**

## 3.2 Symbols

For the purposes of the present document, the symbols given in 3GPP TS 22.280 [3] apply

**Nc6**

## 3.3 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

APN	Access Point Name
BM-SC	Broadcast Multicast Service Centre
CSC	Common Services Core
CSCF	Call Server Control Function
DPF	Direct Provisioning Function
E-UTRAN	Evolved Universal Terrestrial Radio Access Network
EPC	Evolved Packet Core
EPS	Evolved Packet System
GBR	Guaranteed Bit Rate
GCS AS	Group Communication Service Application Server
GCSE_LTE	Group Communication Service Enabler over LTE
GRUU	Globally Routable User agent URI
HSS	Home Subscriber Server
HTTP	Hyper Text Transfer Protocol
I-CSCF	Interrogating CSCF
IARI	IMS Application Reference Identifier
ICE	Interactive Connectivity Establishment