

ETSI EN 300 175-5 V2.8.1 (2019-12)



Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard available at
https://standards.iteh.ai/catalog/standards/sis/01440144-2019-053-e215-4f1c-8455-49d37fd81f7/etsi-en-300-175-v2-8-1-2019-12

ReferenceREN/DECT-00325

KeywordsDECT, IMT-2000, mobility, radio, TDD, TDMA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	16
Foreword.....	16
Modal verbs terminology.....	16
1 Scope	17
2 References	18
2.1 Normative references	18
2.2 Informative references.....	22
3 Definition of terms, symbols and abbreviations.....	23
3.1 Terms.....	23
3.2 Symbols.....	23
3.3 Abbreviations	24
4 Overview of the NWK layer	28
5 Overview of procedures	29
5.1 General	29
5.2 Overview of Call Control (CC)	30
5.2.1 General.....	30
5.2.2 Call establishment.....	30
5.2.2.1 Call setup	30
5.2.2.2 Service negotiation.....	31
5.2.3 Call connect	31
5.2.4 Call information.....	31
5.2.5 Service change	31
5.2.6 Call release.....	32
5.3 Overview of Supplementary Services (SS)	32
5.3.1 General.....	32
5.3.2 Keypad protocol.....	33
5.3.3 Feature key management protocol.....	33
5.3.4 Functional protocol.....	33
5.4 Overview of Connection Oriented Message Service (COMS).....	33
5.4.1 General.....	33
5.4.2 COMS establishment	34
5.4.3 Service negotiation	34
5.4.4 COMS connect.....	34
5.4.5 COMS data transfer	34
5.4.6 COMS suspend and resume	34
5.4.7 COMS release	35
5.5 Overview of ConnectionLess Message Service (CLMS)	35
5.5.0 General.....	35
5.5.1 Fixed length message service.....	35
5.5.2 Variable length message service	35
5.6 Overview of Mobility Management (MM)	35
5.6.1 General.....	35
5.6.2 Identity procedures	36
5.6.3 Authentication procedures	36
5.6.4 Location procedures.....	37
5.6.5 Access rights procedures	37
5.6.6 Key allocation procedure	37
5.6.7 Parameter retrieval procedure	38
5.6.8 Cipherring related procedure.....	38
5.6.9 External protocol information procedure	38
5.7 Overview of Link Control Entity (LCE)	38
5.7.1 General.....	38
5.7.2 Data Link Endpoint Identifier (DLEI)	38
5.7.3 Data link establishment.....	39

5.7.4	Data link re-establishment	39
5.7.5	Data link release	39
5.7.6	Data link suspend and resume.....	40
5.7.7	Queuing of messages	40
5.7.8	Request paging.....	40
6	Message functional definitions.....	40
6.1	Overview of message structures	40
6.1.1	Messages.....	40
6.1.2	Information elements	41
6.2	Message summaries.....	42
6.2.1	Summary of CC messages	42
6.2.2	Summary of CISS messages	42
6.2.3	Summary of COMS messages	43
6.2.4	Summary of CLMS messages.....	43
6.2.5	Summary of MM messages	44
6.2.6	Summary of LCE messages	44
6.3	S-FORMAT message functional contents.....	45
6.3.1	S-FORMAT message overview.....	45
6.3.2	CC-messages.....	45
6.3.2.1	{ CC-SETUP }	45
6.3.2.2	{ CC-INFO }	47
6.3.2.3	{ CC-SETUP-ACK }	48
6.3.2.4	{ CC-CALL-PROC }	49
6.3.2.5	{ CC-ALERTING }	50
6.3.2.6	{ CC-CONNECT }	51
6.3.2.7	{ CC-CONNECT-ACK }	52
6.3.2.8	{ CC-RELEASE }	52
6.3.2.9	{ CC-RELEASE-COM }	53
6.3.2.10	{ CC-SERVICE-CHANGE }	54
6.3.2.11	{ CC-SERVICE-ACCEPT }	55
6.3.2.12	{ CC-SERVICE-REJECT }	55
6.3.2.13	{ CC-NOTIFY }	56
6.3.2.14	{ IWU-INFO }	57
6.3.3	SS-messages (call related and call independent)	58
6.3.3.1	{ FACILITY }	58
6.3.3.2	{ HOLD }	59
6.3.3.3	{ HOLD-ACK }	59
6.3.3.4	{ HOLD-REJECT }	60
6.3.3.5	{ RETRIEVE }	60
6.3.3.6	{ RETRIEVE-ACK }	61
6.3.3.7	{ RETRIEVE-REJECT }	61
6.3.3.8	{ CISS-REGISTER }	62
6.3.3.9	{ CISS-RELEASE-COM }	63
6.3.4	COMS-messages.....	63
6.3.4.1	{ COMS-SETUP }	63
6.3.4.2	{ COMS-INFO }	64
6.3.4.3	{ COMS-ACK }	64
6.3.4.4	{ COMS-CONNECT }	65
6.3.4.5	{ COMS-RELEASE }	65
6.3.4.6	{ COMS-RELEASE-COM }	66
6.3.4.7	{ COMS-NOTIFY }	66
6.3.5	CLMS-message.....	67
6.3.5.1	{ CLMS-VARIABLE }	67
6.3.6	MM-messages.....	68
6.3.6.1	{ ACCESS-RIGHTS-ACCEPT }	68
6.3.6.2	{ ACCESS-RIGHTS-REJECT }	68
6.3.6.3	{ ACCESS-RIGHTS-REQUEST }	69
6.3.6.4	{ ACCESS-RIGHTS-TERMINATE-ACCEPT }	69
6.3.6.5	{ ACCESS-RIGHTS-TERMINATE-REJECT }	70
6.3.6.6	{ ACCESS-RIGHTS-TERMINATE-REQUEST }	70
6.3.6.7	{ AUTHENTICATION-REJECT }	71

6.3.6.8	{ AUTHENTICATION-REPLY }	71
6.3.6.9	{ AUTHENTICATION-REQUEST }	72
6.3.6.10	{ CIPHER-REJECT }	73
6.3.6.11	{ CIPHER-REQUEST }	73
6.3.6.12	{ CIPHER-SUGGEST }	74
6.3.6.13	{ DETACH }	74
6.3.6.14	{ IDENTITY-REPLY }	75
6.3.6.15	{ IDENTITY-REQUEST }	75
6.3.6.16	{ KEY-ALLOCATE }	76
6.3.6.17	{ LOCATE-ACCEPT }	77
6.3.6.18	{ LOCATE-REJECT }	77
6.3.6.19	{ LOCATE-REQUEST }	78
6.3.6.20	{ MM-INFO-ACCEPT }	79
6.3.6.21	{ MM-INFO-REJECT }	79
6.3.6.22	{ MM-INFO-REQUEST }	80
6.3.6.23	{ MM-INFO-SUGGEST }	80
6.3.6.24	{ TEMPORARY-IDENTITY-ASSIGN }	81
6.3.6.25	{ TEMPORARY-IDENTITY-ASSIGN-ACK }	82
6.3.6.26	{ TEMPORARY-IDENTITY-ASSIGN-REJ }	82
6.3.6.27	{ MM-IWU }	83
6.3.6.28	{ MM-NOTIFY }	83
6.3.7	LCE-messages	84
6.3.7.1	{ LCE-PAGE-RESPONSE }	84
6.3.7.2	{ LCE-PAGE-REJECT }	84
6.4	B-FORMAT message functional contents	85
6.4.1	B-FORMAT message overview	85
6.4.2	{ LCE-REQUEST-PAGE }	85
6.4.3	{ CLMS-FIXED }	86
7	S-FORMAT message structures	86
7.1	Overview	86
7.2	Protocol Discrimination (PD) element	87
7.3	Transaction Identifier (TI) element	87
7.4	Message type element	88
7.4.0	General	88
7.4.1	Messages for CC	89
7.4.2	Messages for SS	89
7.4.3	Messages for COMS	89
7.4.4	Messages for CLMS	90
7.4.5	Messages for MM	90
7.4.6	Messages for LCE	90
7.5	Other information elements	91
7.5.1	Coding rules	91
7.5.2	Extensions of codesets	93
7.5.3	Locking shift procedure	93
7.5.4	Non-locking shift procedure	94
7.5.5	Display and keypad elements	94
7.5.6	Repeated elements	94
7.6	Fixed length information elements	95
7.6.1	Summary	95
7.6.2	Sending complete, delimiter request and use TPUI	95
7.6.3	Repeat indicator	96
7.6.4	Basic service	96
7.6.5	Single display	97
7.6.6	Single keypad	97
7.6.7	Release reason	97
7.6.8	Signal	99
7.6.9	Timer restart	100
7.6.10	Test hook control	100
7.7	Variable length information elements	100
7.7.1	Summary	100
7.7.2	Allocation type	102

7.7.3	Alphanumeric	103
7.7.4	Auth type	104
7.7.5	Call attributes	106
7.7.6	Call identity	111
7.7.7	Called party number	112
7.7.8	Called party subaddress	113
7.7.9	Calling party number	113
7.7.10	Cipher info	114
7.7.11	Connection attributes	115
7.7.12	Connection identity	124
7.7.13	Duration	125
7.7.14	End-to-end compatibility	125
7.7.15	Facility	128
7.7.16	Feature activate	129
7.7.17	Feature indicate	131
7.7.18	Fixed identity	133
7.7.19	Identity type	134
7.7.20	Info type	135
7.7.21	InterWorking Unit (IWU) attributes	136
7.7.22	IWU packet	140
7.7.23	IWU to IWU	142
7.7.24	Key	144
7.7.25	Location area	144
7.7.26	Multi-display	145
7.7.27	Multi-keypad	146
7.7.28	NetWoRK (NWK) assigned identity	146
7.7.29	Network parameter	147
7.7.30	Portable identity	149
7.7.31	Progress indicator	152
7.7.32	RAND	153
7.7.33	Rate parameters	154
7.7.34	Reject reason	155
7.7.35	RES	156
7.7.36	RS	156
7.7.37	Segmented info	157
7.7.38	Service change info	157
7.7.39	Service class	159
7.7.40	Setup capability	159
7.7.41	Terminal capability	161
7.7.42	Transit delay	167
7.7.43	Window size	168
7.7.44	ZAP field	169
7.7.45	Escape to proprietary	169
7.7.46	Model identifier	170
7.7.47	MMS Generic Header	171
7.7.48	MMS Object Header	171
7.7.49	MMS Extended header	171
7.7.50	Time-Date	171
7.7.51	Ext h/o indicator	173
7.7.52	Called party Name	174
7.7.53	Calling party Name	175
7.7.54	Codec List	175
7.7.55	Events notification	177
7.7.55.1	General structure	177
7.7.55.2	Event types	178
7.7.56	Call information	182
7.7.57	List change details	186
7.7.58	ULE MAC Configuration Info	188
8	B-FORMAT message structures	188
8.1	General	188
8.2	LCE request paging messages	189

8.2.0	General.....	189
8.2.1	Short format message.....	189
8.2.2	Full format message.....	190
8.2.3	Long format message.....	192
8.2.4	Message elements.....	192
8.2.4.1	LCE paging header.....	192
8.2.4.2	Info fields (Full format).....	193
8.2.4.3	Default setup behaviour.....	194
8.2.4.4	Address elements in collective or group ringing.....	195
8.3	CLMS-FIXED messages.....	196
8.3.1	General message structure.....	196
8.3.2	Message elements.....	196
8.3.3	Standard message structures.....	198
8.3.3.1	General.....	198
8.3.3.2	Messages using 4-bit characters.....	198
8.3.3.3	Messages using 8-bit characters.....	198
9	Call Control (CC) procedures.....	199
9.1	General.....	199
9.2	Call Control (CC) states.....	202
9.2.1	States at PT.....	202
9.2.1.0	General.....	202
9.2.1.1	State T-00: "NULL".....	202
9.2.1.2	State T-19: "RELEASE PENDING".....	202
9.2.1.3	State T-10: "ACTIVE".....	202
9.2.1.4	State T-01: "CALL INITIATED".....	202
9.2.1.5	State T-02: "OVERLAP SENDING".....	202
9.2.1.6	State T-03: "CALL PROCEEDING".....	202
9.2.1.7	State T-04: "CALL DELIVERED".....	202
9.2.1.8	State T-06: "CALL PRESENT".....	202
9.2.1.9	State T-07: "CALL RECEIVED".....	202
9.2.1.10	State T-08: "CONNECT PENDING".....	202
9.2.2	States at FT.....	203
9.2.2.0	General.....	203
9.2.2.1	State F-00: "NULL".....	203
9.2.2.2	State F-19: "RELEASE PENDING".....	203
9.2.2.3	State F-10: "ACTIVE".....	203
9.2.2.4	State F-01: "CALL-INITIATED".....	203
9.2.2.5	State F-02: "OVERLAP SENDING".....	203
9.2.2.6	State F-03: "CALL PROCEEDING".....	203
9.2.2.7	State F-04: "CALL DELIVERED".....	203
9.2.2.8	State F-06: "CALL PRESENT".....	203
9.2.2.9	State F-07: "CALL RECEIVED".....	203
9.2.3	Optional states (PT and FT).....	204
9.2.3.0	General.....	204
9.2.3.1	States T-22 and F-22: "OVERLAP RECEIVING".....	204
9.2.3.2	States T-23 and F-23: "INCOMING CALL PROCEEDING".....	204
9.3	Call establishment procedures.....	204
9.3.1	PT initiated call establishment (outgoing call).....	204
9.3.1.0	General.....	204
9.3.1.1	Call request.....	204
9.3.1.2	Call accept or reject.....	205
9.3.1.3	Selection of lower layer resources.....	205
9.3.1.4	Connection of U-plane.....	206
9.3.1.5	Overlap sending.....	206
9.3.1.6	Call proceeding.....	207
9.3.1.7	Call confirmation.....	207
9.3.1.8	Call connection.....	208
9.3.1.9	Expiry of timer <CC.04>.....	208
9.3.2	FT initiated call establishment (incoming call).....	208
9.3.2.0	General.....	208
9.3.2.1	Call request.....	208

9.3.2.2	Call accept or reject.....	209
9.3.2.3	Selection of lower layer resources	209
9.3.2.4	Connection of U-plane	210
9.3.2.5	Overlap receiving	210
9.3.2.6	Call proceeding	210
9.3.2.7	Call confirmation	210
9.3.2.8	Call connection	211
9.3.2.9	Sending of <<TERMINAL-CAPABILITY>>.....	211
9.3.2.10	Expiry of timer <CC.04>	211
9.4	Call information procedures	211
9.5	Call release procedures.....	212
9.5.1	Normal call release	212
9.5.2	Abnormal call release	212
9.5.2.1	Definitions.....	212
9.5.2.2	Abnormal release general description (PT or FT).....	213
9.5.2.3	Abnormal release in case of call setup collisions.....	214
9.5.3	Release collisions.....	217
9.6	Service change procedures	217
9.6.1	General.....	217
9.6.2	Change of Bandwidth parameters (including changes in connection type)	218
9.6.3	Service rerouting.....	218
9.6.4	NWK layer service suspension and resumption.....	218
9.6.5	Modulation scheme change.....	219
9.7	NWK layer Packet mode procedures.....	219
9.7.1	General.....	219
9.7.2	PT initiated access	220
9.7.3	FT initiated access	220
9.7.4	NWK layer suspend and resume.....	220
9.7.4.1	General	220
9.7.4.2	C-plane NWK layer suspend and resume.....	221
9.7.4.3	U-plane NWK layer suspend and resume	221
9.8	Emergency call procedure	221
9.9	Segmentation of information in CC procedures.....	222
10	Supplementary Services procedures.....	223
10.1	General	223
10.2	Keypad protocol	224
10.3	Feature key management protocol.....	224
10.4	Functional protocol.....	225
10.4.0	General.....	225
10.4.1	Separate messages approach	225
10.4.1.0	General	225
10.4.1.1	Hold procedures	225
10.4.1.2	Retrieve procedures.....	225
10.4.1.3	Auxiliary states for hold and retrieve	226
10.4.2	Common information element approach.....	226
10.4.2.0	General	226
10.4.2.1	Call Related Supplementary Services (CRSS) procedures.....	226
10.4.2.2	Call Independent Supplementary Services (CISS) procedures	226
10.4.2.2.0	General	226
10.4.2.2.1	Transport of CISS.....	227
10.4.2.3	Connectionless Supplementary Service (CLSS) procedure	227
10.5	Co-existence of multiple protocols.....	228
10.6	Application protocols	228
10.6.1	DECT standard functional supplementary services	228
10.6.2	DECT specific supplementary services	229
10.6.2.0	General	229
10.6.2.1	Queue management.....	229
10.6.2.2	Indication of subscriber number.....	229
10.6.2.3	Control of echo control functions.....	230
10.6.2.4	Cost information	230

11	Connection Oriented Message Service (COMS).....	231
11.1	General	231
11.2	COMS states.....	231
11.2.1	States at PT	231
11.2.1.1	State TS-0: "NULL"	231
11.2.1.2	State TS-1: "CONNECT PENDING"	231
11.2.1.3	State TS-2: "RELEASE PENDING"	231
11.2.1.4	State TS-3: "ACTIVE"	231
11.2.2	States at FT	231
11.2.2.1	State FS-0: "NULL"	231
11.2.2.2	State FS-1: "CONNECT PENDING"	231
11.2.2.3	State FS-2: "RELEASE PENDING"	231
11.2.2.4	State FS-3: "ACTIVE"	232
11.3	COMS establishment procedures	232
11.3.1	PT initiated COMS establishment	232
11.3.1.1	COMS request.....	232
11.3.1.2	COMS connection.....	232
11.3.2	FT initiated COMS establishment	233
11.3.2.1	COMS request.....	233
11.3.2.2	COMS connection.....	233
11.4	COMS data transfer procedures	233
11.4.1	Procedure at the sending side.....	233
11.4.2	Procedure at the receiving side	234
11.5	COMS NWK layer suspend and resume procedures.....	235
11.6	COMS release procedures	235
11.6.1	Normal COMS release.....	235
11.6.2	Release collisions.....	235
12	ConnectionLess Message Service (CLMS).....	236
12.1	General	236
12.2	CLMS states	236
12.3	CLMS message transmission procedures.....	236
12.3.1	Fixed length messages	236
12.3.1.0	General	236
12.3.1.1	Procedure in the Fixed radio Termination (FT)	236
12.3.1.2	Procedure in the Portable radio Termination (PT)	237
12.3.2	Variable length messages.....	237
12.3.2.0	General	237
12.3.2.1	Procedure at the sending side.....	237
12.3.2.2	Procedure at the receiving side.....	237
12.3.2.3	Restrictions for portable side initiated messages.....	238
13	Mobility Management (MM) procedures.....	238
13.1	General	238
13.2	Identity procedures	239
13.2.0	General.....	239
13.2.1	Procedure for identification of PT	239
13.2.2	Procedure for temporary identity assignment	240
13.3	Authentication procedures.....	241
13.3.0	General.....	241
13.3.1	Authentication of a PT	241
13.3.2	Authentication of the user.....	243
13.3.3	Authentication of a FT	244
13.4	Location procedures	245
13.4.0	General.....	245
13.4.1	Location registration	245
13.4.2	Detach	247
13.4.3	Location update	247
13.5	Access rights procedure.....	248
13.5.1	Obtaining the access rights	248
13.5.2	Termination of access rights	249
13.5.3	Modification of access rights.....	251

13.6	Key allocation procedure.....	251
13.7	Parameter retrieval procedure.....	253
13.8	Ciphering related procedure	254
13.9	External protocol information procedure	257
13.9.0	General.....	257
13.9.1	Procedure for external protocol information initiated by the FT	257
13.9.2	Procedure for external protocol information initiated by the PT	257
13.9.3	Segmentation of information in MM procedures.....	258
14	Link Control Entity (LCE) procedures.....	259
14.1	General	259
14.2	Connection oriented link control procedures.....	260
14.2.1	Link establishment.....	260
14.2.2	Direct PT initiated link establishment.....	260
14.2.3	Indirect (paged) FT initiated link establishment	261
14.2.4	Direct FT initiated link establishment.....	262
14.2.5	Link maintenance.....	263
14.2.6	Link suspend and resume.....	263
14.2.6.0	General	263
14.2.6.1	Link suspend	263
14.2.6.2	Link resume.....	264
14.2.7	Link release.....	264
14.2.7.0	General	264
14.2.7.1	NLR notification without "partial release" as release reason	264
14.2.7.2	NLR notification with "partial release" as release reason	265
14.3	Connectionless link control procedures.....	265
14.3.1	Message routing.....	265
14.3.2	Broadcast announce procedure	266
14.3.3	LCE paging codes for connectionless service.....	266
14.4	Procedure for collective and group ringing	266
14.5	LCE paging procedures for DPRS	267
14.5.1	DPRS initial setup paging.....	267
14.5.1.0	General	267
14.5.1.1	Assumptions for Short paging format or for Full format with IPUI.....	267
14.5.1.2	Coding for Full paging format with TPUI.....	268
14.5.2	DPRS Resume paging.....	268
14.5.2.0	General	268
14.5.2.1	Assumptions for Short paging format or for Full format with IPUI.....	268
14.5.2.2	Coding for Full paging format with TPUI.....	268
14.5.2.3	LCE Resume Procedure description.....	269
14.5.3	Special cases	269
14.5.3.1	Rule for DPRS Class 1 devices	269
14.5.3.2	Rule for backcompatibility with former A/B 1 devices	269
15	Management procedures.....	270
15.1	Lower Layer Management Entity (LLME)	270
15.2	Service mapping and negotiation	270
15.2.1	General.....	270
15.2.2	Prioritized list negotiation.....	271
15.2.3	Exchanged attribute negotiation	271
15.2.4	Operating parameter negotiation.....	271
15.2.5	Peer attribute negotiation	272
15.3	Service modification procedures	272
15.4	Resource management.....	272
15.5	Management of MM procedures	272
15.6	Call ciphering management.....	274
15.7	External Handover.....	274
15.7.0	General.....	274
15.7.1	Handover candidate procedures.....	275
15.7.1.1	General	275
15.7.1.2	Handover candidate indication.....	275
15.7.1.3	Handover candidate retrieval	275

15.7.1.4	Target FP selection.....	276
15.7.2	Handover reference procedure.....	276
15.7.2.1	General.....	276
15.7.2.2	Handover reference indication.....	276
15.7.2.3	Handover reference retrieval.....	277
15.7.3	External handover suggested by FP.....	277
15.7.4	NWK layer set up procedure.....	277
15.7.4.0	General.....	277
15.7.4.1	Handover request.....	277
15.7.4.2	Handover confirm.....	278
15.7.4.3	Handover accept.....	278
15.7.4.4	Handover reject.....	278
15.7.4.5	Release of old connection.....	278
15.7.4.6	Handover Fall Back.....	278
15.7.5	U-plane handling.....	279
15.7.6	Ciphering procedure.....	279
15.7.7	Interaction with location registration.....	280
15.8	Test management procedures.....	280
15.8.0	General.....	280
15.8.1	Test call back procedure.....	280
15.8.2	Test hook control procedures.....	281
15.8.3	Upper tester procedure.....	281
15.9	Application assistance procedures.....	282
15.9.1	DECT Identity Resolution (Retrieval) Procedure.....	282
15.9.1.0	General.....	282
15.9.1.1	FT (or HyP) initiated Connectionless Identity Resolution procedure.....	282
15.9.1.2	PT initiated Connectionless Identity Resolution procedure.....	282
15.9.1.3	Connection oriented Identity Resolution procedure.....	283
15.9.2	Application Address Resolution (Retrieval) Procedure.....	283
15.9.3	Application Parameter Allocation Procedure.....	283
15.9.3.0	General.....	283
15.9.3.1	FT initiated application parameter allocation procedure.....	283
15.9.3.2	PT initiated application parameter allocation procedure.....	283
15.9.4	Application parameter information procedure.....	284
15.9.4.0	General.....	284
15.9.4.1	FT initiated connection oriented Application parameter information procedure.....	284
15.9.4.2	PT initiated connection oriented Application parameter information procedure.....	284
15.9.4.3	FT initiated connectionless Application parameter information procedure.....	284
15.9.4.4	PT initiated connectionless Application parameter information procedure.....	285
15.9.5	Application Parameter Indication procedure.....	285
16	Primitives.....	286
16.1	Primitive types.....	286
16.2	Primitives to lower layer (DLC layer).....	286
16.3	Primitives to IWU.....	286
16.3.0	General.....	286
16.3.1	Parameter definitions.....	286
16.3.2	MNCC primitives.....	287
16.3.2.0	List of primitives.....	287
16.3.2.1	MNCC_SETUP primitive.....	288
16.3.2.2	MNCC_SETUP_ACK primitive.....	288
16.3.2.3	MNCC_REJECT primitive.....	289
16.3.2.4	MNCC_CALL_PROC primitive.....	289
16.3.2.5	MNCC_ALERT primitive.....	290
16.3.2.6	MNCC_CONNECT primitive.....	290
16.3.2.7	MNCC_RELEASE primitive.....	291
16.3.2.8	MNCC_FACILITY primitive.....	291
16.3.2.9	MNCC_INFO primitive.....	292
16.3.2.10	MNCC_MODIFY primitive.....	292
16.3.2.11	MNCC_HOLD primitive.....	292
16.3.2.12	MNCC_RETRIEVE primitive.....	293
16.3.2.13	MNCC_IWU_INFO primitive.....	293

16.3.3	MNSS primitives	293
16.3.3.0	List of primitives	293
16.3.3.1	MNSS_SETUP primitive	293
16.3.3.2	MNSS_FACILITY primitive	294
16.3.3.3	MNSS_RELEASE primitive	294
16.3.4	MNCO primitives	294
16.3.4.0	List of primitives	294
16.3.4.1	MNCO_SETUP primitive	295
16.3.4.2	MNCO_CONNECT primitive	295
16.3.4.3	MNCO_INFO primitive	295
16.3.4.4	MNCO_ACK primitive	295
16.3.4.5	MNCO_RELEASE primitive	296
16.3.4.6	MNCO_REJECT primitive	296
16.3.5	MNCL primitives	296
16.3.5.0	List of primitives	296
16.3.5.1	MNCL_UNITDATA primitive	296
16.3.6	MM primitives	297
16.3.6.0	List of primitives	297
16.3.6.1	MM_IDENTITY primitive	297
16.3.6.2	MM_IDENTITY_ASSIGN primitive	297
16.3.6.3	MM_AUTHENTICATE primitive	298
16.3.6.4	MM_LOCATE primitive	298
16.3.6.5	MM_DETACH primitive	298
16.3.6.6	MM_ACCESS_RIGHTS primitive	299
16.3.6.7	MM_ACCESS_RIGHTS_TERMINATE primitive	299
16.3.6.8	MM_KEY_ALLOCATE primitive	299
16.3.6.9	MM_INFO primitive	300
16.3.6.10	MM_CIPHER primitive	300
16.3.6.11	MM_IWU primitive	300
17	Handling of error and exception conditions	301
17.0	General	301
17.1	Protocol discrimination error	301
17.2	Message too short	301
17.3	Transaction identifier error	301
17.3.1	Illegal and unsupported transaction identifier value	301
17.3.2	Transaction identifier procedural errors and exception conditions	301
17.3.2.1	Unknown active CC call	301
17.3.2.2	Unknown active CISS call	302
17.3.2.3	Unknown active COMS call	302
17.3.2.4	Unknown active CLMS call	302
17.3.2.5	Unknown active MM transaction	302
17.3.2.6	Unknown active LCE transaction	302
17.3.3	Call Resource Contention	302
17.4	Message type or message sequence errors	303
17.4.1	CC message error	303
17.4.2	CISS message error	303
17.4.3	COMS or CLMS message error	303
17.4.4	MM message error	303
17.4.5	LCE message error	303
17.5	General information element errors	303
17.5.0	General	303
17.5.1	Information element out of sequence	303
17.5.2	Duplicated information elements	304
17.6	Mandatory information element errors	304
17.6.1	Mandatory information element missing in CC messages	304
17.6.2	Mandatory information element content error in CC messages	304
17.6.3	Mandatory information element error in COMS or CLMS messages	304
17.6.4	Mandatory information element error in MM messages	305
17.6.5	Mandatory information element error in LCE messages	305
17.7	Non-mandatory information element errors	305
17.7.0	General	305

17.7.1	Unrecognized information element.....	305
17.7.2	Non-mandatory information element content error	305
17.8	Data link reset.....	306
17.9	Data link failure.....	306
Annex A (normative): System parameters.....		307
A.1	CC timers.....	307
A.2	SS timers	308
A.3	COMS timers.....	308
A.4	CLMS timer.....	309
A.5	MM timers.....	309
A.6	LCE timers	312
A.7	NWK layer constants.....	312
A.8	Restart.....	313
Annex B (normative): CC state transition tables.....		314
B.1	CC state transitions at PT side.....	314
B.1.1	CC state table at PT side.....	314
B.1.2	CC transition procedures at PT side	315
B.2	CC state transitions at FT side.....	317
B.2.1	CC state table at FT side.....	317
B.2.2	CC transition procedures at FT side	317
Annex C (informative): DLC states as viewed by the LCE		320
Annex D (normative): DECT standard character sets		321
D.1	General	321
D.2	DECT standard 8-bit characters	321
D.2.1	General	321
D.2.2	Control codes.....	322
D.2.3	Standard IA5 codes	323
D.2.4	extended codes and escape to alternative character sets.....	323
D.3	DECT standard 4-bit characters	323
Annex E (normative): Default coding of information elements.....		324
E.1	Default coding of <<IWU-ATTRIBUTES>> and <CALL-ATTRIBUTES>> information elements for basic speech.....	324
E.2	Default coding of <<IWU-ATTRIBUTES>>, <<CALL-ATTRIBUTES>> and <<CONNECTION-ATTRIBUTES>> information elements for wideband speech	324
E.2.0	General	324
E.2.1	Default setup attributes for basic service wideband speech	325
Annex F (normative): Broadcast attributes coding		326
F.1	Higher layer capabilities.....	326
F.2	Extended higher layer capabilities	327
F.3	Extended higher layer capabilities (part 2).....	327
F.4	Extended higher layer capabilities (part 3).....	329
Annex G (normative): Use of <<IWU-PACKET>> and <<IWU-TO-IWU>> information elements		330