

SLOVENSKI STANDARD
oSIST prEN 300 175-8 V2.7.14:2019
01-november-2019

**Digitalne izboljšane brezvrvične telekomunikacije (DECT) - Skupni vmesnik (CI) - 8.
del: Kodiranje in prenos govora in zvoka**

Digital Enhanced Cordless Telecommunications (DECT) - Common Interface (CI) - Part
8: Speech and audio coding and transmission

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 175-8 V2.8.1:2020](#)

Ta slovenski standard je istoveten z: [ETSI EN 300 175-8 V2.7.14 \(2019-08\)](https://standards.iteh.ai/catalog/standard/8365c2ba0280/sist-en-300-175-8-v2-8-1-2020)

ICS:

33.070.30 Digitalne izboljšane Digital Enhanced Cordless
 brezvrvične telekomunikacije Telecommunications (DECT)
 (DECT)

oSIST prEN 300 175-8 V2.7.14:2019 en

Draft ETSI EN 300 175-8 v2.7.14 (2019-08)



Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 8: Speech and audio coding and transmission

[SIST EN 300 175-8 V2.8.1:2020](#)

<https://standards.iteh.ai/catalog/standards/sist/85f88032-b5ed-4d67-baa1-8365c2ba0280/sist-en-300-175-8-v2-8-1-2020>

Reference

REN/DECT-00328

Keywords

7 kHz, audio, broadband, codec, DECT, handsfree, IMT-2000, loudspeaking, mobility, narrowband, quality, radio, speech, TDD, TDMA, telephony, terminal

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD REVIEW

(standards.iteh.ai)

Important notice

SIST EN 300 175-8 V2.8.1:2020
The present document can be downloaded from:
<https://standards.iteh.ai/> <http://www.etsi.org/standards-search>

8365c2ba0280/sist-en-300-175-8-v2-8-1-2020

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and

of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and
of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	15
Foreword.....	15
Modal verbs terminology.....	15
1 Scope	16
2 References	16
2.1 Normative references	16
2.2 Informative references.....	18
3 Definition of terms, symbols and abbreviations.....	20
3.1 Terms.....	20
3.2 Symbols.....	21
3.3 Abbreviations	22
4 Configurations.....	24
4.1 Reference configuration	24
4.1.1 Basic configuration	24
4.1.2 Portable Part (PP)	25
4.1.2.1 Functional organization.....	25
4.1.2.2 Volume control	25
4.1.3 Fixed Part (FP).....	26
4.1.3.1 Digital interface.....	26
4.1.3.2 Analog interface	27
4.1.3.3 FP adaptive volume control	27
4.1.3.4 Voice over IP (VoIP) interface	27
4.2 Test configurations	28
5 Encoding.....	28
5.0 General	28
5.1 32 kbit/s full term (ADPCM) G.726.....	29
5.1.1 Algorithm.....	29
5.1.2 Bit sequence	29
5.1.3 Characteristics of G.726 ADPCM codec	29
5.2 64 kbit/s PCM G.711.....	29
5.2.1 Algorithm.....	29
5.2.2 Bit sequence	29
5.2.3 Characteristics of G.711 PCM codec	30
5.2.4 Automatic detection of FAX/modem tone and switch to G.711	30
5.3 Wideband speech codec G.722 at 64 kbit/s	30
5.3.0 General.....	30
5.3.1 Algorithm.....	30
5.3.2 Bit sequence	30
5.3.3 Characteristics of G.722 wideband codec.....	30
5.3.4 Optional Packet Loss Concealment algorithm (PLC)	31
5.4 Wideband speech codec G.729.1 up to 32 kbit/s.....	31
5.4.1 Algorithm.....	31
5.4.2 Bit sequence	31
5.4.3 Characteristics of G.729.1 codec	31
5.4.4 Packet Loss Concealment algorithm (PLC).....	32
5.4.5 Supported bit rate in DECT	32
5.5 Super-wideband MPEG-4 speech and audio coding	32
5.5.1 Algorithm.....	32
5.5.2 64 kbit/s, MPEG-4 ER AAC-LD codec	33
5.5.3 32 kbit/s, MPEG-4 ER AAC-LD codec	33
5.6 Narrowband, wideband and super-wideband/fullband LC3plus speech and audio coding	34
5.6.1 Algorithm.....	34
5.6.2 NB mode at 32 kbit/s gross bit rate.....	34
5.6.3 WB mode at 32 kbit/s gross bit rate	35

5.6.4	SWB mode at 64 kbit/s gross bit rate.....	35
5.6.5	FB mode at 64 kbit/s gross bit rate	35
5.6.6	FB mode at 96 kbit/s gross bit rate	36
5.6.7	FB mode at 128 kbit/s gross bit rate	36
6	Transmission aspects.....	37
6.1	Relative level.....	37
6.2	Acoustic reference level	37
6.3	Volume control.....	37
7	Audio specifications	37
7.1	Overall description	37
7.1.1	Introduction to DECT audio specifications	37
7.1.2	Introduction to the audio types	37
7.1.3	List of Audio types	38
7.1.4	Audio types for Portable Parts	39
7.1.5	Audio types for Fixed Parts	40
7.1.6	Complete DECT system	40
7.1.7	Structure of the specification of the audio types.....	40
7.1.8	Audio Types and codecs	48
7.1.9	Audio Types and physical interfaces	48
7.2	Audio types applicable to Portable Parts.....	48
7.2.0	General.....	48
7.2.1	Performance levels of DECT Portable Parts (handsets).....	48
7.2.2	Type 0: Reference PP (RePP).....	49
7.2.3	PP Type 1a: "Classic" GAP narrowband handset	50
7.2.3.1	Introduction	50
7.2.3.2	Compatible services and codecs.....	50
7.2.3.3	Specification.....	50
7.2.4	PP Type 1b: "Improved" GAP narrowband handset	50
7.2.4.1	Introduction	50
7.2.4.2	Compatible services and codecs.....	51
7.2.4.3	Specification.....	51
7.2.5	PP Type 1c: HATS-tested "standard" narrowband handset	51
7.2.5.1	Introduction	51
7.2.5.2	Compatible services and codecs.....	51
7.2.5.3	Specification.....	51
7.2.6	PP Type 1d: HATS-tested "improved" narrowband handset	52
7.2.6.1	Introduction	52
7.2.6.2	Compatible services and codecs.....	52
7.2.6.3	Specification.....	52
7.2.7	PP Type 3a: HATS tested narrowband "standard" loudspeaking handsfree	52
7.2.7.1	Introduction	52
7.2.7.2	Compatible services and codecs.....	52
7.2.7.3	Specification.....	53
7.2.8	PP Type 3b: HATS tested narrowband "improved" loudspeaking handsfree	53
7.2.8.1	Introduction	53
7.2.8.2	Compatible services and codecs.....	53
7.2.8.3	Specification.....	53
7.2.9	PP Type 2a: P.311-tested wideband handset.....	53
7.2.9.1	Introduction	53
7.2.9.2	Compatible services and codecs.....	53
7.2.9.3	Specification.....	53
7.2.10	PP Type 2b: HATS-tested "standard" wideband handset or headset	54
7.2.10.1	Introduction	54
7.2.10.2	Compatible services and codecs.....	54
7.2.10.3	Specification.....	54
7.2.11	PP Type 2c: HATS tested "improved" wideband handset or headset	54
7.2.11.1	Introduction	54
7.2.11.2	Compatible services and codecs.....	54
7.2.11.3	Specification.....	54
7.2.12	PP Type 4a: HATS tested wideband "standard" loudspeaking handsfree	55

7.2.12.1	Introduction	55
7.2.12.2	Compatible services and codecs	55
7.2.12.3	Specification	55
7.2.13	PP Type 4b: HATS tested wideband "improved" loudspeaking and handsfree	55
7.2.13.1	Introduction	55
7.2.13.2	Compatible services and codecs	55
7.2.13.3	Specification	55
7.2.14	PP Type 5a: super-wideband 14 kHz handset or headset	56
7.2.14.1	Introduction	56
7.2.14.2	Compatible services and codecs	56
7.2.14.3	Specification	56
7.2.15	PP Type 5b: super-wideband 14 kHz loudspeaking handsfree	56
7.2.15.1	Introduction	56
7.2.15.2	Compatible services and codecs	56
7.2.15.3	Specification	56
7.2.16	PP Type 6: PPs with external 2 wire, 3,1 kHz telephony interface	56
7.2.16.1	Introduction	56
7.2.16.2	Compatible services and codecs	56
7.2.16.3	Specification	56
7.2.17	PP Type 7a: fullband 20 kHz handset or headset	56
7.2.17.1	Introduction	56
7.2.17.2	Compatible services and codecs	57
7.2.17.3	Specification	57
7.2.18	PP Type 7b: fullband 20 kHz loudspeaking handsfree	57
7.2.18.1	Introduction	57
7.2.18.2	Compatible services and codecs	57
7.2.18.3	Specification	57
7.2.19	PP Type 7c, d, e: fullband 20 kHz stereo audio device	57
7.2.19.1	Introduction	57
7.2.19.2	Compatible services and codecs	57
7.2.19.3	Specification	57
7.3	Audio transmission types applicable to Fixed Parts	57
7.3.0	General	57
7.3.1	FP Type 0: Reference FP (ReFP)	58
7.3.2	FP Type 1a: "classical" Fixed Part for ISDN Network	58
7.3.2.1	Introduction	58
7.3.2.2	Compatible services and codecs	59
7.3.2.3	Specifications	59
7.3.2.3.1	Transcoding and equalization	59
7.3.2.3.2	PP type detection	59
7.3.2.3.3	Activation of audio processing functions	59
7.3.2.3.4	Transmission specification	60
7.3.3	FP Type 1b: Fixed Part for ISDN Network	60
7.3.3.1	Introduction	60
7.3.3.2	Compatible services and codecs	60
7.3.3.3	Specification	60
7.3.3.3.1	Transcoding and equalization	60
7.3.3.3.2	PP type detection	61
7.3.3.3.3	Activation of audio processing functions	61
7.3.3.3.4	Transmission specification	61
7.3.4	FP Type 2: FP with analog 2-wire interface, 3,1 kHz service	61
7.3.4.1	Introduction	61
7.3.4.2	Compatible services, physical interfaces and codecs	62
7.3.4.3	Specification	62
7.3.4.3.1	Transcoding, equalization and conversion	62
7.3.4.3.2	PP type detection and activation of audio processing functions	62
7.3.4.3.3	Transmission specification	62
7.3.5	FP Type 3: VoIP narrowband Fixed Part	62
7.3.5.1	Introduction	62
7.3.5.2	Compatible services, physical interfaces and codecs	63
7.3.5.3	Specification	63
7.3.5.3.1	Transcoding and equalization	63

7.3.5.3.2	PP type detection	64
7.3.5.3.3	Activation of audio processing functions	64
7.3.5.3.4	Transmission specification	64
7.3.6	FP Type 4: ISDN wideband Fixed Part	65
7.3.6.1	Introduction	65
7.3.6.2	Compatible services and codecs	65
7.3.6.3	Specification	65
7.3.6.3.1	Transcoding and equalization	65
7.3.6.3.2	PP type detection	65
7.3.6.3.3	Activation of audio processing functions	65
7.3.6.3.4	Transmission specification	66
7.3.7	FP Type 5: VoIP wideband, super-wideband or fullband Fixed Part	66
7.3.7.1	Introduction	66
7.3.7.2	Compatible services, physical interfaces and codecs	66
7.3.7.3	Specification	67
7.3.7.3.1	Transcoding and equalization	67
7.3.7.3.2	PP type detection	67
7.3.7.3.3	Activation of audio processing functions	67
7.3.7.3.4	Transmission specification	68
7.3.8	FP Type 6a: FP handling an Internal call inside a DECT FP (any service)	68
7.3.8.1	Introduction	68
7.3.8.2	Compatible services, physical interfaces and codecs	68
7.3.8.3	Specification	68
7.3.9	FP Type 6b: FP handling an n-party conference inside a DECT FP (any service)	68
7.3.9.1	Introduction	68
7.3.9.2	Compatible services, physical interfaces and codecs	68
7.3.9.3	Specification for the conference bridge	69
7.3.10	FP Type 7: DECT Repeater Part (REP)	69
7.3.10.1	Introduction	69
7.3.10.2	Compatible services, physical interfaces and codecs	69
7.3.10.3	Specification	69
7.4	Additional features	69
7.4.1	Introduction	69
7.4.2	Echo canceller in Fixed Part https://catalog.etsi.org/catalog/standards/sist/85188032-based-4d67-baa1-0280-3410-300-175-8-v2-8-1-2020	70
7.4.3	Echo suppressor in Fixed Part https://catalog.etsi.org/catalog/standards/sist/85188032-based-4d67-baa1-0280-3410-300-175-8-v2-8-1-2020	70
7.5	Transmission characteristics for Portable Parts	71
7.5.1	Transmission characteristics for Portable Part type 1a ("Classic GAP" handset)	71
7.5.1.1	PP frequency responses	71
7.5.1.1.1	Sending	71
7.5.1.1.2	Receiving	72
7.5.1.2	PP sending and receiving loudness ratings	72
7.5.1.2.1	Nominal values	72
7.5.1.2.2	User-controlled volume control in PP	72
7.5.1.2.3	PP adaptive volume control	73
7.5.1.3	Sidetone	73
7.5.1.3.1	Talker sidetone	73
7.5.1.3.2	Listener sidetone	74
7.5.1.4	Terminal coupling loss	74
7.5.1.4.1	Weighted Terminal Coupling Loss (TCLw)	74
7.5.1.4.2	Stability loss	74
7.5.1.5	Distortion	75
7.5.1.5.1	Sending	75
7.5.1.5.2	Receiving	75
7.5.1.5.3	Sidetone	75
7.5.1.6	Out of band signals	75
7.5.1.6.1	Sending (discrimination against out of band input signals)	75
7.5.1.6.2	Receiving (spurious out of band signals)	76
7.5.1.7	Noise	76
7.5.1.7.1	Sending	76
7.5.1.7.2	Band-limited noise	76
7.5.1.7.3	Receiving	76
7.5.1.7.4	Level of sampling frequency (receiving)	77

7.5.1.8	Acoustic shock	77
7.5.1.8.0	General	77
7.5.1.8.1	Continuous signal	77
7.5.1.8.2	Peak signal	77
7.5.1.9	PP Delay	77
7.5.1.10	PP ambient noise rejection	77
7.5.2	Additional requirements for PP type 1b ("improved GAP" handset)	78
7.5.2.0	General	78
7.5.2.1	Terminal coupling loss	78
7.5.2.1.1	Weighted Terminal Coupling Loss (TCLw)	78
7.5.2.2	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	78
7.5.2.3	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	78
7.5.2.4	Activation in Sending Direction	79
7.5.2.5	Activation in Receiving Direction	79
7.5.3	Transmission characteristics for PP types 1c and 1d (HATS tested, narrowband telephony handsets)	80
7.5.3.1	Frequency responses	80
7.5.3.1.1	Sending	80
7.5.3.1.2	Receiving	81
7.5.3.2	Sending and receiving loudness ratings	83
7.5.3.2.1	Nominal values	83
7.5.3.2.2	Void	83
7.5.3.2.3	Void	83
7.5.3.2.4	Microphone mute	83
7.5.3.2.5	Positional robustness	84
7.5.3.3	Sidetone	84
7.5.3.3.1	Sidetone masking rating (STMR)	84
7.5.3.3.2	Void	84
7.5.3.3.3	Sidetone delay	84
7.5.3.4	Terminal coupling loss	84
7.5.3.4.1	Terminal Coupling Loss weighted (TCLw)	84
7.5.3.4.2	Stability loss	85
7.5.3.5	Distortion	85
7.5.3.5.1	Sending Distortion	85
7.5.3.5.2	Receiving Distortion	85
7.5.3.6	Out of band signals	85
7.5.3.6.1	Out-of-band Signals in Send direction	85
7.5.3.6.2	Out-of-band signals in receiving direction	86
7.5.3.7	Noise	86
7.5.3.7.1	Sending	86
7.5.3.7.2	Receiving	86
7.5.3.8	Acoustic shock	87
7.5.3.8.0	General	87
7.5.3.8.1	Continuous signal	87
7.5.3.8.2	Void	87
7.5.3.9	Delay	87
7.5.3.10	Void	87
7.5.3.11	Double Talk Performance	87
7.5.3.11.0	General	87
7.5.3.11.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	87
7.5.3.11.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	88
7.5.3.11.3	Detection of Echo Components during Double Talk	88
7.5.3.11.4	Minimum activation level and sensitivity of double talk detection	89
7.5.3.12	Switching characteristics	89
7.5.3.12.0	General	89
7.5.3.12.1	Activation in Sending Direction	89
7.5.3.12.2	Activation in Receiving Direction	90
7.5.3.12.3	Silence Suppression and Comfort Noise Generation	90
7.5.3.12.4	Performance in sending direction in the presence of background noise	90
7.5.3.12.5	Speech Quality in the Presence of Background Noise	90
7.5.3.12.6	Quality of Background Noise Transmission (with Far End Speech)	91
7.5.3.12.7	Void	91
7.5.3.12.8	Positional Robustness of Speech Quality in the Presence of Background Noise	91

7.5.3.13	Quality of echo cancellation.....	91
7.5.3.13.0	General	91
7.5.3.13.1	Temporal echo effects	91
7.5.3.13.2	Spectral Echo Attenuation.....	91
7.5.3.13.3	Variable echo path.....	92
7.5.4	Transmission characteristics for PP types 3a and 3b (narrowband loudspeaking and handsfree devices)	92
7.5.4.1	Sending sensitivity/frequency response	92
7.5.4.2	Receive sensitivity/frequency response.....	93
7.5.4.3	Send loudness rating	95
7.5.4.4	Receive loudness rating.....	95
7.5.4.5	Sending distortion	96
7.5.4.6	Receiving distortion	96
7.5.4.7	Out-of-band signals in sending direction	97
7.5.4.8	Out-of-band signals in receiving direction.....	97
7.5.4.9	Sending noise	97
7.5.4.10	Receiving noise	97
7.5.4.11	Terminal Coupling Loss weighted (TCLw)	98
7.5.4.12	Stability Loss.....	98
7.5.4.13	Double Talk Performance	98
7.5.4.13.0	General	98
7.5.4.13.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	98
7.5.4.13.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	99
7.5.4.13.3	Detection of Echo Components during Double Talk.....	100
7.5.4.13.4	Minimum activation level and sensitivity of double talk detection.....	100
7.5.4.14	Switching characteristics.....	100
7.5.4.14.0	General	100
7.5.4.14.1	Activation in Sending Direction	100
7.5.4.14.2	Activation in Receiving Direction	101
7.5.4.14.3	Silence Suppression and Comfort Noise Generation	101
7.5.4.14.4	Performance in sending direction in the presence of background noise	101
7.5.4.14.5	Speech Quality in the Presence of Background Noise.....	101
7.5.4.14.6	Quality of Background Noise Transmission (with Far End Speech).....	102
7.5.4.15	Quality of echo cancellation.....	102
7.5.4.15.0	General	102
7.5.4.15.1	Temporal echo effects	102
7.5.4.15.2	Spectral Echo Attenuation	102
7.5.4.15.3	Variable echo path.....	103
7.5.4.16	Microphone mute	103
7.5.4.17	Delay	103
7.5.5	Transmission characteristics for PP type 2a (P.311 tested, wideband handset)	103
7.5.5.0	General.....	103
7.5.5.1	Sending characteristics.....	103
7.5.5.1.1	Loudness rating	103
7.5.5.1.2	Sensitivity/frequency characteristics	104
7.5.5.1.3	Noise.....	104
7.5.5.1.4	Distortion.....	104
7.5.5.1.5	Discrimination against out-of-band input signals	104
7.5.5.2	Receiving characteristics.....	104
7.5.5.2.1	Loudness rating	104
7.5.5.2.2	Sensitivity/frequency characteristics	104
7.5.5.2.3	Noise.....	104
7.5.5.2.4	Distortion.....	105
7.5.5.2.5	Spurious out-of-band receiving signals	105
7.5.5.3	Sidetone characteristics.....	105
7.5.5.3.1	Talker sidetone	105
7.5.5.3.2	Sidetone distortion.....	105
7.5.5.4	Echo path loss characteristics.....	105
7.5.5.4.1	Weighted terminal coupling loss	105
7.5.5.4.2	Stability loss	106
7.5.6	Transmission characteristics for PP type 2b and 2c (HATS tested wideband handsets)	106
7.5.6.1	Frequency responses	106

7.5.6.1.1	Sending.....	106
7.5.6.1.2	Receiving.....	107
7.5.6.2	Send and receive loudness ratings.....	110
7.5.6.2.1	Nominal values.....	110
7.5.6.2.2	Void.....	110
7.5.6.2.3	Void.....	110
7.5.6.2.4	Microphone mute.....	110
7.5.6.2.5	Positional robustness	111
7.5.6.3	Sidetone.....	111
7.5.6.3.1	Sidetone masking rating (STMR).....	111
7.5.6.3.2	Void.....	111
7.5.6.3.3	Sidetone delay	111
7.5.6.4	Terminal coupling loss	111
7.5.6.4.1	Terminal Coupling Loss (TCL).....	111
7.5.6.4.2	Stability loss	112
7.5.6.5	Distortion	112
7.5.6.5.1	Sending Distortion.....	112
7.5.6.5.2	Receiving Distortion.....	112
7.5.6.6	Noise	113
7.5.6.6.1	Sending.....	113
7.5.6.6.2	Receiving.....	113
7.5.6.7	Acoustic shock	113
7.5.6.7.0	General	113
7.5.6.7.1	Continuous signal	113
7.5.6.8	Delay	113
7.5.6.9	Void.....	114
7.5.6.10	Double talk Performance.....	114
7.5.6.10.0	General	114
7.5.6.10.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	114
7.5.6.10.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	114
7.5.6.10.3	Detection of Echo Components during Double Talk	115
7.5.6.10.4	Minimum activation level and sensitivity of double talk detection	116
7.5.6.11	Switching characteristics.....	116
7.5.6.11.0	http://standards.etsi.org/catalog/standards/sist/851X8032-based-4d67-baa1-	116
7.5.6.11.1	Activation in Sending Direction	116
7.5.6.11.2	Activation in Receiving Direction	116
7.5.6.11.3	Silence Suppression and Comfort Noise Generation	116
7.5.6.11.4	Performance in Sending in the Presence of Background Noise.....	116
7.5.6.11.5	Speech Quality in the Presence of Background Noise.....	117
7.5.6.11.6	Quality of Background Noise Transmission (with Far End Speech).....	117
7.5.6.11.7	Void.....	117
7.5.6.11.8	Positional Robustness of Speech Quality in the Presence of Background Noise	117
7.5.6.12	Quality of echo cancellation.....	118
7.5.6.12.0	General	118
7.5.6.12.1	Temporal echo effects	118
7.5.6.12.2	Spectral Echo Attenuation	118
7.5.6.12.3	Variable echo path.....	118
7.5.6.13	Out of band signals.....	119
7.5.6.13.1	Out-of-band signals in sending direction.....	119
7.5.6.13.2	Out-of-band signals in receiving direction	119
7.5.7	Transmission characteristics for PP types 4a and 4b (HATS Tested wideband loudspeaking and handsfree devices).....	119
7.5.7.1	Sending sensitivity/frequency response	119
7.5.7.2	Receive sensitivity/frequency response.....	120
7.5.7.3	Send loudness rating	122
7.5.7.4	Receive loudness rating.....	122
7.5.7.5	Sending distortion	123
7.5.7.6	Receiving distortion	123
7.5.7.7	Out-of-band signals in sending direction	124
7.5.7.8	Out-of-band signals in receiving direction	124
7.5.7.9	Sending noise	124
7.5.7.10	Receiving noise	124

7.5.7.11	Terminal Coupling Loss.....	125
7.5.7.12	Stability Loss.....	125
7.5.7.13	Double Talk Performance	125
7.5.7.13.0	General	125
7.5.7.13.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	126
7.5.7.13.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	126
7.5.7.13.3	Detection of Echo Components during Double Talk.....	127
7.5.7.13.4	Minimum activation level and sensitivity of double talk detection.....	127
7.5.7.14	Switching characteristics.....	127
7.5.7.14.0	General	127
7.5.7.14.1	Activation in Sending Direction	127
7.5.7.14.2	Activation in Receiving Direction	128
7.5.7.14.3	Silence Suppression and Comfort Noise Generation.....	128
7.5.7.14.4	Performance in sending direction in the presence of background noise	128
7.5.7.14.5	Speech Quality in the Presence of Background Noise.....	128
7.5.7.14.6	Quality of Background Noise Transmission (with Far End Speech).....	129
7.5.7.15	Quality of echo cancellation.....	129
7.5.7.15.1	Temporal echo effects	129
7.5.7.15.2	Spectral Echo Attenuation.....	129
7.5.7.15.3	Variable echo path.....	130
7.5.7.16	Microphone mute	130
7.5.7.17	Delay	130
7.5.8	Transmission characteristics for PP type 5a ("super-wideband 14 kHz handset or headset")	130
7.5.8.1	Frequency responses	130
7.5.8.1.1	Sending	130
7.5.8.1.2	Receiving	132
7.5.8.2	Send and receive loudness ratings.....	133
7.5.8.2.1	Send Loudness Rating	133
7.5.8.2.2	Receive Loudness Rating	134
7.5.8.3	Sidetone.....	134
7.5.8.3.1	Sidetone Masking Rating STMR (Mouth to ear).....	134
7.5.8.3.2	Sidetone Delay.....	134
7.5.8.4	Terminal Coupling Loss.....	135
7.5.8.4.1	Unweighted Terminal Coupling Loss.....	135
7.5.8.4.2	Stability Loss.....	135
7.5.8.5	Distortion	135
7.5.8.5.1	Sending Distortion.....	135
7.5.8.5.2	Receiving Distortion.....	136
7.5.8.6	Noise	136
7.5.8.6.1	Sending.....	136
7.5.8.6.2	Receiving.....	136
7.5.8.7	Acoustic shock	136
7.5.8.7.0	General	136
7.5.8.7.1	Continuous signal	137
7.5.8.8	Delay	137
7.5.8.9	Double talk performance	137
7.5.8.9.0	General	137
7.5.8.9.1	Attenuation range in send direction during double talk $A_{H,S,dt}$	137
7.5.8.9.2	Attenuation range in receive direction during double talk $A_{H,R,dt}$	138
7.5.8.9.3	Detection of echo components during double talk	138
7.5.8.10	Switching Characteristics	139
7.5.8.10.0	Note	139
7.5.8.10.1	Activation in send direction.....	139
7.5.8.10.2	Silence suppression and comfort noise generation	139
7.5.8.10.3	Performance in Sending in the Presence of Background Noise.....	139
7.5.8.10.4	Speech quality in the presence of background noise	140
7.5.8.10.5	Positional Robustness of Speech Quality in the Presence of Background Noise	140
7.5.8.10.6	Quality of background noise transmission (with far end speech).....	141
7.5.8.11	Quality of echo cancellation.....	141
7.5.8.11.1	Temporal echo effects	141
7.5.8.11.2	Spectral echo attenuation.....	141

7.5.8.11.3	Variable echo path	141
7.5.9	Transmission characteristics for PP type 5b ("super-wideband 14 kHz loudspeaking and handsfree devices")	142
7.5.9.1	Sending sensitivity/frequency response	142
7.5.9.2	Receive sensitivity/frequency response	143
7.5.9.2.1	Handheld terminal	143
7.5.9.2.2	Desktop terminal	143
7.5.9.2.3	Terminals intended to be used simultaneously by several users	144
7.5.9.3	Sending loudness rating	144
7.5.9.3.1	Nominal Value	144
7.5.9.3.2	Microphone mute	144
7.5.9.4	Receive loudness rating	145
7.5.9.5	Sending distortion	145
7.5.9.5.1	Signal to harmonic distortion versus frequency	145
7.5.9.5.2	Signal to harmonic distortion for higher input level	146
7.5.9.6	Receiving distortion	146
7.5.9.7	Sending noise	147
7.5.9.8	Receiving noise	147
7.5.9.9	Terminal Coupling Loss	147
7.5.9.9.1	Unweighted Terminal Coupling Loss	147
7.5.9.9.2	Stability Loss	147
7.5.9.10	Double Talk Performance	147
7.5.9.10.0	General	147
7.5.9.10.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	148
7.5.9.10.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	148
7.5.9.10.3	Detection of Echo Components during Double Talk	149
7.5.9.10.4	Minimum activation level and sensitivity of double talk detection	149
7.5.9.11	Switching characteristics	149
7.5.9.11.0	Note	149
7.5.9.11.1	Activation in Sending Direction	150
7.5.9.11.2	Silence Suppression and Comfort Noise Generation	150
7.5.9.11.3	Performance in sending direction in the presence of background noise	150
7.5.9.11.4	Speech Quality in the Presence of Background Noise	150
7.5.9.11.5	Quality of Background Noise Transmission (with Far End Speech)	151
7.5.9.12	Quality of echo cancellation	151
7.5.9.12.1	Temporal echo effects	151
7.5.9.12.2	Spectral Echo Attenuation	151
7.5.9.12.3	Variable echo path	152
7.5.9.13	Delay	152
7.5.10	Transmission characteristics for PP type 7a ("fullband 20 kHz handset or headset")	152
7.5.10.1	Frequency responses	152
7.5.10.1.1	Sending	152
7.5.10.1.2	Receiving	154
7.5.10.2	Send and receive loudness ratings	155
7.5.10.2.1	Send Loudness Rating	155
7.5.10.2.2	Receive Loudness Rating	156
7.5.10.3	Sidetone	157
7.5.10.3.1	Sidetone Masking Rating STMR (Mouth to ear)	157
7.5.10.3.2	Sidetone Delay	157
7.5.10.4	Terminal Coupling Loss	157
7.5.10.4.1	Unweighted Terminal Coupling Loss	157
7.5.10.4.2	Stability Loss	157
7.5.10.5	Distortion	157
7.5.10.5.1	Sending Distortion	157
7.5.10.5.2	Receiving Distortion	158
7.5.10.6	Noise	158
7.5.10.6.1	Sending	158
7.5.10.6.2	Receiving	159
7.5.10.7	Acoustic shock	159
7.5.10.7.0	General	159
7.5.10.7.1	Continuous signal	159
7.5.10.8	Delay	159

7.5.10.9	Double talk Performance.....	159
7.5.10.9.0	General	159
7.5.10.9.1	Attenuation range in send direction during double talk $A_{H,S,dt}$	160
7.5.10.9.2	Attenuation range in receive direction during double talk $A_{H,R,dt}$	160
7.5.10.9.3	Detection of echo components during double talk	161
7.5.10.10	Switching Characteristics	161
7.5.10.10.0	Note	161
7.5.10.10.1	Activation in send direction.....	161
7.5.10.10.2	Silence suppression and comfort noise generation	162
7.5.10.10.3	Performance in Sending in the Presence of Background Noise.....	162
7.5.10.10.4	Speech quality in the presence of background noise	162
7.5.10.10.5	Positional Robustness of Speech Quality in the Presence of Background Noise	163
7.5.10.10.6	Quality of background noise transmission (with far end speech).....	163
7.5.10.11	Quality of echo cancellation.....	163
7.5.10.11.1	Temporal echo effects	163
7.5.10.11.2	Spectral echo attenuation.....	163
7.5.10.11.3	Variable echo path.....	164
7.5.11	Transmission characteristics for PP type 7b ("fullband 20 kHz loudspeaking and handsfree devices") ..	164
7.5.11.1	Sending sensitivity/frequency response	164
7.5.11.2	Receive sensitivity/frequency response.....	165
7.5.11.2.0	General	165
7.5.11.2.1	Handheld terminal	165
7.5.11.2.2	Desktop terminal	166
7.5.11.2.3	Terminals intended to be used simultaneously by several users.....	167
7.5.11.3	Sending loudness rating	167
7.5.11.3.1	Nominal Value.....	167
7.5.11.3.2	Microphone Mute	167
7.5.11.4	Receive loudness rating.....	167
7.5.11.5	Sending distortion	168
7.5.11.5.1	Signal to harmonic distortion versus frequency	168
7.5.11.5.2	Signal to harmonic distortion for higher input level.....	168
7.5.11.6	Receiving distortion	169
7.5.11.7	Sending noise	169
7.5.11.8	Receiving noise	169
7.5.11.9	Terminal Coupling Loss.....	170
7.5.11.9.1	Unweighted Terminal Coupling Loss.....	170
7.5.11.9.2	Stability Loss.....	170
7.5.11.10	Double Talk Performance	170
7.5.11.10.0	General	170
7.5.11.10.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	170
7.5.11.10.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	171
7.5.11.10.3	Detection of Echo Components during Double Talk	171
7.5.11.10.4	Minimum activation level and sensitivity of double talk detection	172
7.5.11.11	Switching characteristics.....	172
7.5.11.11.0	Note	172
7.5.11.11.1	Activation in Sending Direction	172
7.5.11.11.2	Silence Suppression and Comfort Noise Generation	172
7.5.11.11.3	Performance in sending direction in the presence of background noise	172
7.5.11.11.4	Speech Quality in the Presence of Background Noise.....	173
7.5.11.11.5	Quality of Background Noise Transmission (with Far End Speech).....	173
7.5.11.12	Quality of echo cancellation.....	173
7.5.11.12.1	Temporal echo effects	173
7.5.11.12.2	Spectral Echo Attenuation	174
7.5.11.12.3	Variable echo path.....	174
7.5.11.13	Delay	174
7.5.12	Transmission characteristics for PP type 7c, d, e ("fullband 20 kHz stereo audio device")	174
7.6	Transmission characteristics for Fixed Parts	175
7.6.1	Transmission characteristics for FP type 1a ("Classic" Fixed Part with ISDN Network interface, 3,1 kHz service)	175
7.6.1.1	Reduction of echo from PP	175
7.6.1.2	FP Network echo control	176

7.6.1.3	FP adaptive volume control	176
7.6.1.4	FP Delay.....	176
7.6.2	Transmission characteristics for FP type 1b ("new" Fixed Part with ISDN Network interface, 3,1 kHz service).....	176
7.6.2.0	General.....	176
7.6.2.1	FP Network echo control	176
7.6.2.2	FP adaptive volume control	177
7.6.2.3	FP Delay.....	177
7.6.3	Transmission characteristics for FP type 2 (Fixed Part with analog 2-wire interface, 3,1 kHz service)....	177
7.6.3.1	FP adaptive volume control	177
7.6.3.2	Network echo control.....	177
7.6.3.3	Additional requirements for DECT FP provided with a 2-wire PSTN interface.....	178
7.6.3.3.0	Test methods.....	178
7.6.3.3.1	General requirements.....	178
7.6.3.3.2	Speech performance characteristics.....	179
7.6.3.4	FP Delay.....	179
7.6.4	Transmission characteristics for FP type 3 (Fixed Part with VoIP interface, 3,1 kHz service)	180
7.6.4.1	Void.....	180
7.6.4.2	Void.....	180
7.6.4.3	Adaptive volume control.....	180
7.6.4.4	Clock accuracy.....	180
7.6.4.5	Send Jitter.....	180
7.6.4.6	Send and receive delay - round trip delay	180
7.6.5	Transmission characteristics for FP type 4 (Fixed Part with ISDN network interface, wideband service).....	181
7.6.5.1	FP adaptive volume control	181
7.6.5.2	FP Delay.....	181
7.6.6	Transmission characteristics for FP type 5 (Fixed Part with VoIP interface, wideband, super-wideband or fullband service).....	181
7.6.6.1	Void.....	181
7.6.6.2	Void.....	181
7.6.6.3	FP adaptive volume control	181
7.6.6.4	Clock accuracy	182
7.6.6.5	Send Jitter.....	182
7.6.6.6	Send and receive delay - round trip delay	182
8	Additional features	183
8.1	Loudspeaking hands-free and headset facilities	183
8.1.1	Loudspeaking hands-free facility.....	183
8.1.2	Headset facility	183
8.2	Tandem with mobile radio network.....	183
8.2.0	General.....	183
8.2.1	Tandem with GSM	183
8.2.1.0	Configuration	183
8.2.1.1	Network echo control.....	184
8.2.1.2	Terminal coupling loss	184
8.2.1.3	The GSM mobile transmitter operates in continuous mode	184
8.2.1.4	The GSM mobile transmitter operates in discontinuous mode, DTX	184
8.3	DECT connected to the GSM fixed network.....	184
8.3.0	General.....	184
8.3.1	Network echo control.....	184
8.3.2	Terminal coupling loss.....	185
8.4	Wireless Relay Stations (WRS).....	185
8.4.0	General.....	185
8.4.1	Modified FP network echo control requirements for implementation of 2 and 3 CRFP links in cascade.....	185
Annex A (informative):	Description of "reference" echo control devices.....	187
A.0	General	187
A.1	Handset echo	187
A.1.0	Applicability.....	187