



Network Functions Virtualisation (NFV) Release 3; Management and Orchestration; Interface and Information Model Specification for Multi-Site Connectivity Services

Disclaimer

The present document has been produced and approved by the Network Functions Virtualisation (NFV) ETSI Industry Specification Group (ISG) and represents the views of those members who participated in this ISG. It does not necessarily represent the views of the entire ETSI membership.

Reference

DGS/NFV-IFA032

Keywordsconfiguration, management, MANO, network,
NFV, virtualisation**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important noticeThe present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	11
Foreword.....	11
Modal verbs terminology.....	11
1 Scope	12
2 References	12
2.1 Normative references	12
2.2 Informative references.....	12
3 Definition of terms, symbols and abbreviations.....	13
3.1 Terms.....	13
3.2 Symbols.....	13
3.3 Abbreviations	13
4 Overview of interfaces and information elements for multi-site connectivity services	14
4.1 Introduction	14
4.2 Concepts of multi-site connectivity management.....	15
4.3 Multi-site connectivity network framework and resources	15
4.4 Multi-site connectivity network framework and relationship to Network Service.....	17
4.5 Relation to other NFV Group Specifications.....	17
5 Requirements.....	18
5.1 Introduction and conventions	18
5.1.1 Overview	18
5.1.2 Conventions	18
5.2 WIM interface requirements.....	18
5.3 Interface requirements.....	19
5.3.1 MSCS Management interface requirements	19
5.3.2 Capacity Management interface requirements	19
5.3.3 Fault Management interface requirements.....	20
5.3.4 Performance Management interface requirements.....	20
6 Interfaces exposed by WIM	21
6.1 Introduction	21
6.2 MSCS Management Interface	21
6.2.1 Description.....	21
6.2.2 Create MSCS operation	21
6.2.2.1 Description	21
6.2.2.2 Input Parameters	22
6.2.2.3 Output Parameters.....	22
6.2.2.4 Operation results	22
6.2.3 Query MSCS operation.....	22
6.2.3.1 Description	22
6.2.3.2 Input Parameters	22
6.2.3.3 Output Parameters.....	23
6.2.3.4 Operation results	23
6.2.4 Update MSCS operation	23
6.2.4.1 Description	23
6.2.4.2 Input Parameters	23
6.2.4.3 Output Parameters.....	24
6.2.4.4 Operation results	24
6.2.5 Terminate MSCS operation	24
6.2.5.1 Description	24
6.2.5.2 Input Parameters	24
6.2.5.3 Output Parameters.....	24
6.2.5.4 Operation results	24
6.2.6 Subscribe operation.....	25
6.2.6.1 Description	25

6.2.6.2	Input Parameters	25
6.2.6.3	Output Parameters	25
6.2.6.4	Operation results	25
6.2.7	Notify operation	25
6.2.7.1	Description	25
6.2.8	Query Subscription Info operation	26
6.2.8.1	Description	26
6.2.8.2	Input Parameters	26
6.2.8.3	Output Parameters	26
6.2.8.4	Operation results	26
6.2.9	Terminate Subscription operation	26
6.2.9.1	Description	26
6.2.9.2	Input Parameters	27
6.2.9.3	Output Parameters	27
6.2.9.4	Operation results	27
6.2.10	Create MSCS Reservation operation	27
6.2.10.1	Description	27
6.2.10.2	Input Parameters	27
6.2.10.3	Output Parameters	28
6.2.10.4	Operation results	28
6.2.11	Query MSCS Reservation operation	28
6.2.11.1	Description	28
6.2.11.2	Input parameters	28
6.2.11.3	Output parameters	29
6.2.11.4	Operation results	29
6.2.12	Update MSCS Reservation operation	29
6.2.12.1	Description	29
6.2.12.2	Input parameters	29
6.2.12.3	Output parameters	30
6.2.12.4	Operation results	30
6.2.13	Terminate MSCS Reservation operation	30
6.2.13.1	Description	30
6.2.13.2	Input Parameters	31
6.2.13.3	Output Parameters	31
6.2.13.4	Operation results	31
6.3	Capacity Management interface	31
6.3.1	Description	31
6.3.2	Query Capacity operation	32
6.3.2.1	Description	32
6.3.2.2	Input parameters	32
6.3.2.3	Output parameters	33
6.3.2.4	Operation results	33
6.3.3	Create Capacity Threshold operation	33
6.3.3.1	Description	33
6.3.3.2	Input parameters	33
6.3.3.3	Output parameters	34
6.3.3.4	Operation results	34
6.3.4	Delete Capacity Thresholds operation	34
6.3.4.1	Description	34
6.3.4.2	Input parameters	34
6.3.4.3	Output parameters	34
6.3.4.4	Operation results	34
6.3.5	Query Capacity Threshold operation	35
6.3.5.1	Description	35
6.3.5.2	Input parameters	35
6.3.5.3	Output parameters	35
6.3.5.4	Operation results	35
6.3.6	Query Topology Information operation	35
6.3.6.1	Description	35
6.3.6.2	Input parameters	35
6.3.6.3	Output parameters	36
6.3.6.4	Operation results	36

6.3.7	Query Node Information operation.....	36
6.3.7.1	Description	36
6.3.7.2	Input parameters	36
6.3.7.3	Output parameters	37
6.3.7.4	Operation results	37
6.3.8	Query Link Information operation.....	37
6.3.8.1	Description	37
6.3.8.2	Input parameters.....	37
6.3.8.3	Output parameters.....	37
6.3.8.4	Operation results	38
6.3.9	Query Network Edge Point Information operation.....	38
6.3.9.1	Description	38
6.3.9.2	Input parameters.....	38
6.3.9.3	Output parameters.....	38
6.3.9.4	Operation results	38
6.3.10	Subscribe operation.....	39
6.3.10.1	Description	39
6.3.10.2	Input parameters.....	39
6.3.10.3	Output parameters	39
6.3.10.4	Operation results	39
6.3.11	Notify operation.....	39
6.3.11.1	Description	39
6.3.12	Terminate Subscription operation.....	40
6.3.12.1	Description	40
6.3.12.2	Input parameters.....	40
6.3.12.3	Output parameters	40
6.3.12.4	Operation results	40
6.3.13	Query Subscription Info operation.....	40
6.3.13.1	Description	40
6.3.13.2	Input parameters.....	40
6.3.13.3	Output parameters	41
6.3.13.4	Operation results	41
6.4	Fault Management interface.....	41
6.4.1	Description.....	41
6.4.2	Subscribe operation.....	41
6.4.2.1	Description	41
6.4.2.2	Input parameters.....	42
6.4.2.3	Output parameters	42
6.4.2.4	Operation results	42
6.4.3	Notify operation.....	42
6.4.3.1	Description	42
6.4.4	Terminate Subscription operation.....	43
6.4.4.1	Description	43
6.4.4.2	Input parameters.....	43
6.4.4.3	Output parameters	43
6.4.4.4	Operation results	43
6.4.5	Query Subscription Info operation.....	43
6.4.5.1	Description	43
6.4.5.2	Input parameters.....	43
6.4.5.3	Output parameters	44
6.4.5.4	Operation results	44
6.4.6	Get Alarm List operation	44
6.4.6.1	Description	44
6.4.6.2	Input parameters.....	44
6.4.6.3	Output parameters	44
6.4.6.4	Operation results	44
6.4.7	Acknowledge Alarms operation	45
6.4.7.1	Description	45
6.4.7.2	Input parameters.....	45
6.4.7.3	Output parameters	45
6.4.7.4	Operation results	45
6.5	Performance Management interface.....	45

6.5.1	Description.....	45
6.5.2	Create PM Job operation.....	46
6.5.2.1	Description.....	46
6.5.2.2	Input parameters.....	46
6.5.2.3	Output parameters.....	47
6.5.2.4	Operation results.....	47
6.5.3	Delete PM Jobs operation.....	47
6.5.3.1	Description.....	47
6.5.3.2	Input parameters.....	48
6.5.3.3	Output parameters.....	48
6.5.3.4	Operation results.....	48
6.5.4	Query PM Job operation.....	48
6.5.4.1	Description.....	48
6.5.4.2	Input parameters.....	48
6.5.4.3	Output parameters.....	48
6.5.4.4	Operation results.....	49
6.5.5	Create Threshold operation.....	49
6.5.5.1	Description.....	49
6.5.5.2	Input parameters.....	49
6.5.5.3	Output parameters.....	49
6.5.5.4	Operation results.....	49
6.5.6	Delete Thresholds operation.....	50
6.5.6.1	Description.....	50
6.5.6.2	Input parameters.....	50
6.5.6.3	Output parameters.....	50
6.5.6.4	Operation results.....	50
6.5.7	Query Threshold operation.....	50
6.5.7.1	Description.....	50
6.5.7.2	Input parameters.....	50
6.5.7.3	Output parameters.....	51
6.5.7.4	Operation results.....	51
6.5.8	Subscribe operation.....	51
6.5.8.1	Description.....	51
6.5.8.2	Input parameters.....	51
6.5.8.3	Output parameters.....	51
6.5.8.4	Operation results.....	52
6.5.9	Notify operation.....	52
6.5.9.1	Description.....	52
6.5.10	Terminate Subscription operation.....	52
6.5.10.1	Description.....	52
6.5.10.2	Input parameters.....	52
6.5.10.3	Output parameters.....	52
6.5.10.4	Operation results.....	52
6.5.11	Query Subscription Info operation.....	53
6.5.11.1	Description.....	53
6.5.11.2	Input parameters.....	53
6.5.11.3	Output parameters.....	53
7	Interfaces consumed by WIM.....	53
8	Information elements exchanged.....	53
8.1	Introduction.....	53
8.2	Information elements and notifications related to MSCS Management.....	53
8.2.1	Introduction.....	53
8.2.2	Information elements related to MSCS.....	54
8.2.2.1	Introduction.....	54
8.2.2.2	MscsData Information element.....	54
8.2.2.2.1	Description.....	54
8.2.2.2.2	Attributes.....	54
8.2.2.3	MscsEndpointData information element.....	54
8.2.2.3.1	Description.....	54
8.2.2.3.2	Attributes.....	54

8.2.2.4	MscsProfile information element.....	55
8.2.2.4.1	Description	55
8.2.2.4.2	Attributes	55
8.2.2.5	Mscs Information element.....	55
8.2.2.5.1	Description	55
8.2.2.5.2	Attributes	56
8.2.2.6	Mscnc information element	56
8.2.2.6.1	Description	56
8.2.2.6.2	Attributes	56
8.2.2.7	MscncProfile information element.....	56
8.2.2.7.1	Description	56
8.2.2.7.2	Attributes	57
8.2.2.8	MscsEndpointInfo information element.....	57
8.2.2.8.1	Description	57
8.2.2.8.2	Attributes	57
8.2.3	Information elements related to MSCS Reservation.....	57
8.2.3.1	Introduction	57
8.2.3.2	MscsReservationData information element	58
8.2.3.2.1	Description	58
8.2.3.2.2	Attributes	58
8.2.3.3	ReservedMscs information element	58
8.2.3.3.1	Description	58
8.2.3.3.2	Attributes	58
8.2.4	MscsChangeNotification	59
8.2.4.1	Description	59
8.2.4.2	Trigger conditions	59
8.2.4.3	Attributes.....	59
8.2.5	MscsReservationChangeNotification	60
8.2.5.1	Description	60
8.2.5.2	Trigger conditions	60
8.2.5.3	Attributes.....	60
8.3	Information elements and notifications related to capacity and topology management.....	61
8.3.1	Introduction.....	61
8.3.2	CapacityInfo information element	61
8.3.2.1	Description	61
8.3.2.2	Attributes.....	61
8.3.3	CapacityValueEntry information element	62
8.3.3.1	Description	62
8.3.3.2	Attributes.....	62
8.3.4	TimePeriodInformation information element	62
8.3.4.1	Description	62
8.3.4.2	Attributes.....	62
8.3.5	CapacityThreshold information element.....	63
8.3.5.1	Description	63
8.3.5.2	Attributes.....	63
8.3.6	CapacityChangeNotification.....	63
8.3.6.1	Description	63
8.3.6.2	Trigger Conditions	63
8.3.6.3	Attributes.....	63
8.3.7	NetworkInfo information element	64
8.3.7.1	Description	64
8.3.7.2	Attributes.....	65
8.3.8	TopologyInfo information element.....	65
8.3.8.1	Description	65
8.3.8.2	Attributes.....	65
8.3.9	NodeInfo information element.....	66
8.3.9.1	Description	66
8.3.9.2	Attributes.....	66
8.3.10	LinkInfo information element.....	66
8.3.10.1	Description	66
8.3.10.2	Attributes.....	67
8.3.11	NetworkEdgePointInfo information element.....	67

8.3.11.1	Description	67
8.3.11.2	Attributes	67
8.3.12	ConnectivityServiceEndpointInfo information element	67
8.3.12.1	Description	67
8.3.12.2	Attributes	68
8.3.13	TopologyChangeNotification	68
8.3.13.1	Description	68
8.3.13.2	Trigger Conditions	68
8.3.13.3	Attributes	68
8.4	Information elements and notifications related to Fault management	69
8.4.1	Introduction	69
8.4.2	Alarm information element	69
8.4.2.1	Description	69
8.4.2.2	Attributes	69
8.4.3	AlarmNotification	71
8.4.3.1	Description	71
8.4.3.2	Trigger conditions	71
8.4.3.3	Attributes	71
8.4.4	AlarmClearedNotification	71
8.4.4.1	Description	71
8.4.4.2	Trigger conditions	71
8.4.4.3	Attributes	71
8.4.5	AlarmListRebuiltNotification	72
8.4.5.1	Description	72
8.4.5.2	Trigger conditions	72
8.4.5.3	Attributes	72
8.5	Information elements and notifications related to Performance Management	72
8.5.1	Introduction	72
8.5.2	ObjectSelection information element	72
8.5.2.1	Description	72
8.5.2.2	Attributes	72
8.5.3	PmJob information element	73
8.5.3.1	Description	73
8.5.3.2	Attributes	73
8.5.4	Threshold information element	74
8.5.4.1	Description	74
8.5.4.2	Attributes	74
8.5.5	PerformanceReport information element	75
8.5.5.1	Description	75
8.5.5.2	Attributes	75
8.5.6	PerformanceReportEntry information element	75
8.5.6.1	Description	75
8.5.6.2	Attributes	75
8.5.7	PerformanceValueEntry information element	76
8.5.7.1	Description	76
8.5.7.2	Attributes	76
8.5.8	PerformanceInformationAvailableNotification	76
8.5.8.1	Description	76
8.5.8.2	Trigger Conditions	76
8.5.8.3	Attributes	77
8.5.9	ThresholdCrossedNotification	77
8.5.9.1	Description	77
8.5.9.2	Trigger Conditions	77
8.5.9.3	Attributes	77
Annex A (informative):	Terminology mapping	78
A.1	Introduction	78
A.2	ACTN terminology	78
A.2.1	Introduction	78
A.2.2	Mapping between IFA 032 and ACTN terminology	78
A.2.2.1	Mapping of concepts	78

A.2.2.2	Description of IETF ACTN concepts	78
Annex B (normative):	Performance and capacity metrics and measurements	81
B.1	Metrics and performance measurements	81
B.1.1	Introduction	81
B.1.2	Measured object type definitions.....	81
B.1.2.1	Mscs object type	81
B.1.2.2	Msnr object type.....	81
B.1.3	Performance measurements.....	81
B.1.3.1	MSCS measurements.....	81
B.1.3.1.1	Number of incoming packets	81
B.1.3.1.2	Number of outgoing packets	82
B.1.3.1.3	Number of incoming bytes.....	82
B.1.3.1.4	Number of outgoing bytes.....	83
B.1.3.1.5	Maximum one-way delay.....	83
B.1.3.1.6	Minimum one-way delay	83
B.1.3.1.7	Mean one-way delay	84
B.1.3.1.8	Maximum one-way delay variation.....	84
B.1.3.1.9	Minimum one-way delay variation	85
B.1.3.1.10	Mean one-way delay variation	85
B.1.3.1.11	Packet loss rate.....	85
B.1.3.1.12	Packet collision rate	86
B.1.3.1.13	Number of incoming broadcast packets.....	86
B.1.3.1.14	Number of outgoing broadcast packets.....	86
B.1.3.2	MSNC measurements	87
B.1.3.2.1	Number of incoming packets	87
B.1.3.2.2	Number of outgoing packets	87
B.1.3.2.3	Number of incoming bytes.....	88
B.1.3.2.4	Number of outgoing bytes.....	88
B.1.3.2.5	Maximum one-way delay.....	88
B.1.3.2.6	Minimum one-way delay	89
B.1.3.2.7	Mean one-way delay	89
B.1.3.2.8	Maximum one-way delay variation.....	89
B.1.3.2.9	Minimum one-way delay variation	90
B.1.3.2.10	Mean one-way delay variation	90
B.1.3.2.11	Packet loss rate.....	91
B.1.3.2.12	Packet collision rate	91
B.1.3.2.13	Number of incoming broadcast packets.....	91
B.1.3.2.14	Number of outgoing broadcast packets.....	92
B.2	Metrics and capacity measurements.....	92
B.2.1	Introduction	92
B.2.2	Measured object type definitions.....	92
B.2.2.1	Network object type.....	92
B.2.2.2	Topology object type	93
B.2.2.3	Node object type	93
B.2.2.4	Link object type	93
B.2.3	Capacity measurements.....	93
B.2.3.1	Network measurements.....	93
B.2.3.1.1	Bandwidth	93
B.2.3.1.2	Number of logical networks.....	94
B.2.3.2	Topology measurements.....	94
B.2.3.2.1	Number of circuits (tunnels)	94
B.2.3.2.2	Number of routing areas.....	94
B.2.3.2.3	Number of routing peers	94
B.2.3.2.4	Number of edge nodes per routing area	95
B.2.3.3	Node measurements.....	95
B.2.3.3.1	Number of logical forwarding entries	95
B.2.3.3.2	Number of routing peers of a node.....	95
B.2.3.3.3	Number of bidirectional forwarding detection sessions	95
B.2.3.3.4	Number of link aggregation group members.....	96
B.2.3.3.5	Forwarding load	96

B.2.3.3.6	CPU load.....	96
B.2.3.3.7	Memory load.....	96
B.2.3.4	Link measurements.....	97
B.2.3.4.1	Bandwidth.....	97
Annex C (normative):	Security and Regulatory Concerns.....	98
C.1	Risk analysis and assessment.....	98
Annex D (informative):	Authors & contributors.....	100
History	101

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/ad04b5c1-b8b0-4e1f-81a2-d5ac0df79556/etsi-gs-nfv-ifa-032-v3.2.1-2019-04>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Group Specification (GS) has been produced by ETSI Industry Specification Group (ISG) Network Functions Virtualisation (NFV).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document specifies the interfaces for management of multi-site connectivity services. The services are produced by a WAN Infrastructure Manager (WIM). The present document also describes the operations and the information elements that are exchanged over these interfaces.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI GS NFV-IFA 010: "Network Functions Virtualisation (NFV) Release 3; Management and Orchestration; Functional requirements specification".
- [2] ETSI GS NFV-SEC 012 (V3.1.1): "Network Functions Virtualisation (NFV) Release 3; Security; System architecture specification for execution of sensitive NFV components".
- [3] Recommendation ITU-T X.733: "Information technology - Open Systems Interconnection - Systems Management: Alarm reporting function".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI GS NFV 003: "Network Functions Virtualisation (NFV); Terminology for Main Concepts in NFV".
- [i.2] ETSI GS NFV-MAN 001: "Network Functions Virtualisation (NFV); Management and Orchestration".
- [i.3] ETSI GR NFV-IFA 022: "Network Functions Virtualisation (NFV) Release 3; Management and Orchestration; Report on Management and Connectivity for Multi-Site Services".
- [i.4] IETF RFC 8453: "Framework for Abstraction and Control of TE Networks (ACTN)".

NOTE: Available at <https://tools.ietf.org/html/rfc8453>.

- [i.5] IETF RFC 8454: "Information Model for Abstraction and Control of TE Networks (ACTN)".

NOTE: Available at <https://tools.ietf.org/html/rfc8454>.

- [i.6] ETSI GS NFV-SEC 006 (V1.1.1): "Network Functions Virtualisation (NFV); Security Guide; Report on Security Aspects and Regulatory Concerns".
- [i.7] ETSI GS NFV-SEC 014 (V3.1.1): "Network Functions Virtualisation (NFV) Release 3; NFV Security; Security Specification for MANO Components and Reference Points".
- [i.8] ETSI GS NFV-IFA 031 (V3.2.1): "Network Functions Virtualisation (NFV) Release 3; Management and Orchestration; Requirements and interfaces specification for management of NFV-MANO".
- [i.9] ETSI GS NFV-IFA 005 (V3.2.1): "Network Functions Virtualisation (NFV) Release 3; Management and Orchestration; Or-Vi reference point - Interface and Information Model Specification".
- [i.10] ISO/IEC 9646-7: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in ETSI GS NFV 003 [i.1] and the following apply:

NOTE: A term defined in the present document takes precedence over the definition of the same term, if any, in ETSI GS NFV 003 [i.1].

Multi-site Connectivity Service (MSCS): connectivity service abstracting the details of information regarding the connections between two or more NFVI-PoP (site) network endpoints

Multi-site Network Connection (MSNC): provisioned multi-site network connectivity enabling the data forwarding between two or more network edge points

NOTE: In the present document, the network edge points represent the ingress/egress ports of the network(s) in between the NFVI-PoPs (sites).

Multi-Site Network Service (MSNS): network service whose constituent Network Functions/Network Services are deployed in more than one site

site: NFVI Point of Presence (NFVI-PoP), as defined in ETSI GS NFV 003 [i.1].

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI GS NFV 003 [i.1] and the following apply:

NOTE: An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in ETSI GS NFV 003 [i.1].

Mscs	Multi-site connectivity service
MSNC	Multi-site Network Connection