

ETSI TS 100 392-18-1 V1.7.2 (2018-01)



**Terrestrial Trunked Radio (TETRA);
Voice plus Data (V+D) and Direct Mode Operation (DMO);
Part 18: Air interface optimized applications;
Sub-part 1: Location Information Protocol (LIP)**

Standard PREVIEW
(standards.iteh.ai)
Full standard: https://standards.iteh.ai/catalog/standards/sis/489c-a49d-b46573822401/etsi-ts-100-392-18-1-17-2-2018-01
https://standards.iteh.ai/catalog/standards/sis/489c-a49d-b46573822401/etsi-ts-100-392-18-1-17-2-2018-01

Reference

RTS/TCCE-03232e

Keywords

air interface, location, radio, TETRA, V+D

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2018.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology.....	9
1 Scope	10
2 References	10
2.1 Normative references	10
2.2 Informative references.....	10
3 Definitions, symbols and abbreviations	11
3.1 Definitions.....	11
3.2 Symbols.....	11
3.3 Abbreviations	11
4 Location information protocol.....	12
4.1 General	12
4.2 Location information protocol system architecture.....	13
4.3 Location information protocol service description.....	16
4.3.1 General on services.....	16
4.3.2 Services available at the LIP-SAP.....	16
4.3.3 Service primitives at the LIP-SAP.....	17
4.3.4 Service primitive parameters at the LIP-SAP.....	18
4.3.5 State description.....	18
5 Location information protocol description.....	18
5.1 Description of information elements	18
5.1.1 General on accuracies and uncertainties	18
5.1.2 Acknowledgement request.....	18
5.1.2a Backlog information elements	18
5.1.3 Basic parameters.....	18
5.1.4 Confidence level	18
5.1.5 Direction of travel and direction of travel accuracy.....	19
5.1.6 Horizontal position and horizontal position accuracy.....	19
5.1.7 Horizontal velocity and horizontal velocity accuracy.....	19
5.1.8 Location altitude and location altitude accuracy.....	19
5.1.9 Location information destination	19
5.1.10 Location message reference	20
5.1.11 Location shape	20
5.1.12 Maximum information age	20
5.1.13 Maximum reporting distance	20
5.1.14 Maximum reporting interval	20
5.1.15 Maximum response time.....	20
5.1.16 Minimum reporting interval.....	20
5.1.17 Reason for sending.....	20
5.1.18 Report type.....	21
5.1.19 Request priority	21
5.1.20 Requested/required	21
5.1.21 Start time.....	21
5.1.22 Stop time.....	21
5.1.23 Terminal or location identification	22
5.1.24 Trigger definition.....	22
5.1.25 Trigger type	22
5.1.26 Velocity type.....	22
5.1.27 Vertical velocity and vertical velocity accuracy	22
5.2 Information flows.....	23
5.2.1 General on information flows	23
5.2.2 Pre-programmed MS sending reports	23

5.2.3	Pre-programmed MS sending reports and receiving acknowledgement.....	23
5.2.4	MS receiving basic parameters	24
5.2.5	MS receiving basic parameters and sending response	24
5.2.6	MS reporting basic parameters	25
5.2.7	MS receiving immediate report request and sending response	25
5.2.8	MS receiving immediate report request and asking acknowledgement	26
5.2.9	MS receiving trigger definitions and sending reports	26
5.2.10	MS receiving trigger definitions and sending reports and asking acknowledgements.....	27
5.2.11	MS receiving trigger definitions and sending modification	27
5.2.12	MS receiving trigger definitions and rejecting triggers	28
5.2.13	MS receiving trigger definitions and sending reports to other location information destination.....	28
5.2.14	MS receiving trigger definitions via location server and sending reports to another location information destination	29
5.2.15	Trigger removal	30
5.2.16	Trigger reporting.....	31
5.2.17	Location reporting enabling	31
5.2.18	Location reporting disabling	31
5.2.19	Location reporting temporary control	32
5.2.20	Backlog information flows	33
5.2.21	Allocation of entities.....	34
5.3	Procedures	34
5.3.1	Relations to flow charts	34
5.3.2	General on control messages	34
5.3.3	Accuracy control in control messages	35
5.3.4	General on location report sending	35
5.3.5	General on location report reception.....	36
5.3.6	MS sending unsolicited reports.....	36
5.3.7	MS receiving basic parameters	36
5.3.8	MS reporting basic parameters	36
5.3.9	MS sending immediate reports	36
5.3.10	MS sending immediate report request	37
5.3.11	Triggered report request sending	37
5.3.12	MS receiving triggered reports requests	38
5.3.13	MS sending triggered reports.....	38
5.3.14	MS receiving triggered reports	38
5.3.15	Triggered report reception in location server.....	38
5.3.16	Trigger removal	38
5.3.17	Report trigger request	39
5.3.18	Location report enable/disable request	39
5.3.19	Trigger configuration request	40
5.3.20	Trigger and report type interactions	40
5.3.21	Location message reference usage	40
5.3.22	Triggers for Lost and Regained ability to determine location.....	41
5.3.23	Trigger for Ambience Listening call.....	41
5.3.24	Temporary control of location reporting.....	41
5.3.25	Track retrieval.....	42
5.3.25.1	General on track retrieval.....	42
5.3.25.2	Backlog requesting entity actions	42
5.3.25.3	MT or application actions	43
5.3.25.3.1	Backlog location reporting	43
5.3.25.3.2	Backlog location report recording enabling and disabling	44
5.3.25.3.3	Backlog location report triggers	44
5.3.25.3.4	Result code usage	45
5.3.26	Trigger for call setup.....	45
5.4	Management of time.....	45
6	Location information protocol coding requirements.....	45
6.1	General on coding requirements.....	45
6.2	Location information protocol PDU description tables.....	46
6.2.1	SHORT LOCATION REPORT PDU.....	46
6.2.2	LONG LOCATION REPORT PDU.....	47
6.2.3	LOCATION REPORT ACKNOWLEDGEMENT PDU.....	47

6.2.4	BASIC LOCATION PARAMETERS REQUEST PDU	48
6.2.5	BASIC LOCATION PARAMETERS RESPONSE PDU	49
6.2.6	REPORT BASIC LOCATION PARAMETERS REQUEST PDU	50
6.2.7	REPORT BASIC LOCATION PARAMETERS RESPONSE PDU	50
6.2.8	ADD/MODIFY TRIGGER REQUEST PDU	51
6.2.9	ADD/MODIFY TRIGGER RESPONSE PDU	52
6.2.10	REMOVE TRIGGER REQUEST PDU	53
6.2.11	REMOVE TRIGGER RESPONSE PDU	53
6.2.12	REPORT TRIGGERS REQUEST PDU	53
6.2.13	REPORT TRIGGER RESPONSE PDU	54
6.2.14	LOCATION REPORTING ENABLE/DISABLE REQUEST PDU	55
6.2.15	LOCATION REPORTING ENABLE/DISABLE RESPONSE PDU	55
6.2.16	IMMEDIATE LOCATION REPORT REQUEST PDU	56
6.2.17	LOCATION REPORTING TEMPORARY CONTROL REQUEST PDU	57
6.2.18	LOCATION REPORTING TEMPORARY CONTROL RESPONSE PDU	57
6.2.19	BACKLOG REQUEST PDU	58
6.2.20	BACKLOG RESPONSE PDU	58
6.2.21	Backlog PDUs	58
6.2.21.1	BACKLOG ADD/MODIFY TRIGGERS REQUEST PDU	58
6.2.21.2	BACKLOG ADD/MODIFY TRIGGERS RESPONSE PDU	59
6.2.21.3	BACKLOG CONFIGURATION REQUEST PDU	61
6.2.21.4	BACKLOG CONFIGURATION RESPONSE PDU	61
6.2.21.5	BACKLOG REMOVE TRIGGERS REQUEST PDU	61
6.2.21.6	BACKLOG REMOVE TRIGGERS RESPONSE PDU	61
6.2.21.7	BACKLOG REPORT TRIGGERS REQUEST PDU	62
6.2.21.8	BACKLOG REPORT TRIGGERS RESPONSE PDU	62
6.2.21.9	BACKLOG RETRIEVAL REQUEST PDU	62
6.2.21.10	BACKLOG RETRIEVAL RESPONSE PDU	63
6.3	Location information protocol PDU information elements	63
6.3.1	Acknowledgement request	63
6.3.2	Address or identification type	63
6.3.3	Angle	64
6.3.4	Backlog information elements	64
6.3.4.1	Backlog continuation state	64
6.3.4.2	Backlog denominator rule	64
6.3.4.3	Backlog distance interval rule	65
6.3.4.4	Backlog information available	65
6.3.4.5	Backlog retrieval action	65
6.3.4.6	Backlog retrieval rules	65
6.3.4.7	Backlog location reports present	66
6.3.4.8	Backlog location reports requested	66
6.3.4.9	Backlog order of processing	66
6.3.4.10	Backlog PDU Type	66
6.3.4.11	Backlog time frame rule	67
6.3.4.12	Backlog time interval rule	67
6.3.4a	Confidence level	67
6.3.4b	Default enable/disable lifetime	67
6.3.5	Direction of travel	67
6.3.6	Direction of travel extended	68
6.3.7	Direction of travel accuracy	68
6.3.8	Direction of travel and direction of travel accuracy	68
6.3.9	Direction of travel uncertainty	69
6.3.10	Extended user defined data	69
6.3.11	External subscriber number	69
6.3.12	Half of major axis	69
6.3.13	Half of minor axis	69
6.3.14	Horizontal position accuracy	69
6.3.15	Horizontal position and horizontal position accuracy	70
6.3.16	Horizontal position uncertainty	70
6.3.17	Horizontal velocity	70
6.3.18	Horizontal velocity accuracy	71
6.3.19	Horizontal velocity and horizontal velocity accuracy	72

6.3.20	Horizontal velocity and vertical velocity	72
6.3.21	Horizontal velocity and vertical velocity with uncertainty	72
6.3.22	Horizontal velocity and vertical velocity with direction of travel extended and uncertainty	72
6.3.23	Horizontal velocity uncertainty	73
6.3.24	Horizontal velocity with direction of travel extended	73
6.3.25	Horizontal velocity with direction of travel extended and uncertainty	73
6.3.26	Horizontal velocity with uncertainty	73
6.3.27	Inner radius	74
6.3.28	IPv4 address	74
6.3.29	IPv6 address	74
6.3.30	Latitude	74
6.3.31	Location altitude	74
6.3.32	Location altitude accuracy	75
6.3.33	Location altitude and location altitude accuracy	75
6.3.34	Location altitude uncertainty	75
6.3.35	Location arc	75
6.3.36	Location circle	76
6.3.37	Location circle with altitude	76
6.3.38	Location circle with altitude and uncertainty	76
6.3.39	Location data	77
6.3.40	Location ellipse	77
6.3.41	Location ellipse with altitude	77
6.3.42	Location ellipse with altitude and uncertainty	78
6.3.43	Location information destination	78
6.3.44	Location message reference	78
6.3.45	Location point	79
6.3.46	Location point and position error	79
6.3.47	Location point with altitude	79
6.3.48	Location reporting enable flags	80
6.3.49	Location shape	80
6.3.50	Longitude	80
6.3.51	Maximum information age	81
6.3.52	Maximum reporting distance	81
6.3.53	Maximum reporting interval	82
6.3.54	Maximum response time	82
6.3.54a	Minimum detection interval	82
6.3.55	Minimum reporting interval	83
6.3.56	MNI + SSI	83
6.3.57	MNI + SSI + external subscriber number	83
6.3.58	Name of location	83
6.3.59	Name server type	84
6.3.60	Outer radius	84
6.3.61	PDU type	84
6.3.62	PDU type extension	85
6.3.63	Position error	85
6.3.64	Reason for sending	86
6.3.65	Report type	87
6.3.66	Requested or required	87
6.3.67	Request priority	87
6.3.68	Result code	88
6.3.69	SDS type-1 value	89
6.3.70	SSI	89
6.3.71	SSI + external subscriber number	89
6.3.72	Start angle	89
6.3.73	Start time	90
6.3.74	Status value	90
6.3.75	Stop angle	90
6.3.76	Stop time	90
6.3.76a	Temporary control parameter definition	91
6.3.76b	Temporary control parameter type	91
6.3.76c	Temporary control validity	92
6.3.76d	Temporary maximum reporting distance - relative	92

6.3.76e	Temporary maximum reporting distance - absolute	92
6.3.76f	Temporary minimum reporting interval - absolute	92
6.3.76g	Temporary minimum reporting interval - relative	93
6.3.76h	Temporary report type	93
6.3.77	Terminal or location identification	93
6.3.78	Time elapsed	94
6.3.79	Time of position	94
6.3.80	Time data	95
6.3.81	Time type	95
6.3.82	Trigger definition (one-shot/recurring)	95
6.3.83	Trigger removal	96
6.3.84	Trigger type (one-shot/recurring)	97
6.3.85	Trigger type (recurring)	98
6.3.86	Type 5 element identifier	98
6.3.87	Type of additional data	99
6.3.88	User defined data	99
6.3.89	Velocity data	99
6.3.90	Velocity type	99
6.3.91	Vertical velocity	100
6.3.92	Vertical velocity accuracy	100
6.3.93	Vertical velocity and vertical velocity accuracy	101
6.3.94	Vertical velocity uncertainty	101
6.4	Type 5 information element description	101
6.4.1	Type 5 information element definition	101
6.4.2	Type 5 element length	101
6.4.3	Type 5 element length extension	101
6.4.4	Type 5 information element	102
6.5	Geographical shape descriptions	102
7	Implementation requirements	102
Annex A (informative):	Example of trigger priorities	103
A.1	Trigger priority setting	103
Annex B (informative):	Use of location message reference	105
B.1	Potential usage of location message reference	105
Annex C (informative):	Change Requests	106
History	108

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee TETRA and Critical Communications Evolution (TCCE).

The present document is part 18, sub-part 1 of a multi-part deliverable covering the Terrestrial Trunked Radio (TETRA); the Voice plus Data (V+D), as identified below:

- | | |
|----------------------------|--|
| ETSI EN 300 392-1: | "General network design"; |
| ETSI EN 300 392-2: | "Air Interface (AI)"; |
| ETSI EN 300 392-3: | "Interworking at the Inter-System Interface (ISI)"; |
| ETSI ETS 300 392-4: | "Gateways basic operation"; |
| ETSI EN 300 392-5: | "Peripheral Equipment Interface (PEI)"; |
| ETSI EN 300 392-7: | "Security"; |
| ETSI EN 300 392-9: | "General requirements for supplementary services"; |
| ETSI EN 300 392-10: | "Supplementary services stage 1"; |
| ETSI EN 300 392-11: | "Supplementary services stage 2"; |
| ETSI EN 300 392-12: | "Supplementary services stage 3"; |
| ETSI ETS 300 392-13: | "SDL model of the Air Interface (AI)"; |
| ETSI ETS 300 392-14: | "Protocol Implementation Conformance Statement (PICS) proforma specification"; |
| ETSI TS 100 392-15: | "TETRA frequency bands, duplex spacings and channel numbering"; |
| ETSI TS 100 392-16: | "Network Performance Metrics"; |
| ETSI TR 100 392-17: | "TETRA V+D and DMO specifications"; |
| ETSI TS 100 392-18: | "Air interface optimized applications": |
| Sub-part 1: | "Location Information Protocol (LIP)"; |

- Sub-part 2: "Net Assist Protocol (NAP)";
- Sub-part 3: "Direct mode Over The Air Management protocol (DOTAM)";
- Sub-part 4: "Net Assist protocol 2 (NAP2)".

NOTE 1: Part 3, sub-parts 6 and 7 (Speech format implementation), part 4, sub-part 3 (Data networks gateway), part 10, sub-part 15 (Transfer of control), part 13 (SDL) and part 14 (PICS) of this multi-part deliverable are in status "historical" and are not maintained.

NOTE 2: Some parts are also published as Technical Specifications such as ETSI TS 100 392-2 and those may be the latest version of the document.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are **NOT** allowed in ETSI deliverables except when used in direct citation.

ITeH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/9baf53d9-7c8f-489e-a49d-b46573822401/etsi-ts-100-392-18-1-v1.7.2-2018-01>

1 Scope

The present document defines Location Information Protocol that is optimized for TETRA air interface. It defines services:

- Unsolicited location information reporting.
- Immediate location information reporting.
- Triggered location information reporting.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 392-1: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 1: General network design".
- [2] ETSI EN 300 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".
- [3] IETF RFC 791: "Internet Protocol".
- [4] IETF RFC 3513: "Internet Protocol Version 6 (IPv6) Addressing Architecture".
- [5] ETSI TS 123 032: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); Universal Geographical Area Description (GAD) (3GPP TS 23.032)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 102 021-4: "Terrestrial Trunked Radio (TETRA); User Requirement Specification TETRA Release 2.1; Part 4: Air Interface Enhancements".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ETSI EN 300 392-2 [2] and the following apply:

accuracy: requirement on error of location information in location information requests

location server: entity that collects and optionally stores location information and sends location information reports to its clients

TETRA domain: all entities that are addressed using TETRA defined addresses and understand the binary format of the Location Information Protocol

NOTE: This definition may cover entities that are not controlled by TETRA security features.

uncertainty: error estimation of location information in location information reports

3.2 Symbols

For the purposes of the present document, the following symbols apply:

ra	relationship between original location information source and location information controlling entity
rb	relationship between original location information source and location information destination
rc	relationship between original location information source and location server
rd	relationship between location server and location information controlling entity
re	relationship between location server and location information destination
rf	relationship between the location server in the TETRA domain to the location information controlling entity outside the TETRA domain
rg	relationship between the location server in the TETRA domain to the location information destination entity outside the TETRA domain
rh	relationship between the location server in the TETRA domain to the location information source outside the TETRA domain

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AI	Air Interface
C	Conditional
CR	Change Request
DMO	Direct Mode Operation
ENE	East North East
ESE	East South East
FE	Functional Entity
GPS	Global Positioning System
GSM	Global System for Mobile communications
GSSI	Group Short Subscriber Identity
GTSI	Group TETRA Subscriber Identity
IP	Internet Protocol
IPv4	Internet Protocol version 4
IPv6	Internet Protocol version 6
ISI	Inter System Interface
ISSI	Individual Short Subscriber Identity
ITSI	Individual TETRA Subscriber Identity
LIP	Location Information Protocol
M	Mandatory

M-bit	More-bit
MNI	Mobile Network Identity
MS	Mobile Station
MT	Mobile Terminal
NAP	Net Assist Protocol
NE	North East
NNE	North North East
NNW	North North West
NW	North West
O	Optional
O-bit	Optional-bit
PDU	Protocol Data Unit
PEI	Peripheral Equipment Interface
PICS	Protocol Implementation Conformance Statement
REJ	Rejected
SAP	Service Access Point
SDL	Specification and Description Language
SDS	Short Data Service
SDS-TL	Short Data Service - Transport Layer
SE	South East
SNDP SAP	SubNetwork Dependent Convergence Protocol Service Access Point
SSE	South South East
SSI	Short Subscriber Identity
SSW	South South West
SU	Subscriber Unit
SW	South West
TC	Technical Committee
TMO	Trunked Mode Operation
TSI	TETRA Subscriber Identity
TxI	Transmit Inhibit
URL	Universal Resource Locator
UTC	Universal Time Co-ordinated
WGS84	World Geodetic System 1984
WNW	West North West
WSW	West South West

NOTE: See <http://www.geoconcept.com/2498/WGS84>.

4 Location information protocol

4.1 General

The Location Information Protocol (LIP) is a TETRA air interface optimized application layer protocol that can utilize various transport mechanisms.

The location information protocol may use SDS-TL service at SDS-TL SAP, refer to ETSI EN 300 392-2 [2], clauses 29.1.1 to 29.5.12 in the case of TETRA MS, though it does not use SDS-TL transport mechanisms to ensure delivery. The same protocol can use packet data at SNDP SAP as defined in ETSI EN 300 392-2 [2], clause 28 in the case of TETRA MS.

The location information protocol is location determination technology independent, supports a wide variety of location applications and at the same time optimizes usage of air interface resources. The resource optimization considers both message size and the number of messages, particularly for location reporting. The message size optimization is a compromise between the number bits available and user needs, refer to ETSI TR 102 021-4 [i.1], clause 4.4. As a result the present document defines two basic location reports:

- short location report; and
- long location report.

The first is a general report with restricted information elements and with restricted resolution for some of them. The second provides more flexibility and resolution.

In addition to the location reports the present document defines "control messages" to set and modify MS behaviour and initiate sending of location reports.

The location information protocol can be used in various system configurations including:

- MS to MS communication.
- MS to location server communication.
- Location server to MS communication.

NOTE: Although LIP supports direct MS to individual MS communication; the use of it is discouraged as the optimized air interface usage may be compromised. One possibility to maintain air interface optimization is the use of a group address as the destination address.

4.2 Location information protocol system architecture

Location information may be needed in various entities of the TETRA network or outside the TETRA domain. Physical entities identified for the purpose of the present document are:

- Mobile Station (MS) and location accessory providing or using location information.
- Location server inside the TETRA domain collecting location information and providing it to clients.
- Location information transmission controller.
- Location server outside the TETRA domain.
- Entity outside the TETRA domain providing or using location information.

The functions and services that a location server provides to its clients are outside the scope of the present document and any configuration may be used e.g. a dispatcher station can act as a location server.

A location server outside the TETRA domain may communicate with entities in the TETRA domain using the protocol defined in the present document or e.g. a location server inside the TETRA domain may act as a protocol converter and communicate with the location server or client entities outside the TETRA domain using other protocols. The other protocols are outside the scope of the present document.

The location information exchange contains scenarios:

- MS to MS location information exchange without any action in any other entities.
- MS to location server inside the TETRA domain, where MS is the source of location information and the location server may send requests for it.
- Location server to MS, where the location server has location information of a third party, and MS asks for that location information or the location server distributes the third party location information to MS.
- Location server to MS, where the location server has location information of the requesting MS due a network based location determination, and MS asks for that location information.
- Location server sends location information to any entity outside the TETRA domain.
- Any entity outside the TETRA domain sends locations information to location server.
- Location server or MS may control location information sending triggers and define location information destination.
- Location information transmission controller may control location information sending rate.

Some of the scenarios contain security and privacy risks and may not be supported in all systems. Security and privacy issues are outside the scope of the present document.