

### SLOVENSKI STANDARD SIST ISO 15673:2018

01-junij-2018

#### Smernice za poenostavljeno projektiranje armiranobetonskih konstrukcij za stavbe

Guidelines for the simplified design of structural reinforced concrete for buildings

Lignes directrices pour la conception simplifiée du béton armé pour les structures de bâtiments

(standards.iteh.ai)

Ta slovenski standard je istoveten z: ISO 15673:2016

https://standards.iteh.ai/catalog/standards/sist/72419712-8cee-4b31-93b3-

196e99805e13/sist-iso-15673-2018

ICS:

91.080.40 Betonske konstrukcije Concrete structures

SIST ISO 15673:2018 en

SIST ISO 15673:2018

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 15673:2018

https://standards.iteh.ai/catalog/standards/sist/72419712-8cee-4b31-93b3-196e99805e13/sist-iso-15673-2018

SIST ISO 15673:2018

## INTERNATIONAL STANDARD

ISO 15673

Second edition 2016-12-01

## Guidelines for the simplified design of structural reinforced concrete for buildings

Lignes directrices pour la conception simplifiée du béton armé pour les structures de bâtiments

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 15673:2018

https://standards.iteh.ai/catalog/standards/sist/72419712-8cee-4b31-93b3-196e99805e13/sist-iso-15673-2018



Reference number ISO 15673:2016(E)

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 15673:2018

https://standards.iteh.ai/catalog/standards/sist/72419712-8cee-4b31-93b3-196e99805e13/sist-iso-15673-2018



#### COPYRIGHT PROTECTED DOCUMENT

#### © ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Scope	Contents			Page
1 Scope	Fore	eword		ix
2 Normative references	Introduction			
2 Normative references	1	Scon	ne.	1
3   Terms and definitions   2   2   3   3   4   5   5   5   5   5   6   6   6   6   6		-		
4.1       Symbols       13         4.1       Symbols       13         4.2       Abbreviated terms       16         5       Design and construction procedure       17         5.1       Procedure       17         5.1.1       Step A       17         5.1.2       Step B       17         5.1.3       Step C       17         5.1.4       Step D       17         5.1.5       Step E       17         5.1.6       Step F       17         5.1.7       Step G       17         5.1.8       Step H       17         5.1.9       Step L       STANDARD PREVIEW         18       5.11       Step K       18         5.11       Step K       17         5.1.10       Step K       18         5.2.1       General       18         5.2.2       Lacluation memoric Inductorial report Standards.ifeh.ai)       19         5.2.2       Calculation memoric Inductorial report Standards.stc 72419712-8cc-4b31-93b3-19       19         5.2.2       Specifications       19         6.1       Limitations       19         6.1       Limitations       19     <				
4.1   Symbols	3			
4.2   Abbreviated terms   16	4		bols and abbreviated terms	13
17				
5.1       Procedure       17         5.1.1       Step B       17         5.1.2       Step B       17         5.1.3       Step C       17         5.1.4       Step D       17         5.1.5       Step E       17         5.1.6       Step F       17         5.1.7       Step G       17         5.1.8       Step H       17         5.1.9       Step L       STANDARD PREVIEW       17         5.1.10       Step L       STANDARD PREVIEW       18         5.2.1       General Step L       17         5.1.11       Step L       STANDARD PREVIEW       17         5.1.10       Step L       STANDARD PREVIEW       17         5.1.11       Step L       STANDARD PREVIEW       17         5.1.1       Step L       STANDARD PREVIEW       17         5.1.1       Step L       STANDARD PREVIEW       17         5.1.1       Step L       STANDARD PREVIEW       17         5.1.2       General guides       18         5.2       Calculation memoir Londard Step L       18         5.2       Calculation memoir Londard Step L       19         5.2.1 <td>_</td> <td></td> <td></td> <td></td>	_			
St.1.1   Step A	5			
5.1.2   Step B   17   5.1.3   Step C   17   5.1.5   Step C   17   5.1.5   Step E   17   5.1.6   Step F   17   5.1.6   Step F   17   5.1.8   Step G   17   5.1.8   Step H   17   5.1.9   Step J   STANDARD PREVIEW   17   5.1.10   Step J   STANDARD PREVIEW   17   5.1.10   Step J   STANDARD PREVIEW   18   5.1.11   Step K   STANDARD PREVIEW   18   5.2   Design documentation   18   5.2   Design documentation   19   5.2.1   General   19   5.2.2   Calculation member   ISO 15673-2018   19   5.2.3   Use Georechnical report standards sis 7724   9712-8 ccc - 4631-9363-   19   5.2.4   Structural drawings   13   Step J   19   5.2.5   Specifications   19   6.1   Limitations   19   6.1   Limitations   19   6.1   Limitations   19   6.1.1   Occupancy   19   6.1.2   Maximum number of stories   20   6.1.3   Maximum area per floor   20   6.1.4   Maximum story height   20   6.1.5   Maximum story height   20   6.1.5   Maximum slope of the terrain   20   6.1.7   Minimum number of spans   21   6.1.8   Maximum slope for slabs, girders, beams and joists   21   6.1.10   Maximum slope of the terrain   21   6.3.1   General   21   6.3.2   Required factored strength   22   6.3.3   Design strength   22   6.3.3   Design strength   22   6.3.4   Serviceability limit state design format   22   7   Specific guides   7.1   Structural systems and layout   23   7.1.1   Description of the components of the structure   23   7.1.1   Description of the components of the structure   23   7.1.1   Description of the components of the structure   23   7.1.1   Description of the components of the structure   23   7.1.1   Description of the components of the structure   24   24   25   25   25   25   25   25		3.1		
S.1.3   Step C				
51.5   Step E				
5.1.6       Step F       17         5.1.7       Step G       17         5.1.8       Step H       17         5.1.9       Step I STANDARD PREVIEW       17         5.1.10       Step I STANDARD PREVIEW       18         5.2.1       Step I STANDARD PREVIEW       18         5.2       Design documentation       19         5.2.1       General       19         5.2.2       Calculation memorit ISO 156732018       19         5.2.2       Calculation memorit ISO 156732018       19         5.2.4       Structural drawings 13/sst-so-15673-2018       19         5.2.5       Specifications       19         6.1       Limitations       19         6.1       Limitations       19         6.1.1       Occupancy       19         6.1.2       Maximum number of stories       20         6.1.3       Maximum story height       20         6.1.4       Maximum story height       20         6.1.5       Maximum story height       20         6.1.6       Maximum drifference in span length       20         6.1.5       Maximum drifference in span length       20         6.1.6       Maximum drifference in span			5.1.4 Step D	17
S.1.7   Step G				
5.1.8       Step H.       17         5.1.9       Step L.       STANDARD PREVIEW       17         5.1.10       Step L.       18         5.2       Design documentation       19         5.2.1       General       19         5.2.2       Calculation membric ISO 15673-2018       19         5.2.3       19       5.2.3 tructural drawings e13/sst-so-15673-2018       19         5.2.4       Structural drawings e13/sst-so-15673-2018       19         5.2.5       Specifications       19         6       General guides       19         6.1       Limitations       19         6.1.1       Occupancy       19         6.1.2       Maximum number of stories       20         6.1.3       Maximum area per floor       20         6.1.4       Maximum story height       20         6.1.5       Maximum difference in span length       20         6.1.6       Maximum difference in span length       20         6.1.7       Minimum number of spans       21         6.1.8       Maximum slope for slabs, girders, beams and joists       21         6.1.10       Maximum slope for slabs, girders, beams and joists       21         6.2 <td< td=""><td></td><td></td><td></td><td></td></td<>				
5.1.9   Step   STANDARD PREVIEW   17   5.1.10   Step   Standards.iteh.ai   18   5.2   Design documentation   19   5.2.1   General   19   5.2.2   Galculation membrit ISO 15673-2018   19   5.2.2   Geotechnical report standards/sist/72419712-8cce-4b31-93b3   19   5.2.4   Structural drawings et 3/sist-so-15673-2018   19   5.2.5   Specifications   19   5.2.5   Specifications   19   6.1   Limitations   19   6.1.1   Occupancy   19   6.1.2   Maximum number of stories   20   6.1.3   Maximum area per floor   20   6.1.4   Maximum story height   20   6.1.5   Maximum story height   20   6.1.6   Maximum difference in span length   20   6.1.7   Minimum number of spans   21   6.1.8   Maximum slope for slabs, girders, beams and joists   21   6.1.10   Maximum slope for slabs, girders, beams and joists   21   6.1.10   Maximum slope of the terrain   21   6.3.1   General   21   6.3.2   Required factored strength   22   6.3.3   Design strength   22   6.3.2   Required factored strength   22   6.3.2   Required factored strength   22   6.3.2   Required factored strength   22   6.3.3   Design strength   22   6.3.3   Design strength   22   6.3.5   Specific guides   7.1   Structural systems and layout   23   7.1.1   Description of the components of the structure   23   7.1.2   General programme   24				
5.1.11       Step K       (standards.iteh.ai)       18         5.2       Design documentation       19         5.2.1       General       19         5.2.2       Calculation memoric ISO 15673-2018       19         5.2.3       Description standards/sis/72419712-8cce-4b31-93b3-19       19         5.2.4       Structural drawings e13/sist-so-15673-2018       19         5.2.5       Specifications       19         6       General guides       19         6.1       Limitations       19         6.1       Maximum number of stories       20         6.1.2       Maximum number of stories       20         6.1.3       Maximum story height       20         6.1.4       Maximum story height       20         6.1.5       Maximum span length       20         6.1.6       Maximum solve of spans       21         6.1.7       Minimum number of spans       21         6.1.8       Maximum solpe for slabs, girders, beams and joists       21         6.1.9       Maximum slope of the terrain       21         6.1.1       Distance between centre of mass and centre of rigidity       21         6.2       Limit states       21         6.3				
5.1.11       Step K       (standards.iteh.ai)       18         5.2       Design documentation       19         5.2.1       General       19         5.2.2       Calculation memoric ISO 15673-2018       19         5.2.3       Description standards/sis/72419712-8cce-4b31-93b3-19       19         5.2.4       Structural drawings e13/sist-so-15673-2018       19         5.2.5       Specifications       19         6       General guides       19         6.1       Limitations       19         6.1       Maximum number of stories       20         6.1.2       Maximum number of stories       20         6.1.3       Maximum story height       20         6.1.4       Maximum story height       20         6.1.5       Maximum span length       20         6.1.6       Maximum solve of spans       21         6.1.7       Minimum number of spans       21         6.1.8       Maximum solpe for slabs, girders, beams and joists       21         6.1.9       Maximum slope of the terrain       21         6.1.1       Distance between centre of mass and centre of rigidity       21         6.2       Limit states       21         6.3			5.1.9 Step 1 STANDARD PREVIEW	17 18
5.2.1 General       19         5.2.2 Calculation memoin I ISO 15673.2018       19         5.2.3 Into Georectinical report standards/sist/72419712-8cce-4b31-93b3       19         5.2.4 Structural drawings 13/sist-so-15673-2018       19         5.2.5 Specifications       19         6 General guides       19         6.1 Limitations       19         6.1.1 Occupancy       19         6.1.2 Maximum number of stories       20         6.1.3 Maximum area per floor       20         6.1.4 Maximum story height       20         6.1.5 Maximum span length       20         6.1.6 Maximum difference in span length       20         6.1.7 Minimum number of spans       21         6.1.8 Maximum slope for slabs, girders, beams and joists       21         6.1.10 Maximum slope for slabs, girders, beams and joists       21         6.1.11 Distance between centre of mass and centre of rigidity       21         6.2 Limit states       21         6.3 Ultimate limit state design format       21         6.3.1 General       21         6.3.2 Required factored strength       22         6.3 Required factored strength       22         6.4 Serviceability limit state design format       22         7.1 Structural systems and layout<			5.1.11 Step K (gtandandg ital	18
5.2.1 General       19         5.2.2 Calculation memoin I ISO 15673.2018       19         5.2.3 Into Georectinical report standards/sist/72419712-8cce-4b31-93b3       19         5.2.4 Structural drawings 13/sist-so-15673-2018       19         5.2.5 Specifications       19         6 General guides       19         6.1 Limitations       19         6.1.1 Occupancy       19         6.1.2 Maximum number of stories       20         6.1.3 Maximum area per floor       20         6.1.4 Maximum story height       20         6.1.5 Maximum span length       20         6.1.6 Maximum difference in span length       20         6.1.7 Minimum number of spans       21         6.1.8 Maximum slope for slabs, girders, beams and joists       21         6.1.10 Maximum slope for slabs, girders, beams and joists       21         6.1.11 Distance between centre of mass and centre of rigidity       21         6.2 Limit states       21         6.3 Ultimate limit state design format       21         6.3.1 General       21         6.3.2 Required factored strength       22         6.3 Required factored strength       22         6.4 Serviceability limit state design format       22         7.1 Structural systems and layout<		5.2	Design documentation	19
5.2.5       Specifications       19         6       General guides       19         6.1       Limitations       19         6.1.1       Occupancy       19         6.1.2       Maximum number of stories       20         6.1.3       Maximum area per floor       20         6.1.4       Maximum story height       20         6.1.5       Maximum story height       20         6.1.6       Maximum span length       20         6.1.6       Maximum difference in span length       20         6.1.7       Minimum number of spans       21         6.1.8       Maximum cantilever span       21         6.1.9       Maximum slope for slabs, girders, beams and joists       21         6.1.10       Maximum slope of the terrain       21         6.1.11       Distance between centre of mass and centre of rigidity       21         6.2       Limit states       21         6.3       Ultimate limit state design format       21         6.3.1       General       21         6.3.2       Required factored strength       22         6.3.3       Design strength       22         6.4       Serviceability limit state design format       22			5.2.1 General	19
5.2.5       Specifications       19         6       General guides       19         6.1       Limitations       19         6.1.1       Occupancy       19         6.1.2       Maximum number of stories       20         6.1.3       Maximum area per floor       20         6.1.4       Maximum story height       20         6.1.5       Maximum story height       20         6.1.6       Maximum span length       20         6.1.6       Maximum difference in span length       20         6.1.7       Minimum number of spans       21         6.1.8       Maximum cantilever span       21         6.1.9       Maximum slope for slabs, girders, beams and joists       21         6.1.10       Maximum slope of the terrain       21         6.1.11       Distance between centre of mass and centre of rigidity       21         6.2       Limit states       21         6.3       Ultimate limit state design format       21         6.3.1       General       21         6.3.2       Required factored strength       22         6.3.3       Design strength       22         6.4       Serviceability limit state design format       22			5.2.2 Calculation memoir ISO 156/3:2018	19
5.2.5       Specifications       19         6       General guides       19         6.1       Limitations       19         6.1.1       Occupancy       19         6.1.2       Maximum number of stories       20         6.1.3       Maximum area per floor       20         6.1.4       Maximum story height       20         6.1.5       Maximum story height       20         6.1.6       Maximum span length       20         6.1.6       Maximum difference in span length       20         6.1.7       Minimum number of spans       21         6.1.8       Maximum cantilever span       21         6.1.9       Maximum slope for slabs, girders, beams and joists       21         6.1.10       Maximum slope of the terrain       21         6.1.11       Distance between centre of mass and centre of rigidity       21         6.2       Limit states       21         6.3       Ultimate limit state design format       21         6.3.1       General       21         6.3.2       Required factored strength       22         6.3.3       Design strength       22         6.4       Serviceability limit state design format       22			5.2.3 https://decembicalreport/standards/sist//2419/12-8cee-4031-9303-	
6       General guides       19         6.1       Limitations       19         6.1.1       Occupancy       19         6.1.2       Maximum number of stories       20         6.1.3       Maximum area per floor       20         6.1.4       Maximum story height       20         6.1.5       Maximum span length       20         6.1.6       Maximum difference in span length       20         6.1.7       Minimum number of spans       21         6.1.8       Maximum cantilever span       21         6.1.9       Maximum slope for slabs, girders, beams and joists       21         6.1.10       Maximum slope of the terrain       21         6.1.11       Distance between centre of mass and centre of rigidity       21         6.2       Limit states       21         6.3       Ultimate limit state design format       21         6.3.1       General       21         6.3.2       Required factored strength       22         6.3.3       Design strength       22         6.4       Serviceability limit state design format       22         7.1       Structural systems and layout       23         7.1.1       Description of the components of			5.2.4 Structural drawings 5.2.5 Structural drawings	19
6.1       Limitations       19         6.1.1       Occupancy       19         6.1.2       Maximum number of stories       20         6.1.3       Maximum area per floor       20         6.1.4       Maximum story height       20         6.1.5       Maximum span length       20         6.1.6       Maximum difference in span length       20         6.1.7       Minimum number of spans       21         6.1.8       Maximum cantilever span       21         6.1.9       Maximum slope for slabs, girders, beams and joists       21         6.1.10       Maximum slope of the terrain       21         6.1.11       Distance between centre of mass and centre of rigidity       21         6.2       Limit states       21         6.3       Ultimate limit state design format       21         6.3.1       General       21         6.3.2       Required factored strength       22         6.3       Design strength       22         6.4       Serviceability limit state design format       22         7.1       Structural systems and layout       23         7.1.1       Description of the components of the structure       23         7.1.2 <t< td=""><td></td><td></td><td>•</td><td></td></t<>			•	
6.1.1       Occupancy	6			
6.1.2       Maximum number of stories       20         6.1.3       Maximum area per floor       20         6.1.4       Maximum story height       20         6.1.5       Maximum span length       20         6.1.6       Maximum difference in span length       20         6.1.7       Minimum number of spans       21         6.1.8       Maximum cantilever span       21         6.1.9       Maximum slope for slabs, girders, beams and joists       21         6.1.10       Maximum slope of the terrain       21         6.1.11       Distance between centre of mass and centre of rigidity       21         6.2       Limit states       21         6.3       Ultimate limit state design format       21         6.3.1       General       21         6.3.2       Required factored strength       22         6.3       Design strength       22         6.4       Serviceability limit state design format       22         7       Specific guides       23         7.1       Structural systems and layout       23         7.1.1       Description of the components of the structure       23         7.1.2       General programme       24		6.1		
6.1.3       Maximum area per floor       20         6.1.4       Maximum story height       20         6.1.5       Maximum span length       20         6.1.6       Maximum difference in span length       20         6.1.7       Minimum number of spans       21         6.1.8       Maximum cantilever span       21         6.1.9       Maximum slope for slabs, girders, beams and joists       21         6.1.10       Maximum slope of the terrain       21         6.1.11       Distance between centre of mass and centre of rigidity       21         6.2       Limit states       21         6.3       Ultimate limit state design format       21         6.3.1       General       21         6.3.2       Required factored strength       22         6.3.3       Design strength       22         6.4       Serviceability limit state design format       22         7.1       Structural systems and layout       23         7.1.1       Description of the components of the structure       23         7.1.2       General programme       24				
6.1.4       Maximum story height       20         6.1.5       Maximum span length       20         6.1.6       Maximum difference in span length       20         6.1.7       Minimum number of spans       21         6.1.8       Maximum cantilever span       21         6.1.9       Maximum slope for slabs, girders, beams and joists       21         6.1.10       Maximum slope of the terrain       21         6.1.11       Distance between centre of mass and centre of rigidity       21         6.2       Limit states       21         6.3       Ultimate limit state design format       21         6.3.1       General       21         6.3.2       Required factored strength       22         6.3.3       Design strength       22         6.4       Serviceability limit state design format       22         7.1       Structural systems and layout       23         7.1.1       Description of the components of the structure       23         7.1.2       General programme       24				
6.1.5       Maximum span length       20         6.1.6       Maximum difference in span length       20         6.1.7       Minimum number of spans       21         6.1.8       Maximum cantilever span       21         6.1.9       Maximum slope for slabs, girders, beams and joists       21         6.1.10       Maximum slope of the terrain       21         6.1.11       Distance between centre of mass and centre of rigidity       21         6.2       Limit states       21         6.3       Ultimate limit state design format       21         6.3.1       General       21         6.3.2       Required factored strength       22         6.3.3       Design strength       22         6.4       Serviceability limit state design format       22         7.1       Structural systems and layout       23         7.1.1       Description of the components of the structure       23         7.1.2       General programme       24				
6.1.7 Minimum number of spans       21         6.1.8 Maximum cantilever span       21         6.1.9 Maximum slope for slabs, girders, beams and joists       21         6.1.10 Maximum slope of the terrain       21         6.1.11 Distance between centre of mass and centre of rigidity       21         6.2 Limit states       21         6.3 Ultimate limit state design format       21         6.3.1 General       21         6.3.2 Required factored strength       22         6.3.3 Design strength       22         6.4 Serviceability limit state design format       22         7 Specific guides       23         7.1 Structural systems and layout       23         7.1.1 Description of the components of the structure       23         7.1.2 General programme       24			• •	
6.1.8       Maximum cantilever span.       21         6.1.9       Maximum slope for slabs, girders, beams and joists.       21         6.1.10       Maximum slope of the terrain.       21         6.1.11       Distance between centre of mass and centre of rigidity.       21         6.2       Limit states.       21         6.3       Ultimate limit state design format.       21         6.3.1       General.       21         6.3.2       Required factored strength.       22         6.3.3       Design strength.       22         6.4       Serviceability limit state design format.       22         7       Specific guides.       23         7.1       Structural systems and layout.       23         7.1.1       Description of the components of the structure.       23         7.1.2       General programme.       24			1 0	
6.1.9 Maximum slope for slabs, girders, beams and joists 21 6.1.10 Maximum slope of the terrain 21 6.1.11 Distance between centre of mass and centre of rigidity 21 6.2 Limit states 21 6.3 Ultimate limit state design format 21 6.3.1 General 21 6.3.2 Required factored strength 22 6.3.3 Design strength 22 6.4 Serviceability limit state design format 22 7 Specific guides 23 7.1 Structural systems and layout 23 7.1.1 Description of the components of the structure 23 7.1.2 General programme 24			1	
6.1.10       Maximum slope of the terrain       21         6.1.11       Distance between centre of mass and centre of rigidity       21         6.2       Limit states       21         6.3       Ultimate limit state design format       21         6.3.1       General       21         6.3.2       Required factored strength       22         6.3.3       Design strength       22         6.4       Serviceability limit state design format       22         7       Specific guides       23         7.1       Structural systems and layout       23         7.1.1       Description of the components of the structure       23         7.1.2       General programme       24				
6.1.11 Distance between centre of mass and centre of rigidity       21         6.2 Limit states       21         6.3 Ultimate limit state design format       21         6.3.1 General       21         6.3.2 Required factored strength       22         6.3.3 Design strength       22         6.4 Serviceability limit state design format       22         7 Specific guides       23         7.1 Structural systems and layout       23         7.1.1 Description of the components of the structure       23         7.1.2 General programme       24				
6.2       Limit states       21         6.3       Ultimate limit state design format       21         6.3.1       General       21         6.3.2       Required factored strength       22         6.3.3       Design strength       22         6.4       Serviceability limit state design format       22         7       Specific guides       23         7.1       Structural systems and layout       23         7.1.1       Description of the components of the structure       23         7.1.2       General programme       24				
6.3       Ultimate limit state design format       21         6.3.1       General       21         6.3.2       Required factored strength       22         6.3.3       Design strength       22         6.4       Serviceability limit state design format       22         7       Specific guides       23         7.1       Structural systems and layout       23         7.1.1       Description of the components of the structure       23         7.1.2       General programme       24		6.2		
6.3.2 Required factored strength 22 6.3.3 Design strength 22 6.4 Serviceability limit state design format 22  7 Specific guides 23 7.1 Structural systems and layout 23 7.1.1 Description of the components of the structure 23 7.1.2 General programme 24				
6.3.3 Design strength 22 6.4 Serviceability limit state design format 22  7 Specific guides 23 7.1 Structural systems and layout 23 7.1.1 Description of the components of the structure 23 7.1.2 General programme 24				
6.4 Serviceability limit state design format 22  7 Specific guides 23  7.1 Structural systems and layout 23  7.1.1 Description of the components of the structure 23  7.1.2 General programme 24				
7 Specific guides 23 7.1 Structural systems and layout 23 7.1.1 Description of the components of the structure 23 7.1.2 General programme 24		C 4		
7.1 Structural systems and layout 23 7.1.1 Description of the components of the structure 23 7.1.2 General programme 24				
7.1.1 Description of the components of the structure23 7.1.2 General programme24	7	_		
7.1.2 General programme 24		7.1		
7.1.5 Sit uctural layout				
7.1.4 Feasibility under the guidelines			· · · · · · · · · · · · · · · · · · ·	

8	Actio	ns (load	s)	29		
	8.1		1			
		8.1.1	Load factors and load combinations	29		
		8.1.2	Mass of materials	31		
		8.1.3	Dead loads	31		
		8.1.4	Live loads	32		
		8.1.5	Specified snow load			
		8.1.6	Specified wind forces			
		8.1.7	Specified earthquake forces			
		8.1.8	Seismic design base shear			
9	Gene	General reinforced concrete requirements				
	9.1		1			
	9.2		onal requirements			
	9.3	Materia	als for reinforced concrete			
		9.3.1	General	40		
		9.3.2	Cement			
		9.3.3	Aggregates			
		9.3.4	Water			
		9.3.5	Steel reinforcement	40		
		9.3.6	Admixtures			
		9.3.7	Storage of materials			
		9.3.8	Minimum and maximum reinforcement bar diameter			
		9.3.9	Concrete mixture specification			
		9.3.10	Concrete cover to reinforcement	42		
		9.3.11	Minimum reinforcement bend diameter	43		
		9.3.12	Standard hook dimensions and standard hook dimensions are standard hook dimensions and standard hook di	44		
		9.3.13	Bar spacing and maximum aggregate size	45		
		9.3.14	Maximum nominal coarse aggregate size	45		
		9.3.15	Minimum clear spacing between parallel bars in a layer	46		
		9.3.16	Minimum clear spacing between parallel layers of reinforcement	46		
		9.3.17	Minimum clear spacing between longitudinal bars in columns	47		
		9.3.18	Clear spacing between parallel lap splices	48		
		9.3.19	Maximum flexural reinforcement spacing in solid slabs	48		
		9.3.20	Maximum shrinkage and temperature reinforcement spacing in solid slabs	48		
		9.3.21	Maximum reinforcement spacing in structural concrete walls	49		
		9.3.22	Special details per element type	49		
	9.4	Develo	pment length, lap splicing and anchorage of reinforcement	49		
		9.4.1	Development length	49		
		9.4.2	Lap splice dimensions	51		
		9.4.3	Minimum standard hook anchorage distance	51		
	9.5	Limits	for longitudinal reinforcement	52		
		9.5.1	General	52		
		9.5.2	Solid slabs and footings	52		
		9.5.3	Girders, beams and joists	53		
		9.5.4	Columns			
		9.5.5	Structural concrete walls	55		
	9.6	Minim	um amounts of transverse reinforcement	56		
		9.6.1	General	56		
		9.6.2	Slabs	56		
		9.6.3	Girders, beams and joists	56		
		9.6.4	Columns			
		9.6.5	Structural concrete walls			
	9.7		th of members subjected to bending moments			
		9.7.1	General			
		9.7.2	Factored bending moment at section			
		9.7.3	Minimum design bending moment strength			
		9.7.4	Design moment strength for rectangular sections with tension			
			reinforcement only	61		

		9.7.5 Use of compression reinforcement in girders, beams, and joists 9.7.6 T-beam effect	62
	9.8	Strength of members subjected to shear stresses	66
	7.0	9.8.1 General	
		9.8.2 Factored shear	
		9.8.3 Design shear strength	
		9.8.4 Beam-action shear	
		9.8.5 Two-way action shear (punching shear) in solid slabs and footings	
10	Floor	· systems	71
10	10.1	Types of floor systems	
	20.2	10.1.1 General	
		10.1.2 Slab-on-girder system	
		10.1.3 Description of the basic system	
		10.1.4 Joist systems	
	10.2	Criteria for the selection of the floor system	
	10.3	Guides for structural integrity	78
		10.3.1 General	78
		10.3.2 Perimeter girders in slab-and-girder and joist systems	78
		10.3.3 Other beams and girders	
		10.3.4 Joists	
	10.4	One-way and two-way slabs and load path	78
		10.4.1 General	
		10.4.2 One-way behaviour	
		10.4.3 Two-way behaviour 10.4.4 Floor system foad path	79
		10.4.4 Floor system foad path	79
	10.5	Minimum depth for elements of the floor system  10.5.1 General	79
		10.5.1 General	79
		10.5.2 Solid one-way slabs supported by girders, beams, joists, or structural walls	
		10.5.3 Girders, beams and one way joists supporting the slab	80
	10.6	10.5.4 ps Two way slabs supported by girders, beams, or structural concrete walls	81
	10.6	Initial trial dimensions for the floor system -2018	
11		slabs supported on girders, beams, joists or structural concrete walls	
	11.1	General	
	11.2	Design load definition	
		11.2.1 Loads to be included	
		11.2.2 Dead load and live load	
	11 2	11.2.3 Factored design loads Details of reinforcement	
	11.3	11.3.1 General	
		11.3.2 Shrinkage and temperature reinforcement	
		11.3.3 Positive flexural reinforcement	
		11.3.4 Negative flexural reinforcement	
		11.3.5 Shear reinforcement	
		11.3.6 Corner reinforcement	
	11.4	Top thin solid slab that spans between joists	
	11.1	11.4.1 Dimensional guidelines	
		11.4.2 Factored bending moment	
		11.4.3 Reinforcement	
		11.4.4 Shear strength verification	
		11.4.5 Calculation of the reactions on the joists	
	11.5	Cantilevers of slabs supported on girders, beams or walls	
		11.5.1 Dimensional guidelines	
		11.5.2 Factored negative bending moment	
		11.5.3 Reinforcement	
		11.5.4 Shear verification	
		11.5.5 Calculation of reactions on the supports	

	11.6	One-way one-span solid slabs spanning between girders, beams, or structural	
		concrete walls	
		11.6.1 Dimensional guidelines	
		11.6.2 Factored bending moment	
		11.6.3 Longitudinal flexural reinforcement	
		11.6.4 Shear verification	
		11.6.5 Calculation of the reactions on the supports	
	11.7	One-way solid slabs supported on girders, beams, or walls, with two or more spans.	
		11.7.1 Dimensional guidelines	
		11.7.2 Factored bending moment	
		11.7.3 Longitudinal flexural reinforcement	
		11.7.4 Shear verification	
		11.7.5 Calculation of reactions on the supports	
	11.8	Two-way solid slabs spanning between girders, beams, or structural concrete walls.	
		11.8.1 Dimensional guides	
		11.8.2 Factored flexural moment	
		11.8.3 Longitudinal flexural reinforcement	
		11.8.4 Shear verification	
		11.8.5 Calculation of the reactions on the supports	107
12	Girde	ers, beams and joists	107
	12.1		
	12.2	Design load definition	
		12.2.1 Loads to be included	
	12.3	12.2.2 Factored design loads  Details of reinforcement  Details of reinforcement	109
		12.3.1 General	109
		12.3.1 General (standards.iteh.ai) 12.3.2 Transverse reinforcement	109
		12.3.3 Positive flexural reinforcement	110
		12.3.4 Negative flexural reinforcement 15673:2018	111
		<ul> <li>12.3.3 Positive flexural reinforcement</li> <li>12.3.4 Negative flexural reinforcement 15673:2018</li> <li>12.3.5 Joists and beams supported on girders 72419712-8cee-4b31-93b3-196e99805e13/sist-iso-15673-2018</li> </ul>	115
13	Colur	196e99805e13/sist-iso-15673-2018 mns	122
13	13.1	General	
	13.1	Design load definition	
	13.2	13.2.1 Loads to be included	
		13.2.2 Dead load and live load	
		13.2.3 Factored design loads	
	13.3	Dimensional guidelines	
	13.3	13.3.1 General	
		13.3.2 Limiting section dimensions	
		13.3.3 Distance between lateral supports	
		13.3.4 Column built monolithically with wall	
	13.4	Details of reinforcement	
	15.1	13.4.1 General	
		13.4.2 Longitudinal reinforcement	
		13.4.3 Transverse reinforcement	
	13.5	Flexural design guidelines	
	10.0	13.5.1 Factored loads	
		13.5.2 Initial trial cross-section dimensions and longitudinal reinforcement	
	13.6	Shear design guidelines	
	10.0	13.6.1 Factored shear	
		13.6.2 Shear strength verification	
		13.6.3 Biaxial shear strength verification	
	13.7	Strength of members subjected to axial loads with or without flexure	
	2017	13.7.1 General	
		13.7.2 Combined factored axial load and factored bending moment	
		13.7.3 Design strength for axial compression	
		13.7.4 Balanced strength for axial compression with flexure	

14	Struc	tural concrete walls	139
	14.1	General	139
	14.2	Design load definition	139
		14.2.1 Loads to be included	139
		14.2.2 Dead load and live load	
		14.2.3 Lateral design load	142
		14.2.4 Factored design load	
	14.3	Dimensional guidelines	143
		14.3.1 General	
		14.3.2 Limiting dimensions	143
	14.4	Details of reinforcement	
		14.4.1 General	144
		14.4.2 Number of curtains of reinforcement	
		14.4.3 Vertical reinforcement	
		14.4.4 Horizontal reinforcement	146
		14.4.5 Structural concrete wall reinforcement in seismic zones	
	14.5	Flexural design guidelines	
		14.5.1 Required factored loads	
		14.5.2 Initial trial vertical reinforcement	
		14.5.3 Required factored moment strength verification	
	14.6	Shear guides	147
		14.6.1 Factored shear	
		14.6.2 Shear strength verification	147
	14.7		
		Calculation of reactions at the foundation  14.7.1 Load reaction ANDARD PREVIEW	148
		14.7.2 Moment reaction	148
1 F	Eaum	dations (standards.iteh.ai)	140
15		Dimensioning of the foundation clements	140
	15.1	Dimensioning of the foundation elements  Footings SIST ISO 15673:2018	140
	15.2	15.2 https://daydards.itely.ai/catalog/standards/sixt/70419712-sere-th3-h03b3-d-columns on node	140
		15.2. The Footings supporting circular of regular polygon-shaped columns or pede 15.2.2 Moment in footings e13/sist-iso-15673-2018	140
		15.2.3 Shear in footings	
		15.2.4 Development of reinforcement in footings	
		15.2.5 Minimum footing depth	149
		15.2.6 Transfer of forces at base of column, wall or reinforced pedestal	
		15.2.7 Sloped or stepped footings	
	15.3		
	15.4	Footings on piles	
	13.4	15.4.1 General	
		15.4.2 Anchorage of reinforcement	
		15.4.3 Maximum axial stresses	
		15.4.4 Minimum reinforcement ratios and lengths	
	15.5	Foundation beams	
	13.3	15.5.1 Dimensional guidelines	
		15.5.2 Longitudinal reinforcement	
		15.5.3 Transverse reinforcement	
	15.6	Retaining walls	
	13.0	15.6.1 Lateral earth pressure	
		15.6.2 Types of retaining walls	
		15.6.3 Types of retaining wall failures	
		15.6.4 Static pressures on retaining walls	
		15.6.5 Seismic pressures on retaining walls	
		15.6.6 General requirements for retaining walls	
		15.6.7 Details of reinforcement	
16		al load resisting system	
	16.1		
	16.2	Specified lateral forces	162

#### SIST ISO 15673:2018

### ISO 15673:2016(E)

		16.2.1 General	
		16.2.2 Lateral forces included	162
	16.3	Lateral force resisting structural system  16.3.1 General	162
		16.3.1 General	162
	16.4	Minimum amount of structural concrete walls	
		16.4.1 General	
		16.4.2 Wall area guideline for shear strength	164
		16.4.3 Wall dimensions guideline for lateral stiffness  Special reinforcement details for seismic zones	164
	16.5	Special reinforcement details for seismic zones	164
		16.5.1 General	164
		16.5.2 Girders of frames	164
		16.5.3 Columns	
		16.5.4 Joints	172
		16.5.5 Walls	175
17	Nons	tructural walls	176
Annes	<b>x A</b> (inf	formative) Fourvalent formulae for material factors	178

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 15673:2018

https://standards.iteh.ai/catalog/standards/sist/72419712-8cee-4b31-93b3-196e99805e13/sist-iso-15673-2018

#### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

The committee responsible for this document is ISO/TC 71, Concrete, reinforced concrete and prestressed concrete, Subcommittee SC 5, Simplified design standard for concrete structures.

This second edition cancels and replaces the first edition (ISO-15673:2005); which has been technically revised with the following changes: 6e99805e13/sist-iso-15673-2018

- recent research available in concrete frame and wall buildings as a result of poor structural behaviour observed during recent earthquakes have changed the design and detailing requirements for these type of buildings in seismic prone areas;
- concrete structural design criteria has been unified in almost all countries in order to use similar, if
  not identical load combinations with the same load factors, as well as strength reduction factors; this
  is a substantial change and has been changing in recent years in order to simplify and unify design
  criteria for different construction materials such as timber, steel, masonry and lastly concrete;
- concrete cover requirement have been updated to most recent international building code standards.

#### Introduction

This document is developed for countries that do not have existing national standards. This document should not be used in place of a national standard unless specifically considered and accepted by the national standard body or other appropriate regulartory organization. The design rules are based in simplified worldwide-accepted strength models. This document is self-contained; therefore, actions (loads) and simplified analysis procedures are included, as well as minimum acceptable construction practice guidelines.

The minimum dimensional guidelines contained in this document are intended to account for undesirable side effects that will require more sophisticated analysis and design procedures. Material and construction guidelines are aimed at site mixed concrete, as well as ready-mixed concrete, and steel of the minimum available strength grades.

The earthquake resistance guidelines are included to account for the fact that numerous underdeveloped regions of the world lay in earthquake prone areas. The earthquake resistance is based upon the employment of structural concrete walls (shear walls) that limit the lateral deformations of the structure and provide for its lateral strength.

This document contains guidelines that can be modified by the national standards body due to local design and construction requirements and practices. These guidelines that can be modified are included using ["boxed values"]. The authorities in each member country are expected to review the "boxed values" and may substitute alternative definitive values for these elements for use in the national application of the document.

A great effort was made to include self-explanatory tables, graphics, and design aids to simplify the use of this document and provide foolproof procedures. Notwithstanding, the economic implications of the conservatism inherent in approximate procedures as a substitution to sound and experienced engineering is to be a matter of concern to the designer that employs this document, and to the owner that hires him/her.

https://standards.itch.ai/catalog/standards/sist/72419712-8cee-4b31-93b3-

The purpose of these guidelines is to provide a registered civil engineer or architect with sufficient information to perform the design of the structural reinforced concrete that comprises the structural framing of a low-rise building that complies with the limitations established in <u>6.1</u>. The rules of design as set forth in the present document are simplifications of the more elaborate requirements.

Although the guidelines contained in this document were drawn to produce, when properly employed, a reinforced concrete structure with an appropriate margin of safety, these guidelines are not a replacement of sound and experienced engineering judgement. In order for the resulting structure to attain the intended margin of safety, this document should be used as a whole, and alternative procedures should be employed only when explicitly permitted by the guidelines. The minimum dimensioning guides provided replace, in most cases, more elaborate procedures as those prescribed in the National Building Code, and the eventual economic impact is compensated by the simplicity of the procedures prescribed in this document.

The professional performing the structural design under these guidelines should meet the legal requirements for structural designers in the country of adoption possess a minimum appropriate knowledge of structural mechanics, statics, strength of materials, structural analysis, and reinforced concrete design and construction.

## Guidelines for the simplified design of structural reinforced concrete for buildings

### 1 Scope

This document provides guidelines for the design and construction of low-rise concrete building structures of small area to be built in the less developed areas of the world.

This document is applicable to the planning, design and construction of structural reinforced concrete structures to be used in new low-rise buildings of restricted occupancy, number of stories, and area.

This document can be used as an alternative to the development of a National Concrete Building Code, or equivalent document in countries where no national design codes are available by themselves, or as an alternative to the National Concrete Building Code in countries where specifically considered and accepted by the national standard body or other appropriate regulatory organization.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only/the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 679, Cement — Test methods — Determination of strength

ISO 863, Cement — Test methods — Pozzolanicity test for pozzolanic cements

https://standards.iteh.ai/catalog/standards/sist/72419712-8cee-4b31-93b3-

ISO 2103, Loads due to use and occupancy in residential and public buildings

ISO 2633, Determination of imposed floor loads in production buildings and warehouses

ISO 4354, Wind actions on structures

ISO 6274, Concrete — Sieve analysis of aggregates

ISO 6782, Aggregates for concrete — Determination of bulk density

ISO 6783, Coarse aggregates for concrete — Determination of particle density and water absorption — Hydrostatic balance method

ISO 6935-1, Steel for the reinforcement of concrete — Part 1: Plain bars

ISO 6935-2, Steel for the reinforcement of concrete — Part 2: Ribbed bars

ISO 6935-3, Steel for the reinforcement of concrete — Part 3: Welded reinforcement

ISO 7033, Fine and coarse aggregates for concrete — Determination of the particle mass-per-volume and water absorption — Pycnometer method

ISO 9194, Bases for design of structures — Actions due to the self-weight of structures, non-structural elements and stored materials — Density

ISO 10144, Certification scheme for steel bars and wires for the reinforcement of concrete — Welded-wire reinforcement

ISO 29581-1, Cement — Test methods — Part 1: Analysis by wet chemistry

#### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <a href="http://www.electropedia.org/">http://www.electropedia.org/</a>
- ISO Online browsing platform: available at <a href="http://www.iso.org/obp">http://www.iso.org/obp</a>

#### 3.1

#### acceleration of gravity

g

acceleration produced by gravity at the surface of the Earth

Note 1 to entry: For the application of these guidelines, its value can be approximated to g approximately [10] m/s<sup>2</sup>.

#### 3.2

#### admixture

material other than water, *aggregate* (3.3), or hydraulic cement, used as an ingredient of *concrete* (3.20) and added to concrete before or during its mixing to modify its properties

#### 3.3

#### aggregate

granular material, such as sand, gravel, crushed stone, and iron blast-furnace slag, used in conjunction with a cementing medium to form a hydraulic cement *concrete* (3.20) or mortar

## 3.4 anchorage

(standards.iteh.ai)

device used to anchor a non-structural element to the structural framing

#### 3.5

https://standards.iteh.ai/catalog/standards/sist/72419712-8cee-4b31-93b3-

bar diameter 196e99805e13/sist-iso-15673-2018

<nominal> approximate diameter of a steel reinforcing bar, often used as a class designation

Note 1 to entry: For deformed bars, it is common practice to use the diameter of a plain bar having the same area.

#### 3.6

#### base of structure

level at which earthquake motions are assumed to be imparted to a building

Note 1 to entry: This level does not necessarily coincide with the ground level.

#### 3.7

#### beam

horizontal, or nearly horizontal, structural member supported at one (such as a cantilever) or more points, but not throughout its length, transversely supporting a load, and subjected primarily to flexure

#### 3.8

#### bearing capacity of the soil

maximum permissible stress on the *foundation* (3.51) soil that provides adequate safety against bearing failure of the soil, or *settlement* (3.90) of the foundation of such magnitude as to impair the structure

Note 1 to entry: Its value is defined at the working stress (3.122) level.

#### 3.9

#### bending moment

product of a force and the distance to a particular axis, producing bending effects in a structural element

#### 3.10

#### **boundary** elements

portions along wall edges strengthened by longitudinal and transverse reinforcement (3.117)

Note 1 to entry: Boundary elements do not necessarily require an increase in thickness of the wall.

#### 3.11

#### buildings

structures, usually enclosed by walls and a roof, constructed to provide support or shelter for an intended occupancy (3.76)

#### 3.12

#### caisson

foundation pile of large diameter, built partly or totally above ground and sunk below ground usually by digging out the soil inside

#### 3.13

#### cement

material which, when mixed with water, has hardening properties, used either in *concrete* (3.20) or by itself

#### 3.14

#### center of mass

geometric place where all the mass (3.68) of the floor would be located in plan (assuming the floor diaphragm as an infinite rigid body in its own plane)

#### iTeh STANDARD PREVIEW 3.15

#### center of rigidity

center of rigidity
geometric place located in plan and established assuming that the floor diaphragm is an infinite rigid body in its own plane, where applying an horizontal force, in any direction, no diaphragm rotation is presented around a vertical axis

https://standards.iteh.ai/catalog/standards/sist/72419712-8cee-4b31-93b3-

#### 3.16 column

196e99805e13/sist-iso-15673-2018

vertical member used primarily to support axial compressive *loads* (3.66)

#### 3.17

#### collector elements

elements that serve to transmit the inertia forces within the diaphragm to members of the *lateral-force* resisting system (3.60)

#### 3.18

#### combined footing

footing (3.49) that transmits the load carried by several columns (3.16) or structural concrete walls (3.110) to the supporting soil

#### 3.19

### compression reinforcement

reinforcement (3.85) provided to resist compression stresses induced by bending moments (3.9) acting on the member section

#### 3.20

#### concrete

mixture of portland cement or any other hydraulic cement, fine aggregate, coarse aggregate, and water, with or without admixtures (3.2)

#### concrete mix design

choice and proportioning of the ingredients of *concrete* (3.20)