



**SLOVENSKI STANDARD**  
**oSIST ISO 15673:2018**  
**01-maj-2018**

---

**Smernice za poenostavljeno projektiranje armiranobetonskih konstrukcij za stavbe**

Guidelines for the simplified design of structural reinforced concrete for buildings

iTeh STANDARD PREVIEW  
(standards.iten.eu)

Lignes directrices pour la conception simplifiée du béton armé pour les structures de bâtiments

**Ta slovenski standard je istoveten z: ISO 15673:2016**

**ICS:**

91.080.40      Betonske konstrukcije      Concrete structures

**oSIST ISO 15673:2018**

**en,fr,de**



INTERNATIONAL  
STANDARD

ISO  
15673

Second edition  
2016-12-01

---

---

**Guidelines for the simplified design  
of structural reinforced concrete for  
buildings**

*Lignes directrices pour la conception simplifiée du béton armé pour  
les structures de bâtiments*

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

SIST ISO 15673:2018

<https://standards.iteh.ai/catalog/standards/sist/72419712-8cee-4b31-93b3-196e99805e13/sist-iso-15673-2018>



Reference number  
ISO 15673:2016(E)

© ISO 2016

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 15673:2018

<https://standards.iteh.ai/catalog/standards/sist/72419712-8cee-4b31-93b3-196e99805e13/sist-iso-15673-2018>



## **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
copyright@iso.org  
www.iso.org

# Contents

Page

<b>Foreword</b> .....	<b>ix</b>
<b>Introduction</b> .....	<b>x</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>2</b>
<b>4 Symbols and abbreviated terms</b> .....	<b>13</b>
4.1 Symbols.....	13
4.2 Abbreviated terms.....	16
<b>5 Design and construction procedure</b> .....	<b>17</b>
5.1 Procedure.....	17
5.1.1 Step A.....	17
5.1.2 Step B.....	17
5.1.3 Step C.....	17
5.1.4 Step D.....	17
5.1.5 Step E.....	17
5.1.6 Step F.....	17
5.1.7 Step G.....	17
5.1.8 Step H.....	17
5.1.9 Step I.....	17
5.1.10 Step J.....	18
5.1.11 Step K.....	18
5.2 Design documentation.....	19
5.2.1 General.....	19
5.2.2 Calculation memoir.....	19
5.2.3 Geotechnical report.....	19
5.2.4 Structural drawings.....	19
5.2.5 Specifications.....	19
<b>6 General guides</b> .....	<b>19</b>
6.1 Limitations.....	19
6.1.1 Occupancy.....	19
6.1.2 Maximum number of stories.....	20
6.1.3 Maximum area per floor.....	20
6.1.4 Maximum story height.....	20
6.1.5 Maximum span length.....	20
6.1.6 Maximum difference in span length.....	20
6.1.7 Minimum number of spans.....	21
6.1.8 Maximum cantilever span.....	21
6.1.9 Maximum slope for slabs, girders, beams and joists.....	21
6.1.10 Maximum slope of the terrain.....	21
6.1.11 Distance between centre of mass and centre of rigidity.....	21
6.2 Limit states.....	21
6.3 Ultimate limit state design format.....	21
6.3.1 General.....	21
6.3.2 Required factored strength.....	22
6.3.3 Design strength.....	22
6.4 Serviceability limit state design format.....	22
<b>7 Specific guides</b> .....	<b>23</b>
7.1 Structural systems and layout.....	23
7.1.1 Description of the components of the structure.....	23
7.1.2 General programme.....	24
7.1.3 Structural layout.....	25
7.1.4 Feasibility under the guidelines.....	28

## ISO 15673:2016(E)

<b>8</b>	<b>Actions (loads)</b> .....	<b>29</b>
8.1	General.....	29
8.1.1	Load factors and load combinations.....	29
8.1.2	Mass of materials.....	31
8.1.3	Dead loads.....	31
8.1.4	Live loads.....	32
8.1.5	Specified snow load.....	32
8.1.6	Specified wind forces.....	32
8.1.7	Specified earthquake forces.....	32
8.1.8	Seismic design base shear.....	39
<b>9</b>	<b>General reinforced concrete requirements</b> .....	<b>40</b>
9.1	General.....	40
9.2	Additional requirements.....	40
9.3	Materials for reinforced concrete.....	40
9.3.1	General.....	40
9.3.2	Cement.....	40
9.3.3	Aggregates.....	40
9.3.4	Water.....	40
9.3.5	Steel reinforcement.....	40
9.3.6	Admixtures.....	41
9.3.7	Storage of materials.....	41
9.3.8	Minimum and maximum reinforcement bar diameter.....	41
9.3.9	Concrete mixture specification.....	42
9.3.10	Concrete cover to reinforcement.....	42
9.3.11	Minimum reinforcement bend diameter.....	43
9.3.12	Standard hook dimensions.....	44
9.3.13	Bar spacing and maximum aggregate size.....	45
9.3.14	Maximum nominal coarse aggregate size.....	45
9.3.15	Minimum clear spacing between parallel bars in a layer.....	46
9.3.16	Minimum clear spacing between parallel layers of reinforcement.....	46
9.3.17	Minimum clear spacing between longitudinal bars in columns.....	47
9.3.18	Clear spacing between parallel lap splices.....	48
9.3.19	Maximum flexural reinforcement spacing in solid slabs.....	48
9.3.20	Maximum shrinkage and temperature reinforcement spacing in solid slabs.....	48
9.3.21	Maximum reinforcement spacing in structural concrete walls.....	49
9.3.22	Special details per element type.....	49
9.4	Development length, lap splicing and anchorage of reinforcement.....	49
9.4.1	Development length.....	49
9.4.2	Lap splice dimensions.....	51
9.4.3	Minimum standard hook anchorage distance.....	51
9.5	Limits for longitudinal reinforcement.....	52
9.5.1	General.....	52
9.5.2	Solid slabs and footings.....	52
9.5.3	Girders, beams and joists.....	53
9.5.4	Columns.....	55
9.5.5	Structural concrete walls.....	55
9.6	Minimum amounts of transverse reinforcement.....	56
9.6.1	General.....	56
9.6.2	Slabs.....	56
9.6.3	Girders, beams and joists.....	56
9.6.4	Columns.....	56
9.6.5	Structural concrete walls.....	60
9.7	Strength of members subjected to bending moments.....	61
9.7.1	General.....	61
9.7.2	Factored bending moment at section.....	61
9.7.3	Minimum design bending moment strength.....	61
9.7.4	Design moment strength for rectangular sections with tension reinforcement only.....	61

	9.7.5	Use of compression reinforcement in girders, beams, and joists .....	62
	9.7.6	T-beam effect.....	64
9.8		Strength of members subjected to shear stresses.....	66
	9.8.1	General.....	66
	9.8.2	Factored shear.....	67
	9.8.3	Design shear strength.....	67
	9.8.4	Beam-action shear.....	67
	9.8.5	Two-way action shear (punching shear) in solid slabs and footings .....	70
<b>10</b>		<b>Floor systems.....</b>	<b>71</b>
	10.1	Types of floor systems.....	71
		10.1.1 General.....	71
		10.1.2 Slab-on-girder system.....	71
		10.1.3 Description of the basic system.....	71
		10.1.4 Joist systems.....	74
	10.2	Criteria for the selection of the floor system.....	77
	10.3	Guides for structural integrity.....	78
		10.3.1 General.....	78
		10.3.2 Perimeter girders in slab-and-girder and joist systems.....	78
		10.3.3 Other beams and girders.....	78
		10.3.4 Joists.....	78
	10.4	One-way and two-way slabs and load path.....	78
		10.4.1 General.....	78
		10.4.2 One-way behaviour.....	78
		10.4.3 Two-way behaviour.....	79
		10.4.4 Floor system load path.....	79
	10.5	Minimum depth for elements of the floor system.....	79
		10.5.1 General.....	79
		10.5.2 Solid one-way slabs supported by girders, beams, joists, or structural walls.....	79
		10.5.3 Girders, beams and one-way joists supporting the slab.....	80
		10.5.4 Two-way slabs supported by girders, beams, or structural concrete walls.....	81
	10.6	Initial trial dimensions for the floor system.....	82
<b>11</b>		<b>Solid slabs supported on girders, beams, joists or structural concrete walls.....</b>	<b>82</b>
	11.1	General.....	82
	11.2	Design load definition.....	82
		11.2.1 Loads to be included.....	82
		11.2.2 Dead load and live load.....	82
		11.2.3 Factored design loads.....	82
	11.3	Details of reinforcement.....	83
		11.3.1 General.....	83
		11.3.2 Shrinkage and temperature reinforcement.....	83
		11.3.3 Positive flexural reinforcement.....	83
		11.3.4 Negative flexural reinforcement.....	84
		11.3.5 Shear reinforcement.....	85
		11.3.6 Corner reinforcement.....	85
	11.4	Top thin solid slab that spans between joists.....	87
		11.4.1 Dimensional guidelines.....	87
		11.4.2 Factored bending moment.....	87
		11.4.3 Reinforcement.....	87
		11.4.4 Shear strength verification.....	88
		11.4.5 Calculation of the reactions on the joists.....	88
	11.5	Cantilevers of slabs supported on girders, beams or walls.....	88
		11.5.1 Dimensional guidelines.....	88
		11.5.2 Factored negative bending moment.....	88
		11.5.3 Reinforcement.....	89
		11.5.4 Shear verification.....	91
		11.5.5 Calculation of reactions on the supports.....	92

## ISO 15673:2016(E)

11.6	One-way one-span solid slabs spanning between girders, beams, or structural concrete walls .....	92
11.6.1	Dimensional guidelines .....	92
11.6.2	Factored bending moment .....	92
11.6.3	Longitudinal flexural reinforcement .....	92
11.6.4	Shear verification .....	93
11.6.5	Calculation of the reactions on the supports .....	94
11.7	One-way solid slabs supported on girders, beams, or walls, with two or more spans .....	94
11.7.1	Dimensional guidelines .....	94
11.7.2	Factored bending moment .....	94
11.7.3	Longitudinal flexural reinforcement .....	95
11.7.4	Shear verification .....	97
11.7.5	Calculation of reactions on the supports .....	97
11.8	Two-way solid slabs spanning between girders, beams, or structural concrete walls .....	97
11.8.1	Dimensional guides .....	97
11.8.2	Factored flexural moment .....	98
11.8.3	Longitudinal flexural reinforcement .....	104
11.8.4	Shear verification .....	106
11.8.5	Calculation of the reactions on the supports .....	107
<b>12</b>	<b>Girders, beams and joists .....</b>	<b>107</b>
12.1	General .....	107
12.2	Design load definition .....	108
12.2.1	Loads to be included .....	108
12.2.2	Factored design loads .....	108
12.3	Details of reinforcement .....	109
12.3.1	General .....	109
12.3.2	Transverse reinforcement .....	109
12.3.3	Positive flexural reinforcement .....	110
12.3.4	Negative flexural reinforcement .....	111
12.3.5	Joists and beams supported on girders .....	115
<b>13</b>	<b>Columns .....</b>	<b>123</b>
13.1	General .....	123
13.2	Design load definition .....	123
13.2.1	Loads to be included .....	123
13.2.2	Dead load and live load .....	125
13.2.3	Factored design loads .....	126
13.3	Dimensional guidelines .....	126
13.3.1	General .....	126
13.3.2	Limiting section dimensions .....	126
13.3.3	Distance between lateral supports .....	127
13.3.4	Column built monolithically with wall .....	128
13.4	Details of reinforcement .....	128
13.4.1	General .....	128
13.4.2	Longitudinal reinforcement .....	128
13.4.3	Transverse reinforcement .....	132
13.5	Flexural design guidelines .....	132
13.5.1	Factored loads .....	132
13.5.2	Initial trial cross-section dimensions and longitudinal reinforcement .....	132
13.6	Shear design guidelines .....	133
13.6.1	Factored shear .....	133
13.6.2	Shear strength verification .....	134
13.6.3	Biaxial shear strength verification .....	134
13.7	Strength of members subjected to axial loads with or without flexure .....	134
13.7.1	General .....	134
13.7.2	Combined factored axial load and factored bending moment .....	134
13.7.3	Design strength for axial compression .....	135
13.7.4	Balanced strength for axial compression with flexure .....	135



<b>14</b>	<b>Structural concrete walls</b> .....	<b>139</b>
14.1	General.....	139
14.2	Design load definition.....	139
14.2.1	Loads to be included.....	139
14.2.2	Dead load and live load.....	142
14.2.3	Lateral design load.....	142
14.2.4	Factored design load.....	143
14.3	Dimensional guidelines.....	143
14.3.1	General.....	143
14.3.2	Limiting dimensions.....	143
14.4	Details of reinforcement.....	144
14.4.1	General.....	144
14.4.2	Number of curtains of reinforcement.....	145
14.4.3	Vertical reinforcement.....	145
14.4.4	Horizontal reinforcement.....	146
14.4.5	Structural concrete wall reinforcement in seismic zones.....	147
14.5	Flexural design guidelines.....	147
14.5.1	Required factored loads.....	147
14.5.2	Initial trial vertical reinforcement.....	147
14.5.3	Required factored moment strength verification.....	147
14.6	Shear guides.....	147
14.6.1	Factored shear.....	147
14.6.2	Shear strength verification.....	147
14.7	Calculation of reactions at the foundation.....	148
14.7.1	Load reaction.....	148
14.7.2	Moment reaction.....	148
<b>15</b>	<b>Foundations</b> .....	<b>148</b>
15.1	Dimensioning of the foundation elements.....	148
15.2	Footings.....	148
15.2.1	Footings supporting circular or regular polygon-shaped columns or pedestals.....	148
15.2.2	Moment in footings.....	148
15.2.3	Shear in footings.....	149
15.2.4	Development of reinforcement in footings.....	149
15.2.5	Minimum footing depth.....	149
15.2.6	Transfer of forces at base of column, wall or reinforced pedestal.....	149
15.2.7	Sloped or stepped footings.....	150
15.3	Foundation mats.....	150
15.4	Footings on piles.....	150
15.4.1	General.....	150
15.4.2	Anchorage of reinforcement.....	150
15.4.3	Maximum axial stresses.....	150
15.4.4	Minimum reinforcement ratios and lengths.....	150
15.5	Foundation beams.....	151
15.5.1	Dimensional guidelines.....	151
15.5.2	Longitudinal reinforcement.....	151
15.5.3	Transverse reinforcement.....	151
15.6	Retaining walls.....	151
15.6.1	Lateral earth pressure.....	151
15.6.2	Types of retaining walls.....	152
15.6.3	Types of retaining wall failures.....	153
15.6.4	Static pressures on retaining walls.....	154
15.6.5	Seismic pressures on retaining walls.....	156
15.6.6	General requirements for retaining walls.....	160
15.6.7	Details of reinforcement.....	160
<b>16</b>	<b>Lateral load resisting system</b> .....	<b>161</b>
16.1	General.....	161
16.2	Specified lateral forces.....	162

**ISO 15673:2016(E)**

16.2.1	General.....	162
16.2.2	Lateral forces included.....	162
16.3	Lateral force resisting structural system.....	162
16.3.1	General.....	162
16.4	Minimum amount of structural concrete walls.....	163
16.4.1	General.....	163
16.4.2	Wall area guideline for shear strength.....	164
16.4.3	Wall dimensions guideline for lateral stiffness.....	164
16.5	Special reinforcement details for seismic zones.....	164
16.5.1	General.....	164
16.5.2	Girders of frames.....	164
16.5.3	Columns.....	167
16.5.4	Joints.....	172
16.5.5	Walls.....	175
<b>17</b>	<b>Nonstructural walls.....</b>	<b>176</b>
<b>Annex A (informative) Equivalent formulae for material factors.....</b>		<b>178</b>

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 15673:2018

<https://standards.iteh.ai/catalog/standards/sist/72419712-8cee-4b31-93b3-196e99805e13/sist-iso-15673-2018>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

The committee responsible for this document is ISO/TC 71, *Concrete, reinforced concrete and prestressed concrete*, Subcommittee SC 5, *Simplified design standard for concrete structures*.

This second edition cancels and replaces the first edition (ISO 15673:2005), which has been technically revised with the following changes:

- recent research available in concrete frame and wall buildings as a result of poor structural behaviour observed during recent earthquakes have changed the design and detailing requirements for these type of buildings in seismic prone areas;
- concrete structural design criteria has been unified in almost all countries in order to use similar, if not identical load combinations with the same load factors, as well as strength reduction factors; this is a substantial change and has been changing in recent years in order to simplify and unify design criteria for different construction materials such as timber, steel, masonry and lastly concrete;
- concrete cover requirement have been updated to most recent international building code standards.

## ISO 15673:2016(E)

### Introduction

This document is developed for countries that do not have existing national standards. This document should not be used in place of a national standard unless specifically considered and accepted by the national standard body or other appropriate regulatory organization. The design rules are based in simplified worldwide-accepted strength models. This document is self-contained; therefore, actions (loads) and simplified analysis procedures are included, as well as minimum acceptable construction practice guidelines.

The minimum dimensional guidelines contained in this document are intended to account for undesirable side effects that will require more sophisticated analysis and design procedures. Material and construction guidelines are aimed at site mixed concrete, as well as ready-mixed concrete, and steel of the minimum available strength grades.

The earthquake resistance guidelines are included to account for the fact that numerous underdeveloped regions of the world lay in earthquake prone areas. The earthquake resistance is based upon the employment of structural concrete walls (shear walls) that limit the lateral deformations of the structure and provide for its lateral strength.

This document contains guidelines that can be modified by the national standards body due to local design and construction requirements and practices. These guidelines that can be modified are included using [*boxed values*]. The authorities in each member country are expected to review the “boxed values” and may substitute alternative definitive values for these elements for use in the national application of the document.

A great effort was made to include self-explanatory tables, graphics, and design aids to simplify the use of this document and provide foolproof procedures. Notwithstanding, the economic implications of the conservatism inherent in approximate procedures as a substitution to sound and experienced engineering is to be a matter of concern to the designer that employs this document, and to the owner that hires him/her.

The purpose of these guidelines is to provide a registered civil engineer or architect with sufficient information to perform the design of the structural reinforced concrete that comprises the structural framing of a low-rise building that complies with the limitations established in [6.1](#). The rules of design as set forth in the present document are simplifications of the more elaborate requirements.

Although the guidelines contained in this document were drawn to produce, when properly employed, a reinforced concrete structure with an appropriate margin of safety, these guidelines are not a replacement of sound and experienced engineering judgement. In order for the resulting structure to attain the intended margin of safety, this document should be used as a whole, and alternative procedures should be employed only when explicitly permitted by the guidelines. The minimum dimensioning guides provided replace, in most cases, more elaborate procedures as those prescribed in the National Building Code, and the eventual economic impact is compensated by the simplicity of the procedures prescribed in this document.

The professional performing the structural design under these guidelines should meet the legal requirements for structural designers in the country of adoption possess a minimum appropriate knowledge of structural mechanics, statics, strength of materials, structural analysis, and reinforced concrete design and construction.

# Guidelines for the simplified design of structural reinforced concrete for buildings

## 1 Scope

This document provides guidelines for the design and construction of low-rise concrete building structures of small area to be built in the less developed areas of the world.

This document is applicable to the planning, design and construction of structural reinforced concrete structures to be used in new low-rise buildings of restricted occupancy, number of stories, and area.

This document can be used as an alternative to the development of a National Concrete Building Code, or equivalent document in countries where no national design codes are available by themselves, or as an alternative to the National Concrete Building Code in countries where specifically considered and accepted by the national standard body or other appropriate regulatory organization.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 679, *Cement — Test methods — Determination of strength*

ISO 863, *Cement — Test methods — Pozzolanicity test for pozzolanic cements*

ISO 2103, *Loads due to use and occupancy in residential and public buildings*

ISO 2633, *Determination of imposed floor loads in production buildings and warehouses*

ISO 4354, *Wind actions on structures*

ISO 6274, *Concrete — Sieve analysis of aggregates*

ISO 6782, *Aggregates for concrete — Determination of bulk density*

ISO 6783, *Coarse aggregates for concrete — Determination of particle density and water absorption — Hydrostatic balance method*

ISO 6935-1, *Steel for the reinforcement of concrete — Part 1: Plain bars*

ISO 6935-2, *Steel for the reinforcement of concrete — Part 2: Ribbed bars*

ISO 6935-3, *Steel for the reinforcement of concrete — Part 3: Welded reinforcement*

ISO 7033, *Fine and coarse aggregates for concrete — Determination of the particle mass-per-volume and water absorption — Pycnometer method*

ISO 9194, *Bases for design of structures — Actions due to the self-weight of structures, non-structural elements and stored materials — Density*

ISO 10144, *Certification scheme for steel bars and wires for the reinforcement of concrete — Welded-wire reinforcement*

ISO 29581-1, *Cement — Test methods — Part 1: Analysis by wet chemistry*

## ISO 15673:2016(E)

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

#### 3.1 acceleration of gravity

*g*  
acceleration produced by gravity at the surface of the Earth

Note 1 to entry: For the application of these guidelines, its value can be approximated to *g* approximately [10] m/s<sup>2</sup>.

#### 3.2 admixture

material other than water, *aggregate* (3.3), or hydraulic cement, used as an ingredient of *concrete* (3.20) and added to concrete before or during its mixing to modify its properties

#### 3.3 aggregate

granular material, such as sand, gravel, crushed stone, and iron blast-furnace slag, used in conjunction with a cementing medium to form a hydraulic cement *concrete* (3.20) or mortar

#### 3.4 anchorage

device used to anchor a non-structural element to the structural framing

#### 3.5 bar diameter

<nominal> approximate diameter of a steel reinforcing bar, often used as a class designation

Note 1 to entry: For deformed bars, it is common practice to use the diameter of a plain bar having the same area.

#### 3.6 base of structure

level at which earthquake motions are assumed to be imparted to a building

Note 1 to entry: This level does not necessarily coincide with the ground level.

#### 3.7 beam

horizontal, or nearly horizontal, structural member supported at one (such as a cantilever) or more points, but not throughout its length, transversely supporting a load, and subjected primarily to flexure

#### 3.8 bearing capacity of the soil

maximum permissible stress on the *foundation* (3.51) soil that provides adequate safety against bearing failure of the soil, or *settlement* (3.90) of the foundation of such magnitude as to impair the structure

Note 1 to entry: Its value is defined at the *working stress* (3.122) level.

#### 3.9 bending moment

product of a force and the distance to a particular axis, producing bending effects in a structural element

**3.10****boundary elements**

portions along wall edges strengthened by longitudinal and *transverse reinforcement* (3.117)

Note 1 to entry: Boundary elements do not necessarily require an increase in thickness of the wall.

**3.11****buildings**

structures, usually enclosed by walls and a roof, constructed to provide support or shelter for an intended *occupancy* (3.76)

**3.12****caisson**

foundation pile of large diameter, built partly or totally above ground and sunk below ground usually by digging out the soil inside

**3.13****cement**

material which, when mixed with water, has hardening properties, used either in *concrete* (3.20) or by itself

**3.14****center of mass**

geometric place where all the *mass* (3.68) of the floor would be located in plan (assuming the floor diaphragm as an infinite rigid body in its own plane)

**3.15****center of rigidity**

geometric place located in plan and established assuming that the floor diaphragm is an infinite rigid body in its own plane, where applying an horizontal force, in any direction, no diaphragm rotation is presented around a vertical axis

**3.16****column**

vertical member used primarily to support axial compressive *loads* (3.66)

**3.17****collector elements**

elements that serve to transmit the inertia forces within the diaphragm to members of the *lateral-force resisting system* (3.60)

**3.18****combined footing**

*footing* (3.49) that transmits the load carried by several *columns* (3.16) or *structural concrete walls* (3.110) to the supporting soil

**3.19****compression reinforcement**

*reinforcement* (3.85) provided to resist compression stresses induced by *bending moments* (3.9) acting on the member section

**3.20****concrete**

mixture of portland cement or any other hydraulic cement, fine aggregate, coarse aggregate, and water, with or without *admixtures* (3.2)

**3.21****concrete mix design**

choice and proportioning of the ingredients of *concrete* (3.20)