

# SLOVENSKI STANDARD SIST EN 301 908-15 V15.1.1:2020

01-marec-2020

Celična omrežja IMT - Harmonizirani standard za dostop do radijskega spektra -15. del: Ponavljalniki za razviti prizemni radijski dostop za UMTS (E-UTRA FDD)

IMT cellular networks - Harmonised Standard for access to radio spectrum - Part 15: Evolved Universal Terrestrial Radio Access (E-UTRA FDD) Repeaters

# iTeh STANDARD PREVIEW (standards.iteh.ai)

Ta slovenski standard je istoveten 2.301 90 ETSI EN 301 908-15 V15.1.1 (2020-01) https://standards.iteh.ai/catalog/standards/sist/5c5c96f0-c61c-44dd-a0ac-

89039269f13a/sist-en-301-908-15-v15-1-1-2020

#### ICS:

33.060.99 Druga oprema za radijske Other equipment for komunikacije radiocommunications Other mobile services 33.070.99 Druge mobilne storitve

SIST EN 301 908-15 V15.1.1:2020 en SIST EN 301 908-15 V15.1.1:2020

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 908-15 V15.1.1:2020 https://standards.iteh.ai/catalog/standards/sist/5c5c96f0-c61c-44dd-a0ac-89039269f13a/sist-en-301-908-15-v15-1-1-2020 SIST EN 301 908-15 V15.1.1:2020

# ETSI EN 301 908-15 V15.1.1 (2020-01)



# IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 15: Evolved Universal Terrestrial Radio Access (E-UTRA FDD) Repeaters

https://standards.iteh.ai/catalog/standards/sist/5c5c96f0-c61c-44dd-a0ac-89039269f13a/sist-en-301-908-15-v15-1-1-2020

#### Reference

#### REN/MSG-TFES-15-15

#### Keywords

3G, 3GPP, cellular, digital, E-UTRA, IMT, IMT-2000, LTE, mobile, radio, regulation, repeater, UMTS, WCDMA

#### **ETSI**

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la

Teh Sous-Préfecture de Grasse (06) N° 7803/88/ IEW

(standards.iteh.ai)

#### Important notice

https://standards.iteh.ai/catalog/standards/sist/5c5c96f0-c61c-44dd-a0ac-The present document can be downloaded from: http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at <a href="https://www.etsi.org/deliver">www.etsi.org/deliver</a>.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at <a href="https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx">https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx</a>

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommitteeSupportStaff.aspx

#### **Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020. All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

**GSM**® and the GSM logo are trademarks registered and owned by the GSM Association.

# Contents

Intelle	ctual Property Rights	5
Forewo	ord	5
Modal	verbs terminology	6
Introdu	action	6
1 5	Scope	7
2 1	References	7
2.1	Normative references	
2.2	Informative references.	
2 1		
	Definition of terms, symbols and abbreviations	
3.1 3.2	TermsSymbols	
3.2 3.3	Abbreviations	
4 7	Technical requirements specifications	
4.1	Environmental profile	
4.2	Conformance requirements	
4.2.1	Introduction	
4.2.2	Operating band unwanted emissions	
4.2.2.1	Definition	
4.2.2.2	O General Teh STANDARD PREVIEW	12
4.2.2.2. 4.2.2.2.	U General managing had a university a migricular and a mi	12 12
4.2.2.2. 4.2.2.2.		12 12
4.2.2.2. 4.2.2.2.	Co-existence with services in adjacent frequency bands	10 16
4.2.2.2. 4.2.2.2.	J	10
4.2.2.2.	5 Additional/himits for loperation in Band 32/sist/5c5c96f0-c61c-44dd-a0ac-	17
4.2.2.3	Conformance 89039269f13a/sist-en-301-908-15-v15-1-1-2020	17
4.2.3	Spurious emissions	
4.2.3.1	Definition	
4.2.3.2	Limit	
4.2.3.2.	0 General	17
4.2.3.2.		18
4.2.3.2.		
4.2.3.3	Conformance	
4.2.4	Maximum output power	
4.2.4.1	Definition	
4.2.4.2	Limit	
4.2.4.3	Conformance	
4.2.5	Input intermodulation	
4.2.5.1 4.2.5.2	Definition	
4.2.5.2 4.2.5.2.	Limit	
4.2.5.2. 4.2.5.2.		
4.2.5.3	Conformance	
4.2.6	Out of band gain	
4.2.6.1	Definition	
4.2.6.2	Limits	
4.2.6.3	Conformance	
4.2.7	Adjacent Channel Rejection Ratio	
4.2.7.1	Definition	
4.2.7.2	Limit	23
4.2.7.2.		
4.2.7.2.		
4.2.7.3	Conformance	
4.2.8	Output intermodulation	24

Testing for compliance	e with technical requirements	25
_		
Initial conditi	ions	28
Procedures		28
Out of band gain		29
Initial condiți	ions	29
Procedures	Len Standard Preview	29
Test requirem	nent	29
Output intermed	1991andards:iteh:ai/catalog/standards/sist/5c5c96f0-c61c-44dd-a0ac-	30
Unitial conditi	uration,9039269f13a/sist-cn-301-908-15-v15-1-1-2020	30
rest requirem	iciit	
x A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	32
x B (normative):	Repeater configurations	33
	•	22
Power supply		11
***		
Power supply options		33
Power supply options Combining of Repeate	ers	33
Power supply options		33
Power supply options Combining of Repeate	ers	33 33
Power supply options Combining of Repeate C (normative):	ers  Repeater stimulus signal spectral purity requirements	33 33 34
Power supply options Combining of Repeate  C (normative):  D (informative):	ers  Repeater stimulus signal spectral purity requirements  Recommended maximum measurement uncertainty	33 34 35
	Limit	Limit Conformance  Testing for compliance with technical requirements.  Environmental conditions for testing Interpretation of the measurement results Essential radio test suites  Introduction.  Operating band unwanted emissions  Initial conditions.  Procedures.  Test requirement  Spurious emissions  Initial conditions.  Procedures.  Test requirement  Maximum output power.  Initial conditions.  Procedures.  Test requirement Input intermodulation  Initial conditions.  Procedures.  Test requirement Out of band gain  Initial conditions.  Procedures.  Test requirement.  Out of band gain  Initial conditions  Procedures.  Test requirement  Adjacent Channel Rejection Ratio Indiants.  Procedures.  Test requirement.  Relationship between the present document and the essential requirements of Directive 2014/53/EU.

# Intellectual Property Rights

#### **Essential patents**

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<a href="https://ipr.etsi.org/">https://ipr.etsi.org/</a>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

#### **Trademarks**

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

# **Foreword**

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG).

For non EU countries the present document may be used for regulatory (Type Approval) purposes.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.8] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A-1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 15 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.3].

National transposition dates			
Date of adoption of this EN:	16 December 2019		
Date of latest announcement of this EN (doa):	31 March 2020		
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 September 2020		
Date of withdrawal of any conflicting National Standard (dow):	30 September 2021		

6

# Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

#### Introduction

The present document is part of a set of standards developed by ETSI that are designed to fit in a modular structure to cover radio equipment within the scope of the Radio Equipment Directive [i.1]. The present document is produced following the guidance in ETSI EG 203 336 [i.2] as applicable.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 908-15 V15.1.1:2020 https://standards.iteh.ai/catalog/standards/sist/5c5c96f0-c61c-44dd-a0ac-89039269f13a/sist-en-301-908-15-v15-1-1-2020

# 1 Scope

The present document applies to the following radio equipment types:

Repeaters for Evolved Universal Terrestrial Radio Access (E-UTRA) (FDD).

This radio equipment type is capable of operating in all or any part of the operating bands given in table 1-1.

Table 1-1: E-UTRA Repeater operating bands

E-UTRA FDD band	Direction of transmission	E-UTRA Repeater operating bands
1	Downlink	2 110 MHz to 2 170 MHz
	Uplink	1 920 MHz to 1 980 MHz
3	Downlink	1 805 MHz to 1 880 MHz
	Uplink	1 710 MHz to 1 785 MHz
7	Downlink	2 620 MHz to 2 690 MHz
	Uplink	2 500 MHz to 2 570 MHz
8	Downlink	925 MHz to 960 MHz
	Uplink	880 MHz to 915 MHz
20	Downlink	791 MHz to 821 MHz
	Uplink	832 MHz to 862 MHz
22	Downlink	3 510 MHz to 3 590 MHz
	Uplink	3 410 MHz to 3 490 MHz
28	Downlink	758 MHz to 803 MHz
	Uplink	703 MHz to 748 MHz
31	Downlink	462,5 MHz to 467,5 MHz
	I I e I Uplink I A I I D A	452,5 MHz to 457,5 MHz
32	Downlink	1 452 MHz to 1 496 MHz
(note 1)	Uplinktallual	us.iten.ai) <sub>N/A</sub>
(note 2)		
72	Downlink TEN 301 9	08 15 V15 1 1 20 461 MHz to 466 MHz
	Uplink ://atalog/ata	A51 MHz to 456 MHz

NOTE 1: Restricted to E-UTRA operation when carrier aggregation is configured. The downlink operating band is paired with the uplink operating band (external) of the carrier aggregation configuration that is supporting the configured Pcell.

NOTE 2: Radio equipment in band 32 is only allowed to operate between 1 452 MHz and 1 492 MHz.

The present document covers requirements for E-UTRA Repeaters for 3GPP Release 15.

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.1] is given in annex A.

## 2 References

#### 2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <a href="https://docbox.etsi.org/Reference/">https://docbox.etsi.org/Reference/</a>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

[1] ETSI TS 136 143 (V15.0.0) (09-2018): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); FDD repeater conformance testing (3GPP TS 36.143 version 15.0.0 Release 15)".

- [2] IEC 60068-2-1 (2007): "Environmental testing Part 2-1: Tests Test A: Cold".
- [3] IEC 60068-2-2 (2007): "Environmental testing Part 2-2: Tests Test B: Dry heat".
- [4] ETSI TS 136 141 (V15.3.0) (07-2018): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) conformance testing (3GPP TS 36.141 version 15.3.0 Release 15)".
- [5] ETSI TS 125 141 (V15.3.0) (07-2018): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) conformance testing (FDD) (3GPP TS 25.141 version 15.3.0 Release 15)".

#### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

[i.1]	Directive 2014/53/EU of the European parliament and of the council of 16 April 2014 on the
	harmonisation of the laws of the Member States relating to the making available on the market of
	radio equipment and repealing Directive 1999/5/EC.

- [i.2] ETSI EG 203 336 (V1.1.1) (08-2015): "Electromagnetic compatibility and Radio spectrum Matters (ERM): Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.3] ETSI EN 301 908-1 (V11.1.1): "IMT cellular networks; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU; Part 1: Introduction and common requirements." Introduction and common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and Common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and Common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and Common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and Common requirements. It is a support of the Directive 2014/53/EU; Part 1: Introduction and Com
- [i.4] ETSI TR 100 028 (all parts): (V1.411): U'Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.5] Void
- [i.6] Recommendation ITU-R SM.329-12 (09-2012): "Unwanted emissions in the spurious domain".
- [i.7] ETSI EN 301 908-11 (V11.1.2): "IMT cellular networks; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU; Part 11: CDMA Direct Spread (UTRA FDD) Repeaters".
- [i.8] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

# 3 Definition of terms, symbols and abbreviations

#### 3.1 Terms

For the purposes of the present document, the following terms apply:

carrier: modulated waveform conveying the E-UTRA or UTRA (WCDMA) physical channels

9

**channel bandwidth:** RF bandwidth supporting a single E-UTRA RF carrier with the transmission bandwidth configured in the uplink or downlink of a cell

NOTE: The channel bandwidth is measured in MHz and is used as a reference for transmitter and receiver RF requirements.

channel edge: lowest and highest frequency of the E-UTRA carrier, separated by the channel bandwidth

donor coupling loss: coupling loss between the repeater and the donor Base Station

downlink: signal path where Base Station transmits and mobile receives

downlink operating band: part of the operating band designated for downlink

nominal passband edge: lowest and highest frequency of the pass band of the repeater

**operating band:** frequency range that is defined with a specific set of technical requirements, in which E-UTRA FDD operates

NOTE: The operating band(s) for an E-UTRA Repeater is declared by the manufacturer according to the designations in clause 1, table 1-1. Operating bands for UTRA are designated with Roman numerals, while the corresponding operating bands for E-UTRA are designated with Arabic numerals. Unless specified, operating band refers to the uplink operating band and downlink operating band.

**output power, Pout:** mean power of one carrier at maximum repeater gain delivered to a load with resistance equal to the nominal load impedance of the transmitter

pass band: frequency range that the repeater operates in with operational configuration

NOTE: This frequency range can correspond to one or several consecutive channels. If they are not consecutive each subset of channels is considered as an individual pass band. The Repeater can have one or several pass bands.

**rated output power:** rated output power of the repeater is the mean power level per carrier that the manufacturer has declared to be available at the antenna connector https://standards.iteh.ai/catalog/standards/sist/5c5c96f0-c61c-44dd-a0ac-

**repeater:** device that receives, amplifies and transmits the radiated or conducted RF carrier both in the downlink direction (from the Base Station to the mobile area) and in the uplink direction (from the mobile to the Base Station)

NOTE: In operating bands specified with only down-link or up-link, only the up-link or down-link as specified for the operating band is repeated.

transmission bandwidth: bandwidth of an instantaneous transmission from a UE or BS, measured in Resource Block units

**transmission bandwidth configuration:** highest transmission bandwidth allowed for uplink or downlink in a given channel bandwidth, measured in Resource Block units

uplink: signal path where mobile transmits and Base Station receives

uplink operating band: part of the operating band designated for uplink

## 3.2 Symbols

For the purposes of the present document, the following symbols apply:

 $\Delta f$  The separation between the nominal pass band edge frequency and the nominal -3 dB point of the

measuring filter closest to the carrier frequency

BW<sub>Channel</sub> Channel bandwidth

 $BW_{Config} \qquad \qquad Transmission bandwidth configuration, expressed in MHz, where \\ BW_{Config} = N_{RB} \times 180 \text{ kHz in}$ 

the uplink and BW<sub>Config</sub> = 15 kHz +  $N_{RB} \times 180$  kHz in the downlink

BW<sub>Meas</sub> Measurement bandwidth

10

Bandwidth of the repeater pass band BW<sub>Pass band</sub>

Separation between the nominal pass band edge frequency and the centre of the measuring filter f offset

The largest value of f\_offset used for defining the requirement f\_offset<sub>max</sub>

The lowest frequency of the downlink operating band  $F_{DL\_low}$ The highest frequency of the downlink operating band F<sub>DL\_high</sub>

 $F_{filter}$ Filter centre frequency

The lowest frequency of the uplink operating band  $F_{UL\_low}$ The highest frequency of the uplink operating band  $F_{UL\_high}$ 

Downlink EARFCN  $N_{DL}$ 

Offset used for calculating downlink EARFCN  $N_{Offs-DL}$ Offset used for calculating uplink EARFCN N<sub>Offs-UL</sub>

Transmission bandwidth configuration, expressed in units of resource blocks  $N_{RB}$ 

Uplink EARFCN  $N_{UL}$ 

Pmax Maximum output power

Pout Output power

#### 3.3 **Abbreviations**

For the purposes of the present document, the following abbreviations apply:

**ACLR** Adjacent Channel Leakage Ratio **ACRR** Adjacent Channel Rejection Ratio

**Base Station** BS

Base Transceiver Station AND ARD PREVIEW **BTS** 

BandWidth BW

Continuous Wave (standards.iteh.ai) CW

Digital Terrestrial Television DTT

**DUT** Device Under Test

E-UTRA Absolute Radio Frequency Channel Number. **EARFCN** 

Electronic Communications Committee

Electronic Communications Committee ECC

**EFTA** European Free Trade Association

Electromagnetic compatibility and Radio spectrum Matters **ERM** 

E-UTRA Test Model E-TM **Equipment Under Test** EUT

E-UTRA Evolved Universal Terrestrial Radio Access

Frequency Division Duplex FDD

Global System for Mobile communications **GSM International Mobile Telecommunications IMT** 

ITU-R International Telecommunication Union - Radiocommunication

Long Term Evolution, also known as E-UTRA LTE

MS Mobile Station

MSG Mobile Standards Group

**PCCPCH** Primary Common Control Physical Channel

RF Radio Frequency

**RMS** Root Mean Square (value) Root Raised Cosine **RRC RSS** Root Sum Square

Secondary Common Control Physical Channel **SCCPCH** 

Time Division Duplex **TDD** 

Task Force for European Standards for IMT **TFES UARFCN** UTRA Absolute Radio Frequency Channel Number

UE User Equipment

Universal Terrestrial Radio Access **UTRA WCDMA** Wideband Code Division Multiple Access

# 4 Technical requirements specifications

#### 4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer. The equipment shall comply with all the technical requirements of the present document, which are identified as applicable in annex A, at all times when operating within the boundary limits of the declared operational environmental profile.

The operational environmental profile declared by the manufacturer shall at least contain all test environments specified throughout clause 5 of the present document.

## 4.2 Conformance requirements

#### 4.2.1 Introduction

The requirements in the present document are based on the assumption that the operating band (see table 1-1) is shared between systems of the IMT family (for band 3 and 8 also GSM) or systems having compatible characteristics.

To meet the essential requirement under article 3.2 of Directive 2014/53/EU [i.1] for IMT Repeaters, a set of essential parameters in addition to those in ETSI EN 301 908-1 [i.3] have been identified. Table 4.2.1-1 provides a cross reference between these essential parameters and the corresponding technical requirements for equipment within the scope of the present document.

eh STANDARD PREVIEW
Table 4.2.1-1: Cross references

standards itch ai

Essential parameter	Corresponding technical requirements	Corresponding test suites
Transmitter spectrum mask SIST E	<u>N 301 908-15 V15.1.1;2020</u>	
Transmitter unwanted emissions in thech ai/cat	4.2/2arOperating band unwanted emissions	5.3.1
out-of-band domain 89039269f13a	sist-en-301-908-15-v15-1-1-2020	
Transmitter and receiver unwanted emissions in the spurious domain	4.2.3 Spurious emissions	5.3.2
Transmitter power accuracy	4.2.4 Maximum output power	5.3.3
Receiver radio-frequency intermodulation Receiver desensitization	4.2.5 Input intermodulation	5.3.4
Descriptor adjacent signal calcutivity	4.2.6 Out of band gain	5.3.5
Receiver adjacent signal selectivity	4.2.7 Adjacent Channel Rejection Ratio	5.3.6
Transmitter intermodulation attenuation	4.2.8 Output intermodulation	5.3.7

NOTE: Some of the essential parameters of the ETSI EG 203 336 [i.2] are not included into the present document since those requirements are not applicable for repeater equipment.

The manufacturer shall declare operating band(s) for the Repeater. The technical requirements in the present document apply for the declared operating band(s) as outlined for each requirement. For a Repeater supporting more than one operating band, conformance testing for each technical requirement in clause 5 shall be performed.

The technical requirements also apply to Repeater configurations described in annex B.

### 4.2.2 Operating band unwanted emissions

#### 4.2.2.1 Definition

Unwanted emissions consist of out of band emissions and spurious emissions (Recommendation ITU-R SM.329-12 [i.6]). Out of band emissions are emissions immediately outside the pass band bandwidth resulting from the modulation process and non-linearity in the transmitter, but excluding spurious emissions. Spurious emissions are emissions which are caused by unwanted transmitter effects such as harmonics emission, parasitic emission, intermodulation products and frequency conversion products, but exclude out of band emissions.