

8 [[]HJb]`WV] b]`hY`Y_ca i b]_UW`g_]`g]ghYa `fZuU&ŽL`E`Gd`cýbY`nU hYj`Y`nU
a YXgYVc`bc`XY`cj`Ub`Y`Uj`bY[U`_cdYbg_Y[Ua`cV]`bY[Uca`fYy`UfD@ABL]b
X][]HJbY[Uca`fYy`U`n]`bhY[f]f`Ub]a]`g]c]f]h] Ua]`f]G8`BL`U]`Uj`bY[U`_ca`i`h]f`UbY[U
hY`YZ`bg_Y[Uca`fYy`U`fDGHBL`f]`GA`\$`-`\$`+`ž`f`U`h]`]WU)`" `"%L

Digital cellular telecommunications system (Phase 2+) (GSM); General requirements on interworking between the Public Land Mobile Network (PLMN) and the Integrated Services Digital Network (ISDN) or Public Switched Telephone Network (PSTN) (GSM 09.07 version 5.3.1)

STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/5246a7d8-abc5-434a-84e8-25f411287887/sist-ets-300-976-e2-2003>

Ta slovenski standard je istoveten z: ETS 300 976 Edition 2

ICS:

33.040.35	Telefonska omrežja	Telephone networks
33.070.50	Globalni sistem za mobilno telekomunikacijo (GSM)	Global System for Mobile Communication (GSM)
33.080	Digitalno omrežje z integriranimi storitvami (ISDN)	Integrated Services Digital Network (ISDN)

SIST ETS 300 976 E2:2003 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ETS 300 976 E2:2003

<https://standards.iteh.ai/catalog/standards/sist/5246a7d8-abc5-434a-84e8-25411287887/sist-ets-300-976-e2-2003>



EUROPEAN
TELECOMMUNICATION
STANDARD

ETS 300 976

September 1997

Second Edition

Source: ETSI SMG

Reference: RE/SMG-040907QR3

ICS: 33.020

Key words: Digital cellular telecommunications system, Global System for Mobile communications (GSM)



**Digital cellular telecommunications system (Phase 2+);
General requirements on interworking between the Public Land
Mobile Network (PLMN) and the Integrated Services Digital
Network (ISDN) or Public Switched Telephone Network (PSTN)
(GSM 09.07 version 5.3.1)**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ETS 300 976 E2:2003

<https://standards.iteh.ai/catalog/standards/sist/5246a7d8-abc5-434a-84e8-25411287887/sist-ets-300-976-e2-2003>

Contents

Foreword	7
1 Scope	9
2 Normative references	9
3 Definitions and abbreviations	11
3.1 Definitions	11
3.2 Abbreviations	12
4 Introduction	13
5 Not used	13
6 Network Characteristics	14
6.1 Key Characteristics of Networks Concerned	14
6.1.1 Characteristics of PLMNs	14
6.1.2 Characteristics of PSTNs	14
6.1.3 Characteristics of ISDN	15
7 Interworking classifications	16
7.1 Service interworking	16
7.2 Network interworking	16
7.3 Signalling interworking	18
7.4 Numbering	18
7.5 Supplementary service interworking	18
8 Compatibility and subscription checking	18
9 Interworking to PSTN	19
9.1 Speech Calls	19
9.1.1 Interworking indications to PLMN terminal	19
9.1.2 Transmission aspects	19
9.1.3 Generation of In-band Tones and Announcements (PLMN-PSTN)	19
9.2 Data Calls	19
9.2.1 Network interworking mobile originated	20
9.2.1.1 Selection of interworking function	20
9.2.1.2 Modem Selection	20
9.2.1.3 DTE/Modem interface (Filtering)	21
9.2.1.4 Mapping of BC-IE from GSM 04.08 to ISUP (or other)	22
9.2.2 Network Interworking Mobile terminated PSTN Originated	22
9.2.3 Transparent service support	26
9.2.3.1 Not used	26
9.2.3.2 Rate adaptation process in MSC/IWF	26
9.2.3.3 Mapping of signalling MS/MSC/IWF to modem interface requirements	26
9.2.3.4 Establishment of end-to-end terminal synchronizations	27
9.2.3.5 Network Independent Clocking (NIC)	28
9.2.4 Non-transparent service support	28
9.2.4.1 MSC-IWF Rate adaptation scheme	28
9.2.4.2 Protocol layer structure in the MSC/IWF	28
9.2.4.3 Re-constitution of user data	28
9.2.4.4 Layer 2 relay functionality	29
9.2.4.5 In band signalling mapping flow control	29
9.2.4.5.1 Conditions requiring flow control towards the fixed network	29

		9.2.4.5.2	Conditions requiring flow control towards the MS	30
	9.2.4.6	Data buffers		30
		9.2.4.6.1	Transmit buffers (towards MS).....	30
		9.2.4.6.2	Receive buffers (from MS)	30
	9.2.4.7	Transportation of the Break condition		30
	9.2.4.8	In band signalling mapping modem status information.....		30
	9.2.4.9	Support of out-band flow control		30
	9.2.4.10	Establishment of end-to-end terminal synchronizations		31
	9.2.4.11	Data compression		31
9.3	Interworking	Alternate Speech / Data Calls.....		32
	9.3.1	Alternate Speech/Data Interworking		32
		9.3.1.1	General	32
		9.3.1.2	Mobile originated PSTN terminated calls.....	32
		9.3.1.3	PSTN originated mobile terminated calls.....	32
	9.3.2	Speech followed by data interworking		33
		9.3.2.1	General	33
10	Interworking to the ISDN.....			33
	10.1	Speech Calls		33
	10.2	Data Calls.....		34
	10.2.1	Network interworking mobile originated.....		34
		10.2.1.1	Circuit switched calls.....	34
		10.2.1.2	Packet calls.....	34
	10.2.2	Network interworking mobile terminated		34
		10.2.2.1	Circuit switched calls.....	52
		10.2.2.2	Packet calls.....	52
	10.2.3	Transparent service support (see GSM 03.10)		52
		10.2.3.1	MSC - IWF rate adaptation scheme	52
		10.2.3.2	Rate adaptation process in MSC/IWF	52
		10.2.3.3	Mapping of signalling MS/MSC/IWF to modem interface requirements	52
		10.2.3.4	Establishment of end-to-end terminal synchronizations	52
		10.2.3.5	Network independent Clocking (NIC).....	53
	10.2.4	Non-transparent service support (see GSM 03.10)		53
		10.2.4.1	MSC - IWF Rate adaptation scheme	53
		10.2.4.2	Protocol layer structure in the MSC/IWF.....	54
		10.2.4.3	Re-constitution of user data	54
		10.2.4.4	Layer 2 relay functionality.....	54
		10.2.4.5	In band signalling mapping flow control	54
		10.2.4.5.1	Conditions requiring flow control - if flow control is provided - towards the fixed network	55
		10.2.4.5.2	Conditions requiring flow control towards the MS	55
	10.2.4.6	Data buffers		55
		10.2.4.6.1	Transmit buffers (towards MS).....	55
		10.2.4.6.2	Receive buffers (from MS)	56
	10.2.4.7	BREAK Indication.....		56
	10.2.4.8	Signalling mapping modem status information or in band rate adapted frame information.....		56
	10.2.4.9	Support of out-band flow control		56
	10.2.4.10	Synchronizations		56
		10.2.4.10.1	V110 Frame synchronizations.....	56
		10.2.4.10.2	RLP Frame start indication.....	56
		10.2.4.10.3	L2R Frame synchronizations.....	56
		10.2.4.10.4	Establishment of end-to-end terminal synchronizations.....	56
		10.2.4.11	Data compression	57
		10.2.4.12	V.120 Interworking	57
		10.2.4.13	Interworking with restricted 64 kbps networks	58
	10.2.5	DTE/Modem interface (Filtering)		58
10.3	Interworking	Alternate speech data calls		59

10.3.1	Alternate speech data bearer interworking.....	59
10.3.1.1	General.....	59
10.3.1.2	Mobile originated ISDN terminated.....	59
10.3.1.3	ISDN originated mobile terminated.....	60
10.3.2	Speech followed by data interworking.....	60
10.3.2.1	General.....	60
11	V.110 Frame Synchronization.....	61
11.1	Initial V.110 frame synchronization.....	61
11.2	Action on loss of V.110 frame synchronization for non transparent services.....	61
11.3	Action on loss of V.110 frame synchronization for transparent services.....	61
Annex A (informative):	SDLs.....	62
History.....		64

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 976 E2:2003](https://standards.iteh.ai/catalog/standards/sist/5246a7d8-abc5-434a-84e8-25411287887/sist-ets-300-976-e2-2003)

<https://standards.iteh.ai/catalog/standards/sist/5246a7d8-abc5-434a-84e8-25411287887/sist-ets-300-976-e2-2003>

Blank page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ETS 300 976 E2:2003

<https://standards.iteh.ai/catalog/standards/sist/5246a7d8-abc5-434a-84e8-25411287887/sist-ets-300-976-e2-2003>

Foreword

This European Telecommunication Standard (ETS) has been produced by the Special Mobile Group (SMG) of the European Telecommunications Standards Institute (ETSI).

This ETS identifies the Mobile-services Switching Centre/Interworking functions (MSC/IWFs) and requirements to support interworking between:

- i) PLMN and PSTN
- ii) PLMN and ISDN

within the digital cellular telecommunications system.

The contents of this ETS are subject to continuing work within SMG and may change following formal SMG approval. Should SMG modify the contents of this ETS, it will then be resubmitted for OAP by ETSI with an identifying change of release date and an increase in version number as follows:

Version 5.x.y

where:

- y the third digit is incremented when editorial only changes have been incorporated in the specification;
- x the second digit is incremented for all other types of changes, i.e. technical enhancements, corrections, updates, etc.

Transposition dates	
Date of adoption:	22 August 1997
Date of latest announcement of this ETS (doa):	31 December 1997
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	30 June 1998
Date of withdrawal of any conflicting National Standard (dow):	30 June 1998

Blank page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 976 E2:2003](https://standards.iteh.ai/catalog/standards/sist/5246a7d8-abc5-434a-84e8-25411287887/sist-ets-300-976-e2-2003)

<https://standards.iteh.ai/catalog/standards/sist/5246a7d8-abc5-434a-84e8-25411287887/sist-ets-300-976-e2-2003>

1 Scope

This European Telecommunication Standard (ETS) identifies the Mobile-services Switching Centre/Interworking Functions (MSC/IWFs) and requirements to support interworking between:

- a) PLMN and PSTN
- b) PLMN and ISDN

It is not possible to treat ISDN and PSTN as one type of network, even when both ISDN and PSTN subscribers are served by the same exchange because of the limitations of the PSTN subscribers access i.e. analogue connection without D-channel signalling.

Within this ETS, the requirements for voice and non-voice (data) calls are considered separately.

2 Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references, the latest edition of the publication referred to applies.

- [1] CCITT Recommendation G.711: "Pulse code modulation (PCM) of voice frequencies".
- [2] CCITT Recommendation I.460: "Multiplexing, rate adaption and support of existing interfaces".
- [3] CCITT Recommendation V.25: "Automatic answering equipment and/or parallel automatic calling equipment on the general switched telephone network including procedures for disabling of echo control devices for both manually and automatically established calls".
- [4] CCITT Recommendation V.42bis: "Data compression procedure for Data Circuit-terminating Equipment (DCE) using error correcting procedures".
- [5] CCITT Recommendation V.110: "Support of Data Terminal Equipments (DTEs) with V-Series interfaces by an Integrated Services Digital Network (ISDN)".
- [6] ETS 300 102-1 Edition 1 (1990): "Integrated Services Digital Network (ISDN); User-network interface layer 3 Specifications for basic call control".
- [7] ETS 300 121: "Integrated Services Digital Network (ISDN); Application of the ISDN User Part (ISUP) of CCITT Signalling System No.7 for international ISDN interconnections (ISUP version 1)".
- [8] GSM 01.04 (ETR 350): "Digital cellular telecommunications system (Phase 2+); Abbreviations and acronyms".
- [9] GSM 02.01: "Digital cellular telecommunications system (Phase 2+); Principles of telecommunication services supported by a GSM Public Land Mobile Network (PLMN)".
- [10] GSM 02.02 (ETS 300 904): "Digital cellular telecommunications system (Phase 2+); Bearer Services (BS) supported by a GSM Public Land Mobile Network (PLMN)".
- [11] GSM 02.03 (ETS 300 905): "Digital cellular telecommunications system (Phase 2+); Teleservices supported by a GSM Public Land Mobile Network (PLMN)".

- [12] GSM 02.04 (ETS 300 918): "Digital cellular telecommunications system (Phase 2+); General on supplementary services".
- [13] GSM 02.81: "Digital cellular telecommunications system (Phase 2+); Line identification supplementary services - Stage 1".
- [14] GSM 02.82: "Digital cellular telecommunications system; Call Forwarding (CF) supplementary services - Stage 1".
- [15] GSM 02.83: "Digital cellular telecommunications system; Call Waiting (CW) and Call Holding (HOLD) supplementary services - Stage 1".
- [16] GSM 02.84: "Digital cellular telecommunications system; MultiParty (MPTY) supplementary services - Stage 1".
- [17] GSM 02.85: "Digital cellular telecommunications system; Closed User Group (CUG) supplementary services - Stage 1".
- [18] GSM 02.86: "Digital cellular telecommunications system; Advice of Charge (AoC) supplementary services - Stage 1".
- [19] GSM 02.88: "Digital cellular telecommunications system; Call Barring (CB) supplementary services - Stage 1".
- [20] GSM 03.03 (ETS 300 927): "Digital cellular telecommunications system (Phase 2+); Numbering, addressing and identification".
- [21] GSM 03.08: "Digital cellular telecommunications system (Phase 2+); Organization of subscriber data".
- [22] GSM 03.11 (ETS 300 928): "Digital cellular telecommunications system; Technical realization of supplementary services".
- [23] GSM 03.45 (ETS 300 931): "Digital cellular telecommunications system; Technical realization of facsimile group 3 transparent".
- [24] GSM 03.46: "Digital cellular telecommunications system; Technical realization of facsimile group 3 non-transparent".
- [25] GSM 03.50 (ETS 300 903): "Digital cellular telecommunications system (Phase 2+); Transmission planning aspects of the speech service in the GSM Public Land Mobile Network (PLMN) system".
- [26] GSM 04.08 (ETS 300 940): "Digital cellular telecommunications system (Phase 2+); Mobile radio interface layer 3 specification".
- [27] GSM 04.21 (ETS 300 945): "Digital cellular telecommunications system; Rate adaption on the Mobile Station - Base Station System (MS - BSS) interface".
- [28] GSM 04.22 (ETS 300 946): "Digital cellular telecommunications system (Phase 2+); Radio Link Protocol (RLP) for data and telematic services on the Mobile Station - Base Station System (MS - BSS) interface and the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".
- [29] GSM 07.01 (ETS 300 913): "Digital cellular telecommunications system (Phase 2+); General on Terminal Adaptation Functions (TAF) for Mobile Stations (MS)".
- [30] GSM 07.02 (ETS 300 914): "Digital cellular telecommunications system (Phase 2+); Terminal Adaptation Functions (TAF) for services using asynchronous bearer capabilities".

- [31] GSM 07.03 (ETS 300 915): "Digital cellular telecommunications system (Phase 2+); Terminal Adaptation Functions (TAF) for services using synchronous bearer capabilities".
- [32] GSM 07.05: "Digital cellular telecommunications system (Phase 2+); Use of Data Terminal Equipment - Data Circuit terminating Equipment (DTE - DCE) interface for Short Message Service (SMS) and Cell Broadcast Service (CBS)".
- [35] GSM 08.20: "Digital cellular telecommunications system; Rate adaption on the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".
- [36] GSM 08.60 (ETS 300 737): "Digital cellular telecommunications system (Phase 2+); Inband control of remote transcoders and rate adaptors for Enhanced Full Rate (EFR) and full rate traffic channels".
- [37] GSM 09.02 (ETS 300 974): "Digital cellular telecommunications system (Phase 2+); Mobile Application Part (MAP) specification".
- [38] GSM 09.03: "Digital cellular telecommunications system; Signalling requirements on interworking between the Integrated Services Digital Network (ISDN) or Public Switched Telephone Network (PSTN) and the Public Land Mobile Network (PLMN)".
- [39] GSM 09.05: "Digital cellular telecommunications system; Interworking between the Public Land Mobile Network (PLMN) and the Packet Switched Public Data Network (PSPDN) for Packet Assembly/Disassembly facility (PAD) access".
- [40] GSM 09.06 (ETS 300 975): "Digital cellular telecommunications system (Phase 2+); Interworking between a Public Land Mobile Network (PLMN) and a Packet Switched Public Data Network/Integrated Services Digital Network (PSPDN/ISDN) for the support of packet switched data transmission services".
- [41] CCITT Recommendation V.120: "Support by an ISDN of data terminal equipment with V-series type interfaces with provision for statistical multiplexing".
- [42] ETR 018: "Integrated Services Digital Network (ISDN); Application of the Bearer Capability (BC), High Layer Compatibility (HLC) and Low Layer Compatibility (LLC) information elements by terminals supporting ISDN services".

NOTE: As regards ETS 300 102-1 [6], the first edition of this ETS from 1990 shall be used, with one exception: the encoding of the field modem type in the ISDN BC-IE shall be handled as specified in table 6A and 6B of GSM 09.07.

3 Definitions and abbreviations

3.1 Definitions

Use is made of the following terms within this ETS. These terms refer to information requirements necessary to support interworking functions, some of these terms will be identifiable with their use in other GSM specifications.

bearer capability information: Specific information defining the lower layer characteristics required within the network.

low layer compatibility information: Information defining the lower layer characteristics of the terminal.

high layer compatibility information: Information defining the higher layer characteristics of the terminal.

compatibility information: This term subsumes the entirety of Bearer Capability, Low Layer Compatibility, High Layer Compatibility, Progress Indicator and Address Information conveyed out-of-band prior to call establishment for the support of compatibility checking and terminal/function/service selection at the ISDN-type user-network interface.

protocol identifier: Information defining the specific protocols utilized for the support of data transfer by a terminal.

progress indicator: Information supplied to indicate to the terminal that network interworking has taken place.

out-of-band parameter exchange: Information exchanged via an associated or non-associated signalling link e.g. SS No 7.

PSTN: Subscriber to network interface supports only analogue terminals.

ISDN: Subscriber to network interface supports digital or analogue terminals, plus a standardized user to network associated signalling system and a standardized internetwork signalling system.

autobauding type 1: This information element value may be contained in the setup or call confirm messages from the MS in association with a non transparent data service. This implies that the MSC/IWF may select any speed and modem type according to what it can negotiate with the remote modem on the PSTN/ISDN. The maximum speed to be used by the MSC/IWF is the user speed indicated in the setup/call confirm message.

multi self selecting speed modem: This term applies to V series modems capable of handling one or more lower speeds as a fall back position. When such a modem is requested in the call setup or call confirm message from the MS in association with a non transparent service, the MSC/IWF may select any of the speeds supported according to the negotiation with the remote modem on the PSTN/ISDN. In this instance the maximum starting negotiation speed to be used by the MSC/IWF is the one indicated by the user speed in the setup/call confirm message.

3.2 Abbreviations

[SIST ETS 300 976 E2:2003](https://standards.iteh.ai/catalog/standards/sist/5246a7d8-abc5-434a-84e8-25811287887/sist-ets-300-976-e2-2003)

[https://standards.iteh.ai/catalog/standards/sist/5246a7d8-abc5-434a-84e8-](https://standards.iteh.ai/catalog/standards/sist/5246a7d8-abc5-434a-84e8-25811287887/sist-ets-300-976-e2-2003)

[25811287887/sist-ets-300-976-e2-2003](https://standards.iteh.ai/catalog/standards/sist/5246a7d8-abc5-434a-84e8-25811287887/sist-ets-300-976-e2-2003)

In addition to the following, abbreviations used in this ETS are listed in GSM 01.04 [8].

ADPCM	Adaptive Differential Pulse Coded Modulation
DP	Dial Pulse
ITC	Information Transfer Capability
LE	Local Exchange
NT	Network Termination
PABX	Private Automatic Branch Exchange
SPC	Stored Program Control
SS No.7	Signalling System No.7
TE	Terminal Equipment
TA	Terminal Adaptor
TUP	Telephone User Part (of Signalling System No.7)
DSS1	Digital Subscriber Signalling 1
UNI	User Network Interface

4 Introduction

General Network Interworking Scenarios are described in GSM 09.01. Since the numbering plan for the ISDN era (E.164) includes the numbering plan for the telephone network (E.163), it is not possible to distinguish by the number whether a given subscriber is a PSTN or ISDN subscriber. Further, in some countries both PSTN and ISDN subscribers will be connected to the same exchange, so the only difference for this type of combined network will be in the nature of the customer access. In this document a PSTN is considered to support only an analogue interface towards the subscriber. An ISDN shall be considered to support digital interface towards the subscriber. In addition, the ISDN is considered to support a standardized outband signalling protocol both between the subscriber and the network and within the network, i.e. DSS1 and ISUP, thus enabling the generation and transport of Compatibility Information for compatibility checking and terminal/function/service selection at the user-network interface as well as for MSC/IWF selection.

There now exist networks which do not fall into either of these categories in that they provide for digital connectivity from subscriber to subscriber through the network. The subscribers have access to a wide range of services by a limited set of standard multi-purpose user network interfaces. However, these networks do not support the standardized inter-exchange signalling protocol throughout, in that they are e.g. using TUP or National User Part (NUP). These types of network support 64 kbit/s connections, so in service support are comparable to ISDN, however, the signalling system provided may not support transport of all Compatibility Information allowed for in the standardized ISDN signalling. This document will therefore identify interworking to PSTN and ISDN on the principle of the network characteristics as identified in the previous paragraph. The aforementioned existing networks then constitute one particular case in the ISDN interworking scenarios. These cases will be itemized when the implication of the various degrees of exhaustiveness of the Compatibility Information - delivered via the ISDN - used for deducting a GSM Basic Service needs to be set forth.

When two dissimilar networks are required to interwork in order to support a communication between two subscribers, one on each network, a number of Interworking Functions (MSC/IWFs) are required to support the communication. Some of these are related to the differences in signalling and are dealt with in GSM 09.03.

Examples of other aspects of interworking are:

- a) the need or otherwise of echo control devices;
- b) the need or otherwise of modem pools and network-based rate adaptation.

For the purposes of determining the required MSC/IWFs, it is necessary, however, to consider separately each type of interworking (i.e. PLMN-ISDN and PLMN-PSTN) since, in the worst case, "PSTN" could refer to an essentially analogue network with electromechanical switching not controlled by software and without common-channel signalling.

Some facilities associated with alternate speech and data may not be available with version 1 of the MAP (GSM 09.02). Version 1 of the Mobile Application Part (MAP) does not support transfer between the HLR and VLR, and VLR and VMSC of multiple bearer capabilities. In addition, version 1 of the MAP does not support in-call modification and channel mode modification following an inter-MSC handover.

5 Not used