



**Lawful Interception (LI);
Handover interface for the lawful interception of
telecommunications traffic**

*ITeH STANDARDS PREVIEW
(standards.iteh.ai)
Full standard/catalog/standards/sls/667405e-4109-
4115-92e1-38501dec715b/etsi-es-201-671-v3-2-1-2018-03-05*

Reference

RES/LI-00154

Keywords

data, handover, interface, Lawful Interception,
security, speech

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2018.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	9
Foreword.....	9
Modal verbs terminology.....	9
Introduction	9
1 Scope	10
2 References	10
2.1 Normative references	10
2.2 Informative references.....	14
3 Definitions and abbreviations.....	15
3.1 Definitions.....	15
3.2 Abbreviations	18
4 General requirements	20
4.0 General	20
4.1 Basic principles for the Handover Interface	20
4.2 Legal requirements	20
4.3 Functional requirements	20
5 Overview of Handover Interface.....	21
5.0 General	21
5.1 Handover Interface port 1 (HI1).....	22
5.1.0 General.....	22
5.1.1 Manual interface	23
5.1.2 Electronic interface	23
5.2 Handover Interface port 2 (HI2).....	23
5.3 Handover Interface port 3 (HI3).....	23
6 Specific identifiers for LI	23
6.0 General	23
6.1 Lawful Interception IDentifier (LIID).....	24
6.2 Communication IDentifier (CID).....	24
6.2.0 General.....	24
6.2.1 Network IDentifier (NID).....	24
6.2.2 Communication Identity Number (CIN) - optional	25
7 HI1: Interface port for administrative information.....	25
7.0 General	25
7.1 Information for the activation of lawful interception	25
7.2 LI notifications towards the LEMF	26
8 HI2: Interface port for Intercept Related Information	26
8.0 General	26
8.1 Data transmission protocols	26
8.1.0 Introduction.....	26
8.1.1 Application for IRI (HI2 information).....	27
8.2 Types of IRI records.....	27
9 HI3: Interface port for Content of Communication.....	27
10 Performance and quality.....	28
10.1 Timing	28
10.2 Quality	28
11 Security aspects	28
11.0 General	28
11.1 Security properties.....	28
11.2 Security mechanisms.....	29

12	Quantitative aspects.....	29
Annex A (normative): Circuit switched network handover		30
A.0	General	30
A.1	Specific identifiers for LI	30
A.1.0	General	30
A.1.1	CC Link Identifier (CCLID).....	30
A.1.2	Circuit switched LI correlation between CC and IRI	30
A.1.3	Usage of Identifiers	30
A.2	HI1: interface port for administrative state	31
A.3	HI2: interface port for IRI	31
A.3.1	Definition of Intercept Related Information (IRI)	31
A.3.2	Structure of IRI records.....	32
A.3.2.0	General.....	32
A.3.2.1	Control information for HI2.....	32
A.3.2.2	Basic call information.....	32
A.3.2.3	Information on Supplementary Services, related to a call in progress.....	33
A.3.2.4	Information on non-call related Supplementary Services	33
A.3.3	Selection of parameters for IRI records.....	34
A.3.4	Coding of parameters in IRI records	36
A.3.5	Information content of the IRI record types	37
A.4	HI3: interface port for Content of Communication.....	37
A.4.0	General	37
A.4.1	Delivery of Content of Communication (CC).....	37
A.4.1.0	General.....	37
A.4.1.1	Delivery of TETRA CC over circuit switched handover networks	38
A.4.2	Delivery of packetized Content of Communication (CC) (general).....	38
A.4.2.0	General.....	38
A.4.2.1	Delivery of TETRA CC over packet switched handover networks	39
A.4.3	Control information for circuit switched Content of Communication (CC).....	39
A.4.4	Exception handling.....	40
A.4.4.1	Failure of CC links.....	40
A.4.4.2	Fault reporting	40
A.4.5	Security requirements at the interface port HI3.....	41
A.4.5.0	General.....	41
A.4.5.1	LI access verification.....	41
A.4.5.2	Access protection.....	41
A.4.5.3	Authentication.....	41
A.5	LI procedures for circuit switched supplementary services	42
A.5.1	General	42
A.5.2	CC link Impact	44
A.5.3	IRI impact, general principle for sending IRI records	44
A.5.4	Multi party calls - general principles, options A, B.....	45
A.5.4.0	General.....	45
A.5.4.1	CC links for active and non-active calls (option A).....	45
A.5.4.2	Reuse of CC links for active calls (option B)	45
A.5.5	Subscriber Controlled Input (SCI): Activation/Deactivation/Interrogation of services	46
A.6	Detailed procedures for circuit switched supplementary services.....	46
A.6.1	Advice of Charge services (AOC).....	46
A.6.2	Call Waiting (CW)	46
A.6.2.1	Call Waiting (CW) at target: CC links.....	46
A.6.2.2	Call Waiting: IRI records.....	47
A.6.2.2.1	Target is served user.....	47
A.6.2.2.2	Other party is served user.....	47
A.6.3	Call Hold/Retrieve.....	47
A.6.3.1	CC links for active and non-active calls (option A).....	47
A.6.3.2	Reuse of CC links for active calls (option B)	47

A.6.3.3	IRI records	47
A.6.3.3.1	Invocation of Call Hold or Retrieve by target	47
A.6.3.3.2	Invocation of Hold or Retrieve by other parties	47
A.6.4	Explicit Call Transfer (ECT)	47
A.6.4.1	Explicit Call Transfer (ECT), CC link	47
A.6.4.2	Explicit Call Transfer (ECT), IRI records	48
A.6.5	Calling Line Identification Presentation (CLIP) (IRI Records)	48
A.6.5.1	Call originated by target (other party is served user)	48
A.6.5.2	Call terminated at target (target is served user)	48
A.6.6	Calling Line Identification Restriction (CLIR)	48
A.6.7	COnnected Line identification Presentation (COLP)	48
A.6.7.1	Call terminated at target (other party is served user)	48
A.6.7.2	Call originated by target (target is served user)	48
A.6.8	COnnected Line identification Restriction (COLR)	48
A.6.9	Closed User Group (CUG)	49
A.6.10	Completion of Call to Busy Subscriber (CCBS)	49
A.6.11	COnFERENCE call, add-on (CONF)	49
A.6.11.1	COnFERENCE calls, add on: CC links	49
A.6.11.2	Conference calls: IRI records	49
A.6.12	Three Party Service (Conference)	49
A.6.12.1	CC links	49
A.6.12.2	Three Party Service, IRI Records	49
A.6.13	Meet-Me Conference (MMC)	49
A.6.14	Direct Dialling In (DDI)	50
A.6.15	Multiple Subscriber Number (MSN)	50
A.6.16	DIVersion services (DIV)	50
A.6.16.0	General	50
A.6.16.1	Call Diversion by target	50
A.6.16.1.1	Call Diversion by target, CC links	50
A.6.16.1.2	Call Diversion by target, IRI records	51
A.6.16.2	Forwarded call terminated at target	51
A.6.16.3	Call from target forwarded	51
A.6.17	Variants of call diversion services	51
A.6.18	Void	51
A.6.19	Malicious Call IDentification (MCID)	51
A.6.20	SUBaddressing (SUB)	51
A.6.21	Terminal Portability (TP)	51
A.6.21.1	CC links	51
A.6.21.2	IRI records	51
A.6.21.2.1	Invocation of Terminal Portability by target	51
A.6.21.2.2	Invocation of Terminal Portability by other parties	52
A.6.22	User-to-User Signalling (UUS)	52
A.6.23	Abbreviated Address (AA)	52
A.6.24	Fixed Destination Call (FDC)	52
A.6.25	Alarm Call (AC)/Wake-Up Service (WUS)	52
A.6.26	Incoming Call Barring (ICB)	52
A.6.27	Outgoing Call Barring (OCB)	52
A.6.28	Completion of Calls on No Reply (CCNR)	52
A.6.29	Reverse charging	52
A.6.30	Line hunting	53
A.6.31	Message Wait Indication (MWI)	53
A.6.32	Name display	53
A.6.33	Tones, announcements	53
A.7	Void	53
A.8	GSM circuit switched technology annex	53
A.8.1	Functional architecture	53
A.8.2	Correlation of CC and IRI (see clause 6)	54
A.8.3	HI3 (delivery of CC)	54
A.8.4	HI2 (delivery of IRI)	54
A.9	TETRA technology annex	56

A.10	NGN PSTN/ISDN emulation and simulation services technology annex	56
A.10.0	General	56
A.10.1	Functional architecture	56
A.10.2	Correlation	56
A.10.3	HI2	57
A.10.4	HI3	57
Annex B (normative): Packet switched network handover		58
B.1	Specific identifiers for LI	58
B.2	HI1: interface port for administrative state	58
B.3	HI2: interface port for IRI	58
B.3.1	Definition of Interception Related Information for packet switched	58
B.3.2	Exception handling	58
B.3.3	Security aspects	58
B.4	HI3: interface port for Content of Communication (CC)	59
B.5	GPRS technology annex	59
B.5.1	Functional architecture	59
B.5.2	Correlation	60
B.5.2.1	Correlation of the present document IDs to GSM IDs	60
B.5.2.2	GPRS LI correlation between CC and IRI	60
B.5.3	HI2 (delivery of IRI)	60
B.5.4	HI3 (Delivery of CC)	61
Annex C (normative): HI2 Delivery mechanisms and procedures		62
C.0	Premise	62
C.1	ROSE	62
C.1.1	Architecture	62
C.1.2	ASE_HI procedures	62
C.1.2.1	Sending part	62
C.1.2.2	Receiving part	64
C.1.2.3	Data link management	64
C.1.2.3.0	General	64
C.1.2.3.1	Data link establishment	64
C.1.2.3.2	Data link release	65
C.1.2.4	Handling of unrecognized fields and parameters	65
C.1.3	Void	65
C.2	FTP	65
C.2.1	Introduction	65
C.2.2	Usage of the FTP	66
C.2.3	Profiles	67
C.2.4	File content	69
C.2.5	Exceptional procedures	69
C.2.6	Other considerations	70
Annex D (normative): Structure of data at the Handover Interface		71
D.0	General	71
D.1	Syntax definitions	71
D.2	Object tree	72
D.3	HI management operation	73
D.4	LI management notification	74
D.5	Intercept related information (HI2 PS and CS)	76
D.6	User data packet transfer (HI3 CS)	90

D.7	TETRA data transfer (HI3 interface)	91
D.8	Definition of the UUS1 content associated to the CC link.....	91
D.9	Content of Communication (HI3 GPRS)	92
Annex E (informative):	Use of subaddress and calling party number to carry correlation information.....	94
E.1	Introduction	94
E.2	Subaddress options	94
E.3	Subaddress coding.....	94
E.3.0	General	94
E.3.1	BCD values	94
E.3.2	Field order and layout.....	95
E.4	Field coding.....	101
E.4.0	General	101
E.4.1	Direction.....	101
E.4.2	Coding of the Calling Party Number.....	101
E.5	Length of fields	102
Annex F (informative):	GPRS HI3 Interface.....	103
F.1	Functional architecture	103
F.2	Correlation.....	103
F.3	HI3 Delivery Content of Communication (CC).....	104
F.3.0	General	104
F.3.1	GPRS LI correlation header	104
F.3.1.1	Introduction.....	104
F.3.1.2	Definition of GLIC header	104
F.3.1.3	Exceptional procedure	106
F.3.1.4	Other considerations	106
F.3.2	FTP.....	106
F.3.2.1	Introduction.....	106
F.3.2.2	Usage of the FTP	106
F.3.2.3	Profiles.....	108
F.3.2.4	Exceptional procedures.....	110
F.3.2.5	CC contents for FTP	110
F.3.2.5.1	Fields.....	110
F.3.2.5.2	Information Element syntax	112
F.3.2.6	Other considerations	113
Annex G (informative):	LEMF requirements - handling of unrecognized fields and parameters.....	115
Annex H (informative):	IP Multimedia Subsystem (IMS) handover.....	116
H.0	General	116
H.1	Specific identifiers for LI	116
H.1.0	General	116
H.1.1	Lawful interception identifier.....	117
H.1.2	Network identifier	117
H.1.3	Correlation number.....	117
H.1.4	IRI for IMS.....	118
H.1.4.0	General.....	118
H.1.4.1	Events and information.....	119
H.1.5	Correlation indications of IMS IRI with GSN CC at the LEMF.....	120
Annex I (informative):	Latest ASN.1 module versions.....	122

Annex J (informative):	Bibliography.....	123
Annex K (informative):	Change Request history.....	125
History		128

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/66138d5e-4109-4115-92e1-38501dec715b/etsi-es-201-671-v3.2.1-2018-05>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This final draft ETSI Standard (ES) has been produced by ETSI Technical Committee Lawful Interception (LI), and is now submitted for the ETSI standards Membership Approval Procedure.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

References within the main body of the present document are made if applicable to the 3GPP specification number with in square brackets the reference number as listed in clause 2. In clause 2 "References" the corresponding ETSI specification number is indicated with a reference to the 3GPP specification number. 3GPP specifications are available faster than the equivalent ETSI specifications.

The present document is made historical and is therefore no longer maintained or revised. It has been superseded by ETSI TS 102 232 (all parts) [i.2] and ETSI TS 103 280 [i.3].

1 Scope

The present document is step 3 of a three-step approach to describe a generic Handover Interface (HI) for the provision of lawful interception from a Network Operator, an Access Provider or a Service Provider (NWO/AP/SvP) to the Law Enforcement Agencies (LEAs). The provision of lawful interception is a requirement of national law, which is usually mandatory for the operation of any telecommunication service.

Step 1 contains the requirements for lawful interception from a users (LEAs) point of view and is published in ETSI TS 101 331 [1].

Step 2 describes the derived network functions and the general architecture (or functional model) and is published in ETSI ES 201 158 [2].

The present document specifies:

- the *generic flow of information* as well as the procedures and information elements, which are applicable to any future telecommunication network or service;
- the network/service specific protocols relating to the provision of lawful interception at the Handover Interface (HI), for the following networks/services:
 - switched circuit; and
 - packet data.

The technologies covered in the present document are: GSM, TETRA, GPRS, ISDN, PSTN, fixed NGN (including PSTN/ISDN emulation) and fixed IMS PSTN simulation.

NOTE: As new networks and/or services are developed, the present document will be expanded as the relevant standards become available.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- | | |
|-----|---|
| [1] | ETSI TS 101 331: "Lawful Interception (LI); Requirements of Law Enforcement Agencies". |
| [2] | ETSI ES 201 158: "Telecommunications security; Lawful Interception (LI); Requirements for network functions". |
| [3] | Void. |
| [4] | Void. |
| [5] | ETSI EN 300 356 (all parts): "Integrated Services Digital Network (ISDN); Signalling System No.7 (SS7); ISDN User Part (ISUP) version 4 for the international interface". |

- [6] ETSI EN 300 403-1 (V1.3.2): "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 1: Protocol specification [ITU-T Recommendation Q.931 (1993), modified]".

NOTE: Reference [6] is specific, because the format of the sub parameters "dSS1-Format, DSS1-parameters-codeset-0", "DSS1-SS-parameters-codeset-0" and "UUS1-Content" are defined by V1.3.2.

[7] Void.

[8] Void.

[9] Void.

- [10] ETSI EN 300 061-1: "Integrated Services Digital Network (ISDN); Subaddressing (SUB) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

[11] Void.

[12] Void.

[13] Void.

- [14] ETSI EN 300 097-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Connected Line Identification Presentation (COLP) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

NOTE: Reference [14] is specific, because several parameter format definitions point to V1.2.4.

[15] Void.

- [16] ETSI EN 300 130-1: "Integrated Services Digital Network (ISDN); Malicious Call Identification (MCID) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

[17] Void.

[18] Void.

- [19] ETSI EN 300 185-1: "Integrated Services Digital Network (ISDN); Conference call, add-on (CONF) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

- [20] ETSI EN 300 188-1: "Integrated Services Digital Network (ISDN); Three-Party (3PTY) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

- [21] ETSI EN 300 207-1 (V1.2.5): "Integrated Services Digital Network (ISDN); Diversion supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

NOTE: Reference [21] is specific, because the format of the sub parameters for "DSS1-SS-Invoke-Components" is defined by V1.2.5. In addition several parameter format definitions point to V1.2.5.

[22] Void.

- [23] ETSI EN 300 286-1: "Integrated Services Digital Network (ISDN); User-to-User Signalling (UUS) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

[24] Void.

- [25] ETSI EN 300 369-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Explicit Call Transfer (ECT) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

NOTE: Reference [25] is specific, because the format of the sub parameters for "DSS1-SS-Invoke-Components" is defined by V1.2.4.

[26] Void.

[27] Void.

[28] Void.

- [29] ETSI EN 300 196-1 (V1.3.2): "Integrated Services Digital Network (ISDN); Generic functional protocol for the support of supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

NOTE: Reference [29] is specific, because several parameter format definitions point to V1.3.2.

[30] Void.

- [31] Recommendation ITU-T Q.850 (1998): "Usage of cause and location in the Digital Subscriber Signalling System No. 1 and the Signalling System No. 7 ISDN User Part".

NOTE: Reference [31] is specific, because several parameter format definitions point to version 1988.

- [32] ETSI TS 100 974: "Digital cellular telecommunications system (Phase 2+); Mobile Application Part (MAP) specification (3GPP TS 09.02)".

- [33] Recommendation ITU-T X.680: "Information technology - Abstract Syntax Notation One (ASN.1): Specification of basic notation".

- [34] Recommendation ITU-T X.690: "Information technology - ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER)".

- [35] Recommendation ITU-T X.880: "Information technology - Remote Operations: Concepts, model and notation".

[36] Void.

- [37] Recommendation ITU-T X.882: "Information technology - Remote Operations: OSI realizations - Remote Operations Service Element (ROSE) protocol specification".

[38] Void.

- [39] ETSI EN 300 122-1: "Integrated Services Digital Network (ISDN); Generic keypad protocol for the support of supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

- [40] ETSI EN 300 392-1: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 1: General network design".

- [41] ETSI TS 124 008: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; Mobile radio interface Layer 3 specification; Core network protocols; Stage 3 (3GPP TS 24.008)".

- [42] ETSI TS 101 509: "Digital cellular telecommunications system (Phase 2+) (GSM); Lawful interception; Stage 2 (3GPP TS 03.33)".

- [43] ETSI TS 100 927: "Digital cellular telecommunications system (Phase 2+); Numbering, addressing and identification (3GPP TS 03.03)".

[44] Void.

- [45] ETSI TS 101 347: "Digital cellular telecommunications system (Phase 2+); General Packet Radio Service (GPRS); GPRS Tunnelling Protocol (GTP) across the Gn and Gp Interface (3GPP TS 09.60)".
- [46] IETF RFC 959: "File Transfer Protocol".
- [47] Void.
- [48] Recommendation ITU-T Q.763: "Signalling System No.7 - ISDN User Part formats and codes".
- [49] ETSI TS 101 393: "Digital cellular telecommunications system (Phase 2+); General Packet Radio Service (GPRS); GPRS Charging (3GPP TS 12.15)".
- [50] Void.
- [51] IETF RFC 791: "Internet Protocol".
- [52] IETF RFC 793: "Transmission Control Protocol".
- [53] Void.
- [54] ETSI EN 300 089: "Integrated Services Digital Network (ISDN); Calling Line Identification Presentation (CLIP) supplementary service; Service description".
- [55] ETSI TS 100 940: "Digital cellular telecommunications system (Phase 2+); Mobile radio interface layer 3 specification (3GPP TS 04.08)".
- [56] Recommendation ITU-T Q.931: "ISDN user-network interface layer 3 specification for basic call control".
- [57] ETSI TS 101 109: "Digital cellular telecommunications system (Phase 2+); Universal Geographical Area Description (GAD) (3GPP TS 03.32)".
- [58] Recommendation ITU-T E.164: "The international public telecommunication numbering plan".
- [59] IETF RFC 3261: "SIP: Session Initiation Protocol".
- [60] ETSI TS 129 060: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); General Packet Radio Service (GPRS); GPRS Tunnelling Protocol (GTP) across the Gn and Gp interface (3GPP TS 29.060)".
- [61] ETSI TS 133 108: "Universal Mobile Telecommunications System (UMTS); LTE; 3G security; Handover interface for Lawful Interception (LI) (3GPP TS 33.108)".
- [62] ETSI TS 125 431: "Universal Mobile Telecommunications System (UMTS); UTRAN Iub interface Layer 1 (3GPP TS 25.431)".
- [63] Recommendation ITU-T Q.731.3: "Stage 3 description for number identification supplementary services using Signalling System No. 7: Calling line identification presentation (CLIP)".
- [64] Recommendation ITU-T Q.951.1: "Stage 3 description for number identification supplementary services using DSS 1: Direct-dialling-in (DDI)".
- [65] Recommendation ITU-T Q.951.3: "Stage 3 description for number identification supplementary services using DSS 1: Calling line identification presentation".
- [66] ETSI EN 300 092 (all parts): "Integrated Services Digital Network (ISDN); Calling Line Identification Presentation (CLIP) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol".
- [67] ISO 3166-1: "Codes for the representation of names of countries and their subdivisions - Part 1: Country codes".
- [68] IETF RFC 3966: "The tel URI for Telephone Numbers".