Draft ETSI EN 302 890-1 V1.2.0 (2018-04)



Intelligent Transport Systems (ITS); Facilities layer function;

Part 1: Services Announcement (SA) specification

Tell St. Standard Fill standard of the Anna Standard Stan

Reference REN/ITS-002180

Keywords

interoperability, ITS, service, validation

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from: http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommitteeSupportStaff.aspx

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2018. All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP**TM and **LTE**TM are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intell	lectual Property Rights	4
Forev	word	4
Moda	al verbs terminology	4
Introd	duction	5
1	Scope	6
2 2.1 2.2	References	6
3 3.1 3.2 3.3	Definitions, symbols and abbreviations Definitions Symbols Abbreviations	7 8
4 4.1 4.2 4.2.1 4.2.2 4.2.3 4.2.4	SA functional description SA functional architecture Interfaces of the SA service. Interface between Application entity and Management entity. Interface between Facilities layer and the Management entity Interface between Facilities layer and the Security entity. Interface between Facilities layer and the Networking &Transport layer	9 10 11 11
5 5.1 5.2 5.3 5.4	SAEM format General Service info component Channel info component IPv6 routing advertisement	12 13 13
6 6.1 6.2 6.3 6.4 6.5	SAEM dissemination Identification	14 14 14 15
Anne	ex A (normative): ASN.1 specification of SAEM	16
Anne	ex B (normative): ASN.1 specification of extensions	17
B.1	General	17
B.2 B.2.1	ChannelInfo extensions	
Histo	ory	18

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This draft European Standard (EN) has been produced by ETSI Technical Committee Intelligent Transport Systems (ITS), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document is part 1 of a multi-part deliverable covering Intelligent Transport Systems; Facilities layer function, as identified below:

Part 1: "Services Announcement (SA) specification";

Part 2: "Position and time facility specification"

Proposed national transposition dates			
Date of latest announcement of this EN (doa):	3 months after ETSI publication		
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa		
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa		

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Introduction

Some of the applications of the Basic Set of Applications (see ETSI TR 102 638 [i.1]) require ITS stations (Service Users) to have knowledge of a certain service of interest that is provided by other ITS stations (Service Providers) via defined communication access technologies.

The C-ITS protocol stack supports push and pull mechanisms in order to allow an ITS station to identify the availability of ITS services. The push mechanism is named "ITS service announcement" which is also known as "ITS service advertisement" (see ETSI EN 302 665 [i.2]). Throughout the present document this service is referred to as service announcement service (SA service).

The ITS SA service is a functionality agnostic to the medium and the announced service that can be used by specific services to provide the push functionality mentioned above. In this sense, each specification of an ITS service will tailor the ITS service announcement to its needs. This means that ITS service definitions (e.g. in other standards or technical specifications) should make use of the provisions of the present document to define its service-specific use of ITS service announcement, i.e. to profile the ITS service announcement appropriately (for example the use of service announcement in a Platooning service). The present document defines therefore a general framework which needs to be followed whenever a specific service is specified. Compliance should be tested according to this service specification that defines the application-specific requirements for the service announcement.

IT all ST AND ARD REPLANTED BY A STANDARD STANDA

1 Scope

The present document provides the specification of the Services Announcement (SA) service, including its protocol functions, based on ISO/TS 16460 [1].

The definition of the interface between Service Provider and Service Announcer ITS stations (ITS-S) as well as of the communication steps following the service announcement protocol procedure and related protocol details between Service Announcer and Service User ITS-S are application-specific are not covered by the present document.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at https://docbox.etsi.org/Reference.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

	Description of the second of t
[1]	ISO/TS 16460:2016: "Intelligent transport systems Communication access for land mobiles (CALM) Communications protocol messages for global usage".
[2]	ETSI TS 102 894-2: "Intelligent Transport Systems (ITS); Users and applications requirements; Part 2: Applications and facilities layer common data dictionary".
[3]	ETSI EN 302 636-4-1: "Intelligent Transport Systems (ITS); Vehicular Communications; GeoNetworking; Part 4: Geographical addressing and forwarding for point-to-point and point-to-multipoint communications; Sub-part 1: Media-Independent Functionality".
[4]	ETSI TS 103 097: "Intelligent Transport Systems (ITS); Security; Security header and certificate formats".
[5]	ETSI EN 302 931: "Intelligent Transport Systems (ITS); Vehicular Communications; Geographical Area Definition".
[6]	Recommendation ITU-T X.691/ISO/IEC 8825-2 (2015): "Information technology - ASN.1 encoding rules: Specification of Packed Encoding Rules (PER)".
[7]	ETSI TS 102 965: "Intelligent Transport Systems (ITS); Application Object Identifier (ITS-AID); Registration".
[8]	ETSI TS 103 248: "Intelligent Transport Systems (ITS); GeoNetworking; Port Numbers for the Basic Transport Protocol (BTP)".
[9]	IEEE 1609.3 TM - 2016: "IEEE Standard for Wireless Access in Vehicular Environments (WAVE) - Networking Services".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

[i.1]	ETSI TR 102 638 (V1.1.1): "Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Definitions".
[i.2]	ETSI EN 302 665 (V1.1.1): "Intelligent Transport Systems (ITS); Communications Architecture".
[i.3]	ISO/TS 17423:2014: "Intelligent transport systems Cooperative systems ITS application requirements and objectives for selection of communication profiles".
[i.4]	ETSI TS 102 723-11: "Intelligent Transport Systems (ITS); OSI cross-layer topics; Part 11: Interface between networking and transport layer and facilities layer".
[i.5]	ETSI TS 102 723-5 (V1.1.1): "Intelligent Transport Systems (ITS); OSI cross-layer topics; Part 5: Interface between management entity and facilities layer".
[i.6]	ETSI EN 302 636-5-1: "Intelligent Transport Systems (ITS); Vehicular Communications; GeoNetworking; Part 5: Transport Protocols; Sub-part 1: Basic Transport Protocol".
[i.7]	ETSI TS 103 301: "Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Facilities layer protocols and communication requirements for infrastructure services".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

ITS application: association of two or more complementary ITS-S applications

ITS-S application: fragment of an ITS application available at an ITS-S that uses ITS-S services to connect to one or more other fragments of the same ITS application

ITS-S gateway: gateway functionality based on the ITS-S reference architecture

ITS-S router: routing functionality based on the ITS-S reference architecture

ITS service: service provided by an ITS application to the user of ITS

ITS-S service: communication functionality offered by an ITS-S to an ITS-S application

Services Announcement (SA): provision, via an ITS communication functionality, of information about an ITS service

NOTE: Such information can include the ITS service identity, availability and communication details.

Service announcer ITS-S: ITS-S that announces services on behalf of the service provider ITS-S by transmitting SAEM

Service provider ITS-S: ITS-S that provides remote or local ITS services

Service user ITS-S: consumer of ITS services monitoring SAEM for an announced ITS service opportunity of interest

These definitions are in line with ETSI EN 302 665 [i.2].

3.2 **Symbols**

For the purposes of the present document, the following symbols apply:

changeCount Component of samBody

Component of ServiceInfo pointer to ChannelInfo channelIndex

ChannelInfo Datatype of channelInfos list entry

channelInfos Component of samBody **chOptions** Component of ServiceInfo contentCount Component of changeCount

defaultGateway Component of routingAdvertisement **ExtendedChannelInfos** Component of extensions of samBody

extensions Component of samBody

Component of routingAdvertisement **GatewayMACaddress**

IPv6Address Component of chOptions *ItsPduHeader* Header component of the SAEM messageID Component of the ItsPduHeader protocolType Component of *chOptions* protocolVersion **ProviderMACaddress** routingAdvertisement

saID sam

Sam

samBody

serviceID

ServiceInfo

Component of samBody serviceInfos serviceProviderPort

Unused component of chOptions SrvAdvChangeCount Datatype of *changeCount* stationID Component of the ItsPduHeader Unused component of chOptions systemService

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AID Application Identifier

API **Application Programming Interface**

ASN Abstract Syntax Notation BTP Basic Transport Protocol

C-ITS Cooperative ITS GeoNetworking GN ID Identifier

IETF Internet Engineering Task Force

Internet Protocol IΡ

IPv6 Internet Protocol Version 6

International Organization for Standardization ISO

ITS **Intelligent Transport System**

ITS-S **ITS Station**

ITU-T International Telecommunication Union - Telecommunication Standardization Sector

MAC Medium Access Control

Management to Application Service Access Point MA-SAP

MDA Minimum Dissemination Area MF Management to Facilities

MF-SAP Management to Facilities Service Access Point

Networking & transport to Facilities NF

NF-SAP Networking & transport to Facilities Service Access Point

Packed Encoding Rules PER

RXReception

Services Announcement

SAEM Services Announcement Extended Message

SAM Service Announcement SAP Service Access Point **SfCH** Safety Channel (logical) **SSP** Service Specific Permissions

TXTransmission

SA functional description 4

4.1 SA functional architecture

The Services Announcement (SA) service is a protocol service that is distributed over the facilities layer and the management entity of the ITS-S reference architecture as defined in ETSI EN 302 665 [i.2]. The SA service provides information on available services, applying the Services Announcement protocol with the following functions:

- The SA message processing function of the facility layer is responsible for the periodic transmission and/or reception of SAEM. It shall offer the following functionalities:
 - For the SAEM transmission (TX) service:
 - message encoding;
 - For the SAEM reception (RX) service:

 message decod:-

 - reception management.
- The SA management function of the management entity is responsible for the registration/update/deregistration of applications.

The SA service is implemented in a Service Provider, Service Announcer, or Service User ITS-S.

Figure 1 presents the SA service in the context of the ITS-S reference architecture and its logical interfaces with other entities and layers.

The SA service supports different configurations with respect of the Service Provider role and the Service Announcer role, such as:

- Service Provider and Service Announcer functionality are implemented in the same ITS-S;
- Service Provider and Service Announcer functionality are implemented in separate ITS-S and
- other configurations.