

ETSI TS 137 544 V14.5.0 (2018-04)



**Universal Mobile Telecommunications System (UMTS);
LTE;
Universal Terrestrial Radio Access (UTRA)
and Evolved UTRA (E-UTRA);
User Equipment (UE) Over The Air (OTA) performance;
Conformance testing
(3GPP TS 37.544 version 14.5.0 Release 14)**



ReferenceRTS/TSGR-0537544vE50

KeywordsLTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2018.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	14
1 Scope	15
2 References	15
3 Definitions, symbols and abbreviations	17
3.1 Definitions	17
3.2 Symbols.....	17
3.3 Abbreviations	18
4 General	19
4.1 Terminal classes	20
4.1.1 Mechanical modes	20
4.2 UTRA chip rates.....	20
4.3 DUT positioning.....	20
4.3.1 DUT positioning for Speech Mode with beside the Head Phantom	20
4.3.2 DUT positioning for LMEs on Laptop Ground Plane Phantom	21
4.3.3 DUT positioning for Speech Mode with beside the Head and Hand Phantom	21
4.3.3.1 General	21
4.3.3.2 Mono-blocks and closed sliders	22
4.3.3.3 Folds and open-slides	23
4.3.3.4 PDA.....	23
4.3.4 DUT positioning for Browsing Mode with Hand Phantom	24
4.3.4.1 General	24
4.3.4.2 Narrow DUT	24
4.3.4.3 PDA.....	25
4.3.5 DUT positioning for devices with embedded modules.....	25
4.3.6 DUT positioning for total radiated multi-antenna sensitivity	25
4.3.6.1 Handheld UE – Free Space	25
4.3.6.1.1 MPAC Positioning Guidelines	26
4.3.6.1.2 RTS Positioning Guidelines	26
4.4 Sampling grid	26
4.5 Number of independent samples (for reverberation chamber procedure)	26
5 Measurement frequencies.....	26
5.1 UTRA FDD frequency bands and measurement channels	26
5.2 UTRA TDD frequency bands and measurement channels.....	27
5.3 E-UTRA FDD frequency bands and measurement frequencies allocations.....	28
5.4 E-UTRA TDD frequency bands and measurement frequencies allocations.....	35
5.5 E-UTRA FDD operating bands and measurement frequency allocations for receiver total radiated multi-antenna sensitivity	37
5.6 E-UTRA TDD operating bands and measurement frequency allocations for receiver total radiated multi-antenna sensitivity	39
6 Transmitter Performance	39
6.1 Performance for handheld UE	39
6.1.1 Total Radiated Power (TRP) for UTRA FDD in Speech Mode with beside the Head Phantom.....	40
6.1.1.1 Definition and applicability.....	40
6.1.1.2 Minimum Requirements.....	41
6.1.1.3 Test purpose	41
6.1.1.4 Method of test	41
6.1.1.4.1 Initial conditions	41
6.1.1.4.2 Procedure	42
6.1.1.4.3 Procedure, reverberation chamber method.....	42

6.1.1.5	Test requirements	43
6.1.2	Total Radiated Power (TRP) for UTRA LCR TDD in Speech Mode with beside the Head Phantom.....	43
6.1.2.1	Definition and applicability.....	44
6.1.2.2	Minimum Requirements.....	44
6.1.2.3	Test purpose	45
6.1.2.4	Method of test	45
6.1.2.4.1	Initial conditions	45
6.1.2.4.2	Procedure	46
6.1.2.4.3	Procedure, reverberation chamber method.....	46
6.1.2.5	Test requirements.....	46
6.1.3	Total Radiated Power (TRP) for UTRA FDD in Speech Mode with beside the Head and Hand Phantom	47
6.1.3.1	Definition and applicability.....	47
6.1.3.2	Minimum Requirements.....	48
6.1.3.3	Test purpose	49
6.1.3.4	Method of test	49
6.1.3.4.1	Initial conditions	49
6.1.3.4.2	Procedure	49
6.1.3.4.3	Procedure, reverberation chamber method.....	50
6.1.3.5	Test requirements.....	50
6.1.4	Total Radiated Power (TRP) for UTRA LCR TDD in Speech Mode with beside the Head and Hand Phantom.....	51
6.1.4.1	Definition and applicability.....	51
6.1.4.2	Minimum Requirements.....	52
6.1.4.3	Test purpose	53
6.1.4.4	Method of test	53
6.1.4.4.1	Initial conditions	53
6.1.4.4.2	Procedure	53
6.1.4.4.3	Procedure, reverberation chamber method.....	54
6.1.4.5	Test requirements.....	54
6.1.5	Total Radiated Power (TRP) for E-UTRA FDD in Speech Mode with beside the Head and Hand Phantom.....	55
6.1.5.1	Definition and applicability.....	55
6.1.5.2	Minimum Requirements.....	57
6.1.5.3	Test purpose	57
6.1.5.4	Method of test	57
6.1.5.4.1	Initial conditions	57
6.1.5.4.2	Procedure	58
6.1.5.4.3	Procedure, reverberation chamber method.....	58
6.1.5.5	Test requirements.....	58
6.1.6	Total Radiated Power (TRP) for E-UTRA TDD in Speech Mode with beside the Head and Hand Phantom.....	58
6.1.6.1	Definition and applicability.....	59
6.1.6.2	Minimum Requirements.....	60
6.1.6.3	Test purpose	60
6.1.6.4	Method of test	60
6.1.6.4.1	Initial conditions	60
6.1.6.4.2	Procedure	61
6.1.6.4.3	Procedure, reverberation chamber method.....	61
6.1.6.5	Test requirements.....	61
6.1.7	Total Radiated Power (TRP) for UTRA FDD in Browsing Mode with Hand Phantom	62
6.1.7.1	Definition and applicability.....	62
6.1.7.2	Minimum Requirements.....	63
6.1.7.3	Test purpose	63
6.1.7.4	Method of test	64
6.1.7.4.1	Initial conditions	64
6.1.7.4.2	Procedure	64
6.1.7.4.3	Procedure, reverberation chamber method.....	65
6.1.7.5	Test requirements.....	65
6.1.8	Total Radiated Power (TRP) for UTRA LCR TDD in Browsing Mode with Hand Phantom	65
6.1.8.1	Definition and applicability.....	66
6.1.8.2	Minimum Requirements.....	66
6.1.8.3	Test purpose	67

6.1.8.4	Method of test	67
6.1.8.4.1	Initial conditions	67
6.1.8.4.2	Procedure	68
6.1.8.4.3	Procedure, reverberation chamber method.....	68
6.1.8.5	Test requirements.....	68
6.1.9	Total Radiated Power (TRP) for E-UTRA FDD in Browsing Mode with Hand Phantom.....	69
6.1.9.1	Definition and applicability.....	69
6.1.9.2	Minimum Requirements.....	70
6.1.9.3	Test purpose	70
6.1.9.4	Method of test	70
6.1.9.4.1	Initial conditions	70
6.1.9.4.2	Procedure	71
6.1.9.4.3	Procedure, reverberation chamber method.....	71
6.1.9.5	Test requirements.....	71
6.1.10	Total Radiated Power (TRP) for E-UTRA TDD in Browsing Mode with Hand Phantom	72
6.1.10.1	Definition and applicability.....	72
6.1.10.2	Minimum Requirements.....	73
6.1.10.3	Test purpose	73
6.1.10.4	Method of test	73
6.1.10.4.1	Initial conditions	73
6.1.10.4.2	Procedure	73
6.1.10.4.3	Procedure, reverberation chamber method.....	74
6.1.10.5	Test requirements.....	74
6.2	Performance for LME	74
6.2.1	Total Radiated Power (TRP) for UTRA FDD LME	74
6.2.1.2	Minimum Requirements.....	75
6.2.1.3	Test purpose	76
6.2.1.4	Method of test	76
6.2.1.4.1	Initial conditions	76
6.2.1.4.2	Procedure	76
6.2.1.4.3	Procedure, reverberation chamber method.....	77
6.2.1.5	Test requirements.....	77
6.2.2	Total Radiated Power (TRP) for UTRA LCR-TDD LME	78
6.2.2.2	Minimum Requirements.....	79
6.2.2.3	Test purpose	80
6.2.2.4	Method of test	80
6.2.2.4.1	Initial conditions	80
6.2.2.4.2	Procedure	81
6.2.2.4.3	Procedure, reverberation chamber method.....	81
6.2.2.5	Test requirements.....	82
6.2.3	Total Radiated Power (TRP) for E-UTRA FDD LME.....	82
6.2.4	Total Radiated Power (TRP) for E-UTRA TDD LME	85
6.3	Performance for LEE.....	88
6.3.1	Total Radiated Power (TRP) for UTRA FDD LEE	88
6.3.1.1	Definition and applicability.....	88
6.3.1.2	Minimum Requirements.....	89
6.3.1.3	Test purpose	90
6.3.1.4	Method of test	90
6.3.1.4.1	Initial conditions	90
6.3.1.4.2	Procedure	90
6.3.1.4.3	Procedure, reverberation chamber method.....	91
6.3.1.5	Test requirements.....	91
6.3.2	Total Radiated Power (TRP) for UTRA LCR TDD LEE	93
6.3.2.1	Definition and applicability.....	93
6.3.2.2	Minimum Requirements.....	94
6.3.2.3	Test purpose	94
6.3.2.4	Method of test	95
6.3.2.4.1	Initial conditions	95
6.3.2.4.2	Procedure	95
6.3.2.4.3	Procedure, reverberation chamber method.....	96
6.3.2.5	Test requirements.....	96
6.3.3	Total Radiated Power (TRP) for E-UTRA FDD LEE.....	97

6.3.4	Total Radiated Power (TRP) for E-UTRA TDD LEE	102
7	Receiver Performance	106
7.1	Performance for handheld UE	106
7.1.1	Total Radiated Sensitivity (TRS) for UTRA FDD in Speech Mode with beside the Head Phantom	106
7.1.1.1	Definition and applicability.....	106
7.1.1.2	Minimum requirements.....	106
7.1.1.3	Test Purpose	107
7.1.1.4	Method of test	107
7.1.1.4.1	Initial conditions	107
7.1.1.4.2	Test procedure.....	108
7.1.1.4.3	Test procedure, reverberation chamber method	108
7.1.1.5	Test requirements	108
7.1.2	Total Radiated Sensitivity (TRS) for UTRA LCR TDD in Speech Mode with beside the Head Phantom	109
7.1.2.1	Definition and applicability.....	109
7.1.2.2	Minimum Requirements.....	110
7.1.2.3	Test purpose	110
7.1.2.4	Method of test	110
7.1.2.4.1	Initial conditions	110
7.1.2.4.2	Procedure	111
7.1.2.4.3	Procedure, reverberation chamber method.....	112
7.1.2.5	Test requirements.....	112
7.1.3	Total Radiated Sensitivity (TRS) for UTRA FDD in Speech Mode with beside the Head and Hand Phantom.....	112
7.1.3.1	Definition and applicability.....	112
7.1.3.2	Minimum Requirements.....	113
7.1.3.3	Test purpose	114
7.1.3.4	Method of test	114
7.1.3.4.1	Initial conditions	114
7.1.3.4.2	Procedure	115
7.1.3.4.3	Procedure, reverberation chamber method.....	115
7.1.3.5	Test requirements.....	116
7.1.4	Total Radiated Sensitivity (TRS) for UTRA LCR TDD in Speech Mode with beside the Head and Hand Phantom.....	117
7.1.4.1	Definition and applicability.....	117
7.1.4.2	Minimum Requirements.....	118
7.1.4.3	Test purpose	119
7.1.4.4	Method of test	119
7.1.4.4.1	Initial conditions	119
7.1.4.4.2	Procedure	120
7.1.4.4.3	Procedure, reverberation chamber method.....	120
7.1.4.5	Test requirements.....	121
7.1.5	Total Radiated Sensitivity (TRS) for E-UTRA FDD in Speech Mode with beside the Head and Hand Phantom.....	121
7.1.5.1	Definition and applicability.....	121
7.1.5.2	Minimum Requirements.....	122
7.1.5.3	Test purpose	123
7.1.5.4	Method of test	123
7.1.5.4.1	Initial conditions	123
7.1.5.4.2	Procedure	123
7.1.5.4.3	Procedure, reverberation chamber method.....	124
7.1.5.5	Test requirements.....	124
7.1.6	Total Radiated Sensitivity (TRS) for E-UTRA TDD in Speech Mode with beside the Head and Hand Phantom.....	124
7.1.6.1	Definition and applicability.....	124
7.1.6.2	Minimum Requirements.....	125
7.1.6.3	Test purpose	126
7.1.6.4	Method of test	126
7.1.6.4.1	Initial conditions	126
7.1.6.4.2	Procedure	126

7.1.6.4.3	Procedure, reverberation chamber method.....	126
7.1.6.5	Test requirements.....	127
7.1.7	Total Radiated Sensitivity (TRS) for UTRA FDD in Browsing Mode with Hand Phantom	127
7.1.7.1	Definition and applicability.....	127
7.1.7.2	Minimum Requirements.....	128
7.1.7.3	Test purpose	128
7.1.7.4	Method of test	129
7.1.7.4.1	Initial conditions	129
7.1.7.4.2	Procedure	129
7.1.7.4.3	Procedure, reverberation chamber method.....	130
7.1.7.5	Test requirements.....	130
7.1.8	Total Radiated Sensitivity (TRS) for UTRA LCR TDD in Browsing Mode with Hand Phantom	131
7.1.8.1	Definition and applicability.....	131
7.1.8.2	Minimum Requirements.....	131
7.1.8.3	Test purpose	132
7.1.8.4	Method of test	132
7.1.8.4.1	Initial conditions	132
7.1.8.4.2	Procedure	133
7.1.8.4.3	Procedure, reverberation chamber method.....	133
7.1.8.5	Test requirements.....	133
7.1.9	Total Radiated Sensitivity (TRS) for E-UTRA FDD in Browsing Mode with Hand Phantom.....	134
7.1.9.1	Definition and applicability.....	134
7.1.9.2	Minimum Requirements.....	135
7.1.9.3	Test purpose	135
7.1.9.4	Method of test	135
7.1.9.4.1	Initial conditions	135
7.1.9.4.2	Procedure	135
7.1.9.4.3	Procedure, reverberation chamber method.....	136
7.1.9.5	Test requirements.....	136
7.1.10	Total Radiated Sensitivity (TRS) for E-UTRA TDD in Browsing Mode with Hand Phantom	136
7.1.10.1	Definition and applicability.....	136
7.1.10.2	Minimum Requirements.....	137
7.1.10.3	Test purpose	137
7.1.10.4	Method of test	137
7.1.10.4.1	Initial conditions	137
7.1.10.4.2	Procedure	138
7.1.10.4.3	Procedure, reverberation chamber method.....	138
7.1.10.5	Test requirements.....	138
7.2	Performance for LME	138
7.2.1	Total Radiated Sensitivity (TRS) for UTRA FDD LME	138
7.2.1.1	Definition and applicability.....	139
7.2.1.2	Minimum Requirements.....	139
7.2.1.3	Test purpose	140
7.2.1.4	Method of test	140
7.2.1.4.1	Initial conditions	140
7.2.1.4.2	Procedure	141
7.2.1.4.3	Test procedure, reverberation chamber method	141
7.2.1.5	Test requirements.....	141
7.2.2	Total Radiated Sensitivity (TRS) for UTRA LCR TDD LME	142
7.2.2.1	Definition and applicability.....	142
7.2.2.2	Minimum Requirements.....	143
7.2.2.3	Test purpose	143
7.2.2.4	Method of test	143
7.2.2.4.1	Initial conditions	143
7.2.2.4.2	Procedure	144
7.2.2.4.3	Test procedure, reverberation chamber method	145
7.2.2.5	Test requirements.....	145
7.2.3	Total Radiated Sensitivity (TRS) for E-UTRA FDD LME	145
7.2.3.1	Definition and applicability.....	145
7.2.3.2	Minimum Requirements.....	146
7.2.3.3	Test purpose	146
7.2.3.4	Method of test	146

7.2.3.4.1	Initial conditions	146
7.2.3.4.2	Procedure	147
7.2.3.4.3	Procedure, reverberation chamber method.....	147
7.2.3.5	Test requirements.....	147
7.2.4	Total Radiated Sensitivity (TRS) for E-UTRA TDD LME	148
7.2.4.1	Definition and applicability.....	148
7.2.4.2	Minimum Requirements.....	148
7.2.4.3	Test purpose	149
7.2.4.4	Method of test	149
7.2.4.4.1	Initial conditions	149
7.2.4.4.2	Procedure	149
7.2.4.4.3	Procedure, reverberation chamber method.....	149
7.2.4.5	Test requirements.....	149
7.3	Performance for LEE.....	150
7.3.1	Total Radiated Sensitivity (TRS) for UTRA FDD LEE	150
7.3.1.1	Definition and applicability.....	150
7.3.1.2	Minimum Requirements.....	151
7.3.1.3	Test purpose	152
7.3.1.4	Method of test	152
7.3.1.4.1	Initial conditions	152
7.3.1.4.2	Procedure	153
7.3.1.4.3	Procedure, reverberation chamber method.....	153
7.3.1.5	Test requirements.....	154
7.3.2	Total Radiated Sensitivity (TRS) for UTRA LCR TDD LEE	155
7.3.2.1	Definition and applicability.....	155
7.3.2.2	Minimum Requirements.....	156
7.3.2.3	Test purpose	157
7.3.2.4	Method of test	157
7.3.2.4.1	Initial conditions	157
7.3.2.4.2	Procedure	158
7.3.2.4.3	Procedure, reverberation chamber method.....	158
7.3.2.5	Test requirements.....	159
7.3.3	Total Radiated Sensitivity (TRS) for E-UTRA FDD LEE	160
7.3.3.1	Definition and applicability.....	160
7.3.3.2	Minimum Requirements.....	161
7.3.3.3	Test purpose	162
7.3.3.4	Method of test	162
7.3.3.4.1	Initial conditions	162
7.3.3.4.2	Procedure	163
7.3.3.4.3	Procedure, reverberation chamber method.....	163
7.3.3.5	Test requirements.....	163
7.3.4	Total Radiated Sensitivity (TRS) for E-UTRA TDD LEE	164
7.3.4.1	Definition and applicability.....	164
7.3.4.2	Minimum Requirements.....	165
7.3.4.3	Test purpose	165
7.3.4.4	Method of test	166
7.3.4.4.1	Initial conditions	166
7.3.4.4.2	Procedure	166
7.3.4.4.3	Procedure, reverberation chamber method.....	166
7.3.4.5	Test requirements.....	166
7.4	Radiated Performance of Multiple-antenna Receivers in the UE.....	167
7.4.1	Total Radiated Multi-antenna Sensitivity (TRMS) for E-UTRA FDD for Handheld UE in Free Space.....	167
7.4.1.1	Definition and applicability.....	167
7.4.1.2	Minimum requirements	168
7.4.1.3	Test Purpose	168
7.4.1.4	Method of test for Multi-probe Anechoic Chamber.....	168
7.4.1.4.1	Initial conditions	168
7.4.1.4.2	Procedure	169
7.4.1.5	Test requirements.....	169
7.4.2	Total Radiated Multi-antenna Sensitivity (TRMS) for E-UTRA TDD for Handheld UE in Free Space.....	170

7.4.2.1	Definition and applicability.....	170
7.4.2.2	Minimum requirements.....	171
7.4.2.3	Test Purpose.....	171
7.4.2.4	Method of test for Multi-probe Anechoic Chamber.....	171
7.4.2.4.1	Initial conditions.....	171
7.4.2.4.2	Procedure.....	172
7.4.2.4A	Method of test for Radiated Two-Stage.....	172
7.4.2.4A.1	Initial conditions.....	172
7.4.2.4A.2	Procedure.....	173
7.4.2.5	Test requirements.....	174

Annex A (normative): Test system characterization and environmental requirements.....175

A.1	General.....	175
A.2	Phantom specifications.....	175
A.2.1	Head phantom.....	175
A.2.2	Hand phantom.....	175
A.2.2.1	General.....	175
A.2.2.2	Dimensions.....	175
A.2.2.3	Dielectric properties.....	177
A.2.2.4	Hand phantom grips.....	177
A.2.2.5	Mechanical Requirements of Hand Phantoms.....	179
A.2.3	Laptop Ground Plane Phantom.....	180
A.2.4	Parameters for embedded devices.....	182
A.2.4.1	General.....	182
A.2.4.2	Notebook.....	182
A.2.4.3	Tablet.....	183
A.3	Anechoic chamber constraints.....	183
A.3.1	General.....	183
A.3.2	Quiet zone dimension.....	186
A.3.3	Minimum distance between the DUT and the measurement antenna.....	186
A.3.4	Reflectivity of the quiet zone.....	186
A.3.5	Shielding effectiveness of the chamber.....	186
A.4	Reverberation chamber constraints.....	186
A.4.1	General.....	186
A.4.2	Positioning and mode stirring facilities.....	187
A.4.3	Polarization imbalance and receiving antennas.....	187
A.4.4	Measurement antennas.....	188
A.4.5	Chamber size and characteristics.....	188
A.4.6	Shielding effectiveness of the chamber.....	188
A.5	Anechoic chamber constraints for Radiated Performance of Multiple-antenna Receivers.....	188
A.5.1	General.....	188
A.5.1.1	Multi-probe Anechoic Chamber.....	189
A.5.1.1.1	Concept and configuration.....	190
A.5.1.2	Radiated Two-Stage.....	191
A.5.1.2.1	Concept and configuration.....	192
A.5.2	Testing environment conditions.....	193
A.5.2.1	MPAC Positioning Guidelines.....	200
A.5.2.2	RTS Positioning Guidelines and test zone dimensions.....	204

Annex B (normative): Calibration.....205

B.1	General.....	205
B.2.1	Calibration procedure for Anechoic chamber method.....	205
B.2.2	Calibration procedure for Reverberation chamber method.....	206
B.2.2.1	Measurement of S-parameters through the chamber for a complete stirring sequence.....	207
B.2.2.2	Calculation of the chamber reference transfer function.....	208
B.2.2.3	Cable calibration.....	208
B.2.3	Calibration procedure for Anechoic chamber method with Multiprobe configuration.....	209
B.2.3.1	Example Calibration Procedure.....	209

B.2.4	Calibration procedure for RTS method	211
Annex C (informative): Measurement test report		213
C.1	General	213
Annex D (normative): Maximum uncertainty of test system and test tolerance		214
D.1	Maximum uncertainty of test system	214
D.2	Test tolerances	217
Annex E (informative): Estimation of measurement uncertainty		221
E.1	General	221
E.2	Mismatch uncertainty between measurement receiver and the probe antenna	226
E.2.1	Total combined mismatch uncertainty calculations	226
E.2.1.1	Mismatch uncertainty through the connector between two elements	226
E.2.1.2	Mismatch uncertainty due to the interaction of several elements	227
E.2.2	Total combined mismatch uncertainty	228
E.3	Mismatch uncertainty of the RF relay	228
E.3.1	First part: RF Relay switched on the co-polarized signal	229
E.3.1.1	The mismatch through the connector between two elements	229
E.3.1.2	Mismatch due to the interaction between two elements or more	229
E.3.2	Second part: RF relay switched on the cross-polarized signal	230
E.3.2.1	The mismatch through the connector between two elements	230
E.3.2.2	Mismatch due to the interaction between two elements or more	230
E.3.3	Total combined mismatch uncertainty	231
E.4	Insertion loss of the probe antenna cable	231
E.5	Insertion loss of the probe antenna attenuator (if used)	231
E.6	Insertion loss of the RF relays (if used)	231
E.7	Influence of the antenna cable	232
E.7.1	Probe antenna cable	232
E.7.2	Calibration antenna cable	232
E.8	Absolute gain of the probe antenna	232
E.9	Measurement receiver: uncertainty of absolute level	232
E.10	Measurement distance	232
E.10.1	Offset of DUT phase centre from axis(es) of rotation	232
E.10.2	Mutual coupling	233
E.10.3	Phase curvature	233
E.11	Quality of quiet zone	233
E.12	Tx-power drift of DUT	233
E.13	Uncertainty related to the use of phantoms	234
E.13.1	Uncertainty from using different types of SAM phantom	234
E.13.2	Simulated tissue liquid uncertainty	234
E.13.3	Uncertainty of dielectric properties and shape of the hand phantom	234
E.13.4	Uncertainty from using different types of Laptop Ground Plane phantom	236
E.14	Coarse sampling grid	236
E.15	Random uncertainty	237
E.16	Uncertainty of network analyzer	238
E.17	Uncertainty of the gain/efficiency of the calibration antenna	238
E.18	Base station simulator: uncertainty of the absolute level	238
E.19	BER measurement: output level step resolution	238
E.20	Statistical uncertainty of the BER measurement	238
E.21	BER data rate normalization uncertainty	239
E.22	DUT sensitivity drift	239
E.23	Cable loss measurement uncertainty	239

E.24	Signal generator: uncertainty of the absolute output level	240
E.25	Signal generator: output level stability	240
E.26	Insertion loss: calibration antenna feed cable	240
E.27	Insertion loss: calibration antenna attenuator (if used)	240
E.28	Chamber Statistical Ripple and Repeatability	240
E.29	Additional Power Loss in EUT Chassis	240
Annex F (informative): Suggested recipes of liquid to be used inside SAM phantom		255
F.1	General	255
Annex G (informative): Anechoic chamber specification and validation method		256
G.1	Shielded anechoic chamber specifications	256
G.2	Quiet zone reflectivity level validation	256
G.2.1	Description of a practical method for Quiet Zone characterization	256
G.3	Standard deviation of electric field	257
Annex H (informative): Reverberation chamber specifications and validation method		259
H.1	Shielded reverberation chamber specifications	259
H.2	Reverberation chamber statistical ripple and repeatability validation	259
Annex I (informative): Recommended performance for Handheld UE		260
I.1	General	260
I.2	Total Radiated Power	260
I.2.1	Beside the head phantom position	260
I.2.1.1	UTRA FDD	261
I.2.1.2	UTRA LCR TDD	261
I.2.2	Beside the head and hand phantoms position	261
I.2.2.1	UTRA FDD	262
I.2.2.2	UTRA LCR TDD	262
I.2.2.3	E-UTRA FDD	262
I.2.2.4	E-UTRA TDD	262
I.2.3	Hand phantom browsing mode position	262
I.2.3.1	UTRA FDD	263
I.2.3.2	UTRA LCR TDD	263
I.2.3.3	E-UTRA FDD	263
I.2.3.4	E-UTRA TDD	264
I.3	Total Radiated Sensitivity	264
I.3.1	Beside the head phantom position	264
I.3.1.1	UTRA FDD	264
I.3.1.2	UTRA LCR TDD	264
I.3.2	Beside the head and hand phantoms position	264
I.3.2.1	UTRA FDD	265
I.3.2.2	UTRA LCR TDD	265
I.3.2.3	E-UTRA FDD	266
I.3.2.4	E-UTRA TDD	266
I.3.3	Hand phantom browsing mode position	266
I.3.3.1	UTRA FDD	266
I.3.3.2	UTRA LCR TDD	267
I.3.3.3	E-UTRA FDD	267
I.3.3.4	E-UTRA TDD	267
Annex J (informative): Recommended performance for LME		268
J.1	General	268
J.2	Total Radiated Power	268
J.2.1	UTRA FDD	268
J.2.2	UTRA LCR TDD	268
J.2.3	E-UTRA FDD	269
J.2.4	E-UTRA TDD	269
J.3	Total Radiated Sensitivity	269
J.3.1	UTRA FDD	269
J.3.2	UTRA LCR TDD	269
J.3.3	E-UTRA FDD	270

J.3.4	E-UTRA TDD	270
Annex K (informative):	Recommended performance for LEE	271
K.1	General	271
K.2	Total Radiated Power	271
K.2.1	UTRA FDD	271
K.2.2	UTRA LCR TDD	272
K.2.3	E-UTRA FDD	272
K.2.4	E-UTRA TDD	272
K.3	Total Radiated Sensitivity	273
K.3.1	UTRA FDD	273
K.3.2	UTRA LCR TDD	274
K.3.3	E-UTRA FDD	274
K.3.4	E-UTRA TDD	274
Annex L (informative):	Multi-Probe Anechoic Chamber Specification and Validation Method	275
L.1	Multi-probe anechoic chamber specifications	275
L.2	Multi-probe anechoic chamber minimum distance between the DUT and the measurement antenna	275
L.3	Multi-probe anechoic chamber quiet zone reflectivity level validation	275
L.4	Multi-probe anechoic chamber channel model verification	275
Annex M (normative):	Channel Model emulation of the Base Station antenna pattern configuration for Radiated Performance of Multiple-antenna Receivers	276
M.1	Channel Model(s)	276
M.2	Base Station antenna pattern configuration	277
Annex N (informative):	Estimation of measurement uncertainty for Multiple-antenna receivers	278
N.1	General	278
N.2	Fading channel emulator output uncertainty	282
N.3	External Amplifiers Uncertainty Terms	283
N.3.1	Stability	283
N.3.2	Linearity	283
N.3.3	Noise Figure	283
N.3.4	Mismatch	283
N.3.5	Gain	283
Annex O (normative):	Environmental conditions	283
O.1	General	283
O.2	Environmental requirements	284
O.2.1	Temperature	284
O.2.2	Voltage	284
Annex P (normative):	Base Station (BS) configuration for Radiated Performance of Multiple-antenna Receivers	285
P.1	eNodeB emulator settings	285
Annex Q (informative):	RTS Anechoic Chamber Specification and Validation Method	288
Q.1	RTS anechoic chamber specifications	288
Q.2	RTS anechoic chamber minimum distance between the DUT and the measurement antenna	288
Q.3	RTS anechoic chamber quiet zone reflectivity level validation	288
Q.4	RTS anechoic chamber channel model verification	288
Annex R:	UE ATF Requirements	289
R.1	RSAP	289