



SLOVENSKI STANDARD
oSIST prEN 301 908-24 V15.0.0:2023
01-februar-2023

**Celična omrežja IMT - Harmonizirani standard za dostop do radijskega spektra -
24. del: Nove radijske (NR) bazne postaje (BS), izdaja 15**

IMT cellular networks - Harmonised Standard for access to radio spectrum - Part 24:
New Radio (NR) Base Stations (BS) Release 15

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN 301 908-24 V15.0.0:2023](https://standards.iteh.ai/catalog/standards/sist/301-908-24-v15-0-0-2023)

Ta slovenski standard je istoveten z: **ETSI EN 301 908-24 V15.0.0 (2022-12)**

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.070.99	Druge mobilne storitve	Other mobile services

oSIST prEN 301 908-24 V15.0.0:2023 **en**

Draft **ETSI EN 301 908-24** V15.0.0 (2022-12)



**IMT cellular networks;
Harmonised Standard for access to radio spectrum;
Part 24: New Radio (NR) Base Stations (BS)
Release 15**

[oSIST prEN 301 908-24 V15.0.0:2023](https://standards.iteh.ai/catalog/standards/sist/633a4b88-c52b-4c54-bd29-2ae17e8aa7d1/osist-pren-301-908-24-v15-0-0-2023)

<https://standards.iteh.ai/catalog/standards/sist/633a4b88-c52b-4c54-bd29-2ae17e8aa7d1/osist-pren-301-908-24-v15-0-0-2023>

ReferenceDEN/MSG-TFES-15-24

Keywords3GPP, 5G, base station, cellular, digital, IMT,
IMT-2000, IMT 2020, IMT-Advanced, NR, radio,
regulation**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://standards-portal.etsi.org/People/CommitteeSupportStaff.aspx> 4c54-bd29-

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.

All rights reserved.

Contents

Intellectual Property Rights	9
Foreword.....	9
Modal verbs terminology.....	10
Introduction	10
1 Scope	11
2 References	12
2.1 Normative references	12
2.2 Informative references.....	13
3 Definition of terms, symbols and abbreviations.....	15
3.1 Terms.....	15
3.2 Symbols.....	19
3.3 Abbreviations	20
4 Technical requirements specifications	21
4.1 Environmental profile.....	21
4.2 Requirement set applicability	21
4.3 Conformance requirements	22
4.3.1 Introduction.....	22
4.3.1.1 General	22
4.3.1.2 Conducted transmitter requirements	24
4.3.1.3 Conducted receiver requirements	24
4.3.1.4 Conducted requirements for BS capable of multi-band operation	25
4.3.1.5 Radiated transmitter requirements	26
4.3.1.6 Radiated receiver requirements.....	26
4.3.1.7 Radiated requirements for BS capable of multi-band operation	27
4.3.1.8 Additional BS conformance to other standards.....	27
4.3.2 Operating band unwanted emissions	29
4.3.2.1 Definition and applicability.....	29
4.3.2.2 Limits	29
4.3.2.2.1 General	29
4.3.2.2.2 Wide Area BS.....	31
4.3.2.2.3 Medium Range BS	32
4.3.2.2.4 Local Area BS	34
4.3.2.2.5 Additional limits	35
4.3.2.3 Conformance.....	35
4.3.3 Adjacent Channel Leakage power Ratio (ACLR)	36
4.3.3.1 Definition and applicability.....	36
4.3.3.2 Limits	36
4.3.3.2.1 General	36
4.3.3.2.2 Absolute limits	36
4.3.3.2.3 Relative Limits	37
4.3.3.3 Conformance.....	38
4.3.4 Transmitter spurious emissions.....	38
4.3.4.1 Definition and applicability.....	38
4.3.4.2 Limits	39
4.3.4.2.1 General spurious emissions limits	39
4.3.4.2.2 Limits for protection of the <i>BS receiver</i>	39
4.3.4.2.3 Limits for co-existence with other systems	39
4.3.4.2.4 Additional limits	41
4.3.4.3 Conformance.....	42
4.3.5 Base Station output power	42
4.3.5.1 Definition and applicability.....	42
4.3.5.2 Limits	42
4.3.5.3 Conformance.....	42
4.3.6 Transmit intermodulation	42

4.3.6.1	Definition and applicability.....	42
4.3.6.2	Limits	43
4.3.6.2.1	<i>BS type 1-C</i> : Co-location limits	43
4.3.6.2.2	<i>BS type 1-H</i> : Co-location limits.....	43
4.3.6.2.3	<i>BS type 1-H</i> : Intra-system requirement.....	44
4.3.6.3	Conformance.....	44
4.3.7	Receiver spurious emissions	44
4.3.7.1	Definition and applicability.....	44
4.3.7.2	Limits	45
4.3.7.3	Conformance.....	45
4.3.8	In-band blocking.....	45
4.3.8.1	Definition and applicability.....	45
4.3.8.2	Limits	45
4.3.8.3	Conformance.....	47
4.3.9	Out-of-band blocking.....	47
4.3.9.1	Definition and applicability.....	47
4.3.9.2	Limits	48
4.3.9.3	Conformance.....	48
4.3.10	Receiver intermodulation.....	48
4.3.10.1	Definition and applicability.....	48
4.3.10.2	Limits	48
4.3.10.3	Conformance.....	51
4.3.11	Adjacent Channel Selectivity (ACS)	51
4.3.11.1	Definition and applicability.....	51
4.3.11.2	Limits	51
4.3.11.3	Conformance.....	52
4.3.12	Reference sensitivity level.....	52
4.3.12.1	Definition and applicability.....	52
4.3.12.2	Limits	52
4.3.12.3	Conformance.....	53
4.3.13	OTA <i>operating band</i> unwanted emissions.....	53
4.3.13.1	Definition and applicability.....	53
4.3.13.2	Limits for <i>BS type 1-O</i>	54
4.3.13.2.1	General	54
4.3.13.2.2	Wide Area BS.....	55
4.3.13.2.3	Medium Range BS	57
4.3.13.2.4	Local Area BS	59
4.3.13.2.5	Additional limits.....	59
4.3.13.3	Limits for <i>BS type 2-O</i>	60
4.3.13.4	Conformance.....	61
4.3.14	OTA Adjacent Channel Leakage power Ratio (ACLR)	61
4.3.14.1	Definition and applicability.....	61
4.3.14.2	Limits	61
4.3.14.2.1	General	61
4.3.14.2.2	Absolute limits	61
4.3.14.2.3	Relative Limits	62
4.3.14.3	Conformance.....	65
4.3.15	OTA transmitter spurious emissions.....	65
4.3.15.1	Definition and applicability.....	65
4.3.15.2	Limits	66
4.3.15.2.1	General spurious emission limits for <i>BS type 1-O</i>	66
4.3.15.2.2	General spurious emission limits for <i>BS type 2-O</i>	66
4.3.15.2.3	Limits for protection of <i>BS receiver</i> for <i>BS type 1-O</i>	67
4.3.15.2.4	Limits for co-existence with systems operating in other frequency bands for <i>BS type 1-O</i>	67
4.3.15.2.5	Additional limits	69
4.3.15.3	Conformance.....	69
4.3.16	Radiated transmit power	69
4.3.16.1	Definition and applicability.....	69
4.3.16.2	Limits	70
4.3.16.3	Conformance.....	70
4.3.17	OTA Base Station output power	70
4.3.17.1	Definition and applicability.....	70

4.3.17.2	Limits	70
4.3.17.3	Conformance	71
4.3.18	OTA transmitter intermodulation	71
4.3.18.1	Definition and applicability.....	71
4.3.18.2	Limits	71
4.3.18.2.1	<i>BS type 1-O</i>	71
4.3.18.3	Conformance.....	72
4.3.19	OTA receiver spurious emissions	72
4.3.19.1	Definition and applicability.....	72
4.3.19.2	Limits	72
4.3.19.2.1	<i>BS type 1-O</i>	72
4.3.19.2.2	<i>BS type 2-O</i>	73
4.3.19.3	Conformance.....	74
4.3.20	OTA In-band blocking.....	74
4.3.20.1	Definition and applicability.....	74
4.3.20.2	Limits	74
4.3.20.2.1	<i>BS type 1-O</i>	74
4.3.20.2.2	<i>BS type 2-O</i>	77
4.3.20.3	Conformance.....	78
4.3.21	OTA Out-of-band blocking	78
4.3.21.1	Definition and applicability.....	78
4.3.21.2	Limits	79
4.3.21.2.1	<i>BS type 1-O</i> General blocking	79
4.3.21.2.2	<i>BS type 2-O</i> general blocking	79
4.3.21.3	Conformance	79
4.3.22	OTA Receiver intermodulation.....	80
4.3.22.1	Definition and applicability.....	80
4.3.22.2	Limits	80
4.3.22.2.1	<i>BS type 1-O</i>	80
4.3.22.2.2	<i>BS type 2-O</i>	83
4.3.22.3	Conformance.....	83
4.3.23	OTA Adjacent Channel Selectivity (ACS).....	84
4.3.23.1	Definition and applicability.....	84
4.3.23.2	Limits	84
4.3.23.2.1	<i>BS type 1-O</i>	84
4.3.23.2.2	<i>BS type 2-O</i>	85
4.3.23.3	Conformance.....	85
4.3.24	OTA Sensitivity	86
4.3.24.1	Definition and applicability.....	86
4.3.24.2	Limits	86
4.3.24.3	Conformance.....	86
4.3.25	OTA Reference sensitivity.....	86
4.3.25.1	Definition and applicability.....	86
4.3.25.2	Limits	87
4.3.25.2.1	<i>BS type 1-O</i>	87
4.3.25.2.2	<i>BS type 2-O</i>	88
4.3.25.3	Conformance.....	89
5	Testing for compliance with technical requirements.....	89
5.1	Environmental conditions for testing	89
5.2	Interpretation of measurement results	89
5.3	Essential radio test suites.....	89
5.3.1	Introduction.....	89
5.3.2	<i>Operating band</i> unwanted emissions.....	90
5.3.2.1	General	90
5.3.2.2	Initial conditions	90
5.3.2.3	Procedure	90
5.3.2.4	Test Requirement	91
5.3.3	Adjacent Channel Leakage power Ratio (ACLR)	91
5.3.3.1	General	91
5.3.3.2	Initial conditions	91
5.3.3.3	Procedure	91

5.3.3.4	Test requirement	92
5.3.4	Transmitter spurious emissions.....	92
5.3.4.1	General	92
5.3.4.2	Initial conditions	92
5.3.4.3	Procedure	92
5.3.4.4	Test Requirement	93
5.3.5	Base Station output power	93
5.3.5.1	General	93
5.3.5.2	Initial conditions	93
5.3.5.3	Procedure	93
5.3.5.4	Test Requirement	94
5.3.6	Transmit intermodulation	94
5.3.6.1	General	94
5.3.6.2	Initial conditions	94
5.3.6.3	Procedure	94
5.3.6.3.1	Procedure for co-location requirement	94
5.3.6.3.2	Procedure for intra-system requirement	95
5.3.6.4	Test Requirement	96
5.3.7	Receiver spurious emissions	96
5.3.7.1	General	96
5.3.7.2	Initial conditions	96
5.3.7.3	Procedure	96
5.3.7.4	Test Requirement	97
5.3.8	In-band blocking	97
5.3.8.1	General	97
5.3.8.2	Initial conditions	97
5.3.8.3	Procedure	97
5.3.8.3.1	Procedure for general blocking.....	97
5.3.8.3.2	Procedure for narrowband blocking	98
5.3.8.4	Requirement	98
5.3.9	Out-of-band blocking.....	98
5.3.9.1	General	98
5.3.9.2	Initial conditions	98
5.3.9.3	Procedure	99
5.3.9.4	Test Requirement	99
5.3.10	Receiver intermodulation.....	99
5.3.10.1	General	99
5.3.10.2	Initial conditions	99
5.3.10.3	Procedure	100
5.3.10.4	Test Requirement	100
5.3.11	Adjacent Channel Selectivity (ACS)	100
5.3.11.1	General	100
5.3.11.2	Initial conditions	100
5.3.11.3	Procedure	101
5.3.11.4	Test Requirement	101
5.3.12	Reference sensitivity level.....	101
5.3.12.1	General	101
5.3.12.2	Initial conditions	101
5.3.12.3	Procedure	102
5.3.12.4	Test Requirement	102
5.3.13	OTA <i>operating band</i> unwanted emissions.....	102
5.3.13.1	General	102
5.3.13.2	Initial conditions	102
5.3.13.3	Procedure	103
5.3.13.4	Test Requirement	103
5.3.14	OTA Adjacent Channel Leakage power Ratio (ACLR)	103
5.3.14.1	General	103
5.3.14.2	Initial conditions	103
5.3.14.3	Procedure	104
5.3.14.4	Test Requirement	105
5.3.15	OTA transmitter spurious emissions.....	105
5.3.15.1	General spurious emissions.....	105

5.3.15.1.1	General	105
5.3.15.1.2	Initial conditions	105
5.3.15.1.3	Procedure	106
5.3.15.1.4	Test Requirement	107
5.3.15.2	Protection of <i>BS receiver</i>	107
5.3.15.2.1	General	107
5.3.15.2.2	Initial conditions	107
5.3.15.2.3	Procedure	107
5.3.15.2.4	Test Requirement	108
5.3.15.3	Co-existence with other systems	108
5.3.15.3.1	General	108
5.3.15.3.2	Initial conditions	108
5.3.15.3.3	Procedure	109
5.3.15.3.4	Test Requirement	109
5.3.16	Radiated transmit power	109
5.3.16.1	General	109
5.3.16.2	Initial conditions	109
5.3.16.3	Procedure	110
5.3.16.4	Test Requirement	110
5.3.17	OTA Base Station output power	111
5.3.17.1	General	111
5.3.17.2	Initial conditions	111
5.3.17.3	Procedure	111
5.3.17.4	Test Requirement	112
5.3.18	OTA transmitter intermodulation	112
5.3.18.1	General	112
5.3.18.2	Initial conditions	112
5.3.18.3	Procedure	112
5.3.18.4	Test Requirement	113
5.3.19	OTA receiver spurious emissions	113
5.3.19.1	General	113
5.3.19.2	Initial conditions	114
5.3.19.3	Procedure	114
5.3.19.4	Test Requirement	115
5.3.20	OTA In-band blocking	115
5.3.20.1	General	115
5.3.20.2	Initial conditions	115
5.3.20.3	Procedure	116
5.3.20.4	Test Requirement	116
5.3.21	OTA Out-of-band blocking	116
5.3.21.1	General	116
5.3.21.2	Initial conditions	116
5.3.21.3	Procedure	117
5.3.21.3.1	<i>BS type 1-O</i> procedure for out-of-band blocking	117
5.3.21.3.2	<i>BS type 2-O</i> procedure for out-of-band blocking	117
5.3.21.4	Test Requirement	118
5.3.22	OTA receiver intermodulation	118
5.3.22.1	General	118
5.3.22.2	Initial conditions	118
5.3.22.3	Procedure	119
5.3.22.4	Test Requirement	119
5.3.23	OTA Adjacent Channel Selectivity (ACS)	119
5.3.23.1	General	119
5.3.23.2	Initial conditions	119
5.3.23.3	Procedure	120
5.3.23.4	Test Requirement	120
5.3.24	OTA sensitivity	120
5.3.24.1	General	120
5.3.24.2	Initial conditions	120
5.3.24.3	Procedure	121
5.3.24.4	Test Requirement	121
5.3.25	OTA Reference sensitivity	121

5.3.25.1	General	121
5.3.25.2	Initial conditions	121
5.3.25.3	Procedure	122
5.3.25.4	Test Requirement	122
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	123
Annex B (informative):	Maximum Measurement Uncertainty.....	125
Annex C (normative):	BS configurations for conducted testing	129
C.1	<i>BS type I-C</i>	129
C.1.1	Transmit configurations	129
C.1.1.1	General.....	129
C.1.1.2	Transmission with multiple transmitter antenna connectors.....	129
C.1.2	Receive configurations	129
C.1.2.1	General.....	129
C.1.2.2	Reception with multiple receiver antenna connectors, receiver diversity.....	130
C.1.3	Duplexers	130
C.1.4	Power supply options	131
C.1.5	Ancillary RF amplifiers.....	131
C.2	<i>BS type I-H</i>	131
C.2.1	Transmit configurations	131
C.2.2	Receive configurations	132
C.2.3	Power supply options	132
C.3	BS with integrated Iuant BS modem.....	133
Annex D (normative):	BS configurations for OTA testing.....	134
D.1	Transmit configurations	134
D.2	Receive configurations.....	135
D.3	Power supply options	136
D.4	BS with integrated Iuant BS modem.....	136
Annex E (informative):	Checklist	137
Annex F (informative):	Bibliography.....	138
Annex G (informative):	Change History	139
History		140

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

For non EU countries the present document may be used for regulatory (Type Approval) purposes.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.1] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A-1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 24 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.6].

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part of a set of standards developed by ETSI that are designed to fit in a modular structure to cover radio equipment within the scope of the Radio Equipment Directive [i.2]. The present document is produced following the guidance in ETSI EG 203 336 [i.3] as applicable.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN 301 908-24 V15.0.0:2023](#)

<https://standards.iteh.ai/catalog/standards/sist/633a4b88-c52b-4c54-bd29-2ae17e8aa7d1/osist-pren-301-908-24-v15-0-0-2023>

1 Scope

The present document specifies technical characteristics and methods of measurements for types of radio equipment:

- Base Stations for New Radio (NR).

These radio equipment types are capable of operating in whole or any part of the *operating band(s)* given in tables 1-2 and 1-3. FR1 and FR2 frequency ranges are defined as in table 1-1.

Table 1-1: Frequency ranges

Frequency range designation	Frequency range
FR1	410 MHz to 7 125 MHz
FR2	24 250 MHz to 52 600 MHz

Table 1-2: NR Base Station operating bands in FR1

NR band	Direction of transmission	NR operating bands	Related EC/ECC decision
n1	Transmit	2 110 MHz to 2 170 MHz	[i.19] and [i.20]
	Receive	1 920 MHz to 1 980 MHz	
n3	Transmit	1 805 MHz to 1 880 MHz	[i.17] and [i.18]
	Receive	1 710 MHz to 1 785 MHz	
n7	Transmit	2 620 MHz to 2 690 MHz	[i.21] and [i.13]
	Receive	2 500 MHz to 2 570 MHz	
n8	Transmit	925 MHz to 960 MHz	[i.17] and [i.18]
	Receive	880 MHz to 915 MHz	
n20	Transmit	791 MHz to 821 MHz	[i.12] and [i.13]
	Receive	832 MHz to 862 MHz	
n28 (note 1)	Transmit	758 MHz to 803 MHz	[i.10] and [i.11]
	Receive	703 MHz to 748 MHz	
n38	Transmit	2 570 MHz to 2 620 MHz	[i.22] and [i.23]
	Receive	2 570 MHz to 2 620 MHz	
n40	Transmit	2 300 MHz to 2 400 MHz	[i.21]
	Receive	2 300 MHz to 2 400 MHz	
n41 (note 2)	Transmit	2 496 MHz to 2 690 MHz	[i.22] and [i.23]
	Receive	2 496 MHz to 2 690 MHz	
n50 (note 3)	Transmit	1 432 MHz to 1 517 MHz	[i.14] and [i.15] and [i.16]
	Receive	1 432 MHz to 1 517 MHz	
n51 (note 3, note 6)	Transmit	1 427 MHz to 1 432 MHz	[i.14] and [i.15]
	Receive	1 427 MHz to 1 432 MHz	
n65 (note 7)	Transmit	2 110 MHz to 2 200 MHz	[i.19], [i.20] and [i.27]
	Receive	1 920 MHz to 2 010 MHz	
n75 (note 3)	Transmit	1 432 MHz to 1 517 MHz	[i.14], [i.15] and [i.16]
	Receive	N/A	
n76 (notes 3 and 6)	Transmit	1 427 MHz to 1 432 MHz	[i.14] and [i.15]
	Receive	N/A	
n77 (note 4)	Transmit	3 300 MHz to 4 200 MHz	[i.8] and [i.24]
	Receive	3 300 MHz to 4 200 MHz	
n78 (note 5)	Transmit	3 300 MHz to 3 800 MHz	[i.8] and [i.24]
	Receive	3 300 MHz to 3 800 MHz	
n80	Transmit	N/A	[i.17] and [i.18]
	Receive	1 710 MHz to 1 785 MHz	
n81	Transmit	N/A	[i.17] and [i.18]
	Receive	880 MHz to 915 MHz	
n82	Transmit	N/A	[i.12] and [i.13]
	Receive	832 MHz to 862 MHz	
n83	Transmit	N/A	[i.10] and [i.11]
	Receive	703 MHz to 748 MHz	

NR band	Direction of transmission	NR operating bands	Related EC/ECC decision
n84	Transmit	N/A	
	Receive	1 920 MHz to 1 980 MHz	[i.19] and [i.20]
NOTE 1: In Europe, according to [i.12] and [i.13], radio equipment in band 28 operates between 758 MHz and 791 MHz for the transmitter ($F_{DL_low} = 758$ MHz and $F_{DL_high} = 791$ MHz) and between 703 MHz and 736 MHz for the receiver ($F_{UL_low} = 703$ MHz and $F_{UL_high} = 736$ MHz).			
NOTE 2: In Europe according to [i.22] and [i.23], radio equipment in band 41 operates between 2 570 MHz and 2 620 MHz ($F_{DL_low} = 2 570$ MHz and $F_{DL_high} = 2 620$ MHz).			
NOTE 3: Radio equipment in bands n50 and n51 only operates in transmit mode (downlink only). Only transmitter requirements are applicable.			
NOTE 4: In Europe, according to [i.24] and [i.8], radio equipment in band n77 operates between 3 400 MHz and 3 800 MHz ($F_{DL_low} = 3 400$ MHz and $F_{DL_high} = 3 800$ MHz).			
NOTE 5: In Europe, according to [i.24] and [i.8], radio equipment in band n78 operates between 3 400 MHz and 3 800 MHz ($F_{DL_low} = 3 400$ MHz and $F_{DL_high} = 3 800$ MHz).			
NOTE 6: Only requirements for Local Area <i>BS class</i> are defined.			
NOTE 7: This band includes two frequency ranges that are harmonised in Europe:			
(a) According to [i.19] and [i.20], radio equipment in band n65 operates between 2 110 MHz and 2 170 MHz for the transmitter ($F_{DL_low} = 2 110$ MHz and $F_{DL_high} = 2 170$ MHz), and between 1 920 MHz and 1 980 MHz for the receiver ($F_{UL_low} = 1 920$ MHz and $F_{UL_high} = 1 980$ MHz).			
(b) Based on [i.27], radio equipment in band n65 operates between 2 170 MHz and 2 200 MHz for the transmitter ($F_{DL_low} = 2 170$ MHz and $F_{DL_high} = 2 200$ MHz) and between 1 980 MHz and 2 010 MHz for the receiver ($F_{UL_low} = 1 980$ MHz and $F_{UL_high} = 2 010$ MHz) as the Complementary Ground Component (CGC) of a Mobile-satellite service by reference to the present Harmonised Standard.			

Table 1-3: NR Base Station operating bands in FR2

NR band	Direction of transmission	NR Base Station operating bands	Relevant EC/ECC decision
n257 (note)	Transmit	26 500 MHz to 29 500 MHz	[i.25] and [i.26]
	Receive	26 500 MHz to 29 500 MHz	
n258	Transmit	24 250 MHz to 27 500 MHz	[i.25] and [i.26]
	Receive	24 250 MHz to 27 500 MHz	
NOTE: In Europe according to [i.25] and [i.26], radio equipment in band n257 operates between 26 500 MHz and 27 500 MHz ($F_{UL_low} = 26 500$ MHz and $F_{UL_high} = 27 500$ MHz).			

The present document covers conducted and radiated requirements for NR Base Stations for 3GPP Release 15. Additionally, it includes requirements for selected NR *operating bands* from 3GPP Release 16.

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.1] is given annex A.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 138 141-1 (V15.12.0) (04-2022): "5G; NR; Base Station (BS) conformance testing Part 1: Conducted conformance testing (3GPP TS 38.141-1 version 15.12.0 Release 15)".

- [2] ETSI TS 138 141-2 (V15.14.0) (06-2022): "5G; NR; Base Station (BS) conformance testing Part 2: Radiated conformance testing (3GPP TS 38.141-2 version 15.14.0 Release 15)".
- [3] ETSI TS 138 104 (V15.17.0) (06-2022): "5G; NR; Base Station (BS) radio transmission and reception (3GPP TS 38.104 version 15.17.0 Release 15)".
- [4] ETSI EN 301 908-18 (V15.1.1) (09-2021): "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 18: E-UTRA, UTRA and GSM/EDGE Multi-Standard Radio (MSR) Base Station (BS) Release 15".
- [5] ETSI EN 301 908-23 (V15.1.0) (12-2022): "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 23: Active Antenna System (AAS) Base Station (BS); Release 15".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Commission implementing decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.2] Directive 2014/53/EU of the European parliament and of the council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] ETSI EG 203 336 (V1.2.1) (05-2020): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.4] Recommendation ITU-R SM.329-12 (09-2012): "Unwanted emissions in the spurious domain".
- [i.5] ETSI TR 100 028 (parts 1 and 2) (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.6] ETSI EN 301 908-1 (V15.1.1) (04-2022): "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 1: Introduction and common requirements Release 15".
- [i.7] Recommendation ERC 74-01 (05-2019): "Unwanted emissions in the spurious domain".
- [i.8] Commission implementing Decision (EU) 2019/235 of 24 January 2019 on amending Decision 2008/411/EC as regards an update of relevant technical conditions applicable to the 3 400-3 800 MHz frequency band.
- [i.9] ETSI TS 103 807 (V1.1.1) (06-2021): "Mobile Standards Group (MSG); IMT Cellular Networks Base Stations (BS) Additional Regulatory Requirements".
- [i.10] Commission Implementing Decision (EU) 2016/687 of 28 April 2016 on the harmonisation of the 694-790 MHz frequency band for terrestrial systems capable of providing wireless broadband electronic communications services and for flexible national use in the Union.
- [i.11] ECC Decision (15)01: "Harmonised technical conditions for mobile/fixed communications networks (MFCN) in the band 694-790 MHz including a paired frequency arrangement (Frequency Division Duplex 2x30 MHz) and an optional unpaired frequency arrangement (Supplemental Downlink)", Approved 06 March 2015.