



Designation: D 5136 – 07

Standard Specification for High Purity *p*-Xylene¹

This standard is issued under the fixed designation D 5136; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This specification covers high purity *p*-Xylene.

1.2 The following applies to all specified limits in this specification: for purposes of determining conformance with this specification, an observed value or a calculated value shall be rounded off “to the nearest unit” in the last right-hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E 29.

1.3

1.4 Consult current OSHA regulations, supplier’s Material Safety Data Sheets, and local regulations for all materials used in this specification.

2. Referenced Documents

2.1 *ASTM Standards*:²

D 850 Test Method for Distillation of Industrial Aromatic Hydrocarbons and Related Materials

D 1209 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)

D 3437 Practice for Sampling and Handling Liquid Cyclic Products

D 3798 Test Method for Analysis of *p*-Xylene by Gas Chromatography

D 5386 Test Method for Color of Liquids Using Tristimulus Colorimetry

D 5917 Test Method for Trace Impurities in Monocyclic Aromatic Hydrocarbons by Gas Chromatography and External Calibration

D 7183 Test Method for Determination of Total Sulfur in Aromatic Hydrocarbons and Related Chemicals by Ultra-violet Fluorescence

E 29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications

2.2 *Other Document*:

OSHA Regulations, 29 CFR paragraphs 1910.1000 and 1910.1200³

3. Properties

3.1 High purity *p*-Xylene shall conform to the following requirements:

Property	Specification	ASTM Test Method ⁴
Purity, ^B min, weight %	99.7	D 3798 or D 5917
<i>m</i> -Xylene, max, weight %	0.20	D 3798 or D 5917
<i>o</i> -Xylene, max, weight %	0.10	D 3798 or D 5917
Sulfur, max, mg/kg	1.0	D 7183
Toluene, max, weight %	0.10	D 3798 or D 5917
Ethylbenzene, max, weight %	0.20	D 3798 or D 5917
Nonaromatic hydrocarbons, max, weight %	0.20	D 3798 or D 5917
Appearance		...
Color, max, Pt/Co scale	10	D 1209 or D 5386
Distillation range, including the temperature 138.3°C at 101.3 kPa (760 mm Hg) pressure, max, °C	1.0	D 850

^A If more than one method is listed, the producer and user should agree on the referee method.

^B Purity, molar %, minimum, will be specified when the freeze point procedure under development is completed.

^C Clear liquid free of sediment and haze when observed at 18.3 to 25.6°C (65 to 78°F).

4. Sampling

4.1 The material shall be sampled in accordance with Practice D 3437.

5. Keywords

5.1 *p*-Xylene

³ Available from U.S. Government Printing Office Superintendent of Documents, 732 N. Capitol St., NW, Mail Stop: SDE, Washington, DC 20401, <http://www.access.gpo.gov>.

¹ This specification is under the jurisdiction of ASTM Committee D16 on Aromatic Hydrocarbons and Related Chemicals and is the direct responsibility of Subcommittee D16.01 on Benzene, Toluene, Xylenes, Cyclohexane and Their Derivatives

Current edition approved June 1, 2007. Published July 2007. Originally approved in 1990. Last previous edition approved in 2006 as D 5136 – 06.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard’s Document Summary page on the ASTM website.

*A Summary of Changes section appears at the end of this standard.