

ETSI TS 103 625 V1.1.1 (2019-12)



Emergency Communications (EMTEL); Transporting Handset Location to PSAPs for Emergency Calls - Advanced Mobile Location

STANDARD PREVIEW
(standards.iteh.ai)
Full standard available at: <https://standards.iteh.ai/catalog/standards/sist/103-625-2019-12>
475-9503-85d21636786c/etsi-ts-103-625-v1-1-2019-12

Reference

DTS/EMTEL-00044

Keywords

emergency, handset, location, mobile, transport

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
Introduction	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	6
3 Definition of terms, symbols and abbreviations.....	7
3.1 Terms.....	7
3.2 Symbols.....	7
3.3 Abbreviations	7
4 Overview	8
5 Handset Functionality.....	8
5.1 Positioning methods and time needed to precisely locate	8
5.2 Triggered by emergency call without impacting voice	8
5.3 Availability of MSISDN	9
5.4 Data connectivity.....	9
5.5 Battery life.....	9
6 Location data and data transport	9
6.1 Location data provision by the handset.....	9
6.1.1 Data provided.....	9
6.2 SMS transport.....	10
6.2.1 SMS transport overview	10
6.2.2 SMS Formats	12
6.2.3 Security of SMS transport.....	13
6.2.4 Limitations	13
6.2.4.1 Roaming.....	13
6.2.4.2 Limited Service State/National Roaming.....	14
6.3 HTTPS.....	14
6.3.1 Overview of using HTTPS	14
6.3.2 General Format	14
6.3.3 Security considerations	14
6.3.4 Header.....	14
6.3.5 Body.....	15
6.3.6 Detailed Format	15
6.3.6.1 Header	15
6.3.6.2 Body	15
6.3.7 Receipt of HTTPS Message by PSAP	15
6.3.7.1 Overview of message receipt	15
6.3.7.2 Example Message Sequence	16
6.3.7.3 Example Message Content	16
6.3.7.4 Response Values	16
6.3.8 Limitations	17
6.3.8.1 Availability of MSISDN	17
6.3.8.2 Data connectivity	17
6.4 SIP (network, terminal and PSAP support).....	17
6.5 Next Generation 112	17
7 Mobile Network capabilities	18
7.1 Simultaneous SMS/HTTPS and emergency voice	18
8 Operational Guidance.....	18

8.1	PSAP reception of location (location endpoint)	18
Annex A (normative):	SMS Format	19
Annex B (normative):	HTTPS message format.....	24
B.1	HTTPS fields.....	24
Annex C (informative):	Management of location best practice by PSAPs.....	26
History	27

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/cae069d2-5951-4f75-9503-85d21636786c/etsi-ts-103-625-v1.1.1-2019-12>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI Special Committee Emergency Communications (EMTEL).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

One of the biggest challenges facing the Emergency Services is determining the location of mobile callers. Cell based location has been available to the Emergency Services since 2003. While cell data can help with verbal establishment of a caller's location, a more precise location will allow an even quicker emergency response.

Advanced Mobile Location (AML) allows use of native smart phone technology to pass (Assisted) GNSS or Wi-Fi based location data to Emergency Service PSAPs. These technologies can provide a location precision as good as 5 m outdoors (and averaging to within circular areas of ~25 m radius for indoor locations), a significant improvement on existing cell coverage provided by mobile networks, which average (across the UK as an example) circular areas of about 1,75 km radius.

The present document builds on the Advanced Mobile Location initiative described in ETSI TR 103 393 [i.1] now being used in an increasing number of countries to improve the precision and accuracy of a caller's location information for emergency calls from mobile handsets.

1 Scope

The present document describes the transport methods used for AML messages with handset derived location information and associated data, the content of the AML messages, and allows for the data sent within the message to include further attributes than supported in current deployments.

It also considers the future evolution of transport methods as PSAPs, networks and terminals become increasingly IP based.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 123 040: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); Technical realization of the Short Message Service (SMS) (3GPP TS 23.040)".
- [2] ETSI ES 203 283: "Protocol specifications for Emergency Service Caller Location determination and transport".
- [3] IETF RFC 6442: "Location Conveyance for the Session Initiation Protocol".
- [4] IETF RFC 5491: "GEOPRIV Presence Information Data Format Location Object (PIDF-LO) Usage Clarification, Considerations, and Recommendations".
- [5] ETSI TS 103 479: "Emergency Communications (EMTEL); Core elements for network independent access to emergency services".
- [6] ETSI TS 123 038: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; Alphabets and language-specific information (3GPP TS 23.038)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 103 393 (V1.1.1): "Emergency Communications (EMTEL); Advanced Mobile Location for emergency calls".

3 Definition of terms, symbols and abbreviations

3.1 Terms

Void.

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

3GPP	3G (mobile) Partnership Project
AGNSS	Assisted Global Navigation Satellite System
AML	Advanced Mobile Location
ASCII	American Standard Code for Information Interchange
DCS	Data Coding Scheme
GNSS	Global Navigation Satellite System
GSM	Global System for Mobile
HTTP	HyperText Transfer Protocol
HTTPS	HyperText Transfer Protocol Secure
ICCID	Integrated Circuit Card Identifier
IEI	Information Element Identifier
IMEI	International Mobile Equipment Identity
IMSI	International Mobile Subscriber Identity
IP	Internet Protocol
ISDN	Integrated Services Digital Network
LOC	Level Of Confidence
LS	Location Server
MCC	Mobile Country Code
MNC	Mobile Network Code
MNO	Mobile Network Operator
MSISDN	Mobile Station International Subscriber Directory Number
NG	Next Generation
NTP	Network Time Protocol
OS	Operative System
PDU	Packet Data Unit
PSAP	Public Safety Answering Point
RFC	Request For Comments
SIM	Subscriber Identity Module
SIP	Session Initiation Protocol
SMPP	Short Message Peer to Peer
SMS	Short Message Service
SMSC	Short Message Service Centre
UCS	Universal Character Set
UTC	Universal Time Coordinated
WGS	World Geodetic System

4 Overview

AML functionality is triggered by an emergency call (which is progressed normally by the handset and the network), and is designed to supplement the basic network location provided wherever possible, i.e. with some acknowledgement of limitations in GNSS or Wi-Fi availability for the handset and the time required to acquire location using GNSS.

Location information established by the handset, using its built-in GNSS and Wi-Fi connectivity, together with user plane assistance data from a handset-selected service where available, is transported (e.g. through use of SMS) to the Emergency Service PSAPs. Handsets can use more than one location technology to establish a location, for example the handset may combine location information from Cell and Wi-Fi sources to obtain the best possible, "hybridised", result.

It is important that AML doesn't interfere with the voice call so both the handset and mobile network shall be configured to be able to simultaneously support a standard 3GPP mobile emergency voice call, location determination using GNSS/Wi-Fi capabilities and SMS and/or HTTPS transmission of the location information over the 3GPP mobile network.

5 Handset Functionality

5.1 Positioning methods and time needed to precisely locate

GNSS, or Assisted GNSS, normally offers the best location information but is slower than other methods. At the other end of the spectrum cell based location is quick but typically returns a larger location area. The general rule is that PSAPs need the best data as long as it doesn't take too long to determine, so a 'send us what you have now' timeout [T1] is used.

T1 is the maximum time between the emergency call being initiated and the location message being sent. T1 should be configurable with a T1 value selected in consultation with the provider of the AML functionality on the handset to give best balance between quicker availability to PSAPs and the even higher precision that may become available with a longer T1.

As soon as the emergency call is initiated the handset shall immediately attempt to determine the best possible current location within the period set by the T1 timeout.

This should allow all location capabilities that the handset provides to be used, respecting the end user's preferences by enabling any capability not normally available only to assist for AML functions on an emergency call, and subject to a battery check.

If it is not been possible to get a location from any method then a message shall be sent indicating that all positioning methods have failed.

5.2 Triggered by emergency call without impacting voice

The AML software shall be integrated into all existing emergency call mechanisms available on the handset including manual dial of 112 (or any other national emergency number specified for the mobile network and country being used), and use of the Emergency Call button (as appropriate).

In an emergency callers are often stressed or panicking so it is important that the AML functionality and transmission of the AML message shall be automatically triggered without any manual intervention by the user. The handset software shall be invisible to the users so as not to cause confusion when they are trying to get help, and so as not to attract attention from those who intend to abuse the facility. No record of the AML message shall be available to the user either during or after the emergency call.

If an emergency SMS service, typically for deaf or hard of hearing users is provided in a country, then AML should also be triggered by an emergency SMS message being sent.

5.3 Availability of MSISDN

PSAPs need to be able to match the voice call with the AML data, and to do so they use the MSISDN (Mobile Subscriber ISDN). The MSISDN is included within an SMS message so this is straightforward if SMS is used for AML transport. In some instances, the MSISDN can be accessed by the handset's AML functionality and, if AML is using HTTPS to transport the location data, it shall therefore be included when possible in the HTTPS data string (see clause B.1).

5.4 Data connectivity

The mobile handset requires data connectivity to allow communication with servers operated by the providers of the phone's operating system that:

- a) provide assistance information to allow quick establishment of a GNSS position (AGNSS); and
- b) provide access to primarily crowd sourced databases for location information related to Wi-Fi access points.

In addition such a data connection may support one of the transport mechanisms for AML using an HTTPS message (see clause 6.3).

This data connectivity can be through the mobile network or Wi-Fi access points.

Without such a data connection AML messages are still possible using a GNSS location (without assistance) and SMS transport (see clause 6.1).

5.5 Battery life

Before invoking the AML functionality, the handset should check there is sufficient battery life so that the caller can still make a short 5 minute voice call. The priority in the emergency situation is to allow voice connection to the PSAP.

6 Location data and data transport

6.1 Location data provision by the handset

6.1.1 Data provided

AML is required to communicate a location in the form of a circle.

The location and size of the circle determined by the handset shall be communicated using the attributes of a WGS 84 latitude and longitude measured in decimal degrees for the centre of the circle, and a radius measurement for the location circle in metres. A precision of 5 decimal degrees should be provided which will equate to 1,1 m precision on the ground.

The following attributes are those that are normative for implementation using transport methods described in clauses 6.2 and 6.3:

- The Time of Positioning (TOP): The accuracy of this date and time is important as it will be used to filter out any messages that appear to be too old or have a time in the future. In the first instance the handset should attempt to use the time established by an NTP server, this should be possible if a network connection is available. If NTP is not available then GNSS can be used to give time. Only if these two methods fail then, as a last resort, the handset time and date can be used.
- The Level of Confidence is a percentage probability that the mobile handset is within the area being communicated, for example a 95 % value tells the Emergency Services that there is a 5 % probability that the caller is not within the location area specified by the latitude, longitude and radius values. It is recognized that methods for determining mobile handset location have limitations. For example, the impact of buildings, topography and weather conditions introduce a margin of error into location calculations, and different methods will have different error factors that need to be communicated to the Emergency Services.

- The predominant positioning method used to determine the location area is indicated as one of the following:
 - GNSS or AGNSS;
 - Wi-Fi signals;
 - Cell;
 - Hybridised results shall be used and should be classified according to predominant location method.

It shall also be indicated if it has not been possible to determine the location - see annexes A and B.

- The SIM card identifier of the handset that has made the emergency call (IMSI) and the identifier of the handset that made the emergency call (IMEI).
- Mobile Country Code of the network, used to confirm/determine the country in which the emergency call was made.
- Mobile Network Code, to confirm/determine the mobile network used to make the emergency call.

NOTE 1: The MCC and MNC of the network will normally be the same as the MCC and MNC within the IMSI. Differences between them indicate if the handset is roaming.

A header attribute shall be used to differentiate AML messages from other emergency SMS messages and to also indicate a version number for the interface. For SMS transport, a Message Length attribute shall also be used - see annex A.

In future, when it becomes technically feasible and reliable, and if the transport method has sufficient space available, the following optional information should be passed and the inclusion of additional data indicated by use of a different interface version number:

- Altitude (in metres above the WGS 84 ellipsoid).

NOTE 2: The WGS 84 ellipsoid is a reasonable approximation for the shape of the earth. Altitude above the WGS 84 ellipsoid can differ from the actual altitude above mean sea level.

- Altitude Variance: Indicates the vertical variance, plus or minus, from given altitude.
- Floor number.
- Emergency number used to make the call, including whether voice or SMS activation (to assist PSAPs matching with calls).
- Source to indicate which version of the handset's AML functionality is being used. This is helpful in diagnosing any issues.

The presence of most of these optional information elements is already included for HTTPS - see annex B.

6.2 SMS transport

6.2.1 SMS transport overview

When a PSAP selects SMS transport (see clause 8), the standard mobile network SMS service shall be used to send the AML message from the phone to the SMSC (SMS Centre) within each mobile network (using normal 3GPP network standards).

The Short Message Peer-to-Peer (SMPP) open industry standard protocol for transfer of short message data outside mobile networks should then be used to transport the data from the SMSC to the SMS Aggregator (organization that aggregates SMS messages from various mobile networks).