



SLOVENSKI STANDARD

SIST TBR 006 E3:2004

01-oktober-2004

8][JHUbY]nVc`ÝUbYVfYnj f j] bYHYY_ca i b]_UWYYfB 97 HÉ!`Gd`cýbYnU HÝj YnU
df]_`1 Yj UbYHfa]bUcj

Digital Enhanced Cordless Telecommunications (DECT); General terminal attachment requirements

iTeh STANDARD PREVIEW (standards.iteh.ai)

Ta slovenski standard je istoveten z: [SIST TBR 006 E3:2004](#)
<https://standards.iteh.ai/catalog/standards/sist/d/344da9-4139-4c19-be5e-c64b069ec80d/sist-tbr-006-e3-2004>

ICS:

33.070.30 Öð ãæ^ Á à[|bæ^
à|^: c{çã } ^Á|^\{ { ` } à æ^ Digital Enhanced Cordless
ØðÓVD Telecommunications (DECT)


SIST TBR 006 E3:2004

en

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST TBR 006 E3:2004](#)

<https://standards.iteh.ai/catalog/standards/sist/d7344da9-4139-4c19-be5e-c64b069ec80d/sist-tbr-006-e3-2004>



TECHNICAL BASIS for REGULATION

TBR 6

June 1999

Third Edition

Source: DECT

Reference: RTBR/DECT-000117

ICS: 33.020

Key words: DECT, testing, terminal, radio

iTeh STANDARD PREVIEW (standards.iteh.ai) Digital Enhanced Cordless Telecommunications (DECT); General terminal attachment requirements

<https://standards.iteh.ai/catalog/standards/sist/d7344da9-4139-4c19-be5e-c64b069ec80d/sist-tbr-006-e3-2004>

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

Internet: secretariat@etsi.fr - <http://www.etsi.org>

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1999. All rights reserved.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST TBR 006 E3:2004](#)

<https://standards.iteh.ai/catalog/standards/sist/d7344da9-4139-4c19-be5e-c64b069ec80d/sist-tbr-006-e3-2004>

Contents

Foreword	11
1 Scope	13
2 Normative references	13
3 Definitions and abbreviations	14
3.1 Definitions	14
3.2 Abbreviations	17
4 General	17
4.1 Document layout	17
4.1.1 Test suites	18
4.1.2 Test groups	18
4.1.3 Test cases	19
4.2 Presentation of equipment for testing purposes	19
4.2.1 Choice of model for type examination	19
4.2.2 Description of equipment	19
4.2.2.1 Protocol Implementation Conformance Statement (PICS)	19
4.2.2.2 Protocol Implementation Extra Information for Testing (PIXIT)	20
4.2.2.3 Environmental test conditions	20
4.2.3 Host connected equipment	20
4.2.4 Applicant's declaration	20
4.3 Applicability of type tests	20
4.3.1 Equipment that includes only a DECT RF receiver	20
4.3.2 Equipment that includes a radio transmitter	20
4.3.3 Void	21
4.3.4 Equipment with a synchronization port	21
4.3.5 Equipment incorporating the IPEI (PPs only)	21
4.3.6 All FP equipment	21
4.3.7 PPs with direct PP to PP communication option	21
4.3.8 Installation related issues	21
4.3.9 Wireless relay stations	21
4.3.10 Provision of 2 Mbit/s services. Equipment that is capable of using 4-level and/or 8-level modulation	22
4.3.10.1 Activation of higher level modulations when EUT is in test stand-by mode	22
4.3.11 Equipment supporting additional carriers	23
4.4 Interpretation of the measurement results	23
5 General test requirements	23
5.1 Test philosophy	23
5.2 Test site	24
5.2.1 Open air test site	24
5.2.1.1 Description	24
5.2.1.2 Calibration	25
5.2.2 Anechoic chamber	26
5.2.2.1 General	26
5.2.2.2 Description	26
5.2.2.3 Influence of parasitic reflections	28
5.2.2.4 Calibration and mode of use	28
5.2.3 stripline coupler	28
5.2.3.1 Description	28
5.2.3.2 Calibration	28
5.2.3.3 Mode of use	28
5.3 Standard position	29
5.4 Test antenna of the LT	29

5.5	Substitution antenna	29
5.6	Test fixture	29
5.6.1	Description	29
5.6.1.1	Calibration of the test fixture for the measurement of transmitter characteristics.....	30
5.6.1.2	Calibration of the test fixture for the measurement of receiver characteristics	30
5.6.1.3	Mode of use	31
5.6.2	Equipment with a temporary or internal permanent antenna connector	31
5.6.2.1	Equipment with a temporary antenna connector	31
5.7	Indoor test site	31
5.7.1	Description	32
5.7.2	Test for parasitic reflections	32
5.7.3	Calibration and mode of use	33
5.8	Lower Tester (LT)	33
5.8.1	Description	33
5.8.2	Connections between the EUT and the LT	33
5.8.3	Functions and abilities	34
5.8.4	Signal generation uncertainty	34
5.8.4.1	Modulated DECT-like carrier	34
5.8.4.2	CW interferers	34
5.8.4.3	DECT RF signal.....	34
5.8.4.4	Test modulation signals.....	34
5.8.5	Measurement uncertainty.....	35
5.9	Upper Tester (UT).....	35
5.9.1	Description of the UT.....	35
5.9.2	The test standby mode	35
5.9.3	Test messages.....	36
5.9.4	Dummy setting when EUT is a RFP and it is in test stand-by mode.....	36
5.10	Description of the lower tester FT and PT	36
5.11	General test methods	36
5.11.1	General.....	36
5.11.2	Sampling the RF signal.....	37
5.11.2.1	<small>SIST TBR 006 E3:2004 https://standards.iteh.ai/catalog/standards/sistd7344da9-4139-4c19-be5e-c64b069c80f/sist-tbr-006-e3-2004</small>	37
5.11.2.2	Sampling method.....	37
5.11.3	Determining the reference position	37
5.11.3.1	Case 1: EUTs that cannot transmit.....	37
5.11.3.2	Case 2: EUTs that can transmit.....	37
5.11.4	Bit error rate (BER) and Frame Error Ratio (FER) measurements	37
5.12	Test setup	38
5.12.1	Test setup 1.....	38
5.12.2	Test setup 2.....	38
5.12.3	Test setup 3.....	39
5.12.4	Test setup 4.....	39
5.12.5	Test setup 5.....	40
5.13	Test arrangements for intermodulation measurements.....	40
5.13.1	PT to PT arrangement.....	40
5.13.2	FT to FT arrangement.....	41
5.13.3	FT to PT arrangement.....	41
6	Test conditions, power sources and ambient temperatures	42
6.1	General	42
6.2	Nominal test conditions.....	42
6.3	Extreme test conditions	43
6.4	Test power source - general requirements	44
6.5	Nominal test power source	44
6.5.1	Mains voltage	44
6.5.2	Regulated lead acid battery power sources	44
6.5.3	Nickel cadmium battery	44
6.5.4	Other power sources	44
6.6	Extreme test power source	44
6.6.1	Mains voltage	44
6.6.2	Regulated lead acid battery power sources	45

6.6.3	Nickel cadmium battery.....	45
6.6.4	Other power sources.....	45
6.7	Testing of host connected equipment and plug-in cards.....	45
6.7.1	Alternative A: composite equipment	45
6.7.2	Alternative B: use of a test jig and three hosts.....	45
7	Accuracy and stability of RF carriers	46
7.1	Definition.....	46
7.2	Test environment.....	46
7.3	Method of measurement	46
7.4	Verdict criteria when the EUT is a RFP	47
7.5	Verdict criteria when the EUT is a PP	47
8	Accuracy and stability of timing parameters	47
8.1	Slot structure definitions	47
8.2	Definition of the position of p0	48
8.3	Measurement of packet timing jitter	48
8.3.1	Test environment	48
8.3.2	Method of measurement.....	49
8.3.3	Verdict criteria	49
8.4	Measurement of the reference timing accuracy of a RFP	49
8.4.1	Test environment	49
8.4.2	Method of measurement.....	49
8.4.3	Verdict criteria	49
8.5	Measurement of packet transmission accuracy of a PP	50
8.5.1	Test environment	50
8.5.2	Method of measurement.....	50
8.5.3	Verdict criteria.....	51
iTeh STANDARD PREVIEW		
9	Transmission burst	51
9.1	Definitions.....	51
9.1.1	Physical packets	51
9.1.2	Transmitted power.....	51
9.1.3	Normal Transmitted Power (NTP).....	51
9.1.4	Transmitter attack time	51
9.1.5	Transmitter release time	51
9.1.6	Minimum power.....	51
9.1.7	Maximum power.....	51
9.1.8	Maintenance of transmission after packet end	51
9.1.9	Transmitter idle power output	52
9.2	Test environment.....	52
9.3	Method of measurement	52
9.4	Verdict criteria.....	52
10	Transmitted power	53
10.1	Definitions.....	53
10.1.1	PP and RFP with an integral antenna	53
10.1.2	PP and RFP with external connections for all antennas	53
10.1.3	PP and RFP with both integral and external antennas	53
10.2	PP and RFP with an integral antenna	53
10.2.1	Test environment	53
10.2.2	Method of measurement.....	54
10.2.2.1	Measurement of NTP	54
10.2.2.2	Measurement of antenna gain	54
10.2.3	Verdict criteria for all EUTs	54
10.3	PP and RFP with external antenna connection(s).....	54
10.3.1	Test environment	54
10.3.2	Method of measurement.....	55
10.3.3	Verdict criteria for all EUTs	55
11	RF carrier modulation	55
11.1	Test environment.....	55
11.2	Method of measurement, Parts 1 and 2	55

11.2.1	Part 1	56
11.2.2	Part 2	56
11.3	Method of measurement, Parts 3 and 4	56
11.3.1	Part 3	56
11.3.2	Part 4	57
11.4	Verdict criteria for Part 1	57
11.5	Verdict criteria for Part 2	57
11.6	Verdict criteria for Part 3	57
11.7	Verdict criteria for Part 4	57
12	Unwanted RF power radiation	58
12.1	General test conditions	58
12.2	Emissions due to modulation	58
12.2.1	Definition	59
12.2.2	Test environment	59
12.2.3	Method of measurement	59
12.2.4	Verdict criteria	59
12.3	Emissions due to transmitter transients	60
12.3.1	Definition	60
12.3.2	Test environment	60
12.3.3	Method of measurement	60
12.3.4	Verdict criteria	61
12.4	Emissions due to intermodulation	61
12.4.1	Definition	61
12.4.2	Test environment	61
12.4.3	Method of measurement	61
12.4.4	Verdict criteria	62
12.5	Spurious emissions when allocated a transmit channel	62
12.5.1	Definition	62
12.5.2	Radiated emissions	62
12.5.2.1	Test environment	62
12.5.2.2	Method of measurement	63
12.5.2.3	Verdict criteria	63
12.5.3	Conducted spurious emissions	64
12.5.3.1	Test environment	64
12.5.3.2	Method of measurement	64
	Verdict criteria	64
13	Radio receiver testing	65
13.1	Radio receiver sensitivity	65
13.1.1	Definition	65
13.1.2	Test environment	65
13.1.3	Method of measurement	65
13.1.4	Verdict criteria	65
13.2	Radio receiver reference BER and FER	65
13.2.1	Definition	65
13.2.2	Test environment	65
13.2.3	Method of measurement	66
13.2.4	Verdict criteria	66
13.3	Radio receiver interference performance	66
13.3.1	Definition	66
13.3.2	Test environment	66
13.3.3	Method of measurement	66
13.3.4	Verdict criteria	67
13.4	Radio receiver blocking case 1: owing to signals occurring at the same time but on other frequencies	67
13.4.1	Definition	67
13.4.2	Test environment	67
13.4.3	Method of measurement	67
13.4.4	Verdict criteria	68
13.5	Radio receiver blocking case 2: owing to signals occurring at a different time	69
13.5.1	Definition	69
13.5.2	Test environment	69

13.5.3	Method of measurement.....	69
13.5.4	Verdict criteria	69
13.6	Receiver intermodulation performance	69
13.6.1	Definition	69
13.6.2	Test environment	69
13.6.3	Method of measurement.....	70
13.6.4	Verdict criteria	70
13.7	Spurious emissions when the PP has no allocated transmit channel	70
13.7.1	Definition	70
13.7.2	Test environment	70
13.7.3	Method of measurement.....	70
13.7.4	Verdict criteria (outside the DECT band)	71
13.7.5	Verdict criteria (inside the DECT band)	71
14	Intersystem synchronization (FP only)	71
14.1	Description.....	71
14.2	Test environment.....	71
14.3	Wired synchronization ports	72
14.3.1	FP as a master.....	72
14.3.1.1	Method of measurement	72
14.3.1.2	Verdict criteria	72
14.3.2	FP as a slave	72
14.3.2.1	Method of measurement	72
14.3.2.2	Verdict criteria	73
14.4	GPS synchronization	73
14.4.1	FP with integrated Global Positioning System (GPS) synchronization	73
14.4.1.1	Method of measurement	73
14.4.1.2	Verdict criteria	73
14.4.2	External GPS synchronization device	73
14.4.2.1	Method of measurement	73
14.4.2.2	Verdict criteria	74
15	EMC	74
	https://standards.iteh.ai/catalog/standards/sist/d7344da9-4139-4c19-be5e-c64b069cc80d/sist-tbr-006-e3-2004	
16	Equipment identity testing	74
16.1	PP	74
16.2	FP	74
17	Efficient use of the radio spectrum	74
17.1	Channel selection	74
17.2	Channel confirmation	74
17.2.1	For the PT	74
17.2.2	For the FT	75
17.3	Channel release	75
17.4	General.....	75
18	WRS testing.....	75
18.1	Testing as a PP	76
18.2	Testing as an RFP.....	76
18.3	Applicants declarations.....	76
Annex A (informative):	Bibliography.....	77
Annex B (normative):	Procedures for test fixture calibration and for measurement of radiated spurious emissions	78
B.1	Calibration of test fixture for receiver measurements	78
B.1.1	Method of measurement	78
B.2	Radiated measurements.....	79
B.2.1	General.....	79
B.2.2	Radiated spurious emissions	80
B.2.2.1	Definition	80

B.2.3	B.2.2.2 Method of measurement	80
	Cabinet radiation.....	81
	B.2.3.1 Definition	81
	B.2.3.2 Method of measurement	82
Annex C (normative): Procedure for measurement of conducted spurious emissions		83
C.1	Conducted spurious emissions	83
	C.1.1 Definition	83
	C.1.2 Method of measurement.....	83
Annex D (normative): Test Support Profile (TSP)		84
D.1	Introduction.....	84
D.2	Standardized symbols for the status column	84
D.3	Capabilities of PP (EUT) under test	85
	D.3.1 Services	85
	D.3.2 Messages.....	85
	D.3.3 Message parameters	87
	D.3.4 Procedure support	88
	D.3.5 CSF multiplexing functions	89
	D.3.6 Timer and counter support.....	89
D.4	Capabilities of FP (EUT) under test	90
	D.4.1 Services	90
	D.4.2 Messages.....	90
	D.4.3 Message parameters	92
	D.4.4 Procedure support	94
	D.4.5 CSF multiplexing functions	95
	D.4.6 Timer and counter support.....	95
Annex E (normative): Measurement of BER and FER		96
https://standards.iteh.ai/sist-tbr-006-e3-2004		96
Annex F (informative): Procedures for the measurement of synchronization loss at the EUT by the LT		97
F.1	Description	97
F.2	Method	97
Annex G (normative): Requirements for PPs with direct PP to PP communication mode		98
G.1	Description of operation in direct PP to PP communication mode.....	98
G.2	Requirements	98
	G.2.1 Setting the PP in direct communications mode	98
	G.2.2 When the EUT has initiated a call.....	99
	G.2.3 When the EUT has not initiated a call.....	99
Annex H (normative): Requirements for installation related issues.....		100
H.1	Spectrum efficiency for speech transmission.....	100
H.2	Antennas with directivity	100
H.3	DECT frame synchronization	100
	H.3.1 Guidance for installation of frame synchronized DECT systems.....	101
	H.3.1.1 GPS synchronization	101
	H.3.1.2 Wired synch port synchronization	101
	H.3.1.3 Requirements for DECT air synchronization	102

Annex I (normative):	TBR Requirements Table (TBR-RT).....	103
History		104

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST TBR 006 E3:2004](#)
<https://standards.iteh.ai/catalog/standards/sist/d7344da9-4139-4c19-be5e-c64b069ec80d/sist-tbr-006-e3-2004>

Blank page

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST TBR 006 E3:2004](#)

<https://standards.iteh.ai/catalog/standards/sist/d7344da9-4139-4c19-be5e-c64b069ec80d/sist-tbr-006-e3-2004>

Foreword

This Technical Basis for Regulation (TBR) has been produced by the Digital Enhanced Cordless Telecommunications (DECT) Project of the European Telecommunications Standards Institute (ETSI).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/13/EC [12] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard as requested by the above mentioned mandate, the reference of which will be published in the Official Journal of the European Communities referencing the Council Directive on the approximation of the laws of the Member States concerning telecommunications terminal equipment, including the mutual recognition of their conformity (Directive 98/13/EC [12], known as the "TTE Directive").

A common technical regulation may be established by the European Commission in accordance with the Directive.

Technical specifications relevant to the 98/13/EC [12] Directive are given in the TBR Requirements Table (TBR-RT) in annex I.

Transposition dates	
Date of adoption of this TBR:	4 June 1999
Date of latest announcement of this TBR (doa):	30 September 1999
Date of latest publication of new National Standard or endorsement of this TBR (dop/e):	31 March 2000
Date of withdrawal of any conflicting National Standard (dow):	31 March 2000

SIST TBR 006 E3:2004
<https://standards.iteh.ai/catalog/standards/sist/d7344da9-4139-4c19-be5e-c64b069ec80d/sist-tbr-006-e3-2004>

Blank page

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST TBR 006 E3:2004](#)

<https://standards.iteh.ai/catalog/standards/sist/d7344da9-4139-4c19-be5e-c64b069ec80d/sist-tbr-006-e3-2004>

1 Scope

This TBR covers the general attachment requirements for terminal equipment for the Digital Enhanced Cordless Telecommunications (DECT) common interface.

The present document contains the procedures and requirements for the type examination of DECT equipment.

DECT equipment capable of being physically attached to the public network also needs to meet the appropriate attachment requirements. Speech attachment requirements are covered in TBR 10 (see annex A).

The present document is based on the DECT Common Interface (CI) given in EN 300 175, parts 1 [1] to 8 [8].

The present document specifies the technical characteristics to be provided by terminal equipment which is capable of connection to a public telecommunications network and which uses DECT cordless communications for network access. The cordless transmissions for such terminal equipment operate within the frequency band 1 880 MHz to 1 900 MHz.

The objective of the present document is to ensure that no disturbance occurs to the public network, and to ensure interworking between network and terminal so that calls can be routed successfully through the network, but without any guarantee of terminal to terminal operation.

The requirements in the present document applies together with the attachment requirements for the appropriate public network and the requirements of any other relevant TBR. It does not add to or reduce the attachment requirements unless there is a particular effect on the network which is unique to DECT.

iTeh STANDARD PREVIEW

A DECT terminal equipment comprises two elements, referred to as a Fixed Part (FP) and a Portable Part (PP). The present document is structured to allow type approval of the FP and PP as separate items.

Because of the need for effective use of the radio frequency spectrum, the air interface characteristics between FP and PP are tested.

<https://standards.iteh.ai/catalog/standards/sist/tbr/006/e3:2004>

For each requirement, a test is given, including measurement methods. Requirements apply at the public network interface of the terminal equipment, which may be stimulated to perform the tests by additional equipment if necessary.

Terminal equipment may be subject to additional or alternative requirements in other Common Technical Regulations (CTRs) depending on its functionality, in particular if it supports a service which is considered a justified case for regulation of terminal equipment interworking via the public telecommunications network.

2 Normative references

This TBR incorporates, by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to, or revisions of any of these publications apply to this TBR only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

- [1] EN 300 175-1: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview".
- [2] EN 300 175-2: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical layer (PHL)".
- [3] EN 300 175-3: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer".
- [4] EN 300 175-4: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) layer".