



SLOVENSKI STANDARD

SIST ETS 300 577 E10:2003

01-december-2003

8 [[[HJb]`W] b]`hY`ca i b]_UW`g_]`g]ghYa `fZuU&L`E`F`UX]`g_c`cXXU`Ub`Y]b
gdfY`Ya Ub`Y`f] GA `\$) '\$) žfU`h`]]WU('%, '%L

Digital cellular telecommunications system (Phase 2) (GSM); Radio transmission and reception (GSM 05.05 version 4.18.1)

iteh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: ^{SIST ETS 300 577 E10:2003} **ETS 300 577 Edition 10**
<https://standards.iteh.ai/catalog/standards/sist/b9ac6671-1a70-49c2-b5f6-e2a56d15d829/sist-ets-300-577-e10-2003>

ICS:

33.060.20	Sprejemna in oddajna oprema	Receiving and transmitting equipment
33.070.50	Globalni sistem za mobilno telekomunikacijo (GSM)	Global System for Mobile Communication (GSM)


SIST ETS 300 577 E10:2003

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 577 E10:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/b9ae6671-fa70-49c2-b3f6-e2a56d15d829/sist-ets-300-577-e10-2003>



EUROPEAN
TELECOMMUNICATION
STANDARD

ETS 300 577

August 1997

Tenth Edition

Source: ETSI SMG

Reference: RE/SMG-020505PR9

ICS: 33.020

Key words: Digital cellular telecommunications system, Global System for Mobile communications (GSM)



**Digital cellular telecommunications system (Phase 2);
Radio transmission and reception
(GSM 05.05 version 4.18.1)**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1997. All rights reserved.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 577 E10:2003](https://standards.iteh.ai/catalog/standards/sist/b9ae6671-fa70-49c2-b3f6-e2a56d15d829/sist-ets-300-577-e10-2003)

<https://standards.iteh.ai/catalog/standards/sist/b9ae6671-fa70-49c2-b3f6-e2a56d15d829/sist-ets-300-577-e10-2003>

Contents

Foreword	5
1 Scope	7
1.1 Normative references	7
1.2 Abbreviations	8
2 Frequency bands and channel arrangement.....	8
3 Reference configuration	9
4 Transmitter characteristics	9
4.1 Output power	9
4.1.1 Mobile station	9
4.1.2 Base station.....	10
4.2 Output RF spectrum	11
4.2.1 Spectrum due to the modulation and wide band noise	12
4.2.2 Spectrum due to switching transients.....	15
4.3 Spurious emissions.....	16
4.3.1 Principle of the specification.....	16
4.3.2 Base transceiver station	17
4.3.3 Mobile station	18
4.4 Radio frequency tolerance	19
4.5 Output level dynamic operation	19
4.5.1 Base transceiver station	19
4.5.2 Mobile station	19
4.6 Phase accuracy	19
4.7 Intermodulation attenuation	20
4.7.1 Base transceiver station	20
4.7.2 Intra BTS intermodulation attenuation.....	20
4.7.3 Intermodulation between MS (DCS 1 800 only)	20
4.7.4 Mobile PBX (GSM 900 only).....	20
5 Receiver characteristics	21
5.1 Blocking characteristics	21
5.2 AM suppression characteristics	22
5.3 Intermodulation characteristics	23
5.4 Spurious emissions.....	23
6 Transmitter/receiver performance	23
6.1 Nominal error rates (NER)	24
6.2 Reference sensitivity level	24
6.3 Reference interference level	24
6.4 Erroneous frame indication performance	25
Annex A (informative): Spectrum characteristics (spectrum due to the modulation).....	30
Annex B (normative): Transmitted power level versus time.....	34
Annex C (normative): Propagation conditions	35
C.1 Simple wideband propagation model	35
C.2 Doppler spectrum types	35
C.3 Propagation models	36
C.3.1 Typical case for rural area (RAx): (6 tap setting)	36

C.3.2	Typical case for hilly terrain (HTx): (12 tap setting).....	36
C.3.3	Typical case for urban area (TUx): (12 tap setting).....	37
C.3.4	Profile for equalization test (EQx): (6 tap setting)	37
Annex D (normative):	Environmental conditions.....	38
D.1	General.....	38
D.2	Environmental requirements for the MSs	38
D.2.1	Temperature.....	38
D.2.2	Voltage	38
D.2.3	Vibration	39
D.3	Environmental requirements for the BSS equipment	39
Annex E (normative):	Repeater characteristics	40
E.1	Introduction	40
E.2	Spurious emissions	40
E.3	Intermodulation products	41
E.4	Out of band gain	41
History	42

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 577 E10:2003](https://standards.iteh.ai/catalog/standards/sist/b9ae6671-fa70-49c2-b3f6-e2a56d15d829/sist-ets-300-577-e10-2003)

<https://standards.iteh.ai/catalog/standards/sist/b9ae6671-fa70-49c2-b3f6-e2a56d15d829/sist-ets-300-577-e10-2003>

Foreword

This European Telecommunication Standard (ETS) has been produced by the Special Mobile Group (SMG) of the European Telecommunications Standards Institute (ETSI).

This ETS defines the requirements for transceivers operating in the 900 MHz and 1 800 MHz bands within the digital cellular telecommunications system (Phase 2).

The specification from which this ETS has been derived was originally based on CEPT documentation, hence the presentation of this ETS is not in accordance with the ETSI/PNE Rules.

Transposition dates	
Date of adoption:	25 July 1997
Date of latest announcement of this ETS (doa):	30 November 1997
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	31 May 1998
Date of withdrawal of any conflicting National Standard (dow):	31 May 1998

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 577 E10:2003](https://standards.iteh.ai/catalog/standards/sist/b9ae6671-fa70-49c2-b3f6-e2a56d15d829/sist-ets-300-577-e10-2003)

<https://standards.iteh.ai/catalog/standards/sist/b9ae6671-fa70-49c2-b3f6-e2a56d15d829/sist-ets-300-577-e10-2003>

Blank page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 577 E10:2003](https://standards.iteh.ai/catalog/standards/sist/b9ae6671-fa70-49c2-b3f6-e2a56d15d829/sist-ets-300-577-e10-2003)

<https://standards.iteh.ai/catalog/standards/sist/b9ae6671-fa70-49c2-b3f6-e2a56d15d829/sist-ets-300-577-e10-2003>

1 Scope

This European Telecommunications Standard (ETS) defines the requirements for the transceiver of the pan-european digital mobile cellular and personal communication systems operating in the 900 MHz and 1 800 MHz band (GSM 900 and DCS 1 800).

Requirements are defined for two categories of parameters:

- those that are required to provide compatibility between the radio channels, connected either to separate or common antennas, that are used in the system. This category also includes parameters providing compatibility with existing systems in the same or adjacent frequency bands;
- those that define the transmission quality of the system.

This ETS defines RF characteristics for the Mobile Station (MS) and Base Station System (BSS). The BSS will contain either Base Transceiver Stations (BTS) or microcell base transceiver stations (micro BTS). The precise measurement methods are specified in GSM 11.10 and GSM 11.2x series.

Unless otherwise stated, the requirements defined in this ETS apply to the full range of environmental conditions specified for the equipment (see annex D).

In this ETS, some relaxations are introduced for GSM 900 mobile stations which fulfil the following conditions:

- pertain to power class 4 or 5 (see subclause 4.1.1);
- not designed to be vehicle mounted (see GSM 02.06).

In this ETS, these mobile stations are referred to as "small MS".

NOTE: In this standard, a handheld which can be connected to a car kit is not considered to be vehicle mounted.

[SIST ETS 300 577 E10:2003](https://standards.iteh.ai/telecom/standards/sist-ets-300-577-e10-2003)

Mobile stations may operate on more than one of the frequency bands specified in clause 2. These mobile stations, defined in GSM 02.06, are referred to as "Multi band mobile stations" in this standard. Multi band mobile stations shall meet all requirements for each of the bands supported. The relaxation on GSM 900 for a "small MS" are also valid for a multi band MS if it complies with the definition of a small MS.

The RF characteristics of repeaters are defined in annex E of this ETS. Annexes D and E are the only sections of this ETS applicable to repeaters. Annex E does not apply to the MS or BSS.

1.1 Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references, the latest edition of the publication referred to applies.

- | | |
|-----|--|
| [1] | GSM 01.04 (ETR 100): "Digital cellular telecommunications system (Phase 2); Abbreviations and acronyms". |
| [2] | GSM 02.06 (ETS 300 504): "Digital cellular telecommunications system (Phase 2); Types of Mobile Stations (MS)". |
| [3] | GSM 05.01 (ETS 300 573): "Digital cellular telecommunications system (Phase 2); Physical layer on the radio path General description". |
| [4] | GSM 05.04 (ETS 300 576): "Digital cellular telecommunications system (Phase 2); Modulation". |

- [5] GSM 05.08 (ETS 300 578): "Digital cellular telecommunications system (Phase 2); Radio subsystem link control".
- [6] GSM 05.10 (ETS 300 579): "Digital cellular telecommunications system (Phase 2); Radio subsystem synchronization".
- [7] GSM 11.10 (ETS 300 607): "Digital cellular telecommunications system (Phase 2); Mobile Station (MS) conformity specification".
- [8] GSM 11.11 (ETS 300 608): "Digital cellular telecommunications system (Phase 2); Specification of the Subscriber Identity Module - Mobile Equipment (SIM - ME) interface".
- [9] CCITT Recommendation O.153: "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [10] ETS 300 019-1-3: "Equipment engineering; Environmental conditions and Environmental tests for telecommunications equipment Part 1-3: Classification of Environmental conditions Stationary use at weather protected locations".
- [11] ETS 300 019-1-4: "Equipment engineering; Environmental conditions and Environmental tests for telecommunications equipment Part 1-4: Classification of Environmental conditions Stationary use at non-weather protected locations".

1.2 Abbreviations

Abbreviations used in this ETS are listed in GSM 01.04 [1].

2 Frequency bands and channel arrangement

- i) Standard or primary GSM 900 Band, P-GSM:

for Standard GSM 900 Band, the system is required to operate in the following frequency band:

890 - 915 MHz: mobile transmit, base receive;
935 - 960 MHz: base transmit, mobile receive.

- ii) Extended GSM 900 Band, E-GSM (includes Standard GSM 900 band):

for Extended GSM 900 band, the system is required to operate in the following frequency band:

880 - 915 MHz: mobile transmit, base receive;
925 - 960 MHz: base transmit, mobile receive.

- iii) DCS 1 800 Band:

or DCS 1 800, the system is required to operate in the following band:

1 710 - 1 785 MHz: mobile transmit, base receive;
1 805 - 1 880 MHz: base transmit, mobile receive.

NOTE: The term GSM 900 is used for any GSM system which operates in any 900 MHz band.

Operators may implement networks which operates on a combination of the frequency bands above to support multi band mobile terminals which are defined in GSM 02.06.

The carrier spacing is 200 kHz.

The carrier frequency is designated by the absolute radio frequency channel number (ARFCN). If we call $F_l(n)$ the frequency value of the carrier ARFCN n in the lower band, and $F_u(n)$ the corresponding frequency value in the upper band, we have:

P-GSM 900	$F_l(n) = 890 + 0.2 \cdot n$	$1 \leq n \leq 124$	$F_u(n) = F_l(n) + 45$
E-GSM 900	$F_l(n) = 890 + 0.2 \cdot n$	$0 \leq n \leq 124$	$F_u(n) = F_l(n) + 45$
	$F_l(n) = 890 + 0.2 \cdot (n-1024)$	$975 \leq n \leq 1023$	
DCS 1 800	$F_l(n) = 1710.2 + 0.2 \cdot (n-512)$	$512 \leq n \leq 885$	$F_u(n) = F_l(n) + 95$

Frequencies are in MHz.

3 Reference configuration

The reference configuration for the radio subsystem is described in GSM 05.01.

The micro-BTS is different from a normal BTS in two ways. Firstly, the range requirements are much reduced whilst the close proximity requirements are more stringent. Secondly, the micro-BTS is required to be small and cheap to allow external street deployment in large numbers. Because of these differences the micro-BTS needs a different set of RF parameters to be specified. Where the RF parameters are not different for the micro-BTS the normal BTS parameters shall apply.

4 Transmitter characteristics

Throughout this section, unless otherwise stated, requirements are given in terms of power levels at the antenna connector of the equipment. For equipment with integral antenna only, a reference antenna with 0 dBi gain shall be assumed.

The term output power refers to the measure of the power when averaged over the useful part of the burst (see annex B).

The term peak hold refers to a measurement where the maximum is taken over a sufficient time that the level would not significantly increase if the holding time were longer.

4.1 Output power

4.1.1 Mobile station

The mobile station maximum output power and lowest power control level shall be, according to its class, as defined in the following table (see also GSM 02.06).

Power class	GSM 900 Nominal Maximum output power	DCS 1 800 Nominal Maximum output power	Tolerance (dB) for conditions	
			normal	extreme
1	-- -- --	1 W (30 dBm)	± 2	± 2.5
2	8 W (39 dBm)	0.25 W (24 dBm)	± 2	± 2.5
3	5 W (37 dBm)	4 W (36 dBm)	± 2	± 2.5
4	2 W (33 dBm)		± 2	± 2.5
5	0.8 W (29 dBm)		± 2	± 2.5
NOTE: The lowest nominal output power for all classes of GSM 900 MS is 5 dBm and for all classes of DCS 1 800 MS is 0 dBm.				

A multi band MS has a combination of the power class in each band of operation from the table above. Any combination may be used.

The different power control levels needed for adaptive power control (see GSM 05.08) shall have the nominal output power as defined in the table below, starting from the power control level for the lowest nominal output power up to the power control level for the maximum nominal output power corresponding to the class of the particular mobile station as defined in the table above. Whenever a power control level commands the MS to use a nominal output power equal to or greater than the maximum nominal output power for the power class of the MS, the nominal output power transmitted shall be the maximum nominal output power for the MS class, and the tolerance of ± 2 or 2.5 dB (see table above) shall apply.

GSM 900

DCS 1 800

Power control level	Nominal Output power (dBm)	Tolerance (dB) for conditions		Power control level	Nominal Output power (dBm)	Tolerance (dB) for conditions	
		normal	extreme			normal	extreme
0-2	39	± 2	± 2.5	29	36	± 2	± 2.5
3	37	± 3	± 4	30	34	± 3	± 4
4	35	± 3	± 4	31	32	± 3	± 4
5	33	± 3	± 4	0	30	± 3	± 4
6	31	± 3	± 4	1	28	± 3	± 4
7	29	± 3	± 4	2	26	± 3	± 4
8	27	± 3	± 4	3	24	± 3	± 4
9	25	± 3	± 4	4	22	± 3	± 4
10	23	± 3	± 4	5	20	± 3	± 4
11	21	± 3	± 4	6	18	± 3	± 4
12	19	± 3	± 4	7	16	± 3	± 4
13	17	± 3	± 4	8	14	± 3	± 4
14	15	± 3	± 4	9	12	± 4	± 5
15	13	± 3	± 4	10	10	± 4	± 5
16	11	± 5	± 6	11	8	± 4	± 5
17	9	± 5	± 6	12	6	± 4	± 5
18	7	± 5	± 6	13	4	± 4	± 5
19-31	5	± 5	± 6	14	2	± 5	± 6
				15-28	0	± 5	± 6

NOTE 1: For DCS 1 800, the power control levels 29, 30 and 31 are only used "in call" for power control purposes. These levels are not used when transmitting the parameter TX PWR MAX CCH, for cross phase compatibility reasons. If levels greater than 30 dBm are required from the MS during a random access attempt, then these shall be decoded from parameters broadcast on the BCCH as described in GSM 05.08.

Furthermore, the difference in output power actually transmitted by the MS between two power control levels where the difference in nominal output power indicates an increase of 2 dB (taking into account the restrictions due to power class), shall be $+2 \pm 1.5$ dB. Similarly, if the difference in output power actually transmitted by the MS between two power control levels where the difference in nominal output power indicates an decrease of 2 dB (taking into account the restrictions due to power class), shall be -2 ± 1.5 dB.

NOTE 2: A 2 dB nominal difference in output power can exist for non-adjacent power control levels e.g. power control levels 18 and 22 for GSM 900; power control levels 31 and 0 for class 3 DCS 1 800 and power control levels 3 and 6 for class 4 GSM 900.

A change from any power control level to any power control level may be required by the base transmitter. The maximum time to execute this change is specified in GSM 05.08.

4.1.2 Base station

The base station transmitter maximum output power, measured at the input of the BSS Tx combiner, shall be, according to its class, as defined in the following table:

GSM 900

TRX power class	Maximum output power
1	320 - (<640) W
2	160 - (<320) W
3	80 - (<160) W
4	40 - (<80) W
5	20 - (<40) W
6	10 - (<20) W
7	5 - (<10) W
8	2.5 - (<5) W

DCS 1 800

TRX power class	Maximum output power
1	20 - (<40) W
2	10 - (<20) W
3	5 - (<10) W
4	2.5 - (<5) W

The micro-BTS maximum output power per carrier measured at the antenna connector after all stages of combining shall be, according to its class, defined in the following table.

GSM 900 micro-BTS		DCS 1 800 micro-BTS	
TRX power class	Maximum output power	TRX power class	Maximum output power
M1	(>19) - 24 dBm ((>0.08) - 0.25 W)	M1	(>27) - 32 dBm ((>0.5) - 1.6 W)
M2	(>14) - 19 dBm ((>0.03) - 0.08 W)	M2	(>22) - 27 dBm ((>0.16) - 0.5 W)
M3	(>9) - 14 dBm ((>0.01) - 0.03 W)	M3	(>17) - 22 dBm ((>0.05) - 0.16 W)

SIST ETS 300 577 E10:2003

The tolerance of the actual maximum output power of the BTS shall be ± 2 dB under normal conditions and ± 2.5 dB under extreme conditions. Settings shall be provided to allow the output power to be reduced from its maximum level in at least six steps of nominally 2 dB with an accuracy of ± 1 dB to allow a fine adjustment of the coverage by the network operator. In addition, the actual absolute output power at each static RF power step (N) shall be $2 \cdot N$ dB below the absolute output power at static RF power step 0 with a tolerance of ± 3 dB under normal conditions and ± 4 dB under extreme conditions. The static RF power step 0 shall be the actual output power according to the TRX power class.

As an option the BSS can utilize downlink RF power control. In addition to the static RF power steps described above, the BSS may then utilize up to 15 steps of power control levels with a step size of 2 dB ± 1.5 dB, in addition the actual absolute output power at each power control level (N) shall be $2 \cdot N$ dB below the absolute output power at power control level 0 with a tolerance of ± 3 dB under normal conditions and ± 4 dB under extreme conditions. The power control level 0 shall be the set output power according to the TRX power class and the six power settings defined above.

Network operators may also specify the BTS output power including any Tx combiner, according to their needs.

4.2 Output RF spectrum

The specifications contained in this section apply to both BTS and MS, in frequency hopping as well as in non frequency hopping mode, except that beyond 1 800 kHz offset from the carrier the BTS is not tested in frequency hopping mode.