



**Short Range Devices (SRD) and
Ultra Wide Band (UWB);
Part 1: Measurement techniques
for transmitter requirements**

iTeh 5G NR Standard PREVIEW
Full standard: <https://standards.iteh.ai/catalog/standards/etsi-en-303-883-1-v1-2-0-07-4c36-ab39-e479b85a227>

Reference

REN/ERM-TGUWB-149-1

Keywords

SRD, testing, UWB

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803788

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and
of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology.....	8
Introduction	9
1 Scope	10
2 References	10
2.1 Normative references	10
2.2 Informative references.....	10
3 Definition of terms, symbols and abbreviations.....	12
3.1 Terms.....	12
3.2 Symbols	15
3.3 Abbreviations	16
4 Overview	17
4.1 Info	17
4.2 Basic information about UWB	17
5 TX requirements.....	17
5.1 General	17
5.1.1 General Guidance on TX measurements	17
5.1.2 Emission Concept	18
5.1.2.1 General	18
5.1.2.2 UWB - EUT	18
5.2 Operating Frequency Range (OFR).....	19
5.2.1 Definition.....	19
5.2.2 Conformance Test.....	20
5.3 Radiated Power (RP)	20
5.3.1 Mean e.i.r.p.....	20
5.3.1.1 Description	20
5.3.1.2 Conformance	20
5.3.1.3 Method with a Spectrum Analyser	20
5.3.1.4 Method with an RMS Power Meter	21
5.3.1.5 Method with a Peak Power Meter	21
5.3.2 Mean e.i.r.p. Spectral Density	22
5.3.2.1 Description	22
5.3.2.2 Guidance for Mean e.i.r.p. Spectral Density Conformance Tests	22
5.3.2.3 Mean e.i.r.p. Spectral Density, averaged over 1 ms	22
5.3.2.4 Mean e.i.r.p. Spectral Density, known signal repetition time, averaged over 1 ms.....	23
5.3.2.5 Mean e.i.r.p. Spectral Density, known signal repetition time, averaged over signal repetition time	25
5.3.3 Peak e.i.r.p.	26
5.3.3.1 Description	26
5.3.3.2 Conformance	26
5.3.3.3 Peak e.i.r.p.; Method with a Spectrum Analyser	27
5.3.3.4 Peak e.i.r.p. Method with an RMS Power Meter.....	27
5.3.3.5 Peak e.i.r.p. method with a Peak Power Meter.....	27
5.3.4 Peak e.i.r.p. Spectral Density	28
5.3.4.1 Description	28
5.3.4.2 Peak e.i.r.p. Spectral Density, General Method	28
5.3.4.3 Peak e.i.r.p. Spectral Density, Sparse Spectral Line Method	30
5.4 Other Emissions (OE)	30
5.5 TX Unwanted Emissions (TXUE).....	31
5.5.1 Description.....	31
5.5.2 Limits for the TX Unwanted Emission	32
5.5.3 General for Conformance Test TX Unwanted Emission	32
5.5.3.1 General	32

5.5.3.2	Step 1: Measurement with Peak Detector	32
5.5.3.3	Step 2: RMS Measurement	33
5.6	Total Radiated Power (TRP)	34
5.6.1	Description.....	34
5.6.2	Conformance Test.....	35
5.6.2.1	General.....	35
5.6.2.2	TRP Conformance Assessment in steps:.....	35
5.7	Indirect Emissions	36
5.7.1	Description.....	36
5.7.2	Guidance for Conformance Test	40
5.8	Transmit Power Control	40
5.8.1	Description.....	40
5.8.2	Guidance for Conformance Test	40
5.9	Detect and Avoid.....	41
5.9.1	Description.....	41
5.9.2	Limits.....	41
5.9.2.1	DAA Parameters	41
5.9.2.2	DAA NIM parameters.....	42
5.9.2.3	DAA test parameters	42
5.9.3	Conformance Test.....	42
5.9.3.1	Introduction.....	42
5.9.3.2	Initial Start-Up Test.	44
5.9.3.2.1	Start-up Procedure	44
5.9.3.2.2	Test without a victim test signal during the <i>Minimum Initial Channel Availability Check Time, T_{avail_time_min}</i>	44
5.9.3.2.3	Test with a victim test signal at the beginning of the <i>Minimum Initial Channel Availability Check Time, T_{avail_time_min}</i>	45
5.9.3.2.4	Test with a victim test signal at the end of the <i>Minimum Initial Channel Availability Check Time, T_{avail_time_min}</i>	46
5.9.3.3	In-Operation Test	47
5.9.3.3.1	General Points for In-Operation Test	47
5.9.3.3.2	In-Operation Test Procedure.....	48
5.10	Listen Before Talk (LBT).....	49
5.10.1	Description.....	49
5.10.2	Limits.....	50
5.10.3	Conformance.....	51
5.10.3.1	Measurement Procedure.....	51
5.10.3.2	Test Set-Up	51
5.10.3.3	Test Signal Definition for LBT Mechanism in Band 2 and 3	52
5.10.3.3.1	Band 2: Mobile Satellite Service (MSS) Test Signal.....	52
5.10.3.3.2	Band 3: Land Mobile Service Test Signal	52
5.10.3.4	Test Signal Definition for LBT Mechanism in Band 1 and 4	52
5.10.3.5	Conformance Test to Measure the Timing for LBT within bands 1 and 4	54
5.11	Duty Cycle.....	55
5.11.1	Description.....	55
5.11.2	Conformance.....	55
5.11.2.1	Duty Cycle, Spectrum Analyser Method	55
5.11.2.2	Duty Cycle, Oscilloscope Method	56
5.11.2.3	Duty Cycle Measurement Methods for FMCW, stepped-frequency and Pulsed Systems	58
5.11.2.3.1	General	58
5.11.2.3.2	Method 1: Diode Power Detector	58
5.11.2.3.3	Method 2: Spectrum Analyzer	59
5.11.2.3.4	Method 3: Synchronized Spectrum Analysers.....	60
5.11.2.4	Duty Cycle Measurement Methods within a frequency band for FMCW and stepped-frequency systems.....	61
5.11.2.4.1	General	61
5.11.2.4.2	Synchronized Spectrum Analysers	61
Annex A (normative):	General Considerations and test conditions	64
A.1	Overview	64
A.2	Product Information	64

A.3	Guidance on EUT Modulation for Testing.....	65
A.4	Requirements in Case of EUT with Scanning Antennas.....	65
A.4.1	Classification.....	65
A.4.2	Measurement of Fixed Beam EUT.....	65
A.4.3	Measurement of Constant Pattern EUT.....	65
A.4.4	Measurement of Variable Pattern EUT	66
A.5	Test Conditions, Power Supply and Ambient Temperatures	66
A.5.1	General	66
A.5.2	Power Sources	66
A.5.2.1	Power Sources for Stand-Alone Equipment	66
A.5.2.2	Power sources for plug-in radio devices	67
A.5.3	Normal and Extreme Test Conditions	67
A.5.3.1	Normal Test Conditions.....	67
A.5.3.1.1	Normal Temperature and Humidity	67
A.5.3.1.2	Normal Power Source	67
A.5.3.1.2.1	Mains Voltage	67
A.5.3.1.2.2	Lead-Acid Battery Power Sources used on Vehicles	67
A.5.3.1.2.3	Other Power Sources	67
A.5.3.2	Extreme Conditions	67
A.5.3.2.1	Extreme Temperatures	67
A.5.3.2.1.1	Procedure for Tests at Extreme Temperatures.....	67
A.5.3.2.1.2	Extreme Temperature Ranges	68
A.5.3.2.2	Extreme Test Source Voltages	68
A.5.3.2.2.1	Mains Voltage	68
A.5.3.2.2.2	Other Power Sources	68
A.5.3.2.3	Radio Transparent Temperature Chamber	68
A.5.3.2.4	Use of a Test Fixture	68
A.5.3.2.4.1	General	68
A.5.3.2.4.2	Characteristics	69
A.5.3.2.4.3	Validation of the Test Fixture in the Temperature Chamber	70
A.5.3.2.4.4	Use of the Test Fixture for Measurement in the Temperature Chamber	71
A.6	Choice of Equipment for Test Suites	71
A.6.1	Choice of Model.....	71
A.6.2	Presentation	71
A.7	Testing of Host Connected Equipment and Plug-In Radio Devices	71
A.7.1	General	71
A.7.2	The Use of a Host or Test Fixture for Testing Plug-In Radio Devices.....	72
A.8	Interpretation of the measurement results	72
A.8.1	General points on interpretation of the measurement results	72
A.8.2	Measurement uncertainty is equal to or less than maximum acceptable uncertainty	73
A.8.3	Measurement uncertainty is greater than maximum acceptable uncertainty	73
Annex B (normative):	Test setups	74
B.1	Introduction	74
B.2	Radiated measurements.....	74
B.2.1	General	74
B.2.2	Test Sites and General Arrangements for Measurements Involving the Use of Radiated Fields	74
B.2.2.1	General.....	74
B.2.2.2	Anechoic Chamber	75
B.2.2.3	Anechoic Chamber with a Conductive Ground Plane	76
B.2.2.4	Open Area Test Site (OATS).....	77
B.2.2.5	Test Antenna.....	78
B.2.2.6	Substitution Antenna.....	78
B.2.2.7	Measuring Antenna.....	79
B.2.2.8	Minimum Requirements for Test Sites for Measurements above 18 GHz	79
B.2.3	Guidance on the Use of a Radiation Test Site	80
B.2.3.1	General on Guidance on the Use of a Radiation Test Site	80

B.2.3.2	Verification of the Test Site	80
B.2.3.3	Preparation of the EUT	80
B.2.3.4	Power Supplies to the EUT	81
B.2.3.5	Range Length	81
B.2.3.5.1	General	81
B.2.3.5.2	Practical Test Distances for Accurate Measurements	81
B.2.3.6	Site Preparation	82
B.2.4	Coupling of Signals	82
B.2.4.1	General	82
B.2.4.2	Data Signals	82
B.2.5	Standard Radiated Test Methods	83
B.2.5.0	Initial Measurement Steps	83
B.2.5.1	General Information on Test Methods	83
B.2.5.2	Calibrated Setup	83
B.2.5.3	Substitution Method	83
B.2.6	Standard calibration method	84
B.3	Conducted Measurements	86
B.4	Detailed Information to Standard Test Methods	87
B.4.1	Spherical Scan with Automatic Test Antenna Placement	87
B.4.1.1	General	87
B.5.1.2	Calibrated Setup	88
B.5.1.3	Substitution Method	88
B.5.1.4	Spherical Scan with Rotating EUT	89
B.5.1.4.1	General	89
B.5.1.4.2	Calibrated Setup	89
B.5.1.4.3	Substitution Method	90
B.5.1.5	Spherical Scan Other Methods	91
Annex C (normative):	Signal Repetition Time	92
C.1	Definitions	92
C.2	Signal Types	92
C.2.1	Pulsed signals	92
C.2.2	FMCW signals, Stepped/Hopping Frequency Signals and Similar	93
C.3	Measurement procedure for time parameters	94
Annex D (normative):	All Emission Measurement	95
D.1	General	95
D.2	First step	95
D.3	Second step	97
Annex E (normative):	Guidance for a pre-scan of EUT operating frequency range(s)	98
Annex F (informative):	Measurement of peak e.i.r.p. and mean (average) e.i.r.p. of constant duty cycle wideband pulsed signals	99
F.1	General	99
F.2	Exemplary measurement of pulse signals	99
F.3	Mean e.i.r.p. measurements	100
F.3.1	General	100
F.3.2	Method I: Zero span mode	100
F.3.3	Method II: Channel power measurement	101
F.3.4	Method III: Average power meters	102
F.4	Peak e.i.r.p. measurements	102
F.4.1	General	102
F.4.2	Method I: Zero span mode - direct measurement	102
F.4.3	Method II: Peak e.i.r.p. calculation	103

F.5 Max and mean PSD.....	104
Annex G (informative): Change History	106
History	107

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/af15833e-7e0e-4c36-ab39-e479b85a227/etsi-en-303-883-1-v1.2.0-2020-07>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This draft European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document is part 1 of a multi-part deliverable covering Short Range Devices (SRD) and Ultra Wide Band (UWB), as identified below:

Part 1: "Measurement techniques for transmitter requirements";

Part 2: " Measurement techniques for receiver requirements".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

Ultra Wide Band (UWB) radio technology enables a new generation of high-speed data devices for short-range communication purposes as well as location tracking and Sensor devices and opens new markets with a variety of innovative applications.

UWB devices may form an integral part of other portable electronic equipment such as future generation cellular phones or laptops equipped with UWB enabled short-range air interfaces.

In addition, UWB devices with an operating frequency range of several hundreds of MHz up to several GHz allow tens of centimetre-level accuracy real time localization and positioning even in the presence of severe multipath effects caused by walls, furniture or any other harsh radio propagation environments.

Based on the broad variety of different applications and the broad possible frequency range of operation the number of possible deployed physical signal formats can be very large. The existing range of physical signal and modulation formats range from traditional carrier based systems like OFDM over spread spectrum based system to carrier less systems based on base band pulses. The frequency regulation on the other side only defines a single set of transmission limits and values, which have to be fulfilled by all systems under the UWB regulation. Furthermore, the very high channel bandwidth of a UWB signal gives a specific challenge to the needed measurement setup and the procedures. Existing measurement methods need to be extended and new possible techniques should be described in the present document.

The present document is structured as follows:

- Clauses 1 through 3 provide a general description on the types of equipment covered by the present document and the definitions, symbols and abbreviations used.
- Clause 4 provides an overview on the technical and technology basics which were considered during the preparation of the present document.
- Clause 5 specifies EUT TX requirements and the related conformance procedure.
- Annex A provides information on test conditions, used test sites and procedures.
- Annex B provides necessary information radiated test procedures.
- Annex C provides information on TX signal types.
- Annex D provides information on the all emission concept.
- Annex E provides information for a pre-scan radiated power measurement test procedure.
- Annex F provides information on differences between the different emission power measurements.

1 Scope

The present document summarizes the available information of possible measurement techniques and procedures for the conformance measurement of various signal formats (e.g. Ultra Wide Band) in order to comply with the given transmission limits given in the current regulation.

The present document could be used as a reference for existing and future ETSI standards covering UWB and other technologies.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 102 754: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Technical characteristics of Detect And Avoid (DAA) mitigation techniques for SRD equipment using Ultra-Wideband (UWB) technology".
- [2] ETSI TS 102 321: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Normalized Site Attenuation (NSA) and validation of a fully lined anechoic chamber up to 40 GHz".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document, but they assist the user with regard to a particular subject area.

- [i.1] ETSI TS 103 060: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Method for a harmonized definition of Duty Cycle Template (DCT) transmission as a passive mitigation technique used by short range devices and related conformance test methods".
 - [i.2] ITU Radio Regulations.
- NOTE: Available at <https://www.itu.int/pub/R-REG-RR/en>.
- [i.3] ECC/DEC/(06)04: "ECC Decision of 24 March 2006 on the harmonised conditions for devices using UWB technology in bands below 10.6 GHz, amended 9 December 2011 and amended 8 March 2019".

- [i.4] ECC/DEC/(07)01: "ECC Decision of 30 March 2007 on the harmonised use, exemption from individual licensing and free circulation of Material Sensing Devices using Ultra-Wideband (UWB) technology, amended on 26 June 2009, corrected on 18 November 2016 and amended on 8 March 2019".
- [i.5] 2019/785/EC: "Commission Implementing Decision (EU) 2019/785 of 14 May 2019 on the harmonisation of radio spectrum for equipment using ultra-wideband technology in the Union and repealing Decision 2007/131/EC (notified under document C(2019) 3461)".
- [i.6] ECC/DEC/(11)02: "ECC Decision of 11 March 2011 on industrial Level Probing Radars (LPR) operating in frequency bands 6-8.5 GHz, 24.05-26.5 GHz, 57-64 GHz and 75-85 GHz", updated on 17 November 2017 and amended on 5 July 2019.
- [i.7] ERC/REC 70-03: "ERC Recommendation of 1997 on relating to the use of Short Range Devices (SRD)".

NOTE: Available at https://www.efis.dk/sitecontent.jsp?sitecontent=srd_regulations.

- [i.8] 2019/1345/EC: "Commission Implementing Decision (EU) 2019/1345 of 2 August 2019 amending Decision 2006/771/EC updating harmonised technical conditions in the area of radio spectrum use for short-range devices (notified under document C(2019) 5660)".
- [i.9] ERC/REC 74-01: "ERC Recommendation of 1998 on unwanted Emissions in the Spurious Domain, latest amendment on 29 May 2019".
- [i.10] Recommendation ITU-R SM.329-12 (09/2012): "Unwanted emissions in the spurious domain".
- [i.11] ECC/DEC(06)08: "ECC Decision of 1 December 2006 on the conditions for use of the radio spectrum by Ground- and Wall- Probing Radar (GPR/WPR) imaging systems", updated on 26 October 2018.
- [i.12] ETSI EN 302 372: "Short Range Devices (SRD); Tank Level Probing Radar (TLPR) equipment operating in the frequency ranges 4,5 GHz to 7 GHz, 8,5 GHz to 10,6 GHz, 24,05 GHz to 27 GHz, 57 GHz to 64 GHz, 75 GHz to 85 GHz; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU".
- [i.13] ECC/DEC/(04)03: "ECC Decision of 19 March 2004 on the frequency band 77-81 GHz to be designated for the use of Automotive Short Range Radars".
- [i.14] ETSI TR 103 181-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD) using Ultra Wide Band (UWB);Transmission characteristics Part 2: UWB mitigation techniques"
- [i.15] ETSI TR 103 181-1: "Short Range Devices (SRD) using Ultra Wide Band (UWB); Technical Report Part 1: UWB signal characteristics and overview CEPT/ECC and EC regulation".
- [i.16] ECC Report 120 (07/2008): "Technical requirements for UWB DAA (Detect and Avoid) devices to ensure the protection of radiolocation services in the bands 3.1 - 3.4 GHz and 8.5 - 9 GHz and BWA terminals in the band 3.4 - 4.2 GHz".
- [i.17] ETSI EG 203 367: "Guide to the application of harmonised standards covering articles 3.1b and 3.2 of the Directive 2014/53/EU (RED) to multi-radio and combined radio and non-radio equipment".
- [i.18] ETSI TR 100 028 (all parts) (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.19] Recommendation ITU-R SM.1754-0 (05/2006): "Measurement techniques of ultra-wideband transmissions".
- [i.20] ANSI C63.5-2017/Cor 1-2019: "American National Standard for Electromagnetic Compatibility- Radiated Emission Measurements in Electromagnetic Interference (EMI) Control - Calibration and Qualification of Antennas (9 kHz to 40 GHz) - Corrigendum 1".

- [i.21] ETSI TR 102 273 (all parts) (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [i.22] ETSI TR 102 215: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Recommended approach, and possible limits for measurement uncertainty for the measurement of radiated electromagnetic fields above 1 GHz".
- [i.23] ECC Report 064: "The protection requirements of radiocommunications systems below 10.6 GHz from generic UWB applications".
- [i.24] Recommendation ITU-R SM.1755-0 (05/2006): "Characteristics of ultra-wideband technology".
- [i.25] ETSI TR 102 347: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Equipment for Detecting Movement; Radio equipment operating around e.g. 5,8 GHz, 10 GHz, 25 GHz, 61 GHz, 77 GHz; System Reference Document for Tank Level Probing Radar (TLPR)".
- [i.26] ECC Report 139: "Impact of Level Probing Radars (LPR), using Ultra-Wideband Technology on Radiocommunications Services".
- [i.27] Recommendation ITU-R SM.1541-6 (08/2015): "Unwanted emissions in the out-of-band domain; SM Series".
- [i.28] ETSI EN 303 446-1: "ElectroMagnetic Compatibility (EMC) standard for combined and/or integrated radio and non-radio equipment; Part 1: Requirements for equipment intended to be used in residential, commercial and light industry locations".
- [i.29] ETSI EN 303 446-2: "ElectroMagnetic Compatibility (EMC) standard for combined and/or integrated radio and non-radio equipment; Part 2: Requirements for equipment intended to be used in industrial locations".
- [i.30] RBW influence on peak or mean power measurements of pulsed signals, Application Note 62019-1EF106-1E, 22.04.2020.

NOTE: Available at https://www.rohde-schwarz.com/pk/applications/rbw-influence-on-peak-or-mean-power-measurement-of-pulsed-signals-application-note_56280-648522.html.

- [i.31] ETSI EN 302 729-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Level Probing Radar (LPR) equipment operating in the frequency ranges 6 GHz to 8,5 GHz, 24,05 GHz to 26,5 GHz, 57 GHz to 64 GHz, 75 GHz to 85 GHz; Part 1: Technical characteristics and test methods".
- [i.32] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC (RED).

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

All Emissions (AE): related UWB Emission of the transmitter (RP), transmitter unwanted emissions (TXUE) and Other Emissions (OE) of the EUT

NOTE: See Emission concept in clause 5.1.2.1.

antenna cycle: one complete sweep of a mechanically or electronically scanned antenna beam along a predefined spatial path

antenna scan duty factor: ratio of the solid angle of the antenna beam (measured at its 3 dB point) to the total solid angle scanned by the antenna

associated antenna: antenna and all its associated components which are designed as an indispensable part of the equipment

avoidance level: maximum amplitude to which the UWB transmit power is set for the relevant protection zone

burst: emitted signal whose time duration (T_{on}) is not related to its bandwidth

co-located receiver: receiver is located in the same device housing as the transmitter

combined equipment: any combination of non-radio equipment and a plug-in radio device that would not offer full functionality without the radio device

dedicated antenna: removable antenna supplied and tested with the radio equipment, designed as an indispensable part of the equipment

default avoidance bandwidth: portion of the victim service bandwidth to be protected if no enhanced service bandwidth identification mechanisms are implemented in the DAA enabled devices

detect and avoid time: time duration between a change of the external RF environmental conditions and adaptation of the corresponding UWB operational parameters

Duty Cycle: the ratio, expressed as a percentage, of $\Sigma(T_{on})/(T_{obs})$ where T_{on} is the "on" time of a single transmitter device and T_{obs} is the observation period, see ETSI TS 103 060 [1.1]

Effective Radiated Power (E.R.P.): product of the power supplied to the antenna and its gain relative to a half-wave dipole in a given direction (RR 1.162)

equivalent isotopically radiated power (e.i.r.p.): product of the power supplied to the antenna and the antenna gain in a given direction relative to an isotropic antenna (absolute or isotropic gain)

NOTE: See ITU Radio Regulations [1.2], RR 1.161

far field measurement: measurement at a distance from an antenna sufficient to ensure that the electro-magnetic field approximates a plane wave (see clause B.2.1)

frequency span: frequency range between the start and stop frequency of the RP measurement set-up

gating: transmission that is intermittent or of a low duty cycle referring to the use of burst transmissions where a transmitter is switched on and off for selected time intervals

hopping: spread spectrum technique whereby individual radio links are continually switched from one subchannel to another

hopping cycle: number of hopping positions for a full frequency hopping sequence

host equipment: any equipment which has complete user functionality when not connected to the radio equipment part and to which the radio equipment part provides additional functionality and to which connection is necessary for the radio equipment part to offer functionality

impulse: pulse whose width is determined by its dc step risetime and whose maximum amplitude is determined by its dc step value

integral antenna: permanent fixed antenna, which may be built-in, designed as an indispensable part of the equipment

indirect emissions: emissions radiated in all directions in a specified scenario (see clause 5.7, including direct emissions from the housing/structure of the equipment and emissions reflected or passing through a media under inspection or through a scenario)

NOTE: These emissions are sometimes also named an exterior limit or unwanted emissions.

main beam direction: direction of maximum gain of a directional antenna

NOTE: EUT may have different main beam direction for TX and RX antennas.