



# SLOVENSKI STANDARD SIST ISO 14687-2:2021

01-julij-2021

---

## Vodik kot gorivo - Specifikacija izdelka - 2. del: Gorivne celice z membrano za protonsko izmenjavo (PEM) za cestna vozila

Hydrogen fuel - Product specification - Part 2: Proton exchange membrane (PEM) fuel cell applications for road vehicles

### iTeh STANDARD PREVIEW

Carburant hydrogène - Spécification de produit - Partie 2: Applications des piles à combustible à membrane à échange de protons (MEP) pour les véhicules routiers

[SIST ISO 14687-2:2021](https://standards.iteh.ai/catalog/standards/sist/14687-2-2021/14284-a5e4-0f29e591adfc/sist-iso-14687-2-2021)

Ta slovenski standard je istoveten z: [ISO 14687-2:2012](https://standards.iteh.ai/catalog/standards/sist/14687-2-2021/14284-a5e4-0f29e591adfc/sist-iso-14687-2-2021)

---

#### ICS:

43.060.40	Sistemi za gorivo	Fuel systems
71.100.20	Industrijski plini	Gases for industrial application

**SIST ISO 14687-2:2021**

**en,fr,de**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 14687-2:2021](#)

<https://standards.iteh.ai/catalog/standards/sist/1b59b2f1-a308-4284-a5e4-0f29e591adfc/sist-iso-14687-2-2021>

INTERNATIONAL  
STANDARD

ISO  
14687-2

First edition  
2012-12-01

---

---

**Hydrogen fuel — Product  
specification —**

**Part 2:  
Proton exchange membrane (PEM)  
fuel cell applications for road vehicles**

**iTeh STANDARD PREVIEW**  
*Carburant hydrogène — Spécification de produit —*

*(standards.iteh.ai)*  
*Partie 2: Applications des piles à combustible à membrane à échange  
de protons (MEP) pour les véhicules routiers*

SIST ISO 14687-2:2021

<https://standards.iteh.ai/catalog/standards/sist/1b59b2f1-a308-4284-a5e4-0f29e591adfc/sist-iso-14687-2-2021>



Reference number  
ISO 14687-2:2012(E)

© ISO 2012

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST ISO 14687-2:2021

<https://standards.iteh.ai/catalog/standards/sist/1b59b2f1-a308-4284-a5e4-0f29e591adfc/sist-iso-14687-2-2021>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Requirements</b> .....	<b>2</b>
4.1 Classification.....	2
4.2 Applications.....	2
4.3 Limiting characteristics.....	3
<b>5 Hydrogen fuel qualification test</b> .....	<b>3</b>
5.1 General requirements.....	3
5.2 Report results.....	4
<b>6 Sampling</b> .....	<b>4</b>
6.1 Sample size.....	4
6.2 Gaseous hydrogen.....	4
6.3 Particulates in gaseous hydrogen.....	4
6.4 Liquid hydrogen.....	4
<b>7 Analytical methods</b> .....	<b>4</b>
7.1 General.....	4
7.2 Parameters of analysis.....	5
7.3 Water content.....	5
7.4 Total hydrocarbon content.....	5
7.5 Oxygen content.....	5
7.6 Helium content.....	6
7.7 Argon and nitrogen contents.....	6
7.8 Carbon dioxide content.....	6
7.9 Carbon monoxide content.....	6
7.10 Total sulfur content.....	6
7.11 Formaldehyde content.....	6
7.12 Formic acid content.....	7
7.13 Ammonia content.....	7
7.14 Total halogenated compounds content.....	7
7.15 Particulates concentration.....	7
<b>8 Detection limit and determination limit</b> .....	<b>7</b>
<b>9 Quality assurance</b> .....	<b>8</b>
9.1 On-site fuel supply.....	8
9.2 Off-site fuel supply.....	8
<b>10 Safety</b> .....	<b>8</b>
<b>Annex A (informative) Rationale for the selection of hydrogen contaminants</b> .....	<b>9</b>
<b>Annex B (informative) Suggested analytical and sampling methods with detection and determination limits</b> .....	<b>11</b>
<b>Annex C (informative) One common practice of quality assurance for hydrogen production processes that utilize reforming processes associated with pressure swing adsorption (PSA) purification</b> .....	<b>13</b>
<b>Bibliography</b> .....	<b>15</b>

## ISO 14687-2:2012(E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 14687-2 was prepared by Technical Committee ISO/TC 197, *Hydrogen technologies*.

This first edition of ISO 14687-2 cancels and replaces the first edition of ISO/TS 14687-2:2008.

ISO 14687 consists of the following parts, under the general title *Hydrogen fuel — Product specification*:

- Part 1: All applications except proton exchange membrane (PEM) fuel cell for road vehicles
- Part 2: Proton exchange membrane (PEM) fuel cell applications for road vehicles
- Part 3: Proton exchange membrane (PEM) fuel cell applications for stationary appliances

SIST ISO 14687-2:2021  
<https://standards.iteh.ai/catalog/standards/sist/1b59b2f1-a308-4284-a5e4-0f29e591adfc/sist-iso-14687-2-2021>

## Introduction

This part of ISO 14687 specifies two grades of hydrogen fuel, “Type I, grade D” and — Type II, grade D. These grades are intended to apply to the interim stage of proton exchange membrane (PEM) fuel cells for road vehicles (FCV) on a limited production scale.

It is also noted that this part of ISO 14687 has been prepared based on the research and development focusing on the following items:

- PEM catalyst and fuel cell components tolerance to hydrogen fuel contaminants;
- effects/mechanisms of contaminants on fuel cell systems and components;
- contaminant measurement techniques for laboratory, production, and in-field operations;
- onboard hydrogen storage technology;
- vehicle demonstration results.

Since the FCV and related technology are developing rapidly, this part of ISO 14687 needs to be revised according to technological progress as necessary. Technical Committee ISO/TC 197, *Hydrogen Technologies*, will monitor this technology trend.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 14687-2:2021](https://standards.iteh.ai/catalog/standards/sist/1b59b2f1-a308-4284-a5e4-0f29e591adfc/sist-iso-14687-2-2021)

<https://standards.iteh.ai/catalog/standards/sist/1b59b2f1-a308-4284-a5e4-0f29e591adfc/sist-iso-14687-2-2021>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 14687-2:2021](#)

<https://standards.iteh.ai/catalog/standards/sist/1b59b2f1-a308-4284-a5e4-0f29e591adfc/sist-iso-14687-2-2021>



# Hydrogen fuel — Product specification —

## Part 2:

# Proton exchange membrane (PEM) fuel cell applications for road vehicles

## 1 Scope

This part of ISO 14687 specifies the quality characteristics of hydrogen fuel in order to ensure uniformity of the hydrogen product as dispensed for utilization in proton exchange membrane (PEM) fuel cell road vehicle systems.

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6145 (all parts), *Gas analysis — Preparation of calibration gas mixtures using dynamic volumetric methods*

ISO 14687-1, *Hydrogen fuel — Product specification — Part 1: All applications except proton exchange membrane (PEM) fuel cell for road vehicles*

[SIST ISO 14687-2:2021](https://standards.iteh.ai/catalog/standards/sist/1b59b2f1-a308-4284-a5e4-0f29e591adfc/sist-iso-14687-2-2021)

## 3 Terms and definitions

<https://standards.iteh.ai/catalog/standards/sist/1b59b2f1-a308-4284-a5e4-0f29e591adfc/sist-iso-14687-2-2021>

For the purposes of this document, the terms and definitions given in ISO 14687-1 and the following apply.

### 3.1

#### **constituent**

component (or compound) found within a hydrogen fuel mixture

### 3.2

#### **contaminant**

impurity that adversely affects the components within the fuel cell system or the hydrogen storage system

NOTE An adverse effect can be reversible or irreversible.

### 3.3

#### **detection limit**

lowest quantity of a substance that can be distinguished from the absence of that substance with a stated confidence limit

### 3.4

#### **determination limit**

lowest quantity which can be measured at a given acceptable level of uncertainty

### 3.5

#### **fuel cell system**

power system used for the generation of electricity on a fuel cell vehicle, typically containing the following subsystems: fuel cell stack, air processing, fuel processing, thermal management and water management

**ISO 14687-2:2012(E)****3.6****hydrogen fuel index**

fraction or percentage of a fuel mixture that is hydrogen

**3.7****irreversible effect**

effect, which results in a permanent degradation of the fuel cell power system performance that cannot be restored by practical changes of operational conditions and/or gas composition

**3.8****on-site fuel supply**

hydrogen fuel supplying system with a hydrogen production system in the same site

**3.9****off-site fuel supply**

hydrogen fuel supplying system without a hydrogen production system in the same site, receiving hydrogen fuel which is produced out of the site

**3.10****particulate**

solid or aerosol particle that can be entrained somewhere in the delivery, storage, or transfer of the hydrogen fuel

**3.11****reversible effect**

effect, which results in a temporary degradation of the fuel cell power system performance that can be restored by practical changes of operational conditions and/or gas composition

ITEH STANDARD PREVIEW  
(standards.iteh.ai)

**4 Requirements**

[SIST ISO 14687-2:2021](https://standards.iteh.ai/catalog/standards/sist/1b59b2f1-a308-4284-a5e4-0f29e591adfc/sist-iso-14687-2-2021)

**4.1 Classification**

<https://standards.iteh.ai/catalog/standards/sist/1b59b2f1-a308-4284-a5e4-0f29e591adfc/sist-iso-14687-2-2021>

Hydrogen fuel for PEM fuel cell applications for road vehicles shall be classified according to the following types and grade designations:

- a) Type I (grade D): Gaseous hydrogen
- b) Type II (grade D): Liquid hydrogen

**4.2 Applications**

The following information characterizes representative applications of each type and grade of hydrogen fuel. It is noted that suppliers commonly transport hydrogen of a higher quality than some users may require.

Type I (grade D) Gaseous hydrogen fuel for PEM fuel cell road vehicle systems

Type II (grade D) Liquid hydrogen fuel for PEM fuel cell road vehicle systems

NOTE 1 Type I, grade A, B, C, Type II, grade C and Type III, which are applicable for all applications except PEM fuel cells applications, are defined in ISO 14687-1.

NOTE 2 There is no equivalent grade A and B for Type II fuels.

NOTE 3 Hydrogen fuel specifications applicable to PEM fuel cell applications for stationary appliances are addressed in ISO 14687-3.

### 4.3 Limiting characteristics

The fuel quality requirements at the dispenser nozzle applicable to the aforementioned grades of hydrogen fuel for PEM fuel cells in road vehicles shall meet the requirements of Table 1. The fuel specifications are not process or feed stock specific. Non-listed contaminants have no guarantee of being benign.

NOTE Annex A provides the rationale for the selection of the impurities specified in Table 1.

**Table 1 — Directory of limiting characteristics**

Characteristics (assay)	Type I, Type II
	Grade D
Hydrogen fuel index (minimum mole fraction) <sup>a</sup>	99,97 %
Total non-hydrogen gases	300 µmol/mol
<b>Maximum concentration of individual contaminants</b>	
Water (H <sub>2</sub> O)	5 µmol/mol
Total hydrocarbons <sup>b</sup> (Methane basis)	2 µmol/mol
Oxygen (O <sub>2</sub> )	5 µmol/mol
Helium (He)	300 µmol/mol
Total Nitrogen (N <sub>2</sub> ) and Argon (Ar) <sup>b</sup>	100 µmol/mol
Carbon dioxide (CO <sub>2</sub> )	2 µmol/mol
Carbon monoxide (CO)	0,2 µmol/mol
Total sulfur compounds <sup>c</sup> (H <sub>2</sub> S basis)	0,004 µmol/mol
Formaldehyde (HCHO)	0,01 µmol/mol
Formic acid (HCOOH)	0,2 µmol/mol
Ammonia (NH <sub>3</sub> )	0,1 µmol/mol
Total halogenated compounds <sup>d</sup> (Halogenate ion basis)	0,05 µmol/mol
Maximum particulates concentration	1 mg/kg
For the constituents that are additive, such as total hydrocarbons and total sulfur compounds, the sum of the constituents are to be less than or equal to the acceptable limit.	
<sup>a</sup> The hydrogen fuel index is determined by subtracting the “total non-hydrogen gases” in this table, expressed in mole percent, from 100 mole percent.	
<sup>b</sup> Total hydrocarbons include oxygenated organic species. Total hydrocarbons shall be measured on a carbon basis (µmolC/mol). Total hydrocarbons may exceed 2 µmol/mol due only to the presence of methane, in which case the summation of methane, nitrogen and argon shall not exceed 100 µmol/mol.	
<sup>c</sup> As a minimum, total sulphur compounds include H <sub>2</sub> S, COS, CS <sub>2</sub> and mercaptans, which are typically found in natural gas.	
<sup>d</sup> Total halogenated compounds include, for example, hydrogen bromide (HBr), hydrogen chloride (HCl), chlorine (Cl <sub>2</sub> ), and organic halides (R-X).	

## 5 Hydrogen fuel qualification test

### 5.1 General requirements

Quality verification requirements for the qualification tests shall be performed at the dispenser nozzle under applicable standardized sampling and analytical methods where available. Alternatively, the quality verification requirements may be performed at other locations or under other methods acceptable to the supplier and the customer.