### INTERNATIONAL STANDARD

ISO 2575

Eighth edition 2010-07-01 **AMENDMENT 1** 2011-07-15

### Road vehicles — Symbols for controls, indicators and tell-tales

**AMENDMENT 1** 

Véhicules routiers — Symboles pour les commandes, indicateurs et témoins

iTeh STANDEMEND PREVIEW (standards.iteh.ai)

ISO 2575:2010/Amd 1:2011 https://standards.iteh.ai/catalog/standards/sist/3a589383-4609-433a-8994-349077e1dbe6/iso-2575-2010-amd-1-2011



### iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 2575:2010/Amd 1:2011 https://standards.iteh.ai/catalog/standards/sist/3a589383-4609-433a-8994-349077e1dbe6/iso-2575-2010-amd-1-2011



#### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2011

Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

ii

#### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to ISO 2575:2010 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 13, *Ergonomics applicable to road vehicles*.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 2575:2010/Amd 1:2011 https://standards.iteh.ai/catalog/standards/sist/3a589383-4609-433a-8994-349077e1dbe6/iso-2575-2010-amd-1-2011

## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 2575:2010/Amd 1:2011 https://standards.iteh.ai/catalog/standards/sist/3a589383-4609-433a-8994-349077e1dbe6/iso-2575-2010-amd-1-2011

# Road vehicles — Symbols for controls, indicators and tell-tales AMENDMENT 1

Symbol number	Symbol form/shape	Symbol description/application	ISO/IEC registration number
A.33		Position lights, trailer	ISO 7000-2953
A.34		Interior light, trailer  ANDARD PREVIEW  andards.iteh.ai)	ISO 7000-2954
A.35	https://stoncords.teh.a	Snowplough lights ISO 25/5:2010/Amd 1:2011 i/catalog/standards/sist/3a589383-4609-433a-8994- 7e1dbe6/iso-2575-2010-amd-1-2011	ISO 7000-2955
A.36		Automatic high beam  The letter "A" may be deleted and replaced by "AUTO" added below the symbol.	ISO 7000-2956
A.37		Automatic low beam  The letter "A" may be deleted and replaced by "AUTO" added below the symbol.	ISO 7000-2957
D.43		Interior temperature, trailer	ISO 7000-2958

Symbol number	Symbol form/shape	Symbol description/application	ISO/IEC registration number
F.27		Diesel exhaust fluid (DEF)  Emission clouds and droplets may be replaced by the word "UREA" or the typical name of reduction agent (e.g. trade name).  NOTE F.27 is interchangeable with F.24.	ISO 7000-2946
F.28	STOP	Engine stop required  "STOP" may be placed inside the engine shape, in which case "STOP" should be as large as possible.  Red tell-tale indicates a hazard warning.	ISO 7000-3026
H.17		Transmission service	ISO 7000-2959
K.23		Obstacle detection, proximity of vehicle Sensor waves may be removed or relocated to better represent the actual sensor detection zone.  (standards.iteh.ai)	ISO 7000-2961
K.24	Ntt s://standa	Rest break 75:2010/Amried 12011  Rest break 75:2010/Amried 12011  The shape of the cup and saucer may be adjusted.	ISO 7000-3028
L.20		Hood release, truck	ISO 7000-2962
L.21		Forward motion inhibited, truck	Application of ISO 7000-3029
N.04		Head-up display (HUD)	ISO 7000-2963

3

Symbol number	Symbol form/shape	Symbol description/application	ISO/IEC registration number
N.08		eCall, emergency call	ISO 7000-2964
		The phone icon may be reoriented or omitted.	
	SOS		
Y.06	Г	Economic vehicle operation	Informative
	ECO	May be used either alone or as a supplement to a symbol showing any energy saving mode.	
Y.07		Ready state	Informative
1.07	READY	May be used either alone or as a supplement to a symbol to indicate "ready for operation" for any system state that needs human intervention to proceed.	miormative

### iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 2575:2010/Amd 1:2011 https://standards.iteh.ai/catalog/standards/sist/3a589383-4609-433a-8994-349077e1dbe6/iso-2575-2010-amd-1-2011

© ISO 2011 – All rights reserved

ISO 2575:2010/Amd.1:2011(E)

### iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 2575:2010/Amd 1:2011 https://standards.iteh.ai/catalog/standards/sist/3a589383-4609-433a-8994-349077e1dbe6/iso-2575-2010-amd-1-2011

ICS 01.080.20; 43.040.30

Price based on 3 pages