INTERNATIONAL STANDARD

Fourth edition 2013-03-01

Bases for design of structures — Names and symbols of physical quantities and generic quantities

Bases du calcul des constructions — Noms et symboles des grandeurs physiques et grandeurs génériques

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 3898:2013</u> https://standards.iteh.ai/catalog/standards/sist/2c6c804f-4b43-4966-aa53-9357f3ed2f0d/iso-3898-2013



Reference number ISO 3898:2013(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 3898:2013</u> https://standards.iteh.ai/catalog/standards/sist/2c6c804f-4b43-4966-aa53-9357f3ed2f0d/iso-3898-2013



COPYRIGHT PROTECTED DOCUMENT

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Page

Contents

Forew	vord		iv		
0	Intro	duction	v		
1	Scope				
2	Norn	native references	1		
3	Names and symbols for physical quantities and units				
	3.1	General rules and method for forming and writing names and symbols			
	3.2	Rules and method for forming and writing names and symbols of physical quantities			
	3.3	Rules for forming and writing names and symbols of units			
	3.4	Additional rules for forming of symbols	5		
	3.5	Tables	6		
Anne	x A (no	ormative) Definition and scope of generic quantities			
Biblic	ograph	y	41		

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 3898:2013</u> https://standards.iteh.ai/catalog/standards/sist/2c6c804f-4b43-4966-aa53-9357f3ed2f0d/iso-3898-2013

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 3898 was prepared by Technical Committee ISO/TC 98, *Bases for design of structures*, Subcommittee SC 1, *Terminology and symbols*.

This fourth edition cancels and replaces the third edition (ISO 3898:1997), which has been technically revised. **iTeh STANDARD PREVIEW**

The main reasons for this fourth edition of ISO 3898 are (Standards.iteh.ai)

- application of new techniques and methods in the analysis and design of structures, e.g. probabilistic and partial factor methods, introduction of <u>codes</u> for new design situations, and more advanced materials have increased the need for cat more fundamental set of rules for the formation and presentation of symbols, and
 9357fBed2f0d/iso-3898-2013
- revisions of the ISO Guide 31 series for the International System of Units (S.I.).

The major technical changes from the previous edition are the following:

- the normative references have been updated; particularly with regard to the ISO 80000 series;
- the so-called 'kernel-index-method' for forming and writing names and new (compound) symbols is presented;
- the presentation of the (tables of) indices has been altered in accordance herewith;
- the concept of 'generic quantities' is introduced (<u>Annex A</u>).

0 Introduction

0.1 The concept of a 'physical quantity'

The concept of a 'physical quantity' is, according to ISO/IEC Guide 99, defined by the following descriptive statement: an attribute of a phenomenon, body or substance that can be distinguished qualitatively and determined quantitatively.

The concept 'physical quantity' is designated by a name [= a verbal designation of an individual concept (see 3.4.2 of ISO 1087-1:2000)] and a corresponding symbol.

A physical quantity is characterized by its unique dimension. The dimension of a physical quantity is expressed in units (of measurement).

NOTE 1 According to the ISO/IEC Directives, Part 2 for drafting International Standards, SI units are applied.

NOTE 2 Physical quantities can be dimensionless, e.g. often the case with factors. In that case their dimension is noted as 1.

The names and symbols of the most important physical quantities (according ISO/IEC Guide 99: physical quantities in a general sense) - and their characterizing units - within the field of physical sciences and technology are given in ISO 80000-1. However, this is a limited set of names and symbols.

0.2 General method for forming and writing names and symbols of physical quantities

The names and symbols of the most important physical quantities (and their units) within the field of the design of structures are given in this document: see the Tables 2 to $\frac{4}{2}$ of this International Standard (but necessarily there will/must be some overlap with ISO 80000-1).

This set of names and symbols is also limited, but with the help of the method given in this International Standard (*kernel-index-method*) the user will be able to form/compose new and unique (compound) symbols for a wide variety of physical quantities (according ISO/IEC Guide 99: particular physical quantities). 9357Bed2f0d/iso-3898-2013

Adapted 'reading' of the compound symbols moreover enables the user to designate and particularize the corresponding unique names of the physical quantities (see examples in <u>3.2.2.5</u> and <u>3.2.2.8</u>).

The method itself is presented/worked-out in <u>3.1</u> of this International Standard, the kernel of a compound symbol is given in or has to be chosen from the above mentioned <u>Tables 2</u> to <u>4</u> and the indices forming that unique (compound) symbol (mostly subscripts) are given in or have to be chosen from <u>Tables 5</u> to <u>10</u>.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 3898:2013</u> https://standards.iteh.ai/catalog/standards/sist/2c6c804f-4b43-4966-aa53-9357f3ed2f0d/iso-3898-2013

Bases for design of structures — Names and symbols of physical quantities and generic quantities

1 Scope

This International Standard covers physical quantities in a general sense. The kernel-index-method enables to form (compound) symbols of physical quantities related to a particular material and/or a particular technical field of design of structures.

It also gives the main names, symbols, and units for physical quantities within the field of design of structures.

<u>Annex A</u> in a general sense covers 'generic quantities' which are genuine to this field. The kernel-indexmethod can likewise be applied.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 80000-1, Quantities and units Part 1: General PREVIEW

ISO 80000-2, Quantities and units Part 2: Mathematical signs and symbols to be used in the natural sciences and technology

ISO 3898:2013 ISO 80000-3, Quantities/and units et al. Part 3:/Space and times04f-4b43-4966-aa53-ISO 80000-4, Quantities and units — Part 4: Mechanics

3 Names and symbols for physical quantities and units

3.1 General rules and method for forming and writing names and symbols

The kernel of a (compound) symbol can be chosen from <u>Tables 2</u>, <u>3</u> and <u>4</u> and indices (mostly subscripts) forming that unique (compound) symbol can be chosen from <u>Tables 5</u> to <u>10</u>.

NOTE 1 The rules are mainly adopted from the ISO 80000 series. In <u>3.2</u> the 'kernel-index-method' (KIM) has been formulated for the first time in an ISO International Standard. The method stems from the mathematical disciplines: Riemannian geometry and Affinor/Tensor analysis (Second half of nineteenth century).

NOTE 2 ISO 10241 can be used as a basis for formulating the correct name and definition of terms and quantities.

3.2 Rules and method for forming and writing names and symbols of physical quantities

3.2.1 Names

The name (in general) of a general physical quantity is (mostly) one term, being a noun, written in Latin lower case letter symbols in Roman (upright) type.

For several systems of physical quantities the names (and the symbols) of some physical quantities in a general sense are given in the ISO 80000 series. For the design of structures the system of physical quantities in a general sense is given in the <u>Tables 2</u>, <u>3</u> and <u>4</u> of this International Standard.

In case of the name of a new or a particular physical quantity a new name/term can be chosen/composed, for instance, by combining the name of an already existing physical quantity with all kinds of other terms.

For some terms like: coefficient, factor, parameter, number, ratio, level and constant, some guidance for applying them is given in ISO 80000-1.

EXAMPLE 1 One term of a physical quantity: area, thickness, force, strength, factor, etc.

EXAMPLE 2 A combination of (one of the above mentioned terms with other) terms:

- maximum area, nominal thickness of a flange, design value of a force,
- admissible (value of the) strength of timber in direction *x*, friction factor, etc.

3.2.2 Symbols

The following applies to the forming and notation of symbols:

3.2.2.1 The symbol of a physical quantity is a one-letter symbol, the kernel, written in italic type.

NOTE There is one exception: a characteristic number has two letter symbols, see ISO 80000-11.

3.2.2.2 A letter symbol for a kernel can be a lower case or an upper case letter symbol of the Latin or the Greek alphabet (see <u>Tables 2</u>, <u>3</u> and <u>4</u>). In most cases the choice for a kernel of a physical quantity shall be based on considerations of dimension or the main usage, as given in <u>Table 1</u> of this International Standard. A dimension or a main usage of a physical quantity not included in <u>Table 1</u> shall comply the nearest appropriate category listed.

(standards.iteh.ai)

3.2.2.3 The kernel may be modified by applying one or more subscripts/indices (and sometimes superscripts), a so-called: compound symbol. <u>ISO 3898:2013</u>

https://standards.iteh.ai/catalog/standards/sist/2c6c804f-4b43-4966-aa53-

3.2.2.4 Subscripts/indices may be formed from letter symbols, digits and graphical symbols: they are written in Roman (upright) type. If the kernel of a physical quantity is used as a subscript/index it is written in italic type. Several kinds of subscripts/indices are given in the <u>Tables 5</u> to <u>10</u>.

3.2.2.5 A subscript/index is placed at the bottom right position of the kernel. By applying more than one subscript/index (sometimes superscript) the distinct indices should preferably be separated by a semi-colon (;). In the case of simple and clear, distinctive index symbols also a space or comma (,) is allowed. For simply two or three of these index symbols no separation at all may be appropriate.

NOTE Other positions, e.g. at the upper right, are possible too. However, in general these positions are reserved for other applications.

EXAMPLES

F _{ext}	external force;
K _{nom}	nominal (value of) external couple;
N_{x}, V_{y}, V_{z}	normal and shear forces in a cross-section of a beam;
M_{y}, M_{z}, T_{x}	bending and torsional moments in a cross-section of a beam;
m_{xx} , m_{yy} , m_{xy}	internal bending and torsional moments per length in a plate or shell;
Wser	serviceability limit (state) of deflection;
fu	ultimate limit (state) of strength;
ε_x , 1/2 γ_z , ε_y	two-dimensional normal and shear strains in general;
γ _R	partial factor for the transfer of material properties, geometry of structure and actions into resistance of structure;
γs	partial factor for the transfer of actions, geometry of structure and material prop- erties into response of structure;
v _{sat}	humidity per volume at saturation.
	iTeh STANDARD PREVIEW

3.2.2.6 By applying more than one subscript/index, the order of the subscripts/indices is from right to left as follows (if necessary/relevant the same rules can be applied for superscripts):

General format (*K*: kernel of a physical quantity virto i: indices):

	https://standards.iteh.ai/catalog/standards/sist/2c6c804f-4b43-4966-aa53-
K _{vi;v;iv;iii;ii;i}	9357f3ed2f0d/iso-3898-2013

- index i): subscripts/indices related to probabilistic and partial factor methods of analysis and design;
- EXAMPLES rep(resentative), nom(inal), k (characteristic), d(esign), etc.;
- index ii): subscripts/indices related to types of limit state;
- EXAMPLES u(ltimate), ser(viceability), fat(igue), fi(re), etc.;
- index iii): subscripts/indices related to various aspects;

EXAMPLES g(uaranteed), max(imum), obs(erved), *i*, *j* (ordinal numbers), etc.;

index iv): subscripts/indices related to the Basic variables and the Performance functionals. The preferred order is: first the indices 'S', 's' and 'R', 'r', then the other indices iv).

EXAMPLES

Basic variables:

F: f	f	(Action in	general, I	Loadcase),	a(ccidental)), g (permanent)	, sn(ow),etc.;
------	---	------------	------------	------------	--------------	--------	------------	----------------

- GE: ge (Geometry of structure in general);
- M: m (Material property in general), el(asticity), cr(eepiness), etc.;

ISO 3898:2013(E)

Performance functionals:

- S: s (Response of structure, Sequel or Effect of action(s), Action-effect), dyn(amical), sli(ding), etc.; NOTE Sometimes deviating from S, the symbol E is used, e.g. in a number of Eurocodes, and erroneously in ISO 22111:2007.
- R: r (Resistance of structure, Capacity), frac(tional), fat(igue), etc.

index v): subscripts/indices related to (1) place, then to (2) direction;

EXAMPLES 1 (joint, knot, point, foundation) A, B, C, ..., a, b, c, ..., 1, 2, 3, ..., etc.;

EXAMPLES 2 x, y, z, //, etc.

index vi): subscripts/indices related to types of material;

EXAMPLES c(oncrete), ma(sonry), etc.

3.2.2.7 If, by applying the subscripts/indices i to vi (or superscripts), the dimension of the original physical quantity does not change, so $\langle K \rangle = \langle K_{index} \rangle$, such subscripts/indices are called descriptive subscripts/indices (or superscripts).

3.2.2.8 A (compound) symbol is written without a final full stop (except for normal punctuation).

EXAMPLES

iTeh STANDARD PREVIEW

physical quantities with names with ostandards.iteh symbol

area	<u>ISO 3898:2013</u>	Α		
thickness	https://standards.iteh.ai/catalog/standards/sist/2c6 9357f3ed2f0d/iso-3898-20	c804f-4b43-4966-aa53-)15		
force		F		
strength		f		
factor		μ		
physical quantities with names as a combination of terms symbol				
maximum area		A _{max}		
nominal thickness of a fla	nge	t _{fl;nom}		
design (value of a) force	F _d			
admissible (value of the) s	fti; <i>xx</i> ;adm			
friction factor	$\mu_{ m fric}$			

NOTE For the equivalent rules in the case of generic quantities reference here is made to A.4.3.

3.3 Rules for forming and writing names and symbols of units

NOTE This International Standard adopts (the rules of) the International System of units (SI).

3.3.1 Names

All names are given in ISO 80000-1. The names are written in Latin lower case letter.

EXAMPLES

(7) base units: metre, kilogram, second, ampere, kelvin, mole and candela;

(18+3) derived units: newton, pascal, radian, etc.;

(20 prefixes for) multiples of units: (multiple:) megapascal, etc.; (sub-multiple:) millimetre, etc.;

compound units: newton metre, metre per second, etc.

3.3.2 Symbols

The symbol of a unit is only (a kernel of) one or more successive separate (mostly) Latin lower and/or upper case letter symbols, written in Roman (upright) type (irrespective of the type used in the rest of the text).

EXAMPLES m, K, kg, s, N, Pa, rad, MPa, mm, etc.

No subscripts (and superscripts) are allowed.

The symbol of a compound unit: a multiplication is indicated by one space or a half-high dot and a division can be indicated by a solidus (/).

EXAMPLES N·m or N m, m/s or m s⁻¹, etc.

A (compound) symbol is written without a final full stop (except for normal punctuation) and shall be placed after the numerical value, leaving a space between that value and the unit symbol.

EXAMPLE $F = 10_{h} \Re_{P} k N_{h} etclards.iteh.ai/catalog/standards/sist/2c6c804f-4b43-4966-aa53-$

9357f3ed2f0d/iso-3898-2013

3.4 Additional rules for forming of symbols

3.4.1 Symbols of physical quantities

3.4.1.1 Subscripts/indices

In most cases a subscript/index may be selected from the <u>Tables 5</u> to <u>11</u>. If other subscripts/indices (or superscripts) are used a clear definition of their meaning shall be given.

3.4.1.2 Precautions

In preventing confusion the following precautions shall be taken:

- where there is a possibility of confusing 1 (numeral) with *l* (letter symbol), the letter symbol *L* or ℓ shall be used in place of the letter symbol *l*;
- the Latin upper case letter symbol *O* shall not be used as a main letter symbol owing to the possibility of confusion with the numeral 0 (zero). The Latin lower case letter symbol *o* may, however, be used as a subscript/index with the same meaning as the numeral 0 (zero);
- the Greek lower case letter symbols iota (l), omicron (o) and upsilon (v) shall not be used owing to the possibility of confusing them with various Latin letter symbols. For the same reason, it is recommended to avoid, as far as possible, the use of the Greek lower case letter symbols kappa (κ) and chi (χ). If the Greek lower case letter symbols eta (η), mu (μ) and omega (ω) are used, care must be taken in writing these letter symbols to avoid confusion with the Latin lower case letter symbols n, u and w.

3.4.2 Kernel-extending-subscripts/indices

In contrast with a descriptive subscript/index by applying a so-called 'kernel-extending-subscript/index' (k-e-index), the dimension of the (original) physical quantity will be changed (slightly). The order of both types of subscripts/indices is as follows (the graphical symbol ' | ' separates the descriptive indices from the kernel-extending-indices):

*K*_{k-e-index}|descriptive indices

or

*K*_{k-e-index|vi;v;iv;iii;ii;i}

A kernel-extending-subscript/index can be one of the types vi to i and if more than one k-e-index is necessary the order of these subscripts/indices shall conform to <u>3.2.2.6</u>.

EXAMPLE By applying descriptive subscripts/indices the dimension of the original physical quantity X does not change, so $\langle X \rangle = \langle X_{|vi;...;i} \rangle$. But in particular cases the dimension of $\langle X_{index|} \rangle$ will be (slightly) altered, so $\langle X \rangle \neq \langle X_{vi;...;i} \rangle$.

Compare the following physical quantities, viz. the original physical quantity X versus the particular physical quantity X_{index} :

'force' (*X*) versus 'force per area' (*X*_{index}) or 'number' (*X*) versus 'number per year' (*X*_{index}), etc.

In some cases, for the symbol of the particular physical quantity, this International Standard gives another, new kernel, e.g.: (standards.iteh.ai)

symbol of the physical quantity 'force': F with [F] = N versus the symbol of the physical quantity 'force per area': ISO 3898:2013

p with $[p] = N/m^2$. https://standards.iteh.ai/catalog/standards/sist/2c6c804f-4b43-4966-aa53-9357f3ed2f0d/iso-3898-2013

But in other cases the original kernel will only be changed/extended by a so-called 'kernel-extending-subscript/index', e.g.:

symbol of the physical quantity 'number': n with [n] = 1 versus the symbol of the physical quantity 'number per year': n_{al} with $[n_{al}] = 1$ /year.

In this last example the subscript/index 'a' is mentioned a 'kernel-extending-subscript/index' or the compound symbol ' n_a ' can be considered as a new kernel.

3.5 Tables

3.5.1 Format of the tables in this International Standard

3.5.1.1 <u>Table 1</u> General use in the design of structures of types of alphabets

Table 1 in this International Standard is arranged so that it consists of three columns. The first column (from the left) gives the types of alphabets (in combination with upper case respectively lower case letter symbols), the second column gives dimensions and the third column gives common examples and recommendations of physical quantities having that dimension.

3.5.1.2 Tables 2 to 4 of physical quantities

The tables of physical quantities and units in this International Standard (<u>Tables 2</u> to <u>4</u>) are - in accordance with ISO 80000 arranged so that the physical quantities are presented in the first 5 columns

and the units in columns 6 to 8. The quantities and corresponding symbols and units are in accordance with ISO 80000-3 and ISO 80000-4.

NOTE In the ISO 80000 series this layout is presented on two opposite pages.

All units between two full lines on the right-half belong to the physical quantities between the corresponding full lines on the left-half of the pages.

In each table the symbols of the physical quantities (so the rows of a table) are arranged in alphabetical order with respect to the alphabet involved.

With respect to the numbering of the items, the first digit of the number corresponds with the number of the table.

3.5.1.3 <u>Tables 5</u> to <u>10</u> of indices

The tables of indices in this International Standard (<u>Tables 5</u> to <u>7</u>, <u>9</u> and <u>10</u>) are arranged so that every table consists of two columns: the left column gives the symbol (mostly one or more successive separate letter symbols) and the right column gives the meaning of the index involved.

<u>Table 8</u> of this International Standard is arranged so that it consists of three columns: the first column (from the left) gives the upper case (of one or more successive) letter symbols, the second column gives the lower case letter symbols and the third column gives the meaning of the index involved.

The index symbols (so the rows of the table) in each of the five subdivisions of the columns (three Basic variables and two Performance functionals) of the table are arranged in alphabetical order.

3.5.1.4 <u>Table 11</u> of mathematical signs and graphical symbols for use in the analysis and design of structures

The table of mathematical signs and graphical symbols in this International Standard (<u>Table 11</u>) is arranged so that the table consists of two columns: the left column gives the mathematical sign or graphical symbol and the right column gives a description of the sign/symbol with a short explanation.

3.5.2 Descriptive contents of the tables in this International Standard

3.5.2.1 <u>Table 1</u> General use in the design of structures of types of alphabets

This table gives general guide-lines for the use of types of alphabets/scripts in combination with upper case and lower case letter symbols for forming symbols for physical quantities in general: common and new.

3.5.2.2 Tables 2 to 4 of physical quantities

The names (only in English) of the most important physical quantities in a general sense within the field of the design of structures are given together with their symbols and - in some cases - definitions. These names and symbols are recommendations. The definitions are given for identification of the physical quantities involved.

The scalar or vector character of the physical quantities is pointed out, especially, when this is needed for definitions.

In most cases one name but always one symbol for the physical quantity is given. If two or more names are given for one physical quantity and no special distinction is made, they are equivalent.

With respect to the system of units only the International System of Units (SI) is applied (see ISO 80000-1). (In some cases non-SI units are given, but this is explicitly mentioned in the column 'Remarks'.) Only the names (in English) and the international SI-symbols for the corresponding physical quantities are given and some remarks.