

---

---

**UV-C Devices — Safety information —  
Permissible human exposure**

*Dispositifs UV-C — Information sur la sécurité — Limites admissibles  
pour l'exposition humaine*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 15858:2016](https://standards.iteh.ai/catalog/standards/sist/7e09ed07-b1d6-4fba-9597-7fed313adeb7/iso-15858-2016)

<https://standards.iteh.ai/catalog/standards/sist/7e09ed07-b1d6-4fba-9597-7fed313adeb7/iso-15858-2016>



**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 15858:2016

<https://standards.iteh.ai/catalog/standards/sist/7e09ed07-b1d6-4fba-9597-7fed313adeb7/iso-15858-2016>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
copyright@iso.org  
www.iso.org

# Contents

	Page
<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Sources of UVC exposure</b> .....	<b>4</b>
4.1 General.....	4
4.2 UVC energy penetration.....	4
4.3 UVC radiation measurement.....	4
4.4 Measuring Threshold Limit Values.....	4
<b>5 Exposure limits to UVC</b> .....	<b>5</b>
5.1 General information.....	5
5.2 Maximum permissible UVC exposure.....	5
5.3 Personal protective equipment.....	5
5.4 Personnel safety training.....	6
<b>Bibliography</b> .....	<b>7</b>

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 15858:2016](https://standards.iteh.ai/catalog/standards/sist/7e09ed07-b1d6-4fba-9597-7fed313adeb7/iso-15858-2016)

<https://standards.iteh.ai/catalog/standards/sist/7e09ed07-b1d6-4fba-9597-7fed313adeb7/iso-15858-2016>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 142, *Cleaning equipment for air and other gases*.

ISO 15858:2016

<https://standards.iteh.ai/catalog/standards/sist/7e09ed07-b1d6-4fba-9597-7fed313adeb7/iso-15858-2016>

## Introduction

This International Standard was developed in response to a worldwide demand for minimum specifications on UVC safety for products and equipment utilizing UVC lamp fixtures. In this International Standard, when it comes to personal damage of UV disinfection, the whole UVC band range is more likely to be included. As for lamps of product equipment, UVC prefers to the 254 nm wavelength.

UVC radiation is a low-penetrating form of UV as compared to UVA or UVB radiation. Measurements of human tissue show that 4 % to 7 % of UVC radiation, along with a wide range of wavelengths from 250 nm to 400 nm, is reflected<sup>[6]</sup> and absorbed in the first 2 µm of the stratum corneum. Hence, the amount of UVC transmitted through the epidermis is minimized.<sup>[7]</sup>

UVC radiation is invisible to humans and exposure to UVC radiation may have an effect on health. Ocular damage generally begins with photokeratitis but can also result in photokeratoconjunctivitis. Symptoms, which may not be evident until several hours after exposure, can include an abrupt sensation comparable to sand in eyes, tearing, and eye pain of various degrees. Such symptoms may appear within 1 h to 12 h after UVC exposure and resolve fully within 24 h to 48 h. Acute overexposure to UVC band radiation may cause incapacity due to eye discomfort, but this generally regresses after several days, leaving no permanent damage.

Cutaneous damage consists of erythema, a reddening of the skin akin to sunburn but without tanning. The maximum effect of erythema occurs at a wavelength of 297 nm in the UVB band. UVC radiation at a wavelength of 254 nm is less effective in causing erythema. Therefore, the areas subject to exposure should be marked. Warning signs should be placed in certain locations to protect personnel or passers-by from UV hazards. Appropriate locations include access doors, air handling unit outside walls, equipment room doors, etc.

The International Commission on Illumination (CIE) 2010 completed a review of UVC photocarcinogenesis risks from germicidal lamps using basic biophysical principles due to the attenuation provided by the stratum corneum and epithelial tissues of the skin. Upper air disinfection could be safely used without significant risk for long-term delayed effects such as skin cancer.<sup>[5]</sup>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 15858:2016

<https://standards.iteh.ai/catalog/standards/sist/7e09ed07-b1d6-4fba-9597-7fed313adeb7/iso-15858-2016>

# UV-C Devices — Safety information — Permissible human exposure

## 1 Scope

This International Standard specifies minimum human safety requirements for the use of UVC lamp devices.

It is applicable to in-duct UVC systems, upper-air in room UVC systems, portable in-room disinfection UVC devices, and any other UVC devices which may cause UVC exposure to humans.

It is not applicable to UVC products used for water disinfection.

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 170, *Personal eye-protection — Ultraviolet filters — Transmittance requirements and recommended use*

EN 14255-1, *Measurement and assessment of personal exposures to incoherent optical radiation — Part 1: Ultraviolet radiation emitted by artificial sources in the workplace*

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

### 3.1

#### wavelength

distance between repeating units of a wave pattern

Note 1 to entry: Commonly designated by the Greek letter lambda ( $\lambda$ ).

### 3.2

#### waveband

spectrum section

spectrum band

electromagnetic spectrum that is usually divided into a large spectral region, small spectral band and narrow spectral lines

Note 1 to entry: Waveband is commonly expressed as a specific *wavelength* (3.1) range of values, sometimes uses numbers or letters as code.

### 3.3

#### ultraviolet radiation

*wavelength* (3.1) of the electromagnetic spectrum of radiation from 10 nm to 400 nm

Note 1 to entry: The range between 100 nm and 400 nm is commonly subdivided into:<sup>[1]</sup>

- UVA: 315 nm to 400 nm;
- UVB: 280 nm to 315 nm;
- UVC: 200 nm to 280 nm;

## ISO 15858:2016(E)

— Vacuum UV: 100 nm to 200 nm.

### 3.4

#### UV dose

product of UV irradiance and specific exposure time on a given microorganism or surface

Note 1 to entry: UV dose is expressed in millijoules per square centimetre (mJ/cm<sup>2</sup>).

### 3.5

#### fluence rate

fluence across a surface

Note 1 to entry: Fluence rate is expressed in J/m<sup>2</sup>, J/cm<sup>2</sup>, or W·s/cm<sup>2</sup>.

### 3.6

#### irradiance

power of electromagnetic radiation incident on a surface per unit surface area

Note 1 to entry: Irradiance is expressed in microwatts per square centimetre (μW/cm<sup>2</sup>).<sup>[2]</sup>

### 3.7

#### effective irradiance

power of UVC radiation from electromagnetic radiation received on a surface per unit surface area

### 3.8

#### disinfection

less lethal process of inactivating microorganisms compared to sterilization

### 3.9

#### ultraviolet germicidal irradiation

##### UVGI

killing or inactivating microorganisms by emitting radiation predominantly at a wavelength (3.1) of 253,7 nm

### 3.10

#### radiometer

instrument used to measure radiometric quantities, particularly UV irradiance (3.6) or fluence

### 3.11

#### in-duct systems

UVC lamp devices placed up-stream or down-stream of the cooling coil or in other enclosed sections of the HVAC duct system

Note 1 to entry: See Reference <sup>[4]</sup>.

### 3.12

#### upper-air in room systems

UVC lamp devices mounted underneath room ceilings with UVC energy directed upward with adjustable louvers to keep UVC rays above eye and head level

Note 1 to entry: See Reference <sup>[4]</sup>.

### 3.13

#### portable in-room disinfection UVC device

easy-to-carry equipment to use in spaces requiring ultraviolet ray disinfection

EXAMPLE UVC device installed on mobile car.<sup>[4]</sup>

### 3.14

#### exposure

subjection to infectious agents, irradiation, particulates, or chemicals that could have harmful effects



**3.15****permissible exposure time****PET**

calculated time period that humans, with unprotected eyes and skin, can be exposed to a given level of UV *irradiance* (3.6) without exceeding the NIOSH recommended exposure limit (REL) or ACGIH *Threshold Limit Value*<sup>®</sup> (TLV<sup>®</sup>) (3.16) for UV radiation

Note 1 to entry: See References [8], [9], and [10].

**3.16****Threshold Limit Value<sup>®</sup>****TLV<sup>®</sup>**

guidelines on *exposure* (3.14) level under which most people can work consistently for eight hours a day, day after day, without adverse effects

Note 1 to entry: Used by the ACGIH to designate degree of exposure to contaminants.

Note 2 to entry: TLVs can be expressed as approximate milligrams of particulate per cubic meter of air (mg/m<sup>3</sup>). TLVs are listed either for 8 h as a time-weighted average (TWA) or for 15 min as a short-term exposure limit (STEL).

Note 3 to entry: See Reference [10].

**3.17****ocular damage**

any damage to the eye, particularly that caused by *exposure* (3.14) to UV energy

**3.18****photokeratitis**

corneal inflammation after over *exposure to ultraviolet radiation* (3.3)

Note 1 to entry: See Reference [3].

**3.19****photokeratoconjunctivitis**

inflammation of cornea and conjunctiva after *exposure* (3.14) to UV radiation

Note 1 to entry: Exposure to *wavelengths* (3.1) shorter than 320 nm is most effective in causing this condition. The peak of the action spectrum is approximately 270 nm.[3]

**3.20****stratum corneum**

outer dead layer of human skin

**3.21****cutaneous damage**

any damage to the skin, particularly that caused by *exposure* (3.14) to UVC energy

**3.22****erythema**

<actinic> reddening of the skin, with or without inflammation, caused by the actinic effect of solar radiation or artificial optical radiation

**3.23****personal protective equipment****PPE**

protective clothing, helmets, goggles, respirators, or other gear designed to protect the wearer from injury from a given hazard, typically used for occupational safety and health purposes