

---

---

**Agricultural and forestry  
machinery — Inspection of sprayers in  
use —**

**Part 3:  
Sprayers for bush and tree crops**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**  
*Matériel agricole et forestier — Contrôle des pulvérisateurs en  
service —  
Partie 3: Pulvérisateurs pour cultures arbustives et arboricoles*

[ISO 16122-3:2015](https://standards.iteh.ai/catalog/standards/sist/39f4d94c-e1c7-4a41-a2bb-feafc9d5cf7/iso-16122-3-2015)

[https://standards.iteh.ai/catalog/standards/sist/39f4d94c-e1c7-4a41-a2bb-  
feafc9d5cf7/iso-16122-3-2015](https://standards.iteh.ai/catalog/standards/sist/39f4d94c-e1c7-4a41-a2bb-feafc9d5cf7/iso-16122-3-2015)



**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 16122-3:2015](https://standards.iteh.ai/catalog/standards/sist/39f4d94c-e1c7-4a41-a2bb-feafc9d5cf7/iso-16122-3-2015)

<https://standards.iteh.ai/catalog/standards/sist/39f4d94c-e1c7-4a41-a2bb-feafc9d5cf7/iso-16122-3-2015>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
Foreword .....	v
Introduction .....	vi
<b>1 Scope .....</b>	<b>1</b>
<b>2 Normative references .....</b>	<b>1</b>
<b>3 Terms and definitions .....</b>	<b>1</b>
<b>4 Requirements and method of verification .....</b>	<b>2</b>
4.1 Leaks and dripping .....	2
4.1.1 Static leaks .....	2
4.1.2 Dynamic leaks .....	2
4.1.3 Spraying and dripping on parts .....	2
4.2 Pump(s) .....	2
4.2.1 Capacity .....	2
4.2.2 Pulsations .....	3
4.2.3 Air chamber .....	3
4.3 Spray mix agitation .....	3
4.3.1 Hydraulic .....	3
4.3.2 Mechanical .....	3
4.4 Spray liquid tank(s) .....	3
4.4.1 Lid .....	3
4.4.2 Filling hole(s) .....	3
4.4.3 Induction hopper .....	4
4.4.4 Pressure compensation .....	4
4.4.5 Tank content indicator(s) .....	4
4.4.6 Tank emptying .....	4
4.4.7 Tank filling .....	4
4.4.8 Cleaning device for plant protection product containers .....	4
4.4.9 Cleaning equipment .....	4
4.5 Measuring systems, controls and regulation systems .....	5
4.5.1 General .....	5
4.5.2 Pressure indicator .....	5
4.5.3 Other measuring devices .....	6
4.5.4 Pressure adjusting devices .....	6
4.6 Lines (pipes and hoses) .....	6
4.7 Filters .....	6
4.7.1 Filter presence .....	6
4.7.2 Isolating device .....	6
4.7.3 Filter insert changeability .....	6
4.8 Nozzles .....	6
4.8.1 Symmetry .....	6
4.8.2 Dripping .....	7
4.8.3 Switching off .....	7
4.8.4 Adjustment .....	7
4.9 Pressure drop .....	7
4.9.1 General .....	7
4.9.2 Compensative returns .....	7
4.9.3 Distribution .....	7
4.10 Blower .....	8
4.10.1 Switching off .....	8
4.10.2 Adjustability .....	8
4.11 Spray guns and lances .....	9
4.11.1 Trigger .....	9
4.11.2 Adjustment of flow rate and angle .....	9

<b>5</b>	<b>Test methods</b>	<b>9</b>
5.1	Test facilities	9
5.2	Spray and agitation pump(s)	9
5.2.1	Pump capacity test	9
5.2.2	Pump pulsations	10
5.3	Sprayer's pressure indicators	10
5.3.1	Specifications of pressure indicators used for verification	10
5.3.2	Verification method of the sprayer pressure indicator	11
5.4	Flow meters for controlling the volume/hectare rate	11
5.4.1	General	11
5.4.2	Operating procedure No. 1: Verification by nozzle flow rate measurement	11
5.4.3	Operating Procedure No. 2: Verification by installing a calibrated flow meter on the circuit of the sprayer	12
5.5	System for controlling forward speed	12
5.6	Flow rate of the spray nozzles	13
5.6.1	General	13
5.6.2	Measurement with nozzles fitted on the sprayer	13
5.6.3	Measurement with nozzles removed from the sprayer	13
5.7	Pressure drop	14
5.8	Pressure variation when the spray is switched off	14
5.9	Pressure distribution	14
	<b>Bibliography</b>	<b>15</b>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 16122-3:2015](https://standards.iteh.ai/catalog/standards/sist/39f4d94c-e1c7-4a41-a2bb-feafc9d5cf7/iso-16122-3-2015)

<https://standards.iteh.ai/catalog/standards/sist/39f4d94c-e1c7-4a41-a2bb-feafc9d5cf7/iso-16122-3-2015>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. [www.iso.org/directives](http://www.iso.org/directives)

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. [www.iso.org/patents](http://www.iso.org/patents)

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

ISO 16122-3 was prepared by the European Committee for Standardization (CEN) Technical Committee CEN/TC 144, *Tractors and machinery for agriculture and forestry*, in collaboration with ISO Technical Committee TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 6, *Equipment for crop protection*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

ISO 16122 consists of the following parts, under the general title *Agricultural and forestry machinery — Inspection of sprayers in use*:

- *Part 1: General*
- *Part 2: Horizontal boom sprayers*
- *Part 3: Sprayers for bush and tree crops*
- *Part 4: Fixed and semi-mobile sprayers*

## Introduction

There are two main reasons for the inspection:

- less potential risk of environmental contamination by plant protection products;
- good control of the pest with the minimum possible input of plant protection product.

In order to use plant protection products in agricultural production safely, it is necessary to define the requirements and test methods for sprayers in use. This is a relevant step after having standardized minimum requirements for new sprayers, in respect of safety hazards (see ISO 4254-6) and potential risks of environmental contamination (see ISO 16119 series).

Standardising the requirements and methods for inspection of sprayers in use, takes into consideration not only the original performance of the sprayer, but also its use, care and maintenance. This is a logical link to ensure the continued benefit arising from the supply of new sprayers of good quality.

The inspection of sprayers in use can be a mandatory requirement or adopted on a voluntary basis. In both cases further requirements, outside the scope of this standard, are necessary for the management of inspections. These include, for example, requirements for the competence of persons carrying out inspections and the frequency of inspections.

NOTE National or local regulations may also apply concerning the qualifications and competence of inspectors.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 16122-3:2015](https://standards.iteh.ai/catalog/standards/sist/39f4d94c-e1c7-4a41-a2bb-feafc9d5cfa7/iso-16122-3-2015)

<https://standards.iteh.ai/catalog/standards/sist/39f4d94c-e1c7-4a41-a2bb-feafc9d5cfa7/iso-16122-3-2015>

# Agricultural and forestry machinery — Inspection of sprayers in use —

## Part 3: Sprayers for bush and tree crops

### 1 Scope

This part of ISO 16122, when used together with ISO 16122-1, specifies the requirements and test methods for the inspection of sprayers for bushes and trees, when in use.

The requirements relate mainly to the condition of the sprayer with respect to its potential risk for the environment and its performance to achieve a good application.

NOTE Requirements for the protection of inspectors during an inspection are given in ISO 16122-1.

### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5682-2:1997, *Equipment for crop protection — Spraying equipment — Part 2: Test methods for hydraulic sprayers*

<https://standards.iteh.ai/catalog/standards/sist/39f4d94c-e1c7-4a41-a2bb-8af9d5cf67/iso-16122-3-2015>

ISO 16122-1:2015, *Agricultural and forestry machinery — Inspection of sprayers in use — Part 1: General*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 16122-1 and the following apply.

#### 3.1

##### **sprayer for bush and tree crops**

machine for spraying plant protection products on bush and tree crops such as grapes, fruits or hops (including annual plants/crops), the application being mostly directed sideways and/or upwards to the target

Note 1 to entry: Characteristics of sprayers for bushes and tree crops are specified in ISO 16122-1:2015, Table A.1.

#### 3.2

##### **plant protection product container**

collective name for plant protection product packaging

EXAMPLE Can, bottle, bag, sack, box.

#### 3.3

##### **cleaning device**

device for cleaning the inside of empty plant protection product containers

Note 1 to entry: The device may be an integral part of the sprayer or an independent installation (e.g. stationary equipment).

## 4 Requirements and method of verification

### 4.1 Leaks and dripping

#### 4.1.1 Static leaks

The sprayer shall be filled with water to its nominal capacity.

With the pump not running and the sprayer parked on a level horizontal surface, a visual inspection for any leakage from the tank, pump and associated pipes shall be carried out.

For high capacity tanks, water filling can be reduced to no less than half of the nominal tank volume, provided an additional inspection of the tank is carried out in order to identify any cracks, holes or other damage that can cause leakage.

Compliance shall be checked by inspection.

#### 4.1.2 Dynamic leaks

##### 4.1.2.1 Leak-test when not spraying

With the sprayer running at a pressure which is equal to the maximum obtainable pressure for the system, with the section valves closed, there shall be no leakage from any part of the sprayer.

Compliance shall be checked by inspection.

##### 4.1.2.2 Leak-test while spraying

While spraying at a pressure that is equal to the maximum working pressure recommended by the sprayer manufacturer, or the nozzle manufacturer for the nozzles mounted on the sprayer if lower, there shall be no leakage from any part of the sprayer or spray boom.

Compliance shall be checked by inspection.

#### 4.1.3 Spraying and dripping on parts

Regardless of the distance between the spray nozzles to the target to be sprayed, in the range between the nozzles and the target surface, no liquid shall be sprayed directly on to the sprayer itself (e.g. parts of the sprayer, hoses). This does not apply if needed by function (e.g. sensors) and if dripping is minimised.

Compliance shall be checked by inspection and function test.

### 4.2 Pump(s)

#### 4.2.1 Capacity

The pump capacity shall be suited to the needs of the sprayer:

- a) The pump capacity shall be at least 90 % of its original nominal flow given by the sprayer manufacturer or another minimum pump capacity given by the sprayer manufacturer.

Compliance shall be checked by measurement according to [5.2.1.2.2](#) or [5.2.1.2.3](#).

- b) Or, alternatively, the pump(s) shall have sufficient flow rate capacity in order to be able to spray while maintaining a visible agitation as specified in [4.3.1](#).

Compliance shall be checked by inspection.



#### 4.2.2 Pulsations

The pulsations shall not exceed 10 % of the working pressure.

Compliance shall be checked by measurement and function test according to [5.2.2](#).

#### 4.2.3 Air chamber

If an air chamber is present the membrane shall not be damaged, there shall be no appearance of liquid when operated at the maximum pressure recommended by the sprayer manufacturer. The air pressure shall be the pressure recommended by the sprayer manufacturer or between 30 % to 70 % of the working pressure for the nozzles in use.

Compliance shall be checked by function test and measurement

### 4.3 Spray mix agitation

#### 4.3.1 Hydraulic

A clearly visible agitation shall be maintained:

- when spraying at the maximum working pressure as recommended by the sprayer or nozzle manufacturer (whichever is the lower);
- with the largest nozzles mounted on the sprayer;
- with pump rotation speed as recommended by the sprayer manufacturer;
- with the tank filled to half its nominal capacity.

Compliance shall be checked by inspection. <https://standards.iteh.ai/catalog/standards/sist/39f4d94c-e1c7-4a41-a2bb-feafc9d5cfa7/iso-16122-3-2015>

#### 4.3.2 Mechanical

A clearly visible agitation shall be maintained when the agitation system is working as recommended by the sprayer manufacturer, with the tank filled to half its nominal capacity.

Compliance shall be checked by inspection.

### 4.4 Spray liquid tank(s)

#### 4.4.1 Lid

The tank(s) shall be provided with a lid that shall be well adapted and in good condition.

This lid shall be tightly sealed to prevent leakage and shall avoid unintended opening.

If a vent is fitted in the lid (according to [4.4.4](#)), it shall prevent spillage.

Compliance shall be checked by inspection.

#### 4.4.2 Filling hole(s)

There shall be a strainer in good condition in the filling hole(s).

Compliance shall be checked by inspection.

#### 4.4.3 Induction hopper

If there is an induction hopper, it shall:

- prevent any object greater than 20 mm diameter from entering into the sprayer tank.

Compliance shall be checked by measurement.

- function and not leak.

Compliance shall be checked by function test.

#### 4.4.4 Pressure compensation

There shall be a pressure compensation device to avoid over-pressure and under-pressure in the tank.

Compliance shall be checked by inspection.

#### 4.4.5 Tank content indicator(s)

The volume of liquid in the tank shall be clearly readable from the driver's position and/or from where the tank is filled.

Compliance shall be checked by inspection.

#### 4.4.6 Tank emptying

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

It shall be possible to:

- empty the tank, e.g. using a tap, and
- collect the liquid without contamination of the environment and without potential risk of exposure of the operator.

ISO 16122-3:2015  
https://standards.iteh.ai/catalog/standards/sist/16122-3-2015/16122-3-2015  
feaf9d5cfa7/iso-16122-3-2015

Compliance shall be checked by inspection.

#### 4.4.7 Tank filling

If there is a water filling device on the sprayer, water from the sprayer shall be prevented from returning to the water source, e.g. by means of a non-return valve.

Compliance shall be checked by inspection and function test.

#### 4.4.8 Cleaning device for plant protection product containers

If provided, the cleaning device for plant protection product container shall function.

Compliance shall be checked by inspection.

#### 4.4.9 Cleaning equipment

If provided, tank cleaning devices, devices for external cleaning, devices for cleaning of induction hoppers, and devices for the internal cleaning of the complete sprayer, shall function.

Compliance shall be checked by inspection and function test.

## 4.5 Measuring systems, controls and regulation systems

### 4.5.1 General

All devices for measuring, indicating and/or adjusting the pressure and/or flow rate shall function.

The valves for switching on or off the spray shall function.

Switching on and off of all nozzles shall be possible simultaneously.

The controls to be operated during spraying shall be operable from the operator's position and the instrument displays shall be readable from this position.

NOTE Turning of the head and the upper body is acceptable to achieve these requirements.

Compliance shall be checked by inspection and function test.

Application to one side only shall be possible by switching off the other side.

Compliance shall be checked by inspection and function test.

### 4.5.2 Pressure indicator

#### 4.5.2.1 Scale and dimension of pressure indicator

At least one digital or analogue pressure indicator shall be fitted at a position where it is clearly readable from the operator's position. Pressure indicators shall be suitable for the working pressure range used.

Compliance shall be checked by inspection.

#### 4.5.2.2 Scale of analogue pressure indicator

The scale of analogue pressure indicators shall provide graduations:

- at least every 0,2 bar<sup>1)</sup> for working pressures less than 5 bar;
- at least every 1,0 bar for working pressures between 5 bar and 20 bar;
- at least every 2,0 bar for working pressures more than 20 bar.

Compliance shall be checked by inspection.

#### 4.5.2.3 Accuracy of pressure indicator

The accuracy of the pressure indicator shall be:

- $\pm 0,2$  bar for working pressures at 2 bar and below;
- $\pm 10$  % of the real value for pressures at 2 bar and above.

This requirement shall be achieved within the working pressure range suitable for the nozzles mounted on the sprayer under test.

Compliance shall be checked by measurement according to [5.3](#).

#### 4.5.2.4 Diameter of analogue pressure indicator

For analogue pressure indicators, the minimum diameter shall be 63 mm, except for those mounted on spray guns and lances which shall have a minimum diameter of 40 mm.

1) 1 bar = 0,1 MPa = 0,1 N/mm<sup>2</sup> = 10<sup>5</sup> N/m<sup>2</sup>.